

Exercise 3 - Solution

Q1.

No, $AB^+ = \{A, B, C\}$, a proper subset of $\{A, B, C, D, E\}$

Yes, $ABD^+ = \{A, B, C, D, E\}$

Q2.

Let us use the following shorthand notation:

C = CourseNo, SN = SecNo, OD = OfferingDept, CH = CreditHours, CL = CourseLevel,

I = InstructorSSN, S = Semester, Y = Year, D = Days_Hours, RM = RoomNo,

NS = NoOfStudents

Hence, $R = \{C, SN, OD, CH, CL, I, S, Y, D, RM, NS\}$, and the following functional dependencies hold:

$\{C\} \rightarrow \{OD, CH, CL\}$

$\{C, SN, S, Y\} \rightarrow \{D, RM, NS, I\}$

$\{RM, D, S, Y\} \rightarrow \{I, C, SN\}$

First, we can calculate

since these sets of attributes

(1) $\{C\}^+ = \{C, OD, CH, CL\}$

(2) Since $\{C, SN, S, Y\} \rightarrow \{D, RM, NS, I\}$, and $\{C\}^+ =$

$\{C, SN, S, Y\}^+ = \{C, SN, S, Y, D, RM, NS, I, OD, CH, CL\} = R$

(3) Since $\{RM, D, S, Y\} \rightarrow \{I, C, SN\}$, we know that $\{RM, D, S, Y\}^+$ contains $\{RM, D, S, Y, I, C, SN\}$. But $\{C\}^+$ contains $\{OD, CH, CL\}$ so these are also contained in $\{RM, D, S, Y\}^+$ since C is already there. Finally, since $\{C, SN, S, Y\}$ are now all in $\{RM, D, S, Y\}^+$ and $\{C, SN, S, Y\}^+$ contains $\{NS\}$ (from (2) above), we get:

$\{RM, D, S, Y\}^+ = \{RM, D, S, Y, I, C, SN, OD, CH, CL, NS\} = R$

Hence, both $K_1 = \{C, SN, S, Y\}$ and $K_2 = \{RM, D, S, Y\}$ are (candidate) keys of R .

Q3.

(a) The key for this relation is Book_title, Authurname. This relation is in 1NF and not in 2NF as no attributes are FFD on the key. It is also not in 3NF.

(b)

3NF decomposition:

Book0(Book_title, Authurname)

Book1-1(Book_title, Publisher, Book_type)

Book1-2(Book_type, Listprice)

Book2(Authorname, Author_affil)

Q4.

(a)

- $\{M\}$ IS NOT a candidate key since it does not functionally determine attributes Y or P.
- $\{M, Y\}$ IS a candidate key since it functionally determines the remaining attributes P, MP, and C.
- $\{M, C\}$ IS NOT a candidate key since it does not functionally determine attributes Y or P.

(b)

REFRIG is not in 2NF, due to the partial dependency $\{M, Y\} \rightarrow MP$ (since $\{M\} \rightarrow MP$ holds). Therefore REFRIG is neither in 3NF nor in BCNF.

Alternatively: BCNF can be directly tested by using all of the given dependencies and finding out if the left hand side of each is a superkey (or if the right hand side is a prime

attribute). In the two fields in REFRIG: $M \rightarrow MP$ and $MP \rightarrow C$. Since neither M nor MP is a superkey, we can conclude that REFRIG is neither in 3NF nor in BCNF.

(c) Yes. Please follo

Q5.

1) List the candidate keys for R .

EH/ABH/BDH/CDE

2) Determine the highest normal form of R with resp

1NF. Non-prime attribute G is functionally determined by D .

3) Is the decomposition $\{ABCD, DEGH\}$ (with the same FD set F) of R lossless-join?

No.

Decomposition	A	B	C	D	E	G	H
$R_1(A, B, C, D)$	a	a	a	a	b	b	b
$R_2(D, E, G, H)$	b	b	b	a	a	a	a

Decomposition	A	B	C	D	E	G	H
$R_1(A, B, C, D)$	a	a	a	a	b	a	b
$R_2(D, E, G, H)$	a	b	b	a	a	a	a

4) Find a minimal cover F_m for F .

$F_m = \{AB \rightarrow C, D \rightarrow A, D \rightarrow G, E \rightarrow B, AB \rightarrow D, E \rightarrow A, CD \rightarrow E\}$

5) Decompose into a set of 3NF relations if it is not in 3NF. Make sure your decomposition is dependency-preserving and lossless-join.

For $F_m = \{AB \rightarrow C, D \rightarrow A, D \rightarrow G, E \rightarrow B, AB \rightarrow D, E \rightarrow A, CD \rightarrow E\}$:

From $AB \rightarrow C, AB \rightarrow D$, derive $R_1\{A, B, C, D\}$

From $D \rightarrow A, D \rightarrow G$, derive $R_2\{A, D, G\}$

From $E \rightarrow B, E \rightarrow A$, derive $R_3\{A, B, E\}$

From $CD \rightarrow E$, derive $R_4\{C, D, E\}$

None of the relation schemas contains a key of R , add one relation schema $R_5\{E, H\}$

6) Decompose it into a collection of BCNF relations if it is not in BCNF. Make sure your decomposition is lossless-join.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro