

COMP9334

# Capacity Planning for Computer Systems and Networks

Assignment Project Exam Help

Week 3B <https://eduassistpro.github.io/> Compute the  
state balance equation automatically  
Add WeChat edu\_assist\_pro

# Deriving state balance equations

- The aim of this document is to explain how you can derive the following equations of the database server automatically

$$6 P_{(2,0,0)} - 4 P_{(1,1,0)} - 2 P_{(1,0,1)} + 0 P_{(0,2,0)} + 0 P_{(0,1,1)} + 0 P_{(0,0,2)} = 0$$

$$-3 P_{(2,0,0)} + 10 P_{(1,1,0)} + 0 P_{(1,0,1)} - 4 P_{(0,2,0)} - 2 P_{(0,1,1)} + 0 P_{(0,0,2)} = 0$$

$$-3 P_{(2,0,0)} + 0 P_{(1,1,0)} + 0 P_{(1,0,1)} + 0 P_{(0,2,0)} - 2 P_{(0,1,1)} + 0 P_{(0,0,2)} = 0$$

$$0 P_{(2,0,0)} - 3 P_{(1,1,0)} + 0 P_{(1,0,1)} + 4 P_{(0,2,0)} + 0 P_{(0,1,1)} + 0 P_{(0,0,2)} = 0$$

$$0 P_{(2,0,0)} - 3 P_{(1,1,0)} - 3 P_{(1,0,1)} + 0 P_{(0,2,0)} + 6 P_{(0,1,1)} + 0 P_{(0,0,2)} = 0$$

$$0 P_{(2,0,0)} + 0 P_{(1,1,0)} - 3 P_{(1,0,1)} + 0 P_{(0,2,0)} + 0 P_{(0,1,1)} + 2 P_{(0,0,2)} = 0$$

# Deriving state balance equations

- We rewrite the equations from the last page as a matrix

(2,0,0)	[	6	-4	-2	0	0	0
(1,1,0)		-3	10	0	-4	-2	0
(1,0,1)		-3	0	8	0	-4	-2
(0,2,0)		0	0	0	0	0	0
(0,1,1)		0	0	0	0	0	0
(0,0,2)		0	0	-3	0	0	2]
(2,0,0)							
(1,1,0)							
(1,0,1)							
(0,2,0)							
(0,1,1)							
(0,0,2)							

- This matrix is sufficient for you to solve the equations, so this matrix is what we need
- We have also added row labels (in red) and column labels (in green)
- Let us first understand the meaning of the row and column labels

## Meaning of the row labels

- The row label  $(2,0,0)$  means the corresponding row comes from the state balance equation for the state  $(2,0,0)$
- The meaning is similar for the other rows

$(2,0,0)$	[ 6	-4	-2	0	0	0
$(1,1,0)$	-3			-2		0
$(1,0,1)$	-3			-4		-2
$(0,2,0)$	0	3	0	0		0
$(0,1,1)$	0	-3	-3	6		0
$(0,0,2)$	0	0	-3	0	0	2]
	$(2,0,0)$	$(1,1,0)$	$(1,0,1)$	$(0,2,0)$	$(0,1,1)$	$(0,0,2)$

# Meaning of the column labels

- The column label  $(2,0,0)$  means the numbers in the column should be multiplied by  $P_{(2,0,0)}$
- Similarly for the other columns
- You can check that by going back to Page 1

$(2,0,0)$	6	-4	-2	0	0	0
$(1,1,0)$	-3			-2		0
$(1,0,1)$	-3			-4		-2
$(0,2,0)$	0	3	0	0		0
$(0,1,1)$	0	-3	-3	6		0
$(0,0,2)$	0	0	-3	0	0	2
	$(2,0,0)$	$(1,1,0)$	$(1,0,1)$	$(0,2,0)$	$(0,1,1)$	$(0,0,2)$

# Signs of the number

- Note that
  - All diagonal elements have positive values
  - All non-diagonal elements have negative or zero values

(2,0,0)	6	-4	-2	0	0	0
(1,1,0)	-3	3	-2	-2	0	0
(1,0,1)	-3	0	-4	0	-2	0
(0,2,0)	0	-3	0	0	0	0
(0,1,1)	0	-3	-3	6	0	0
(0,0,2)	0	0	-3	0	0	2
(2,0,0)	(1,1,0)	(1,0,1)	(0,2,0)	(0,1,1)	(0,0,2)	

Let us now examine where the non-diagonal elements are coming from

The number 4 is the transition rate from state  $(1,1,0)$  (column label) to state  $(2,0,0)$  (row label)

The number 2 is the transition rate from state  $(1,0,1)$  (column label) to state  $(2,0,0)$  (row label)

Assignment Project Exam Help

$(2,0,0)$	[	6	<a href="https://eduassistpro.github.io/">https://eduassistpro.github.io/</a>	0	0	
$(1,1,0)$		-3	10	0	-2	0
$(1,0,1)$		-3	0	8	-4	-2
$(0,2,0)$		0	-3	0	4	0
$(0,1,1)$		0	-3	-3	0	6
$(0,0,2)$		0	0	-3	0	0
						2]
		$(2,0,0)$	$(1,1,0)$	$(1,0,1)$	$(0,2,0)$	$(0,1,1)$
					$(0,0,2)$	

## Using nested for-loops to find the non-diagonal elements

- On the last slide, we say that the off-diagonal elements is given by  $(-1) * (\text{transition rate of the column label to the row label})$
- This suggests that we can use a nested for-loop to obtain the off-diagonal elements. The pseudo-code is:

```
for i from 1 to 6      # r
  for j from 1 to 6    #
    if i not equal j   # Off-diagonal ele
      col_i = label of i-th row
      row_j = label of j-th row
      determine the transition rate from col_i to col_j
```

- The next question is how you can determine the transition rate by using the row and column labels.



In order to understand how you can determine the transition rate given the row and column labels, let us focus on the transitions that give the number -4 in the matrix. The table below summarises all the three possible transitions. We find that if we do an elementwise subtraction of the row label from the column label, we always get (1,-1,0). What does (1,-1,0) represent? Recall that the state is (#users in CPU,#users in fast disk,#users in slow disk). Therefore, the difference (1,-1,0) means a user has left the fast disk to go to the CPU. An important lesson is that we can use the column label minus the row label to tell us what the state transition should be.

Row label	Column label	Column label minus row label
(2,0,0)	(1,1,0)	$(2,0,0) - (1,1,0) = (1,-1,0)$
(1,1,0)	(0,2,0)	$(1,1,0) - (0,2,0) = (1,-1,0)$
(1,0,1)	(0,1,1)	$(1,0,1) - (0,1,1) = (1,-1,0)$

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

(2,0,0)	[ 6	-4	-2	0	0	
(1,1,0)	-3	10	0	-4	-2	0
(1,0,1)	-3	0	8	0	-4	-2
(0,2,0)	0	-3	0	4	0	0
(0,1,1)	0	-3	-3	0	6	0
(0,0,2)	0	0	-3	0	0	2]
	(2,0,0)	(1,1,0)	(1,0,1)	(0,2,0)	(0,1,1)	(0,0,2)

For the database server, there are four state transitions that have a non-zero transition rate. See the table below. All other transitions will have zero transition rate. For example, the transition from column label (0,2,0) to row label (1,0,1) has difference (1,-2,1). This difference is not listed in the first column below, so it has zero transition rate. The next slide shows the pseudo code that you use to find all the off-diagonal elements.

Column label minus row label	Meaning
(1,-1,0)	User finishes at fast disk and goes to CPU
(1,0,-1)	User finishes at slow disk and goes to CPU
(-1,1,0)	and goes to fast disk
(-1,0,1)	and goes to slow disk

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

(2,0,0)	[ 6	-4	-2	0	0	0
(1,1,0)	-3	10	0	-4	-2	0
(1,0,1)	-3	0	8	0	-4	-2
(0,2,0)	0	-3	0	4	0	0
(0,1,1)	0	-3	-3	0	6	0
(0,0,2)	0	0	-3	0	0	2]
	(2,0,0)	(1,1,0)	(1,0,1)	(0,2,0)	(0,1,1)	(0,0,2)

Pseudo code to find the non-diagonal elements

```
for i from 1 to 6      # row index
  for j from 1 to 6    # column index
    if i not equal j    # Off-diagonal element
      col_i = label of i-th row
      row_j = label of j-th row
      transition = col_i – row_j
      if transition == (1,-1,0)
        # user move from
      else if transition == (-1,1,0)
        # user move from slow disk to CPU
      else if transition == (-1,0,1)
        # user move from CPU to fast disk
      else if transition == (1,0,-1)
        # user move from fast disk to CPU
      else
        # transition rate is zero
```

Assignment Project Exam Help  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

Once you can determine the type of transition, you can fill in the transition rate which is a constant for a given transition. We still need to determine the diagonal elements.

The boxes below explain how the diagonal elements are coming from. This means that once we have identified a transition from the column label to a row label, we can accumulate it in the diagonal element corresponding to the column label.

You can see the complete code in `rate_matrix_automated.py`

The number 6 is the sum of  
transition rate from  $(2,0,0)$  to  $(1,1,0)$ , and  
transition rate from  $(2,0,0)$  to  $(0,2,0)$

The number 10 is the sum of  
transition rate from  $(1,1,0)$  to  $(2,0,0)$ , and  
rate from  $(1,1,0)$  to  $(0,2,0)$ , and  
rate from  $(1,1,0)$  to  $(0,1,1)$

<https://eduassistpro.github.io/>

Add WeChat: [edu\\_assist\\_pro](#)

$(2,0,0)$	[ 6	-4	-2	0	0	0
$(1,1,0)$	-3	10	0	-4	-2	0
$(1,0,1)$	-3	0	8	0	-4	-2
$(0,2,0)$	0	-3	0	4	0	0
$(0,1,1)$	0	-3	-3	0	6	0
$(0,0,2)$	0	0	-3	0	0	2]
	$(2,0,0)$	$(1,1,0)$	$(1,0,1)$	$(0,2,0)$	$(0,1,1)$	$(0,0,2)$

You can see the complete code in `rate_matrix_automated.py`

Finally, you may have noticed already that the sum of each column is 0. This is a consequence of state balance. This implies the following sanity check: If the column sum of the matrix that you have obtained is non-zero, then something is wrong.

## Assignment Project Exam Help

<https://eduassistpro.github.io/>

(2,0,0)	[ 6	-4	-2	0	0	0
(1,1,0)	-3	10	0	-4	-2	0
(1,0,1)	-3	0	8	0	-4	-2
(0,2,0)	0	-3	0	4	0	0
(0,1,1)	0	-3	-3	0	6	0
(0,0,2)	0	0	-3	0	0	2]
(2,0,0)	(1,1,0)	(1,0,1)	(0,2,0)	(0,1,1)	(0,0,2)	