NUMERICAL OPTIMISATION ASSIGNMENT 3

MARTA BETCKE KIKO RUL·LAN

EXERCISE 1

Derive the 2D subspace trust region method for convex functions (with s.p.d. Hessian). Note that

- (i) when p is constraint to a subspace $V = \text{span}(g, B^{-1}g)$, it can be expressed as a linear combination of basis vectors p = Va. You can use any basis, here orthonormal basis is useful;
- (ii) use the result in Theorem 4.1 to obtain optimal p. Observe that complementarity condition (Theorem 4.1 equation (4.8a)) results in two cases;
- (iii) use Theorem 4.1 equation (4.8a) to obtain an explicit expression for each coefficient a_i and plug them into the remaining condition; Hint: After using the eigenvalue decomposition of $B_V = V^T B V$, this can be reduced to finding the roots of a 4th order polynomial.

Submit sold Salar Signment Project Exam Help [40pt]

EXERCISE 2

Implement the 2D substitution should r. // eduassistpro.github.io/implementation should r. // Eduassistpro.github.io/implementation should r. // Eduassistpro.github.io/implementation via Cody Coursework. [20pt]

EXERCISE 3 Add WeChat edu_assist_pro

Implement a trust region function based on Algorithm 4.1 in Nocedal Wright. Let this function take a handle to a solver for the constraint quadratic model problem as an argument. This will allow us to plug in different solvers to obtain different trust region methods.

Submit your implementation via Cody Coursework.

[20pt]

EXERCISE 4

Apply the trust region method to Rosenbrock function with a nearby starting point (1.2, 1.2) and a farther away point (-1.2, 1). Pay attention to the choice of trust region radius in each case. Hint: In case you are not confident with your implementation of the 2D subspace method, you can implement the dogleg method, which is provided in Nocedal Wright.

Submit solution via TurnitIn.

[20pt]

Remark. The submission to TurnitIn should not be longer than 4 pages. Avoid submitting more code than needed (if any) and focus on explaining your results.