

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Software Testing

Making the Right Software, and Making Software
Right

QUIZ

Assignment Project Exam Help

■ Join YACR <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Software Failure

There are three ways to describe problems with the software system. A failure

Assignment Project Exam Help

<https://eduassistpro.github.io/>

A: an unacceptable deviation of the system.

Add WeChat edu_assist_pro

B: a flaw in any aspect of the system that contributes to a larger problem with the system.

C: a slip up or inappropriate decision by a software developer that leads to the introduction of a defect.

D: none of the above

Software Failure

Assignment Project Exam Help
There are three ways to describe problems with the software system. A failure

<https://eduassistpro.github.io/>

A: **an unacceptable behaviour of the system.**

B: a flaw in any aspect of the system that contributes to a larger problem with the system.

C: a slip up or inappropriate decision by a software developer that leads to the introduction of a defect.

D: none of the above

Software Testing

Assignment Project Exam Help

A software engineer, working in a hurry, accidentally added a duplicated

<https://eduassistpro.github.io/>

This is an example of:

Add WeChat edu_assist_pro

A: Defect

B: Failure

C: Fault

D: Error

Software Testing

Assignment Project Exam Help

A software engineer, working in a hurry, accidentally added a duplicated

<https://eduassistpro.github.io/>

This is an example of:

Add WeChat edu_assist_pro

A: Defect

B: Failure

C: Fault

D: **Error**

Why is Testing Important?

- All software development models include testing
- Small or large projects can benefit from better code
- More sophisticated techniques can improve efficiency

Software Testing

- Testing can only show the presence of errors, not their absence.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

How Much Testing?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Validation versus Verification

- Validation - Build the Right Product
- Verification <https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Types of Testing

- Black/Opaque Box Testing
 - When you have no access to the source code
 - Test Input and Output functionality
- White/Clear/Glass Box Testing
 - When you have access to the source code, and design test cases to cover paths

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Testing Coverage

- Black Box – You can only test based on inputs and expected outputs

<https://eduassistpro.github.io/>

- Glass Box – Coverage can include finding all possible paths, and covering all possible edges, and cover all nodes

- In both cases, you should be able to design a set of tests that put a system through it's paces. Check baseline, valid, and invalid input as a standard approach to testing.

Equivalence Classes: Basic Approach

■ Valid, Invalid **Assignment Project Exam Help**

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Equivalence Classes

- Another way to think about validity. Divide all possible inputs into groups that should be treated the same way.

Assignment Project Exam Help

- For Example: Valid <https://eduassistpro.github.io/> validation.

Add WeChat edu_assist_pro

- | | |
|---------------------|--------------------------|
| ■ Equivalence Class | Range of Values |
| ■ Invalid – Larger | 13 to 2^{31} (Max int) |
| ■ Valid | 1 to 12 |
| ■ Invalid – Smaller | 0 to -2^{31} (Min int) |

Equivalence Classes

- Telephone Number Validation

Assignment Project Exam Help

- Invalid – Null Inp <https://eduassistpro.github.io/>

- Invalid – Too Few Digits **Add WeChat edu_assist_pro**

- Invalid – Correct Number of Digits without leading 0

- Valid – Correct Number of Digits with leading 0

- Invalid – Too Many Digits

JUnit

- JUnit is a testing tool, it is already incorporated into Eclipse

<https://eduassistpro.github.io/>

- Create a JUnit test case – Add WeChat edu_assist_pro JUnit Test Case

- Run Test Cases – Right Click on Project -> Run As -> JUnit Test Case

Test Assertions

- ❑ fail
 - ❑ assertTrue
 - ❑ assertFalse
 - ❑ assertEquals
 - ❑ assertNull
 - ❑ assertNotNull
 - ❑ assertSame
 - ❑ assertNotSame
- Assignment Project Exam Help**
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Test Annotations

- @Test **Assignment Project Exam Help**
- @Test(expect=) **<https://eduassistpro.github.io/>**
- @Test(timeout=) **Add WeChat edu_assist_pro**
- @Before
- @After
- @BeforeClass
- @AfterClass
- @Ignore

Break

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A JUnit test class

```
import org.junit.*;
import static org.junit.Assert.*;

public class ...

    @Test
    public void myInssimpleTest() {
        ...
    }
}
```

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro
test case method

- A method with `@Test` is flagged as a JUnit test case.
 - All `@Test` methods run when JUnit runs your test class.

JUnit assertion methods

<code>assertTrue(test)</code>	fails if the boolean test is <code>false</code>
<code>assertFalse(test)</code>	fails if the boolean test is <code>true</code>
<code>assertEquals(expect</code>	<code>s</code> are not equal
<code>assertSame(expected</code>	<code>s</code> are not the same (by <code>==</code>)
<code>assertNotSame(expected, actual)</code>	if <code>s</code> are the same (by <code>==</code>)
<code>assertNull(value)</code>	if <code>value</code> is <i>not</i> null
<code>assertNotNull(value)</code>	fails if the given value is null
<code>fail()</code>	causes current test to immediately fail

Each method can also be passed a string to display if it fails:

e.g. `assertEquals("message", expected, actual)`

JUnit exercise

Given a Date class with the following methods:

```
public Date(int year, int month, int day)
public Date() // today
public int getYear()
public void addDays(int days)
public int dayOfMonth()
public String dayOfWeek() // "Sunday"
public boolean equals(Object o)
public boolean isLeapYear()
public void nextDay() // advances by 1 day
public String toString()
```

- Come up with unit tests to check the following:
 - That no Date object can ever get into an invalid state.
 - That the addDays method works properly.
 - It should be efficient enough to add 1,000,000 days in a call.

A common mistake

```
public class DateTest {  
    @Test  
    public void test1() {  
        Date d = new Date(2050, 2, 15);  
        d.addDays(4);  
        assertEquals(d.getYear(), 2050);  
        assertEquals(d.getMonth(), 2);  
        assertEquals(d.getDay(), 19);  
    }  
  
    @Test  
    public void test2() {  
        Date d = new Date(2050, 2, 15);  
        d.addDays(14);  
        assertEquals(d.getYear(), 2050);  
        assertEquals(d.getMonth(), 3);  
        assertEquals(d.getDay(), 1);  
    }  
}
```

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Expectation on the left

```
public class DateTest {
    @Test
    public void test1() {
        Date d = new Date(2050, 2, 15);
        d.addDays(14);
        assertEquals(2050, d.getYear()); // expected
        assertEquals(3, d.getMonth()); // value should
        assertEquals(1, d.getDay()); // be at LEFT
    }

    @Test
    public void test2() {
        Date d = new Date(2050, 2
        d.addDays(14);
        assertEquals("year after +14 days", 2050, d.getYear());
        assertEquals("month after +14 days", 3, d.getMonth());
        assertEquals("day after +14 days", 1, d.getDay());
    }
    // test cases should usually have messages explaining
    // what is being checked, for better failure output
}
```

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Objects are good to simplify tests

```
public class DateTest {  
    @Test  
    public void test1() {  
        Date d = new Date(2050, 2, 15);  
        d.addDays(4);  
        Date expected  
        assertEquals
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>
a expected answer
to minimize tests

```
    @Test  
    public void test2() {  
        Date d = new Date(2050, 2, 15);  
        d.addDays(14);  
        Date expected = new Date(2050, 3, 1);  
        assertEquals("date after +14 days", expected, d);  
    }  
}
```

Add WeChat edu_assist_pro
just have toString
equals methods)

Use informative name

```
public class DateTest {
    @Test
    public void test addDays withinSameMonth 1() {
        Date actual = new Date(2050, 2, 15);
        actual.addDays(14);
        Date expected = new Date(2050, 2, 19);
        assertEquals(actual);
    }
    // give test case descriptive names

    @Test
    public void test addDays wrapTo() {
        Date actual = new Date(2050, 2, 15);
        actual.addDays(14);
        Date expected = new Date(2050, 3, 1);
        assertEquals("date after +14 days", expected, actual);
    }
    // give descriptive names to expected/actual values
}
```

Variable messages? ... not so good

```
public class DateTest {
    @Test
    public void Day_1() {
        Date actual = new Date(15);
        Date expected = new Date(2, 16);
        assertEquals("should have gotten " + expected + "\n" +
                     "but instead got " + actual + "\n",
                     expected, actual);
    }
    ...
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Tests with a timeout

```
@Test(timeout = 5000)
```

```
public void name() { ... }
```

- The above method should finish running within 5000 ms

```
private static final int TIMEOUT = 2000;  
...  
  
@Test(timeout = TIMEOUT)  
public void name() { ... }
```

- Times out / fails after 2000 ms

Pervasive timeouts

```
public class DateTest {  
    @Test(timeout = DEFAULT_TIMEOUT)  
    public void test_addDays_withinSameMonth_1() {  
        Date d = new Date(2050, 2, 15);  
        d.addDays(4);  
        Date expected = new Date(2050, 2, 19);  
        assertEquals("date after +4 days", expected, d);  
    }  
}
```

<https://eduassistpro.github.io/>

```
@Test(timeout = DEFAULT_TIMEOUT)  
public void test_addDays_withinMonth_2() {  
    Date d = new Date(2050, 2, 15);  
    d.addDays(14);  
    Date expected = new Date(2050, 3, 1);  
    assertEquals("date after +14 days", expected, d);  
}
```

```
// almost every test should have a timeout so it can't  
// lead to an infinite loop; good to set a default, too  
private static final int DEFAULT_TIMEOUT = 2000;
```

```
}
```

Testing for exceptions

```
@Test(expected = ExceptionType.class)
public void name() {
    ...
}
```

Assignment Project Exam Help

- Will pass if it does
 - If the excepti
 - Use this to test for expected error

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

```
@Test(expected = ArrayIndexOutOfBoundsException.class)
public void testBadIndex() {
    ArrayIntList list = new ArrayIntList();
    list.get(4);    // should fail
}
```

Setup and teardown

@Before

```
public void name() { ... }
```

@After

```
public void name() { ... }
```

- ▣ methods to run before/after the test method is called

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

@BeforeClass

```
public static void name() { ... }
```

@AfterClass

```
public static void name() { ... }
```

- ▣ methods to run once before/after the entire test class runs

PI Questions

▣ Join YACRS Session 1262

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

PI 7.1 @Before example

```
import org.junit.*;
import static org.junit.Assert.*;
import java.util.*;
```

```
public class SimpleTest {
    private Collection<Object> collection;
```

@Before

```
public void setUp() {
    collection = new ArrayList<>();
}
```

@Test

```
public void testEmptyCollection() {
    assertTrue(collection.isEmpty());
}
```

@Test

```
public void testOneItemCollection() {
    collection.add("itemA");
    assertEquals(1, collection.size());
}
```

What is the execution order?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A: f1 > f2 > f3

: f1 > f2 > f1 > f3

• D: f2 > f1 > f3 > f1

PI 7.1 @Before example

```
import org.junit.*;
import static org.junit.Assert.*;
import java.util.*;
```

```
public class SimpleTest {
    private Collection<Object> collection;
```

Assignment Project Exam Help

```
@Before
public void setUp() {
    collection = new ArrayList<>();
}
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
@Test
public void testEmptyCollection() {
    assertTrue(collection.isEmpty());
}
```

```
@Test
public void testOneItemCollection() {
    collection.add("itemA");
    assertEquals(1, collection.size());
}
```

What is the execution order?

A: f1 > f2 > f3

: f1 > f2 > f1 > f3

• C: f3 > f1 > f2 > f1

• D: f2 > f1 > f3 > f1

@Before and @After

```
import org.junit.*;
import static org.junit.Assert.*;
import java.io.*;
public class OutputTest {
    private File output;
```

Execution order:

- createOutputFile()
- testSomethingWithFile()

```
@Before
public void createOutputFile() {
    output = new File(...);
}
```

```
@After
public void deleteOutputFile() {
    output.delete();
}
```

```
@Test
public void testSomethingWithFile() {
    ...
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Execution order

```
public class SimpleTest {  
    private Collection collection;  
    @BeforeClass  
    public static void oneTimeSetUp() { //f1  
        // one-time initialization code  
    }
```

```
    @AfterClass  
    public static void oneTimeTearDown() {  
        // one-time cleanup  
    }
```

```
    @Before  
    public void setUp() { //f3  
        collection = new ArrayList();  
    }  
    @After  
    public void tearDown() { //f4  
        collection.clear();  
    }  
    ..
```

```
    @Test  
    public void testEmptyCollection() { //f5  
        assertTrue(collection.isEmpty());  
    }  
    @Test  
    public void testOneItemCollection() { //f6  
        collection.add("itemA");  
        assertEquals(1, collection.size());  
    }  
}
```

oneTimeSetUp()
setUp()
testEmptyCollection()
tearDown()
setUp()
testOneItemCollection()
tearDown()
oneTimeTearDown()

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

JUnit exercise

Given our Date class seen previously:

```
public Date(int year, int month, int day)
public Date() // today
public int getDay(), getMonth(), getYear()
public void addDays(int days) // advances by days
public int day
public String toString()
public boolean equals(Object o)
public boolean isLeapYear()
public void nextDay() // advances by 1 day
public String toString()
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Come up with unit tests to check the following:
 - That no Date object can ever get into an invalid state.
 - That the addDays method works properly.
 - It should be efficient enough to add 1,000,000 days in a call.

A bit cluttered code

```
public class DateTest {
    @Test
    public void test addDays withinSameMonth 1() {
        Date actual = new Date(2050, 2, 15);
        actual.addDays(14);
        Date expected = new Date(2050, 2, 19);
        assertEquals(actual);
    }
    // give test case descriptive names

    @Test
    public void test addDays wrapTo() {
        Date actual = new Date(2050, 2, 15);
        actual.addDays(14);
        Date expected = new Date(2050, 3, 1);
        assertEquals("date after +14 days", expected, actual);
    }
    // give descriptive names to expected/actual values
}
```

Squashing redundancy

```
public class DateTest {
    @Test(timeout = DEFAULT_TIMEOUT)
    public void addDays_withinSameMonth_1() {
        addHelper(2050, 2, 15, +4, 2050, 2, 19);
    }

    @Test(timeout = DEFAULT_TIMEOUT)
    public void addD
        addHelper(20
    }

    // use lots of helpers to make s extremely short
    private void addHelper(int y1, int d1, int add,
                           int y2, int d2) {
        Date act = new Date(y, m, d);
        actual.addDays(add);
        Date exp = new Date(y2, m2, d2);
        assertEquals("after +" + add + " days", exp, act);
    }

    // can also use "parameterized tests" in some frameworks
    ...
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Organizing Tests

Option 1:

```
src
  com
    xyz
      SomeClass.java
      SomeClassTest
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Option2:

```
src
  com
    xyz
      SomeClass.java
test
  com
    xyz
      SomeClassTest.java
```

Add WeChat edu_assist_pro

Test-driven development

- Unit tests can be written after, during, or even *before* coding.
- test-driven development:** Write tests, *then* write code to pass them.

Assignment Project Exam Help

- Imagine that we'd like to add a method `addWeeks` to our `Date` class, that shifts this date by the given number of weeks.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

- Write code to test this method *before* it has been written.
- Then once we do implement the method, we'll know if it works.

P7. 2 Test First Development

How many of the following statements are true about test first development?

Assignment Project Exam Help

Test first development reduces testing by only using tests are the beginning of developme

<https://eduassistpro.github.io/>

Test cases can be used t
form.

table

Add WeChat edu_assist_pro

Test first development prevents the occurrenc

A: 0

B: 1

C: 2

D: 3

Test First Development

How many of the following statements are true about test first development?

Assignment Project Exam Help

Test first development reduces testing by only using tests are the beginning of developme

**[https://eduassistpro.github.io/
table](https://eduassistpro.github.io/table)**

Test cases can be used to form.

Add WeChat edu_assist_pro

Test first development prevents the occurrenc

A: 0

B: 1

C: 2

D: 3

Testing Credit Cards

You must develop a set of equivalence classes for a credit card processing system.

The only credit cards accepted are MasterCard and Visa. Card numbers must be 16 digits long. MasterCards must start with a 5, and Visa must start with 4.

Assignment Project Exam Help

How many equivalence classes are there for valid credit card numbers?
<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A: 5

B: 6

C: 7

D: 8

Equivalence Classes

- ❑ Too Few Digits – Null Input

Assignment Project Exam Help

- ❑ Too Few Digits –

- ❑ Correct Digits wi <https://eduassistpro.github.io/>

- ❑ Correct Digits with Valid Master [Add WeChat edu_assist_pro](#)

- ❑ Correct Digits with Valid Visa Format

- ❑ Too Many Digits - >16 Digits

Equivalence Classes: Testing Boundaries

Errors often happen at the boundaries of equivalence classes, so choosing a meaningful boundary and testing it thoroughly is important.

In the credit card example, how would you test the boundary cases?

A: By testing the digit length for invalid input

B: By testing the Max Int and Max Int -1 digit lengths for invalid input.

C: By testing invalid leading digits 3 and 6

D: Something else

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Equivalence Classes: Testing Boundaries

Errors often happen at the boundaries of equivalence classes, so choosing a meaningful boundary and testing it thoroughly is important.

In the credit card example, how would you test the boundary cases?

Assignment Project Exam Help

A: By testing the different invalid input. *There might be*

These boundaries are general we would focus on boundaries beyond invalid.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

B: By testing the Max Int and Max Int -1 digit lengths for invalid input. **We would expect that these values could reasonably behave the same and would probably be a waste of time to test both**

C: By testing invalid leading digits 3 and 6 **These are a good boundary case for valid integers since we might uncover an arithmetic and off by one error in our validation.**

D: Something else **Another boundary case is checking that 15 and 17 digits both come back as invalid**

Next Week

- ▣ Lab review, and more on testing

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro