

# C/CPS 506

Assignment Project Exam Help

Compara

Languages

<https://eduassistpro.github.io/>

Prof. Ale

Add WeChat edu\_assist\_pro

**Topic 10:** Ownership and lifetime in Rust

# Notice!

---

**Obligatory copyright notice in the age of digital  
delivery and online classrooms:**

**Assignment Project Exam Help**

**<https://eduassistpro.github.io/>**

*The copyright to this work is reserved by Alex Ufkes. Students registered in course CCPS 506 can use the work for the purposes of this course but no other use is permitted, and there can be no sale or transfer or use of the work for any other purpose without explicit permission of Alex Ufkes.*

# Course Administration

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Getting closer! Two **Add WeChat edu\_assist\_pro** res.
- Don't forget about the assignments!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Control Flow

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# if / else

---

- As with other imperative languages, the else is optional.
- Recall that this is not the case with Haskell!
- a complete if-then-else

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Boolean Conditions?

---

Mandatory.

**In C/C++ (and Elixir, with caveats):**

- Non-zero values are “truthy”
- Only 0/nil considered “falsy”

```
if (3.141592)
    cout << “Valid!” << endl;
```

**In Java (and Haskell, Rust):**

Conditions must be Boolean

```
1592)
.out.println(
    “Compile Error”);
```

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Converting non-Boolean to Boolean requires implicit conversion, which, as we’ve seen, Rust does not do.

# Boolean Conditions?

---

Mandatory.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Ah! But can we cast?

---

Nope.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# if / else if / else

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- As we'd expect, } even though there's only one per branch
- red.
- treats these as blocks whose last line can be an expression.

# if / else if / else

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# if / else if / else

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

- `let state = {...};` is a statement
- `{...}` is an expression that will evaluate to a string. `if == expression!`  
"n", "Liquid", or "Boiling"  
ion is in a scope block { }  
e of a scope block is the last expression
- Leaving the `;` off makes these strings expressions.

# if / else if / else

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Problem?

---

Assignment Project Exam Help

○ <https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

Might return float, might return int

**Remember:** Strong, static typing. No implicit conversion!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Looping

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Just like `while(true){}` in Java



# Conditional Looping: `while`

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Rust u

Add WeChat edu\_assist\_pro

other

ages.

=

```
Command Prompt

C:\_RustCode>main
1
2
3
4
5
6
7
8
9
10

C:\_RustCode>
```

# Conditional Looping: **for**

---

Similar to an enhanced for loop in Java:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Invoke iter() method of array nums
- **elem** takes the value of each element in the array.  
! Never go out of bounds.

# Conditional Looping: **for**

---

Use .. to create a range

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Create a *Range* containing 0 to **9**
- Top of range not included!
- Just like range() in Python

# Conditional Looping: **for**

---

Not as safe!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



- Here we must be careful
- Higher chance of accidentally overrunning array bounds

# A loop is a loop is a loop

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

***Wait, what?***

# Wait, what?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- We didn't specify the type of `i`, but shouldn't it default to `i32`?  
pe, `i32` should be default.
- Rust now signed integers to be indexes!
- It inferred the type as unsigned! Thus checking less than zero is pointless.

```
C:\_RustCode>rustc main.rs
warning: comparison is useless due to type limits
--> main.rs:8:12
8          if i < 0 { break; }
              ^^^^^
```

***Rust doesn't allow signed integers to be used as array indexes!***

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro




# Need to adjust our logic a bit...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro





**M** Assignment Project Exam Help **n...**

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Ownership

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Ownership

---

Arguably Rust's most unique feature:

- In C, the programmer is responsible for allocating and freeing memory. Memory leaks are common!
- In Java, garbage collection looks for unused memory and frees it.
- Rust takes a third approach: A system of ownership with rules checked at compile time.
  - Thus, the program is not slowed at run-time

# Reminder: Stack VS Heap

---

## Stack:

- Last in, first out
- Push/pop stack frames is fast
- Data has known, fixed size

## Heap:

- Less organized
- Slower access, follow pointers
- Size can be unknown

- If we dynamically allocate memory, a pointer goes on the stack, the memory itself is in the heap.
- Heap memory is allocated by the OS at the request of the program.
- Stack memory (some fixed amount) belongs to the program, no need to invoke the OS.

# Ownership

---

## Three rules:

1. Each value in Rust has a variable that's called its *owner*.
2. There can only <https://eduassistpro.github.io/>
3. When the owner goes out of scope value is dropped.

Add WeChat [edu\\_assist\\_pro](#)

# Scope in Rust

---

**This is normal, nothing new.**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Primitives stored on the stack behave as per usual.
- How does Rust clean up data stored on the heap?
- Consider Strings – A complex type stored on the heap.

# Strings

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- String literals are different from regular strings. Their size is fixed, encoded directly into the executable. Strings not defined as a literal don't have unknown size
- They are stored on the heap.

```
Command Prompt

C:\_RustCode>rustc main.rs

C:\_RustCode>main
Hello
Hello, World!
```

# Heap Strings

---

- Memory for string requested at run time.
- Memory must be returned to the OS when we're done with the string.

## Assignment Project Exam Help

- Call `new String()` to request a memory request.
- Once the string is no longer needed, call `String.intern()` to return the memory to the OS. In Java we would say:  
`String s = new String("hello");` accomplish the same.

What happens when we no longer need that string?



## What happens when we no longer need that string?

- Without garbage collection, we must identify when memory is no longer being used and free it explicitly.
- This has historically been a difficult programming problem.
- Too early, variable memory. Do it late, waste problem.
- We need to pair `malloc` with `free()`.

In Rust, memory is automatically returned when the variable that ***owns*** it leaves scope.

*In Rust, memory is automatically returned  
when the variable that owns it leaves scope.*

What about having multiple references to a single object?  
Freeing after one leaves scope invalidates the others. In Java:

**Assignment Project Exam Help**

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

**Three references, one object!**

# But Remember!

---

## Ownership - Three Rules:

1. Each value in Rust has a variable that's called its *owner*.
  2. There can only <https://eduassistpro.github.io/>
  3. When the owner goes out of scope, the value is dropped.
- Add WeChat edu\_assist\_pro

***There can only be one!***

*In Rust, memory is automatically returned when the variable that owns it leaves scope.*

- When a variable goes out of scope, Rust calls a special function automatically called **drop()**
- This function is called at the closing }
- What happens when variables interact

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
fn main()
{
    let x = 5;
    let y = x;
}
```

- With primitives, we get two separate variables stored in memory (stack)
- **x** and **y** are separate – changing one does not affect the other
- This is typical, and efficient

```
fn main()
{
    let s1 = String::from("Hello");
    let s2 = s1;
}
```




Assignment Project Exam Help

On the stack

<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

On the heap

```
fn main()
{
    let s1 = String::from("Hello");
    let s2 = s1;
}
```



## Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

- C data is more expensive.
- In most imperative languages.
- We can still potentially free data twice
- We can still potentially invalidate other references

1. Each value in Rust has a variable that's called its *owner*.
- 2. There can only be one owner at a time.**
3. When the owner goes out of scope, the value is dropped.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

1. Each value in Rust has a variable that's called its *owner*.
- 2. There can only be one owner at a time.**
3. When the owner goes out of scope, the value is dropped.

## Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- When we say `let s2=s1`,  
1 becomes invalid.  
Thus, when it leaves scope,  
memory is not freed.
- We can no longer use s1!



```
fn main()
{
    let s1 = String::from("Hello");
    let s2 = s1;
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/> we say s1 gets *moved* to s2

Add WeChat edu\_assist\_pro

In Rust, we say s1 gets *moved* to s2

Different from Python, since the  
old reference is invalidated.  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

Only one reference can free the heap memory.


# clone()

Like most languages, Rust can clone:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# clone()

---

Like most languages, Rust can clone:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Ownership and Functions

---

Passing an argument moves or copies, just like assignment:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Ownership and Functions

---

Passing an argument moves or copies, just like assignment:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Ownership moved from **s** to **word**!  
invalid!  
y different from any other  
e're used to.
- happen with primitives  
because they will simply be copied.
- We get a hint:

```
= note: move occurs because `s` has type `std::string::String`,  
which does not implement the `Copy` trait
```

# Returning Ownership

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Returning Ownership

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Ownership moved from **s** to **word** and back to **s**  
valid when we move to **word**  
invalid when moved to **s**  
because **s** is mutable.  
ing\_pass reaches }, **word**  
has already been moved to **s**
- Thus **word** is invalid and the string on the heap isn't freed.



# Returning Ownership

---

Limiting. Forced to use return value for ownership.

Assignment Project Exam Help  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

- `s1` moves to `word`, `word` moves to `s2` tuple consisting of the `word`, and `word` itself.
- `len` returns length of array.

```
Command Prompt

C:\_RustCode>rustc main.rs

C:\_RustCode>main
Weird has 5 characters

C:\_RustCode>
```

# Ownership: Moving VS Borrowing

---

Instead of returning a tuple, pass a reference:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- This looks like C++
- **word** is now a *reference* to **s1**
- What about ownership?
- What's happening in memory?

# Ownership: Moving VS Borrowing

---

word

s1

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- word is a reference to s1, it does NOT point to the string in the heap.
- word has no ownership over s1.
- We call this ***borrowing***.

# Ownership: Moving VS Borrowing

---

Unlike C++, we can't modify something we're borrowing:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



&String) -> usize

----- use `&mut String` here to make mutable

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

**word** is a mutable reference, borrowed from **s1**



# Borrowing Rules

---

Can only have one mutable borrow at a time:

Assignment Project Exam Help

---



<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

**When the first mutable borrow goes out of scope, we can borrow again**

# Borrowing Rules

---

Can only have one mutable borrow at a time:

Assignment Project Exam Help

• push\_str must make  
mutable borrow of s1  
not allowed!

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

*When the first mutable borrow goes out of scope, we can borrow again*

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro  
pe of r1

Scope of r2




*When the first mutable borrow goes out of scope, we can borrow again*

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



Here, **r3** is already a reference.  
We're not borrowing again.

# Borrowing Rules

---

Using an immutably borrowed value prevents mutable borrow:

```
fn main()
{
    let mut word = String::from("
    let r1 = &word;
    word.push_str(", or what?");
    println!("{}", r1);
}
```

Assignment Project Exam Help  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

# Borrowing Rules: In Short

---

**In any given scope, only ONE of the following can be true:**

1. We can have a single mutable borrow
2. We can have <https://eduassistpro.github.io/> mutable borrows

Add WeChat edu\_assist\_pro

These restrictions keep mutation under control

# Slices

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Slices

---

Reference to a subset of an array

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- We've seen this notation before!
- Remember that the second index is *not* included

# Slices, Arguments, Functions

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- **Reminder:** indexes must be **usize**
- Pass in reference to array
  - slice (reference to subarray)
  - only e memory
  - indices point to different parts of the same memory.

# String Slices


---

... are a little bit different.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



A screenshot of a Windows Command Prompt window titled "Command Prompt". The window has a black background with white text. The command prompt shows the following sequence of commands and output:

```
C:\_RustCode>rustc main.rs  
  
C:\_RustCode>main  
Hello  
World!  
  
C:\_RustCode>
```

Overlaid on the right side of the Command Prompt window is a yellow rectangular box with a black border containing the text "Normal so far".

# String Slice Type

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- &str is a reference to a string slice
- &String is a reference to a String
- String VS string slice: different types than that, the function works the same as with numeric arrays. A string slice is effectively a **read-only** view of a String.



# String Slice Type

---



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

Better to d

```
fn get_slice(w: &str, s: usize, e: usize) -> &str  
{  
    &w[s..e]  
}
```

Works for both Strings and string slices

# String Literals

---

## Recall:

- String literals are different from regular strings.
- Their size is fixed, ***encoded directly into the executable.***
- They are immutable.

In <https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

type of `msg` is `&str`

- It's a slice pointing to a specific point of the binary file.
- This is why string literals are immutable!

# Lifetime


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Rust Features

---



Assignment Project Exam Help

Memory Safety

*to be memory safe  
pointers are not*

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

# Dangling References

---

Rust prevents them:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- s goes out of scope when dangle function ends.
- What happens to the reference that was returned?

# Dangling References

---

Rust prevents them:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Lifetime?

# Lifetime is a very distinct feature of Rust:

Every reference in Rust has *lifetime*

The lifetime of a reference is the scope for which it is valid.

Lifetimes are typically inferred, but can be defined explicitly

Just like variable types!

# Example

---

- **r** is a reference to **x**
- **x** goes out of scope while **r** is still referring to it!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# The Borrow Checker

---

- The Rust compiler has a “Borrow Checker” that compares scope to determine if borrows are valid
- If one variable borrows a value that is already being borrowed must have a lifetime at least as long as the borrowing.

Add WeChat edu\_assist\_pro

What happens if the borrow checker gets confused?

# Generic Lifetimes

---

Consider:

Assignment Project Exam Help

gram:

<https://eduassistpro.github.io/>

Add WeChat: edu\_assist\_pro

It accepts two string slices,  
the slice that is longer.

Both slices are just references

- There's no ownership changing here
- No moves

# Generic Lifetimes

---

Consider:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Generic Lifetimes

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

The Borrow Checker can't determine lifetime of the return value, because it's not clear which input argument the return value will borrow from.

**More generally:** The borrow checker follows certain patterns when determining lifetime. If none of its patterns apply, we get a lifetime error.

# Generic Lifetimes

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- We as programmers know that this function is perfectly safe.
- ...er to string literals which live ...ire d ...e program.
- What's obvious to us is not necessarily obvious to the compiler.
- Thus, we get compile errors.

# Generic Lifetimes

---

It even happens when the return reference is fixed:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Lifetime Annotation Syntax

When the borrow checker is confused (for whatever reason), we must be specific:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

generic lifetime

generic type:  $\langle T \rangle$

es a generic lifetime, a

is reference has lifetime a



Command Prompt

```
C:\_RustCode>main  
abcde
```

```
C:\_RustCode>
```

# Generic Lifetimes

---

## What does mean precisely?

- The function accepts two arguments
- Both live at least as long as lifetime **a**  
  the string slice returned will live  
  long as lifetime **a**
- Now what **a** is, just that both  
  the return value have the  
  same lifetime.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Generic Lifetimes

---

## However!

- We're **NOT** actually changing any lifetimes! We're just explicitly indicating them to help the Borrow Checker.

<https://eduassistpro.github.io/> checker will reject any values that do not conform to these constraints.

Assignment Project Exam Help

Add WeChat edu\_assist\_pro

**So how can we  
break this?**

# Consider

---

- Lifetime of **s1** is different from **s2** and **s3**.
- Lifetime of **a** is the scope in which **x** and **y** are valid when **s1** and **s2** are valid.
- **s3** is something that is valid until after the last time **s3** is used.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Now This:

- Here, lifetime **a** excludes a reference made by **s3**
- **s3** references something that *might* be out of scope (**s2** will be, **s1** won't be)
- When we last use **s3**, **s2** is no longer valid.   
it doesn't matter, because **s1** and **s2** as string slices.
- Slices are **add** and thus references to them will always be valid.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

**Oops. Let's try again with  
Strings instead...**

Command Prompt

```
C:\_RustCode>rustc main.rs
```

```
C:\_RustCode>main  
abcde
```

## Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Lifetime Considerations

---

In general, we need some sort of lifetime indication any time we're passing in more than one reference and returning a reference.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

eit pointless

Add WeChat edu\_assist\_pro

```
fn sum_len (x: &str, y: &str) -> usize
{
    x.len() + y.len()
}
```

As is this

# Lifetime Considerations

---

Originally, every reference required a lifetime specifier.

The Rust developers noticed some cases of reference passing were always the same, and thus added annotations to help the compiler to recognize them without requiring lifetime annotations.

Add WeChat edu\_assist\_pro

```
fn sum_len (x: &str, y: &str) -> usize
{
    x.len() + y.len()
}
```

```
fn first (x: &str) -> &str
{
    x
}
```

# Lifetime Considerations

---

The compiler first checks its list of known patterns

Assignment Project Exam Help

If none are found, we <https://eduassistpro.github.io/> ch as we've been seeing

Add WeChat edu\_assist\_pro  
What are theses ?

# Lifetime Inference Rules

---

1. The compiler first assigns a *different* lifetime to each reference input parameter.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat  edu\_assist\_pro

```
fn sum_len<'a, 'b> (x: &'a str, y: &'b str) -> usize
{
    x.len() + y.len()
}
```



# Lifetime Inference Rules

---

1. The compiler first assigns a *different* lifetime to each reference input parameter.
2. If there is ~~one~~ **Assignment Project Exam Help** input reference parameter, it is assigned the same lifetime as any

<https://eduassistpro.github.io/>

```
fn first (x: &str) -> &str
{
    x
}
```

**Is seen as:**

Add WeChat edu\_assist\_pro

# Lifetime Inference Rules

---

1. The compiler first assigns a *different* lifetime to each reference input parameter.
2. If there is **one** input reference parameter, it is assigned the same lifetime as any
3. If there are multiple input reference parameters and one of them is **&self**, then the output references have lifetime as **&self**.

If, after applying these rules, there are still references *without* a lifetime specifier, we get a compile error.

*If, after applying these rules, there are still references without a lifetime specifier, we get a compile error.*

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

We don't get errors here, because applying rules 1 and 2 results in all references having annotated lifetimes

We get an error here, because even after applying all three rules, we still don't have a lifetime annotation for the output:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
fn first<'a,'b> (x: &'a str, y: &'b str) -> &str {
    {
        x
    }
}
```

1. The compiler first assigns a *different* lifetime to each reference input parameter.

There is **one** input reference

parameter, it is assigned the same lifetime as any output references.

If there are multiple input references, but one of them is **&self**, then the output references have the same lifetime as **&self**.

**Rule 1 applies, Rules 2 and 3 do not**

We get an error here, because even after applying all three rules, we still don't have a lifetime annotation for the output:

- No lifetime annotation after applying rules.
- compile error.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
fn first<'a,'b> (x: &'a str, y: &'b str) -> &str
{
    x
}
```

```
Command Prompt
C:\_RustCode>rustc main.rs
error[E0106]: missing lifetime specifier
  --> main.rs:17:45
17 | fn first<'a,'b> (x: &'a str, y: &'b str) -> &str
    |                                           ^ expected lifetime parameter
```

# Static Lifetime

---

- A special lifetime that is simply the duration of the program.
- String literals have a static lifetime.
- Makes sense, they're not on the heap but embedded in the executable

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Static Lifetime

---

- You might get error messages suggesting you use static lifetime.
- Be careful doing so. Does your reference really need to live for the duration of t
- It's a lazy solution to avoid using pointers or references of global variables

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Fantastic Rust Reference:

Assignment Project Exam Help

<https://doc.rust-lang.org/second-edition/>

Add WeChat edu\_assist\_pro



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro