

C/CPS 506

Assignment Project Exam Help

Compara

Languages

<https://eduassistpro.github.io/>

Prof. Ale

Add WeChat edu_assist_pro

Topic 6: Type systems, pure functional with Haskell

Notice!

**Obligatory copyright notice in the age of digital
delivery and online classrooms:**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

The copyright to this work is reserved by Alex Ufkes. Students registered in course CCPS 506 can use the work for the purposes of this course but no other use is permitted, and there can be no sale or transfer or use of the work for any other purpose without explicit permission of Alex Ufkes.

Course Administration

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Elixir assignment

9

Today

Type systems: Assignment Project Exam Help

<https://eduassistpro.github.io/>

Intro to Has Add WeChat edu_assist_pro

- Pure functional
- Typing in Haskell

Assignment Project Exam Help
Ty <https://eduassistpro.github.io/> **ms**
Add WeChat edu_assist_pro

Type System

- A set of rules that assigns a property called **type** to constructs of a program.
- These constructs include variables, functions, expressions, etc.

<https://eduassistpro.github.io/>

The whole point is to reduce bu

- For example, if a pattern of 32 bits is encoded using 2s complement, we don't want to read it using IEEE 754
- And we *can* do this in many languages!

Declare large 64-bit integer



Assignment Project Exam Help

<https://eduassistpro.github.io/> int as int, print as double

Add WeChat edu_assist_pro

- The 2s comp bit pattern was read as an IEEE 754 double.
- (The integer constant was deliberately picked to produce a bit pattern that would yield 1.000000 as double)

Type Checking

Clearly, type checking isn't performed in the context of a `printf` statement in C++

Assignment Project Exam Help

- Think of type <https://eduassistpro.github.io/> puzzle pieces together.
- Does the output type of a function match the variable we're trying to store it in?
- Do the input arguments to a function match the types indicated in the parameter list?
- If no, will we allow implicit conversion?

Add WeChat edu_assist_pro

Static VS Dynamic

When are types checked?

Statically typed languages perform type checking at *compile time*

- Checked while converting source code to machine (or byte) code

Dynamically typed languages perform type checking at *run-time*

- Checked on the fly while instructions are executed.

Statically Typed languages: C/C++, Java, Haskell, Rust

Dynamically Typed languages: Python, Smalltalk, Elixir

Static Type Checking

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



```
incompatible types: java.lang.String cannot be  
converted to double
```


- In dynamically typed languages, every operation knows the types for which it is valid.
- Providing invalid arguments or operands will yield a run-time error that can be recoverable
- Such things can be anticipated and mitigated in various ways, such as verifying explicitly

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Dynamic Type Checking



```
factorial: n  
  | fac |
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

```
ifTrue: [1  
  [:a | fac  
    ^fac  
  ]  
ifFalse: [  
  ^'Bad input'  
  ].
```

- In Java, the parameter would be defined as **int**
- Compile error if arg isn't **int**, or 't be implicitly cast as an **int**.

Add WeChat edu_assist_pro


- Of course, polymorphism in Java complicates this.
- Still statically typed.

Dynamic Type Checking...?

`#(1 2 3 4) + 18.2`

- Does Smalltalk have type errors in the strict sense?
- Different objects send different messages.
- A “type error” doesn’t have a method to handle a particular message.
- “Type” errors in Smalltalk are as a result of not finding a method (DNU, Did Not Understand).
- Above, the error occurs because the Array class doesn’t have an instance *method* for symbolic operator `#+`
- Smalltalk enthusiasts debate this.

Dynamic Type Checking



```
defmodule UserMath do
```

```
  def fib(n) when not is_integer(n) or n < 0 do  
    :error  
  end
```

```
  def fib(n), do: fib(n-1)
```

```
  def fac(n) when not is_integer(n) or n < 0 do  
    :error  
  end
```

```
  def fac(0), do: 1  
  def fac(n), do: n*fac(n-1)
```

```
end
```

Static VS Dynamic

Advantages? Disadvantages?

Static:

- Reliably find errors at compile time.
- Code will execute faster
assumed to be correct at run time.
- Type-specific optimization can be performed at compile time.
- I.e., integer arithmetic is faster than floating point

Dynamic:

- Interpreters run faster
in dynamically loaded code
- Easier code reuse
 - Smalltalk, MATLAB, iex

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Static VS Dynamic

Advantages? Disadvantages?

- There is much disagreement among programmers about just how much of a problem and scheme of things.
- Does the added cost of statically typed language make sense if type-related bugs are a small fraction?
- Of the type-related bugs that occur, what portion of those would have been solved by a type checker anyway?
- They aren't perfect after all.

Strong VS Weak Typing

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Strong VS Weak (or *Loose*)

Refers to how strict statically typed languages are at compile time

There is actually no universally accepted definition of what
co typing

<https://eduassistpro.github.io/>

Of strongly typed

Add WeChat edu_assist_pro

1974: "Whenever an object is passed to a called function, its type must be **compatible** with the type declared in the called function."

Compatible is open to interpretation. Is float compatible with double? Integer with short integer?

Strong VS Weak (or *Loose*)

Refers to how strict statically typed languages are at compile time

1974: "Whenever an object is passed from a calling function to a called function, its type must be compatible with the type of the function."

1977: "In a strongly typed language, each data area will have a distinct type and each process will state its ***communication requirements*** in terms of these types."

Parameter lists, return types, etc.

Strong VS Weak (or *Loose*)


To what degree does a statically typed language allow implicit type conversion?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- C is weakly typed.
- Happy to perform all manner of implicit conversion without warning or error.



Strong VS Weak (or *Loose*)

In C, pointer arithmetic can be used to ***completely bypass*** the type system:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: edu_assist_pro

- We're using pointer arithmetic to read the first 2 bytes of an **int** as a **short**.
ne with any two types.
he rightmost 4 by
- We can treat memory any way we want

quincy

15651

Press Enter to return to Quincy...



Strong VS Weak (or *Loose*)

C++ will give warnings where C did not, but still compiles and runs in this case:


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A screenshot of a Visual Studio console window. The window has a blue title bar and a dark background. The text in the console is as follows:

```
uration: Debug Win32 -----  
warning C4244: 'initializing' : conversion from 'double' to 'int', possible loss of data  
est\Debug\test.exe  
to-date, 0 skipped =====
```



Strong VS Weak (or *Loose*)

Java will throw compile errors when a *loss of precision* occurs:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- No implicit promotion from floating point to integer
- Floating point constants are double precision
- Need to indicate single precision explicitly

Java will throw compile errors when a loss of precision occurs:

Careful! Loss of precision does not **only** occur when going from floating point type to integer type!

Assignment Project Exam Help


int is 32 bits two'

float is a 23-bit

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

32-bit:



Imprecision of Floating Point

- Integers are represented *precisely*. The integer 42 is **exactly** 42.
- The single-precision (32 bits) floating point value 0.1 is **actually** 0.100000001490116119384765625
- *Double*-precision values are more accurate, but still not perfect

Assignment Project Exam Help

Add WeChat edu_assist_pro

But why?

- Floating point values exist on an infinite continuum.
- Between any two floating point values are an ***infinite*** number of additional floating point values.
- Integers are discrete. Between any two integers are a ***finite*** number of integers.

Imprecision of Floating Point

- A double-precision float is represented using 64 bits.
- A *finite* number of bits cannot represent an *infinite* number of floating point values.

Assignment Project Exam Help

010010111000001010001

<https://eduassistpro.github.io/>

1011000110001110000011

Add WeChat edu_assist_pro

- There are 2^{64} ways to arrange 64 bits. A large number to be sure, but certainly not infinite.

Infinite Integers?

But there are an infinite number of integers!

- 100% correct. We can't represent every possible integer either.
- Rather, there is integer has a range of $-2,147,483,648$ to $2,147,483,647$.
- Every integer within this range is represented precisely.
- Anything outside this range can't be represented using 32 bits.
- If we try, we overflow.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

IEEE-754

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Functional Programming

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


Functional Programming

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Functional Programming



Higher-order functions:

- Can return functions or accept them as arguments.

F

- <https://eduassistpro.github.io/> returned as values.
- Think of them as values, just like integers or floats

Add WeChat edu_assist_pro

Pure Functions:

- Functions that have no side effects. No interaction with world outside of local scope
- Easier to verify correctness, thread-safe when no data dependency is present.

Pure
function

Impure
function

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Functional Programming

Strict (eager) VS. non-strict (lazy) evaluation:

- Strict: evaluate function arguments before invoking the function.
- Lazy: Evaluates arguments if their value is required to invoke the function.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



**Elixir largely performs strict evaluation
(some exceptions, recall Stream, Range)**

Functional Programming


Strict (eager) VS. non-strict (lazy) evaluation:

- Strict: evaluate function arguments before invoking the function.
- Lazy: Evaluates arguments if their value is required to invoke the function.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



<https://www.haskell.org/>

A great intro to Haskell syntax

Haskell: Functional Programming cranked up to 11

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

History

- Named after logician Haskell Curry
interest in lazy functional programming
- There is a growing consensus to define an operator for such languages

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

History

- Haskell 1.0 was defined in 1990
 - Continued with version 1.1, 1.2, 1.3, etc.

Assignment Project Exam Help

○ Culminated with *Haskell 98*

published in July 2010

<https://eduassistpro.github.io/> controversial features

pre led via compiler flags

Add WeChat edu_assist_pro

- Next version worked on – Haskell 2020
 - Though progress seems to have stalled
 - Perhaps it should be called Haskell 202X

Features

Purely Functional:

- Every function is *pure*
- Even side-effect inducing operations are

<https://eduassistpro.github.io/>
e code
only expressions

- Cannot have variables (local or global)
- Support for attaching
- Side effects are handled using *monads*

Features

Statically Typed:

- Every expression has a type

Assignment Project Exam Help

- Determined at compile time

g an expressions must match

<https://eduassistpro.github.io/>

file error

Add WeChat edu_assist_pro

Type Inf

- Types don't have to be written out explicitly
 - Though you can if you want
- They will be inferred at compile time

Features

Lazy Evaluation:

- Functions don't evaluate their arguments

Assignment Project Exam Help

- Control constructs written as functions

ins of functions together
<https://eduassistpro.github.io/>
ver takes place unless a

result
Add WeChat edu_assist_pro

Concurrency:

- GHC (Haskell compiler) includes high performance parallel garbage collector
- Light-weight concurrency library

Haskell in Industry?

Assignment Project Exam Help

https://wiki.educassesspro.github.io/haskell_in_industry
Add WeChat edu_assist_pro

Notable companies that use or have used Haskell:

- Nvidia
- AT&T
- Ericsson
- Facebook
- Google
- Intel
- Microsoft

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Typically Haskell is used on specialized internal projects or research. Not necessarily company-wide.

Installing Haskell:

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Neat!





Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

WinGHCi
Desktop app

 winghouse tampa

Assignment Project Exam Help

- <https://eduassistpro.github.io/> just like Elixir.
- Haskell's i Add WeChat edu_assist_pro

Hello, World!

```
Prelude> main
Hello, World!
Prelude>
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
putStrLn == System.out.println()
putStr == System.out.print()
```

define a main function.

When executing a Haskell

program, main is the entry point

- Just like C or Java

Execute main function

Compiling Haskell

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Notepad++ features Haskell
syntax highlighting!



Assignment Project Exam Help

As with E and in the
interactive shell until it tedious.

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Literals & Arithmetic

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Divi

floating point

Literals & Arithmetic



Tuples

Assignment Project Exam Help

- sorts tuples.
- <https://eduassistpro.github.io/> the same types.

Add WeChat edu_assist_pro

There are functions for accessing first and second elements. Great for coordinates.

fst and **snd** only
work on pair tuples!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Lists

Must be *homogeneous*:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

r literals get
floating point

do not

Lists

Elements can be added to the *beginning* of a list with the **cons** (:) operator

Assignment Project Exam Help

<https://eduassistpro.github.io/>

list

Add WeChat edu_assist_pro

and an empty list

In fact, when we write **[1, 2, 3]** the compiler is actually doing **1:2:3:[]**
[1, 2, 3] notation is *syntactic sugar*.

Lists & Tuples

Tuples can be heterogeneous, lists must be homogeneous.

Assignment Project Exam Help
However: We can have lists of tuples,
each tuple is heterogeneous.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Lists & Tuples

Tuples can be heterogeneous, lists must be homogeneous.

Assignment Project Exam Help

However #2:

of tuples, each tuple
ve the same format:

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Strings

Strings are simply lists of chars:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

We can **cons** chars into an empty list to form a string

We can concatenate strings using the ++ operator

Strings

Concatenate multiple types? Java lets us...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Strings

show() and **read()** functions

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Convert non-string
argument to string

Add WeChat edu_assist_pro

Read numeric

a string (like *sscanf* in C)

Error when no numeric value is present

Operations on Lists

- In functional programming, computation is done in large part by operating on lists.
- We say `fold` in Elixir.
- Haskell <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Three primary list-processing functions: **map**, **filter**, **foldr** (and **foldl**)

Head & Tail

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

ir:

• returns the first element

• the rest, as a list

• any cases:

○ Single element lists

○ Empty lists

map

Similar to Elixir's `Enum.map`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Add WeChat edu_assist_pro
- First class function, does what the name suggests.
 - Alphabetical characters are upped, everything else is left the same.

Recall: map operates on lists, but a string is just a list of characters

map

Similar to Elixir's `Enum.map`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Map takes two arguments **A function**, and **a list** of values to which the function is to be applied.

A diagram consisting of two arrows. An orange arrow originates from the text 'A function' (which is circled in orange) and points to the URL 'https://eduassistpro.github.io/'. A blue arrow originates from the text 'a list' (which is circled in blue) and points to the text 'Add WeChat edu_assist_pro'.

filter

“Remove” items from a list based on some criteria:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Function

List

foldl, foldr

Replaces the cons operator with some other function. This takes some explaining.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro
Is actually s

1:2:3:4:5:[]

By the compiler.

foldl, foldr

Replaces the cons operator with some other function. This takes some explaining.

Recall that the list:

[1, 2, 3, 4, 5]

Is actually seen as:

1:2:3:4:5:[]

By the compiler.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

replaces the cons operator

with a function of our choosing.

- This is **Enum.reduce** in Elixir.
- The empty list is replaced with some initial value.

foldl, foldr

Replaces the cons operator with some other function. This takes some explaining.

- **foldr** in effect replaces the cons operator with another function.
- This is similar to <https://eduassistpro.github.io/> Elixir.
- The empty list is replaced by the initial value.

foldr (+) 0 [1, 2, 3, 4, 5]



Three arguments: **function**, **initial value**, **list**

foldl, foldr

Replaces the cons operator with some other function. This takes some explaining.

`foldr (+) 0 [1, 2, 3, 4, 5]`

<https://eduassistpro.github.io/>

`foldr (+) 0 :5:[]`

`1 + 2 + 3 + 4 + 5 + 0`

`15`

foldl, foldr

Assignment Project Exam Help

<https://eduassistpro.github.io/>

120
Prelude>

Add WeChat edu_assist_pro

foldr to perform factorial!

foldl VS foldr

foldr is *right associative*. Meaning:

`foldr (+) 0 [1, 2, 3, 4, 5]`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

1 + 2 + 3 + 4 + 5 + 0

Add WeChat edu_assist_pro

Is actually:

$(1 + (2 + (3 + (4 + (5 + 0)))))$

Doesn't matter for addition, but subtraction...

foldl VS foldr

foldr is *right associative*. Meaning:

`foldr (-) 1 [4, 8, 5]`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

4 - 8 -
Add WeChat edu_assist_pro

Is actually:

$(4 - (8 - (5 - 1)))$



0

foldl VS foldr

foldl is *left associative*. Meaning:

`foldl (-) 1 [4, 8, 5]`

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Is actually:

$((1 - 4) - 8) - 5$

-16

foldl VS foldr

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

List Generation

Syntactic sugar:

List declaration: `list = [1, 2, 3, 4, 5, 6, 7, 8, 9]`

Can be written: <https://eduassistpro.github.io/>

Specify interval: `list = [1, edu_assist_pro
= [1, 3, 5, 7, 9]`

Interval is discerned from difference between first two elements

Infinite Lists?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Try it, but be ready
to interrupt

Infinite Lists?

Assignment Project Exam Help

Haskell is lazy!

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Why? How?

ind x to the expression
nerate an infinite list.

n't have to *evaluate*
to do so!

- Displaying the list, however, requires evaluation.

Infinite Lists?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Finding the length of the list requires counting the elements.
- Be ready to interrupt.

- Grab first three elements of list
- Doesn't matter if infinite, we're only evaluating first three items

Infinite Lists?

We're allowed to perform operations on a *finite subset* of an infinite list.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- **zip** “zips” two lists together into tuples.
- If one list is finite, the other can be infinite.

Types in Haskell

Statically Typed:

- Haskell uses static type checking.
- Every expression is assigned a type.
- If a function type, a compiler expects

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Type Inference

- Like Python, and unlike Java, we need not specify type.
- It is inferred by the context: `X = "Hello"`, `X` is a string.
- However, we can explicitly specify types.
- Good practice when we know what types we want; compiler will give errors upon type mismatch.

Types in Haskell

`:t` can be used to reveal type:

Assignment Project Exam Help

<https://eduassistpro.github.io/> of **Num** type class.
1.0 of **Fractional** type class.

Add WeChat edu_assist_pro

- 'a' is a **Char**
- "Hello" is a **[Char]**
- **[Char]** = **String**
- `t` is a **Bool**

Num p => p ?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

p is a *type* *v* e value can be any
type in type integer, Float, etc.)
Add WeChat edu_assist_pro

- Haskell is free to treat 7 as it sees fit, so long as it does so in a way that adheres to the operations defined in type class **Num**.

Typeclasses?

Assignment Project Exam Help

<https://eduassistpro.github.io/> types as generic as possible

- If we explicitly declare a variable as integer, it can't be passed to a function requiring float.
- However, if we generically infer it to be a **Num**, it can be used anywhere any other member of Num is allowed.

Types in Haskell

We can explicitly indicate types:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
Prelude> :t 5::Int
5::Int :: Int
Prelude> :t 5.0::Double
5.0::Double :: Double
Prelude> |
```

- Us a type
- My advice for you is to start by letting the inference engine figure it out.
- **At this point, it knows better than you.**


Types in Haskell

We can explicitly indicate types:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



When defining a name, can
indicate type explicitly:

Type Classes

Type polymorphism and type variables:

Recall: Overloading

- In languages that support overloading, functions can be defined for different types.
- Numeric type equality and inequality are performed differently.
- In general, if we want to compare two values of type α , we use an **α -compare**
- α is a *type variable*, because its value is a type.

Type Classes

Consider the equality (==) operator:

Takes two parameters, each of the same type (call it α), and returns a Boolean

This operator <https://eduassistpro.github.io/> pes, just some.

Add WeChat edu_assist_pro

Thus, we can associate == with a specific ***type class*** containing those types for which == is defined.

This type class is called **E_q** in Haskell.

Eq Type Class

(==) is defined for types in typeclass **Eq**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- `(==)` takes two arguments of type `a`, where `a` is a type class `Eq`
- It returns `Bool`

- If a concrete type, **a**, belongs to a certain type class, we say **a** is an *instance* of that type class.
- **Int** is an instance of **Eq**, for example.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Num Type Class

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- This allows numbers freedom to be an integer or floating point as the compiler sees fit.
- **Num** class contains all numbers, and certain operations over them such as addition.

Num Type Class

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- **p** is a variable
- The type of 5 is **p**, and **p** is a member of type class **Num**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Show Type Class

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

The members of the **Show** class have functions which convert their value to a String.

Function Types

Assignment Project Exam Help

← <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

`tail` containing type **a**,
and returns a list containing type **a**

a and **b** can be *literally any type*!

Function Types

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Same as [Char]

- `thing` returns ***IO action***.
- `function`
- `ut, IO()` is output.
- More on IO actions later.

We'll create our own types soon, and see how to
add them to our classes.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Functions in Haskell

As expected of a pure functional language, functions are central in Haskell

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

If we're compiling our code into an executable, we need a main.

- If we're using the GHCi shell, we don't.

Functions in Haskell

Let's start simple:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Define function called **square**
that takes one argument **x**

Squa $\rightarrow x \rightarrow x * x$, where
x is the input argument

Functions in Haskell

Let's start simple:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

function square
typical fashion

Functions in Haskell

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Functions in Haskell

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

19

Prelude>

Passing in four args

Functions in Haskell

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat: [edu_assist_pro](#)

- that we're doing and adding)... **square** and
- Haskell determined that input and output type should be instances of typeclass **Num**.
 - **(+)** and **(*)** are both defined for all types in typeclass **Num**.

Haskell Modules

This is getting tedious to type interactively.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Let's create a module!
Add WeChat edu_assist_pro

- Similar to modules in Elixir
- We can load the module in GHCi
- Access its functions and expressions

Loading a Module



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



When we make changes to Test module, can reload with 1 click!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Loading a Module

Use **:load** in terminal GHCi:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Use **:reload** for previously
loaded module



Control Structures

if then else

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

1 f 67

1

Prelude> f 0

1

Prelude> f (-6) ←

0

Prelude> f -6 ←

- Brackets required around negative arguments
- Otherwise it thinks you're subtracting 6 from f

<interactive>:203:1: error:

- Non type-variable argument in the constr

aint Num (a -> p)

Control Structures

`if then else if then else`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Here we have a function named `isZero` that takes one argument `x`

- 0 if `x` is 0

- If/else construct in Haskell is similar to most other languages.
- It must include a **then** and an **else**

Control Structures

`if then else if then else`


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro




We can now format across multiple lines.
HOWEVER: Indentation matters in Haskell!



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Indenting in Haskell

Assignment Project Exam Help



<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

show
begin

part of some expression
indented further than the
next expression

<https://en.wikibooks.org/wiki/Haskell/Indentation>

If all that weren't enough, Tabs don't work properly unless you use them exactly.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell Tutorials/References:

Assignment Project Exam Help
<https://en.wikiboo> [ther_Haskell_Tutorial](https://en.wikiboo)
<https://eduassistpro.github.io/>
<http://cheatsheet.codeslo> Add WeChat edu_assist_pro [Heatsheet.pdf](http://cheatsheet.codeslo)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro