

# C/CPS 506

Assignment Project Exam Help

Compara

Languages

<https://eduassistpro.github.io/>

Prof. Ale

Add WeChat edu\_assist\_pro

**Topic 9:** Rust intro & typing

# Notice!

---

**Obligatory copyright notice in the age of digital  
delivery and online classrooms:**

**Assignment Project Exam Help**

**<https://eduassistpro.github.io/>**

*The copyright to this work is reserved by Alex Ufkes. Students registered in course CCPS 506 can use the work for the purposes of this course but no other use is permitted, and there can be no sale or transfer or use of the work for any other purpose without explicit permission of Alex Ufkes.*

# Course Administration

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

- Getting closer! Rust **Add WeChat edu\_assist\_pro** language.
- Don't forget about the assignments!

# Moving on...

Assignment Project Exam Help  
**erative.**

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Rust is an imperative language. How see many cool features  
that remind us of the functional languages we've seen.


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Rust History

---



- Grew out of a personal project by Mozilla employee Graydon Hoare in 2006
- Started sponsoring the project in 2009

<https://github.com/eduassistpro/eduassistpro>

- Rust.com fully tested in 2011
- Pre-alpha used in 2012
- Rust 1.0, the first stable release, arrived on May 15, 2015
- Youngest language we've seen so far
- Open source

# IEEE Developer's Survey 2018

---

% using who want  
to keep using

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Also #1 in 2017 and 2016!

# In Industry?

---

## Mozilla in collaboration with Samsung

- Parallel web browser engine

## Dropbox

- Magic Pocket file system, peta machines


## Tor (The Onion Router)

- Experimenting with porting to Rust (from C) for safety features.



# Rust Features

---



## Systems Programming Language:

Assignment Project Exam Help  
In contrast with application languages.


<https://eduassistpro.github.io/> includes things like  
operating system, utility software,  
device drivers, compilers, linkers, etc.

Add WeChat edu\_assist\_pro

- System languages tend to feature more direct access to physical hardware of a given machine.

# Rust Features

---



## Syntax:

- Similar to C/C++
- Limited by { }
- Structures supported (if, else, for, etc.)
- Support matching! (match)
- Need not use return, last expression creates return value
- Functions largely composed of expressions


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Rust Features

---



## Memory Safety:

Assignment Project Exam Help

- Rust is designed to be *memory safe* pointers are not permitted.

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

*“Null or dangling pointers are not permitted”*

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- In C, we're allowed to try and access any memory we want.
- This code compiles!  
roduces a run-time error when index into pointer x.
- Checking array bounds does not necessarily give a run time error!
- Very unsafe use of memory.

*“Null or dangling pointers are not permitted”*

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Java is safer.
- This code *compiles*, but **always** throws an exception when we access outside array bounds.  
/C++ only errors if going out of bounds
- `nums1` accesses memory that your program doesn't have write permission for.
- Java still allows dangling references.
- `nums2` can be created without instantiating its object.

# Rust Features

---



Assignment Project Exam Help

Memory Safety

to be *memory safe*

<https://eduassistpro.github.io/>

pointers are not permitted.

What lists? Null pointers are useful.  
Add WeChat edu\_assist\_pro


- Rust d *tion* type, which can be used

to test if a pointer has *Some* value or *None*

- What does this remind you of?

# Rust Features

---



## Memory Management:


- Rust does not do garbage collection  
*ition is initialization*

<https://eduassistpro.github.io/>

- Constr to acquire and initialize objects
- Resou tion is done by the destructor.
- No valid reference to object == no object.
- Not so in Java! Up to garbage collector.

# Rust Features

---



## Types and Polymorphism:

Assignment Project Exam Help

- Type system supports mechanism called

<https://eduassistpro.github.io/>

by Haskell's type class


Add WhatsApp [edu\\_assist\\_pro](https://eduassistpro.github.io/) for variables  
declared with **let** keyword.

- Compile error if inference fails.
- Keyword **mut** for mutable variables.



# Rust Features

---



Assignment Project Exam Help

Pattern Matching:

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

- We alr

Pattern matching!


g is considered a

people learning Rust.

xperience with it

# Rust & Safety

---




## Strongly, statically typed

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Strong typing means limited implicit type convert between numeric types. Perhaps a compile warning in C++.
- Java raises compile error if there's a loss of precision (double to float for example).




```
int main(void)
{
    int x = 3.14159;
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro




Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Rust & Safety

---




## No “Undefined Behavior”

- Null pointer dereferencing  
dereference address 0


Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Rust & Safety



## No “Undefined Behavior”

- Null pointer dereferencing  
dereference address 0  
before it's initialized  
whatever was in  
re that.
- In
- Only globals auto-initialize to 0

<https://eduassistpro.github.io/>


Add WeChat edu\_assist\_pro

```
Quincy 2005 - [Text1 *]  
File Edit View Project Debug Tools Window Help  
int x;  
int main(void)  
{  
    int y;  
    printf("%d\n%d\n", x, y);  
}
```

```
quincy  
0  
4199232
```

# Rust & Safety

---



## No “Undefined Behavior”

- Null pointer dereferencing
  - dereference address 0 before it's initialized
  - whatever was in there that.
- Only globals auto-initialize to 0
- Array index out of bounds
  - May or may not cause runtime error (in C), depends who owns memory

Assignment Project Exam Help


<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Rust & Safety

---



## No “Undefined Behavior”

- Signed integer overflow & optimization


<https://eduassistpro.github.io/>

Add WeChat: edu\_assist\_pro

- If overflow is fired, compiler can just optimize this to simply **true**.
- Dangerous if X can overflow!
- Forcing compiler to consider overflow means we lose certain optimizations.

# Rust Non-Goals

---



- We do not employ any particularly cutting-edge technologies. Old, established techniques are better.
- We do not prize expressiveness, minimalism or elegance above other goals.
- We do not imitate the feature-set of C++, or any other language. Rust should have majority-case features.
- We do not intend to be 100% safe, 100% reflective, or too dogmatic in any other sense. Trade-offs exist.
- We do not demand that Rust run on “every possible platform”. It must eventually work without unnecessary compromises on widely-used hardware and software platforms.



# Installing Rust


<https://www.rust-lang.org/en-US/index.html>

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro





# Installing Rust

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Editing Rust Code

---

Any text editor will do, but I like VSCode:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Visual Studio Code:

- Supports Rust syntax coloring
- Useful for other languages

# Compiling Rust Code

---

Command Line - **rustc**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

← Add WeChat edu\_assist\_pro

<https://www.rustaceans.org/>

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



Much of the syntax is reminiscent of C/C++

```
fn main() {  
    print("world!");  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Like C, C++, Java, Haskell, and many others, `main()` defines the entry point for executing a Rust program.

```
fn main() {  
    print "world!";  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## println vs print!

- The ! indicates we're calling a macro.
- A standard function call doesn't include !

# Variables

---

- By default, Rust variables are immutable
- Once initialized, can't change.
- Like `final` or `const` in other languages
- Declare using

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
fn main() {  
    let x = 7;  
    println!("value: {}", x);  
}
```

```
fn main() {  
    let x = 7;  
    println!("value: {}", x);  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Curly brace pair in a println string acts  
as a C/C++ style placeholder

# Variables

---

```
fn main() {  
  let x = 7;  
  x = 5;  
  println!("value: {}", x);  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Mutable Variables

---

Use **mut** keyword:

```
fn main() {  
    let mut x = 7;  
    x = 5;  
    println!("value: {}", x);  
}
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- We get a warning, and it's sensible.
- We change the value of x before the initial value is ever read.
- Pointless.

# Constant/Global Variables

---

Rust still has them:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

`const` instead of `let`

is immutable

is declared in global

, unlike `let`

- Must indicate data type (u32)
- More on types coming up.

# Constant/Global Variables

---

Can be declared in global scope, unlike `let`

Assignment Project Exam Help

← <https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Shadowing

Variables with the same name?

In Java, variables can have the same name so long as their scope does not overlap:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

**BAD**

```
int r = 10;
{
    = Math.sqrt(x);
}
```

```
if (x >= 0) {
    double r = Math.sqrt(x); }
else {
    float r = 0; }
```

**OK**

# Shadowing

Variables with the same name?

C++ is less strict. Scopes  
can overlap, but they  
can't be identical:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
int r = 10;
```

```
{
```

```
    r = sqrt(4.0);
```

```
}
```

**OK**

```
if (x >= 0) {  
    double r = sqrt(4.0);  
    float r = 0;  
}
```

**BAD**

# Shadowing

---

Variables with the same name?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Shadowing

---

Variables with the same name?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- What we're doing here is like binding in Haskell or Elixir. 't work with mutable variables.
- Think of this mathematically – We're simply saying let  $x =$  something else.

# Shadowing VS `mut`

---

Why not just use shadowing? Why do we need `mut`?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Mutable variables are stuck with their type.
- Can't assign a value of a different type.

# Shadowing VS `mut`

---

Why not just use shadowing? Why do we need `mut`?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- With shadowing (rebinding) we can use different types.
- Again, we get a warning because we're rebinding before the original binding is ever used.

# Shadowing VS `mut`

---

Why not just use shadowing? Why do we need `mut`?

- With `mut`, we're *mutating* a variable in memory.
- Storing a different value in the same variable.
- The name `mut` is in a different place, thus the **type `mut`**
- With shadowing, we're getting a new variable in memory each time.
- We're changing what a given name is referring to.
- We're not changing the existing value.

# Data Types

---

**Two subsets:** Scalar and Compound

**Reminder:** Rust is statically typed. Must know all variable types at compile time.

**Scalar types represent** <https://eduassistpro.github.io/>

- Rust has four: integers, floats, booleans, characters.

**Compound types group multiple values:**

- Two primitive compound types: tuples and arrays.



# Scalar Types: Integers

Length	Signed	Unsigned
8-bit	i8	u8
16-bit	i16	u16
32-bit	i32	u32
64-bit	i64	u64
arch	isize	usize

- Signed integers are stored using 2s comp  
arch will be 32 bits on a 32 stem, 64 bits on a 64 system.
- When not specified, Rust defaults to i32

# Specify Type?

---

Rust has type inference, but we can be explicit:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Integer Literals

In addition to just writing the value...

Number literals	Examp
Decimal	98_222
Hex	0xff
Octal	0o77
Binary	0b1111_0000
Byte (u8 only)	<u>b'A'</u>

Bytes can be character literals

Assignment Project Exam Help

Notice the

dy visual sugar

<https://eduassistpro.github.io/>

nt the zeroes in 1000000000.

is this?

Add WeChat edu\_assist\_pro

000\_000\_000 is one billion.

```
main.rs x
1 fn main() {
2     let x = 1_000_000_000;
3     println!("x: {}", x);
4 }
5
```

# Scalar Types: Floating Point

---

- Two kinds – 32 and 64 bit (float and double, single and double precision)
- Represented using standard IEEE-754

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Default



# Numeric Operations

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Numeric Operations

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat  edu\_assist\_pro 

# Mixed Expressions?

---



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Rust doesn't mess around when it comes to implicit type conversion.

# Mixed Expressions?

---



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Mixed Expressions?

---

Assignment Project Exam Help Cast using: **as** *type*

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Comments same as Java/C/C++
- Both block and single-line

*Finally!*

# Mixed Expressions?

---

Division may truncate, good reason to avoid implicit conversion...

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
main.rs x
1 fn main() {
2     let r1 = 3 + 4.0;
3     println!("r1: {}", r1);
4 }
```

# Why?!

---

- Adding **float** to **int** means converting the integer to a floating-point type, then adding.
- CPU doesn't add different types.
- Float and integer use different instructions on CPU.
- It's possible to introduce precision!
- An integer in binary is exact.
- The same value represented as a floating point may lose significant digits.
- Most languages don't even warn about this – Rust doesn't allow it at all.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

IEEE-754

# Scalar Types: Boolean

---

`true`, `false`. Easy:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Scalar Types: Characters

---

Rust supports Unicode:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Compound Types: Tuples

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Tuples can be heterogeneous, and we need not specify type. Rust can infer it.

# Accessing Elements


---

De-structuring!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
42, 3.141592, !
C:\_RustCode>
```



# Accessing Elements

---


Can also access directly:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Can we go out of bounds?



```
Command Prompt

C:\_RustCode>rustc main.rs

C:\_RustCode>main
42, 3.141592, !
```

# Accessing Elements

---

Out of bounds:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



Compile error in Rust

# Accessing Elements

---

Can we fool it?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

**Nope.**

# Compound Types

## Arrays

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
1, 2, 3, 4, 5
C:\_RustCode>
```

Arrays in Rust are: homogeneous, zero-indexed, fixed in size.

# Accessing Elements

---

Out of bounds:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Runtime error, much like Java.  
Prevents out of bounds array accesses.

# Array of Tuples


---

Same rules as Haskell:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
1, a
C:\_RustCode>
```

# Array of Tuples

---

Same rules as Haskell: Tuple types must be the same

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
Command Prompt
C:\_RustCode>rustc main.rs
error[E0308]: mismatched types                                --> main.rs:3:41
   |
3  |     let nums = [(1, 'a'), (2, 'b'), (3, 42)];
   |                                ^^ expected char, found u8
error: aborting due to previous error
```

# Types & Literals: Summary

---

## 4 Scalar types:

Integer – u8, u16, u32, u64, usize, i8, i16, i32, i64, isize

Floating Point – f32, f64

Boolean – bool (true, false)

Character – Unicode: 'Z' etc

## 2 Compound types:

Tuple – heterogeneous

Arrays – homogeneous

Rust supports other data structures such as strings and vectors. These are not base types, but very useful.



# Strings

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

String literals and escape  
characters are as expected

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Functions

---

We've seen `main()`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Returns nothing, accepts no arguments.
- Convention for naming functions is snake\_case.
- Words separated by underscores.

# Functions

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

Unlike C/C++, Rust doesn't  
care about ordering

# Parameters

---

**identifier:** **type**

- Parameters separated by commas.

Assignment Project Exam Help

- Indicating type is **mandatory**

thing too unusual here

<https://eduassistpro.github.io/>



Add WeChat edu\_assist\_pro

# Careful Now...

---

Assignment Project Exam Help

— <https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Statements & Expressions

---

Rust is *primarily* expression based, but still has statements.

## Two types of statements:

- Declaration state
- Expression state

`let x = 6; // This is an expression statement`

The above does not return a value. We can't do the following:

`let y = (let x = 6);`

# Statements & Expressions

---

Rust is *primarily* expression based, but still has statements.

## Two types of statements:

- Declaration state
- Expression state

`5 + 2; // This is an expression statement`

The above expression is evaluated, but the result is ignored (not saved).

`5 + 2` is an **expression**. It evaluates to 7.

`y = 5+2;` is an **expression statement**. It returns (), but the result of the nested expression 5+2 is saved to y



# Statements & Expressions

---

```
let y = (let x = 6);
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Statements & Expressions

---

OK

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Not O

*at does this error mean?*

Add WeChat edu\_assist\_pro

main.rs

```
1 fn main()
2 {
3     let mut x: i32;
4     let mut y: i32;
5     x = (y = 8);
6 }
```

# Statements & Expressions

---

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

- Variable **y** gets re-assigned.
- The *expression statement* **(y=8)** returns an empty tuple in Rust.
- Can't assign an empty tuple to a variable declared to hold **i32**!

# Statements & Expressions

---


Assignment Project Exam Help  
Here:

<https://eduassistpro.github.io/> value of x will be 3  
Add WeChat edu\_assist\_pro of y will be ()  
y tuple

# Statements & Expressions


`x + 6`

`// This is an expression`



Expression  
statement

**In fact:**



statement

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

expression statement

expression

# Scope Blocks as Expressions

---

Creating a new scope block?

We can do this in Java and C/C++, though again it isn't so common:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



Not a control structure or method, just a block of code with its own scope

# Scope Blocks as Expressions

---

Scope blocks like this are expressions in Rust:

There's a few things going on here:

g to bind a value to y.

Block { } should evaluate to

<sup>s</sup>  
Add WeChat edu\_assist\_pro

• no semicolon after z + 1

- z + 1 is an expression.
- Adding a semi-colon would make it an *expression statement*.
- Thus, the block { } would return ( ).
- Probably not what we want.

# Scope Blocks as Expressions

Scope blocks like this are expressions in Rust:

*expression!*

Assignment Project Exam Help

```
let y = { https://eduassistpro.github.io/ x + 1 } ;
```

Add WeChat edu\_assist\_pro



This whole thing is a declaration statement



# Scope Blocks as Expressions

---

Scope blocks like this are expressions in Rust:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

# Return Value

---

Think of functions the same way.  
The last line should be an expression – no semi-colon.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

type

ly indicate return type  
of expression gets returned



```
Command Prompt

C:\_RustCode>rustc main.rs

C:\_RustCode>main
13

C:\_RustCode>
```

# Return Value

---

Add semicolon? It becomes expression statement, returns ( ), type mismatch:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



# Fantastic Rust Reference:

Assignment Project Exam Help

<https://doc.rust-lang.org/second-edition/>

Add WeChat edu\_assist\_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro