

C/CPS 506

Assignment Project Exam Help

Compara

Languages

<https://eduassistpro.github.io/>

Prof. Ale

Add WeChat edu_assist_pro

Topic 8: Actions in Haskell

Notice!

**Obligatory copyright notice in the age of digital
delivery and online classrooms:**

Assignment Project Exam Help

<https://eduassistpro.github.io/>

The copyright to this work is reserved by Alex Ufkes. Students registered in course CCPS 506 can use the work for the purposes of this course but no other use is permitted, and there can be no sale or transfer or use of the work for any other purpose without explicit permission of Alex Ufkes.

Course Administration

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Getting closer! Thr eeks.
- Don't forget about the assignments!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Let's Get Started!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Last Week

Assignment Project Exam Help

○ <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

ine what it means for two Pt2
iables to be considered equal

Declare **Pt** to be
an instance of **Eq**



Last Week

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Last Week

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Last Week

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

no longer need to derive
we've made our own

- Use string concatenation to create a pleasing visual output for Pt2.
- In doing so, we make use of show as defined for Floats

Pure Code,

Mo

Ac

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Every function is pure



Pure Functions: Functions that have no side effects.

Assignment Project Exam Help



A function can be said to be pure if it has an observable interaction with the outside world in returning a value.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



- Modify global variable
- Raise an exception
- **Write data to display** or file

Write to Display

This was the very first thing we saw!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell and I/O

- Haskell separates pure functions from computations where side effects must be considered
- Encodes side effect-producing functions with a specific type.
- We've already

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Haskell and I/O

Assignment Project Exam Help

- The actual **act** of printing to the screen
cur as a result of a function call.

<https://eduassistpro.github.io/> the screen is an **action**.



Add WeChat edu_assist_pro

- A **value**, they have a type!
- **putStrLn** accepts a **String** argument.
- What it returns is an action of type **IO()**

Haskell and I/O

Speaking precisely:

- **putStrLn** is a *function* (no side effects!)
 - Takes a `String` as an input argument
 - Returns an action, whose type is `IO()`

Assignment Project Exam Help

<https://eduassistpro.github.io/>

`IO()` action is **executed**, it

Add WeChat ^redu_assist_pro

- Returns a `String` as an empty tuple.
- The *action*, when executed, produces a side effect.
- The **putStrLn** *function*, strictly speaking, does **not**.

Haskell and I/O

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Execute the action

- Actions are values, just like strings and numbers.
- They are completely inert – they do not affect the real world until executed.

Haskell and I/O

- Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro
- We can also look at `getLine`
 - `getLine` returns an IO action also
s a String (IO String vs IO ())
Haskell *evaluation* doesn't
ns to be executed.
 - GHCi will execute actions for us, as
seen previously.



Just remember: *actions* are not *functions*.

Functions are pure. Actions (specifically IO actions),
when executed are not.

Assignment Project Exam Help

Functions are *executed* or *run*
<https://eduassistpro.github.io/>

Actions are values. Actions can be *passed* by functions
or passed as arguments.

Actions have a type. We've seen one so far, **IO**

Actions can only be executed from within other actions.

Assignment Project Exam Help

A compiled Haskell program can be executed by executing a
sin 0()

Add WeChat edu_assist_pro

https://wiki.haskell.org/Introduction_to_Haskell_IO/Actions

main :: IO()

Recall: Every compiled Haskell program must have a main function:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- The main function is a single action
- This action is executed when the program is run.
- A Haskell program, by itself, is a single action that is executed when we run the program.

Staying Grounded

- A Haskell program begins with the execution of a single action (`main :: IO()`)
 - Functions that return `IO a` are often incorrectly referred to as actions.
- From within this action, other actions can be executed
- Pure functions can also be executed within actions!
- However – actions cannot be executed from pure functions.
- If we try, Haskell will infer the type of the function as an action.

Staying Grounded

- An action can be thought of as a *recipe*
- This recipe (in the case of IO) is a list of instructions that would produce the output
- *The act of creating a function has side effects.*
- The recipe can be the output of a function.
- Same inputs to the function, same recipe.

IO Actions

We can use the <- operator to execute:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- The <- operator is used to pull out the result from executing an IO action.
- We can then bind a name to it.
- The return value of getLine is an action.
- Executing that action returns a String.

IO Actions

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Combining Actions

We can do this using the **do** keyword:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

When using the do keyword, we can execute one action per line.

Combining Actions

do is syntactic sugar for **>>**

• **>>** says execute this, then this.
first action produces a result,
do we want to use the result?
>= operator to pipe the result
into the next action.

Assignment Project Exam Help
<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

Combining Actions

do is syntactic sugar for **>>**

- **>>** says execute this, then this.
first action produces a result,
handled
do we want to use the result?
>= operator to pipe the result
into the next action.
- Here, we grab a string using `getLine`,
and display it using `putStrLn`
- `getLine` returns an action that
produces a string
- `putStrLn` takes string as an argument.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro


More Complicated

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Lambda function accepting 1 arg, name
- Received directly from the getLine above

A screenshot of a WinGHCi terminal window. The window has a title bar with the WinGHCi logo and name. Below the title bar is a menu bar with 'File', 'Edit', 'Actions', 'Tools', and 'Help'. Under the menu bar is a toolbar with icons for file operations (folder, copy, paste, save), execution (play, pause, refresh), and settings (gear, wrench). The main area of the window contains the following text:

```
*Main> :reload
Ok, one module loaded.
*Main> main
What is your name?
Alex
Hello, Alex!
*Main>
```

Up until now, we've only really seen how to evaluate expressions (and execute actions, though we didn't know that's what we

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Now we're seeing how to write, and execute a complete Haskell program consisting of actions.

Add WeChat edu_assist_pro

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Actions & Functions

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Use `<-` when binding the result of executing an action
- Use **let** and `=` when binding the result of an expression

Problem?

- We are executing actions in **main**
- Its return type must be an action.
- The value of a “do” block is the value expression evaluated

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

return ()

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Return is NOT a keyword; it is a function.
- It wraps data in an ***IO monad***.
- In this case, we're wrapping an empty tuple ()



Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



Monads

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Here we get a clue about monads
- Monad is actually a type class
- This syntax resembles other type classes we've seen.

Monads

Monad is a typeclass:

Assignment Project Exam Help

← <https://eduassistpro.github.io/>

Add WeChat edu_assist_pro in these:

- >>= passes the result on the left into the function on the right.
- >> Ignores the result on the left
- return wraps data in a monad

Monad Jargon

“Monadic”

Pertaining to monads. A monadic type is an instance of type class Monad (IO, for example)

**“type xxx is a
Monad”**

Assignment Project Exam Help

xxx is an instance of type class Monad. xxx

<https://eduassistpro.github.io/>

“action”

Another name for a monadic value

By the way:

- It turns out that Monads are good for things other than side effect-producing IO.
- We’ll see an example coming up.

>>= VS >>

Where the
magic happens

>>=

Chains actions together. Result of left side is given as input to the right side.

>> <https://eduassistpro.github.io/> then ignore
result of le
Add WeChat edu_assist_pro

a >> b VS a >>= _ -> b

>> can be defined in terms of >>=


Non-main Example

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- Function that reads in a number
- Returns true if x is zero, false otherwise
- We're executing IO actions
- type cannot be Boolean
- | something



The image shows a screenshot of a WinGHCi window. The title bar says 'WinGHCi'. The menu bar includes 'File', 'Edit', 'Actions', 'Tools', and 'Help'. The toolbar contains icons for file operations (folder, copy, paste, save), execution (play, pause, refresh), and settings (gear, wrench, question mark). The main text area displays a red error message: 'Test.hs:7:3: error:'. Below this, there are two bullet points: '• Couldn't match expected type 'IO b' with actual type 'Bool'' and '• In a stmt of a 'do' block: (read num :: Double) < 0'. At the bottom, it says 'In the expression:' followed by 'do putStrLn "Enter a number: "'.

```
Test.hs:7:3: error:
• Couldn't match expected type 'IO b' with actual type 'Bool'
• In a stmt of a 'do' block: (read num :: Double) < 0
In the expression:
do putStrLn "Enter a number: "
```


Non-main Example

What if we still want to get a Boolean back?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`

Extract the value from the action using <-

- The return type of positive is an IO action.
- When executed, that action produces a Bool

Calling Pure Code

We can still call pure functions from actions:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Best Practice

Separate pure code into its own functions:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Pure!

Add WeChat edu_assist_pro

!Pure

When looking at `main`, Haskell looks rather imperative...

Even at this point, however, Haskell sets itself apart
from imperative languages.

Assignment Project Exam Help

It creates a separate <https://eduassistpro.github.io/cts> construct for operations

Add WeChat edu_assist_pro

We can always be sure of which parts of the code will alter the state
of the world, and which parts won't.

Imperative languages do no such thing, and make no guarantees
whatsoever regarding function purity

Assignment Project Exam Help

https://wiki.haskell.org/Haskell_IO/Actions

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

<https://wiki.haskell.org/Monad>

“The essence of monad is thus separation of composition timeline from the composed computation's execution timeline, as well as the ability of computation to implicitly carry extra data”

Assignment Project Exam Help

<https://eduassistpro.github.io/>

“This lends monads to supplementing computations with features like I/O, common environment, mutable state, etc.”

Add WeChat edu_assist_pro

Not just for I/O! Not just for side effects!

Maybe Monad

Monads were originally introduced for IO operations

It turns out, as a <https://eduassistpro.github.io/> useful for modelling other things

Add WeChat edu_assist_pro

For example: exception handling, non-determinism, etc.

Maybe Monad

Represents a computation that might not produce a result

Assignment Project Exam Help

Comp <https://eduassistpro.github.io/> "wrong"

For example – calling tail wit [Add WeChat edu_assist_pro](#) it might be empty

We can use Maybe to create a safety wrapper for functions that might fail, depending on input.

Maybe Monad

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Maybe:

- Custom data type
instance of Monad
be a can be
hing, or Just a

We've seen this before...

Pt can take the value Pt3 Float
Float Float, or Pt2 Float Float

Assignment Project Exam Help

take the value
g or just a

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Maybe Monad

Assignment Project Exam Help

<https://eduassistpro.github.io/>
Add WeChat edu_assist_pro

- Define safe functions for head and tail.
guards - |
failing on e
nothing.
- If a tail or head can be found, evaluate to Just head x, or Just tail x
- Just head? Just tail?

Maybe Monad

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

- When we call `safeHead` on a non-list, we don't get the head. *it just head*
the head of the list in a Maybe monad.
- Remember that `Maybe` is a type, just like our custom `Pt` type

Maybe Monad

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Unwrap Just a?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Just like pulling values
out of our Pt data type!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Unwrap *Nothing*?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

If you need to decide on some numeric literal for **Nothing**, you can do so

Why Not This?

```
safeHead x
| (length x > 0) = head x
| oth
```

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Zero as error code

- What if head of list is *actually* 0?
- Static typing means list passed to safeHead can only be instance of Num!
- **Just** can contain anything
- **Nothing** is useful as an “error” value

Using Maybe

Maybe can make code safer by gracefully dealing with failure.

Assignment Project Exam Help

Should <https://eduassistpro.github.io/> anything?

Add WeChat edu_assist_pro

No. Not everything has a chance of $(x > y)$ in Maybe only serves to obfuscate your code.

Consider a Lookup Table

We have a list of tuple pairs:

Assignment Project Exam Help

```
book = [ ("Alex", 444),  
         ("John", 333),  
         ("Tim", 222),  
         ("Mark", 111) ]
```

want to search the
ame
nd, return its number
If not found, return.... ?

Use lookup

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- It's not obvious what to return if an item is not found.
- We might return -1, or 0, but what if these are legitimate values that could be returned if a key was found?
- In Haskell we can use Maybe for this.
- Preferable to an arbitrary default value, or an exception.

Just 555 VS 555

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- We would like to extract
eric value 555
o arithmetic on
for example.

Just 555 VS 555

If we have a **Just** value, we can see its contents and extract through pattern matching

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Use lookup

Assignment Project Exam Help



<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



- Value from book1 is the key to book2
- Value of book2 is the key to book3
- t the value from book3

- every value in book1 responds to a key in book2.
- Not every value in book2 corresponds to a key in book3
- There are several ways a lookup could fail

- 
- 
- What happens if lookup fails to find a match?
 - We saw that it returns **Nothing**
 - What happens if we try to lookup **Nothing**?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

```
Just "First"  
*Test> getPlace "Tim"  
Nothing  
*Test> getPlace "Mark"  
Nothing  
*Test> fm (getPlace "Alex")  
"First"  
*Test>
```


Cascading Failure

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

**Is the
same as:**

Cascading Failure

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- When the first argument to ($>>=$) is **Nothing**, it just returns **Nothing** while ignoring the given function causes failure to cascade up fails, **Nothing** is into the second $>>=$.
- The failure then cascades into the third $>>=$, and is returned.
- After the first **Nothing**, subsequent $>>=$ pass that **Nothing** to each other

*When the first argument to (>>=) is **Nothing**, it just returns **Nothing** while ignoring the given function*

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Haskell Tutorials/References:

Assignment Project Exam Help
<https://en.wikiboo> [ther_Haskell_Tutorial](https://en.wikiboo)
<https://eduassistpro.github.io/>
<http://cheatsheet.codeslo> Add WeChat edu_assist_pro [cheatsheet.pdf](http://cheatsheet.codeslo)

Moving on...

Assignment Project Exam Help
erative.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Rust is an imperative language. How see many cool features
that remind us of the functional languages we've seen.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro