Advanced Network Technologies

Wireless 2

Dr. Wei Bao | Lecturer
School of Computer Science

THE UNIVERSITY OF SYDNEY

Insert Partner Logo
- Delete if not required

THE UNIVERSITY OF SYDNEY

IEEE 802.11 Wireless LANs

IEEE 802.11 WiFi

IEEE 802.11 standard	Year	Max data rate	Range	Frequency
802.11b	1999	11 Mbps	30m	2.4 Ghz
802.11a	1999	54 Mbps	30m	5 Ghz
802.11g	2003	54 Mbps	30m	2.4 Ghz
802.11n (WiFi 4)				2.4, 5 Ghz
802.11ac (WiFi 5)				5 Ghz
802.11ax (WiFi 6)	2020 (exp.)	14 Gbps		2.4, 5 Ghz
802.11af	2014	35 – 560 Mbps	1 Km	unused TV bands (54-790 MHz)
802.11ah	2017	347Mbps	1 Km	900 Mhz

- all use CSMA/CA for multiple access, and have base-station and ad-hoc network versions

802.11 LAN architecture



- wireless host communicates with base station
  - base station = access point P)
  - Service Set (BSS) (aka in infrastructure
  - ontains:
    - wireless hosts
    - access point (AP): base station
    - ad hoc mode: hosts only

802.11: Channels, association

- 802.11b: 2.4GHz-2.485GHz spectrum divided into 11 channels at different frequencies
  - AP admin chooses frequency for AP
  - interference possible: channel can be same as that chosen by neighboring AP!
- host: must *associate* with
  - scans channels, listening for beacon frames containing AP's name (SSID) and MAC address
  - selects AP to associate with
  - may perform authentication
  - will typically run DHCP to get IP address in AP's subnet

802.11: passive/active scanning



passive scanning:

(1) beacon frames sent from APs
(2) association Request frame sent: H1 to selected AP
(3) association Response frame sent from selected AP to H1

(est frame broadcast from H1
(2) Probe Response frames sent from APs
(3) Association Request frame sent: H1 to selected AP
(4) Association Response frame sent from selected AP to H1

collisions

spatial layout of nodes

- collisions *can* occur:
  propagation delay means two nodes may not hear each other's transm

- collision: frame transmission time wasted

Wired Networks: CSMA/CD (collision detection)

CSMA/CD:

- collisions *detected* within short time
- colliding transmissions aborted, reducing channel wastage

› collision detection:

- wired LANs: measu nsmitted, received signals
  - Can transmit and sense at the same ti
- wireless LANs: received signal strength by local transmission strength
  - CSMA-CD cannot be used in wireless LAN

CSMA/CD (collision detection)



IEEE 802.11: multiple access

- 802.11: *no* collision detection!
  - difficult to receive (sense collisions) when transmitting due to weak received signals (fading)
  - can not sense all collisions in any case: hidden terminal, fading
  - goal: *avoid collisions:*





IEEE 802.11 MAC Protocol: CSMA/CA

802.11 sender

1 if sense channel idle for **DIFS** (Distributed inter-frame space) then

transmit entire frame (no CD)

2 if sense channel busy then

start random backoff tim

timer counts down while channel idle

transmit when timer expires

802.11 receiver

- if frame received OK

return ACK after **SIFS** (Shorter inter-frame spacing)

Sender : if no ACK, increase random backoff interval, repeat 2



Avoiding collisions (more)

idea: allow sender to "reserve" channel rather than random access of data frames: avoid collisions of long data frames

- sender first transmits *small* request-to-send (RTS) packets to BS using CSMA
  - RTSs may still collid ort)
- BS broadcasts clear-to-send CTS in RTS
- CTS heard by all nodes
  - sender transmits data frame
  - other stations defer transmissions

avoid data frame collisions completely using small reservation packets!

Collision Avoidance: RTS-CTS exchange



802.11: advanced capabilities

Rate adaptation

- base station, mobile dynamically change transmission rate (physical layer modulation as mobile moves, varies



QAM256 (8 Mbps)
QAM16 (4 Mbps)
BPSK (1 Mbps)
operating point

1. SNR decreases, BER increase as node moves away from base station

2. When BER becomes too high, switch to lower transmission rate but with lower BER

Exposed Terminal

Source: Wikipedia

Exposed Terminal

Ideal: S1->R1 and S2->R2 simultaneously

However: S2 can sense the carrier of S1 so that it keeps silence

Can RTS-CTS fail? Yes

Source: http://www.cs.jhu.edu/~cs647/mac_lecture_3.pdf

Can RTS-CTS fail? Yes

Source: http://www.cs.jhu.edu/~cs647/mac_lecture_3.pdf

THE UNIVERSITY OF SYDNEY

Cellular Internet Access

Archit ndards

Components of cellular network architecture

MSC
- connects cells to wired tel. net.
- manages call setup (more later!)
- handles mobility (more later!)

cell
- covers geographical region
- *base station* (BS) analogous to 802.11 A
- *mobile users* attach to network through BS
- *air-interface:* physical and link layer protocol between mobile and BS



Cellular networks: the first hop

Two techniques for sharing mobile-to-BS radio spectrum

- combined FDMA/TDMA: divide spectrum in frequ
  divide each chann
  slots
- CDMA: code division multiple access



2G (voice) network architecture



Base transceiver station (BTS)

Base station controller (BSC)

Mobile Switching Center (MSC)

Mobile subscribers

3G (voice+data) network architecture



Key insight: new cellular data network operates *in parallel* (except at edge) with existing cellular voice network

- voice network unchanged in core
- data network operates in parallel

4G: Long-Term Evolution (LTE)

Two important innovations over 3G

1. Evolved packet core (EPC): simplified all-IP core network that unifies the cellular circuit-switched voice network and the packet switche



4G: Long-Term Evolution (LTE)

Two important innovations over 3G

2. LTE Radio Access Networks: uses a combination of orthogonal frequency-division multiplexing (OFDM) and time division multip

http://www.slideshare.net/ravi4s/modulation-multiple-acces-schemes

4G: Long-Term Evolution (LTE)

Two important innovations over 3G

2. LTE Radio Access Networks: uses a combination of orthogonal frequency-division multiplexing (OFDM) and time division multip



Mobility principles: Addressi to mobile

What is mobility?

› spectrum of mobility, from the *network* perspective:



mobile wireless user, using same access point

mobile user, disconnecting from network when moving.

mobile user, passing through multiple access point while maintaining ongoing connections (like cell phone)

Should Address always remain the same?

- Mobile phone: the phone number remains the same at all time when you travel

- How about IP A

Mobility: vocabulary

home network: permanent "home" of mobile
(e.g., 128.119.40/24)

home agent: *entity that will perform mobility functions on behalf of mobile*



permanent address:
address in home network, *can always* be used to reach mobile
e.g., 128.119.40.186

Mobility: more vocabulary

permanent address: remains constant (e.g., 128.119.40.186)

Foreign (visited) network: network in which mobile currently resides (e.g., 79.129.13/24)

care-of-address: address in visited network.



foreign agent: *entity in visited network that performs mobility functions on behalf of mobile.*

correspondent: *wants to communicate with mobile*

How do *you* contact a mobile friend:

Consider friend frequently changing addresses, how do you find her?



- search all phone b
- call her parents?
- expect her to let you know where he/she is?

Mobility: approaches

- *let routing handle it:* routers advertise permanent address of mobile-nodes-in-residence via usual routing table exchange.
  - routing tables indicate where each mobile located
  - no changes to end-s
- *let end-systems h*
  - *indirect routing:* communication from corr mobile goes through home agent, then forwarded to remote
  - *direct routing:* correspondent gets foreign address of mobile, sends directly to mobile

Mobility: approaches

- *let routing handle it:* route[illegible]ertise permanent address of mobile-nodes-in-resi[illegible]al routing table exchange.
  - routing tables indicate w[illegible]ated
  - no changes to end-s
- *let end-systems h*
  - *indirect routing:* comm[illegible]ication from corr[illegible]obile goes through home agent, then forwarded to remote
  - *direct routing:* correspondent gets foreign address of mobile, sends directly to mobile



Mobility: registration



end result:

- foreign agent knows about mobile
- home agent knows location of mobile

Mobility via indirect routing



Indirect Routing: comments

- mobile uses two addresses:
  - permanent address: used by correspondent (hence mobile location is *transparent* to correspondent)
  - care-of-address: used by home agent to forward datagrams to mobile
- triangle routing: corr bile
  - inefficient when corr twork



Indirect routing: moving between networks

- suppose mobile user moves to another network
  - registers with new foreign agent
  - new foreign agent registers with home agent
  - home agent upd obile
  - packets continu ile (but with new care-of-address)
- changing foreign networks transparent: *on going connections can be maintained!*

Mobility via direct routing



Mobility via direct routing: comments

- overcome triangle routing problem
- *non-transparent to correspondent:* correspondent must get care-of-address from home agent
  - what if mobile changes visited network?



Accommodating mobility with direct routing

- anchor foreign agent: FA in first visited network
- data always routed first to anchor FA
- when mobile moves: new FA arranges to have data forwarded from old FA (chaining)



Mobile IP

Mobile IP

- RFC 3344
- has many features we have seen:
  - home agents, foreign agents, foreign-agent registration, care-of-addresses
- three components to standard:
  - indirect routing of datag
  - agent discovery
  - registration with home agent

Mobile IP: indirect routing



Mobile IP: agent discovery

› *agent advertisement:* foreign/home agents advertise service by broadcasting ICMP (Internet Control Message Protocol) messages (typefield = 9)

H,F bits: home and/or foreign agent

R bit: registration required



Mobile IP: registration example



Mobilit etworks

Components of cellular network architecture

recall:



different cellular networks,
operated by different providers

Handling mobility in cellular networks

- *home network:* network of cellular provider you subscribe to (e.g., Vodafone)
  - *home location register (HLR):* database in home network containing permanent cell phone #, profile information (services, preferences, billing), information about current location (could be in another network)
- *visited network:* network in which mobile currently resides
  - *visitor location register (VL* er currently in network
  - could be home network

GSM: indirect routing to mobile



GSM: handoff with common MSC



› *handoff goal:* route call via new base station (without interruption)

handoff:

al to/from new BSS

nectivity, less battery

- load balance: free up channel in current BSS

› handoff initiated by old BSS

GSM: handoff with common MSC



1. old BSS informs MSC of impending handoff, provides list of 1+ new BSSs
2. MSC sets up path (allocates resources) to new BSS
3. new BSS allocates radio channel for
als MSC, old BSS: ready
5. old bile: perform handoff to
ne
6. mobile, new BSS signal to activate new channel
7. mobile signals via new BSS to MSC: handoff complete. MSC reroutes call

8 MSC-old BSS resources released

Handoff algorithm: a brief overview

Signal Strength of Two Base Stations: when to handoff?

Handoff algorithm: a brief overview

- Naive way: Compare the RSSs (Received Signal Strength) of two BSs
  Handoff at

Ping-pong effect

Handoff back and forth.

Smarter ways

- RSS: initiate handoff to BS new if
  - $P_{new} > P_{old}$
- RSS with threshold(PT): choose BS new if
  - P > P and P < P
- RSS with hysteresis(P
  - $P_{new} > P_{old}$
- RSS with threshold(PT) and hysteresis(PH): choose BS new if
  - $P_{new} > P_{old} + P_H$ and $P_{old} < P_T$
- Even better: Add a Dwell Timer to the above algorithms: start timer when above condition is met; initiate handoff if condition persists when timer expires

Wireless, mobility: impact on higher layer protocols

- logically, impact *should* be minimal …
  - best effort service model remains unchanged
  - TCP and UDP can (and do) run over wireless, mobile
- … but performance-wise:
  - packet loss/delay due t elays for link-layer retransmissions), and h
  - TCP interprets loss as congestion, will decr window un-necessarily
  - delay impairments for real-time traffic