

Advanced Network Technologies

Week 2:

Network performance

Network Application Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Dr. Wei Bao | Lecturer
School of Computer Science





THE UNIVERSITY OF
SYDNEY

Network Performance:

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

- › **throughput:** rate (bits/time unit) at which bits transferred between sender/receiver
 - *instantaneous:* rate at given point in time
 - *average:* rate over long


Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat `edu_assist_pro`



- › $R_s < R_c$ What is average end-end throughput?



- › $R_s > R_c$ What is <https://eduassistpro.github.io/>




bottleneck link

link on end-end path that constrains end-end throughput

Internet Scenario

- per-connection end-end throughput: $\min(R_c, R_s, R/10)$



10 connections (fairly) share backbone bottleneck link R bits/sec

- › bit: basic unit. “b”
- › byte: 8 bits. “B”
- › bps: bit per second [Assignment Project Exam Help](#)
- › Network/Teleco <https://eduassistpro.github.io/>
 - Kb/Mb/Gb: $10^3, 10^6, 10^9$ bit
 - Kbps/Mbps/Gbps: $10^3, 10^6, 10^9$ bit per second [Add WeChat edu_assist_pro](#)
 - By default in this course
- › File system:
 - KB/MB/GB: $2^{10}, 2^{20}, 2^{30}$ byte ($1024, 1024^2, 1024^3$ byte)



THE UNIVERSITY OF
SYDNEY

Bit and byte

Assignment Project Exam Help

<https://eduassistpro.github.io/>^{2¹⁰ byte}

^{10⁹ bit per second}

Add WeChat edu_assist_pro



THE UNIVERSITY OF
SYDNEY

Network Performance:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

In reality: two considerations

› Efficiency

› Fairness

Assignment Project Exam Help


<https://eduassistpro.github.io/>

› However, they are contradic

Add WeChat edu_assist_pro

Three flows: A-B, B-C, A-C


Assignment Project Exam Help



Q: How can we allocate the link bandwidths to the three flows?

Three flows: A-B, B-C, A-C


Assignment Project Exam Help



However: Network throughput, only 1.5Mbps

Three flows: A-B, B-C, A-C

Assignment Project Exam Help




Very unfair!

However: Network throughput, 2Mbps

Bottleneck for a flow: The link that limits the data rate of the flow

Assignment Project Exam Help



- › Maximize the minimum
- › Try to increase the “poorest” as much as possible
 - A richer flow can be sacrificed.
 - A poorer flow cannot be sacrificed.
- › Try to increase the third “poorest” as much as possible
- › ...

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

s




- › Max-min Fairness criteria: if we want to improve one flow, we can only achieve this by sacrificing a poorer or equal flow.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Bottleneck for a flow: The link limits its data rate




Bottleneck approach

- › 1 Start with all zero flows, potential flow set = {all flows}
- › 2 Slowly increase flows in the potential flow set until there is a (new) link saturated
 - “Pouring water in the n
- › 3 Hold fix the flows them from the potential flow set
 - <https://eduassistpro.github.io/>
 - Add WeChat [edu_assist_pro](#)
- › 4 If potential flow set is not empty, go to step 2 (still has potential to increase)

Each link between two routes with capacity 1


Assignment Project Exam Help

Potential flow set {A, B, C, D}



Each link between two routes with capacity 1


Assignment Project Exam Help



Each link between two routes with capacity 1

Assignment Project Exam Help

Potential flow set {}




Can you solve the following problem?

link rate: AB=BC=1, CA=2

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro



Can you solve the following problem?


link rate: AB=BC=1, CA=2

Assignment Project Exam Help



More comment: Max-min fairness is too fair!


Assignment Project Exam Help



You are using two links. How can we get a same share?

Another form of fairness proportional fairness

Assignment Project Exam Help



Longer routes are penalized



THE UNIVERSITY OF
SYDNEY

The Application Layer

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

- › e-mail
 - › web
 - › text messaging
 - › remote login
 - › P2P file sharing
 - › multi-user network games
 - › streaming stored video
(YouTube, Netflix)
 - › voice over IP (e.g., Skype)
 - › real-time video conferencing
- Assignment Project Exam Help**
social networking
- <https://eduassistpro.github.io/>
- Add WeChat **edu_assist_pro**

Creating a network app

write programs that:

- › run on (different) end systems
- › communicate over network
- › e.g., web server software
communicates with bro


Assignment Project Exam Help

<https://eduassistpro.github.io/>

no need to write software for network-
core devices

Add WeChat edu_assist_pro

- › network-core devices do not run user applications
- › applications on end systems allows for rapid app development, propagation



Possible structure of applications


- › Client-server
- › Peer-to-peer (P2P)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Client-server architecture




server:

- › always-on
- › permanent IP address
- › designed for scaling
- › may be intermittently connected
- › may have dynamic IP addresses
- › do not communicate directly with each other

- › no always-on server
- › arbitrary end systems directly communicate
- › peers request service, provide service to other peers
 - self scalability – new peers bring new service capacity, as well as new service demands
- › peers are intermittently connected and change IP addresses
 - complex management

Assignment Project Exam Help

Add WeChat edu_assist_pro



process: program running
within a host

- › within same host, two processes comm
inter-process co
(defined by OS)

clients, servers


client process: process that initiates communication

server process: process that receives communication

- ❖ aside: applications with P2P architectures have client processes & server processes

- › process sends/receives messages to/from its **socket**
- › socket analogous to door
 - sending process shoves message out door
 - sending process <https://eduassistpro.github.io/> structure on other side of door to receiving process

Add WeChat **edu_assist_pro**



- › to receive messages, process must have *identifier*
- › host device has unique 32-bit IP address (or 128 in IPv6)
- › Q: does IP address <https://eduassistpro.github.io/> suffice for identifying the process?
 - A: no, many processes can be running on same host
 - › *identifier* includes both IP address and port numbers associated with process on host.
 - port numbers:
 - r: 80
 - Add WeChat edu_assist_pro 25
 - › to send HTTP message to gaia.cs.umass.edu web server:
 - IP address: 128.119.245.12
 - port number: 80
 - › more shortly...

- › types of messages exchanged,
 - e.g., request, response
- › message syntax:
 - what fields in messages & how fields are delineate
 - e.g. First line: method. Second line: URL
 - message semantics
 - meaning of information in fields
 - e.g. 404 means “not found”
- › rules for when and how processes send & respond to messages

open protocols:

- › defined in RFCs

Assignment Project Exam Help

allows for interoperability
TP, SMTP
<https://eduassistpro.github.io/>

ry protoc
Add WeChat edu_assist_pro

What transport service does an app need?

data integrity

- › some apps (e.g., file transfer, web transactions) require 100% reliable data transfer
- › other apps (e.g., au tolerate some loss <https://eduassistpro.github.io/>)

timing

- › some apps (e.g., Internet telephony, interactive games) require low delay to be “effective”

throughput

- ❖ some apps (e.g., multimedia) require minimum amount of throughput to be effective
- apps (“elastic apps”) us er

Add WeChat `edu_assist_pro` pup they get

TCP service:

- › *reliable transport* between sending and receiving process
- › *flow control*: sender won't overwhelm receiver
- › *congestion control*: sender when network overloaded
- › *does not provide*: timing, minimum throughput guarantee
- › *connection-oriented*: setup required between client and server processes

UDP service:

- › *unreliable data transfer* between sending and process
- › *provide*: reliability, ordering, throughput guarantee, or connection setup,

Internet apps: application, transport protocols

application	application layer protocol	underlying transport protocol
remote terminal access	telnet [RFC 854]	TCP
Web file transfer	HTTP	TCP
streaming multimedia	RTP [RFC 1886]	TCP or UDP
Internet telephony	SIP, RTP, proprietary (e.g., Skype)	TCP or UDP

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



THE UNIVERSITY OF
SYDNEY

Assignment Project Exam Help Web and HTTP

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

First, a review...


- › web page consists of *base HTML-file* which includes *several referenced objects*
 - *HTML: HyperText Markup Language*
- › object can be JPEG i <https://eduassistpro.github.io/>
- › each object is addressable by a *URL (Uniform Locator)*, e.g.,
Add WeChat [edu_assist_pro](https://eduassistpro.github.io/)

www.someschool.edu/someDept/pic.gif


host name

path name

File: usually base-html file
(HyperText Markup Language)



Browser shows



HTTP: hypertext transfer protocol

- › Web's application layer protocol
- › client/server mod
 - *client*: browser sends requests, receives, (using HTTP protocol) and “displays” Web objects
 - *server*: Web server sends (using HTTP protocol) objects in response to requests

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro



uses TCP:

- › client initiates TCP connection (creates socket) to server, port 80
 - How to know IP address?
 - DNS (Domain Name S
- › server accepts TCP connection from client
- › HTTP messages (application-layer protocol messages) exchanged between browser (HTTP client) and Web server (HTTP server)
- › TCP connection closed

HTTP is “stateless”

- › server maintains no information about past client requests

~~https://eduassistpro.github.io/~~ aside

Add WeChat ~~edu_assist_pro~~ complex!

- ❖ y (state) must be maintained
- ❖ if server/client crashes, their views of “state” may be inconsistent, must be reconciled

non-persistent HTTP

- › at most one object sent over TCP connection
 - connection th <https://eduassistpro.github.io/>
- › downloading multiple objects required multiple connections

persistent HTTP

- › multiple objects can be sent over single TCP

Add WeChat  edu_assist_pro

suppose user enters URL:

`www.someSchool.edu/someDepartment/home.index`

(contains text,
references to 10
jpeg images)

Ia. HTTP client initiates TCP connection to HTTP server (process) at `www.someSchool.edu` on port 80

Ib. HTTP server at host `www.someSchool.edu` waiting for TCP connection on port 80. “accepts” connection, notifying client

2. HTTP client sends HTTP `message` into TCP connection socket. Message indicates that client wants page `someDepartment/home.index`

receives request message, `message` containing requested page, and sends message

5. HTTP client receives response message containing html file, displays html. Parsing html file, finds 10 referenced jpeg objects to download

4. HTTP server closes TCP connection.

time
↓

suppose user enters URL:

`www.someSchool.edu/someDepartment/home.index`

(contains text,
references to 10
jpeg images)

Ia. HTTP client initiates TCP connection to HTTP server (process) at `www.someSchool.edu` on port 80

Ib. HTTP server at host `www.someSchool.edu` waiting for TCP connection on port 80. “accepts” connection, notifying client

2. HTTP client sends HTT

https://eduassistpro.github.io/
message into TCP connection socket. Message indicates that client wants object `someDepartment/object1.jpg`

receives request message, *response message* containing requested object, and sends message

5. HTTP client receives response message containing object, displays the object.

4. HTTP server closes TCP connection.

time
↓

6. Steps 1-5 repeated for each of 10 jpeg objects


RTT (definition): time for a small packet to travel from client to server and back

HTTP response time:

Assignment Project Exam Help

- › one RTT to initiate
- › one RTT for HTTP first few bytes of HTTP response to return
- › file transmission time
- › non-persistent HTTP response time =

$$2\text{RTT} + \text{file transmission time}$$



suppose user enters URL:

`www.someSchool.edu/someDepartment/home.index`

(contains text,
references to 10
jpeg images)

Ia. HTTP client initiates TCP connection to HTTP server (process) at `www.someSchool.edu` on port 80

Ib. HTTP server at host `www.someSchool.edu` waiting for TCP connection on port 80. “accepts” connection, notifying client

2. HTTP client sends HTTP `message` into TCP connection socket. Message indicates that client wants page `someDepartment/home.index`

receives request message, `message` containing requested page, and sends message

5. HTTP client receives response message containing html file, displays html. Parsing html file, finds 10 referenced jpeg objects to download

TCP is still on

time
↓

suppose user enters URL:

`www.someSchool.edu/someDepartment/home.index`

(contains text,
references to 10
jpeg images)

Assignment Project Exam Help

2. HTTP client sends HTT

https://eduassistpro.github.io/
message into TCP connection

socket. Message indicates that client
wants object
`someDepartment/object1.jpg`

Add WeChat *edu_assist_pro*

receives request message,
message containing
requested object, and sends message


4. HTTP client receives response message
containing object, displays the object.

Repeated for each of 10 jpeg objects

10 rounds later HTTP server closes TCP
connection.

time
↓

Non-persistent vs. persistent



non-persistent HTTP issues:

- › requires 2 RTTs + file transmission time per object

persistent HTTP:

- › server leaves connection open after sending response

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`

HTTP messages
same client/server
open con
requests as soon
as it encounters a referenced
object

- › as little as one RTT + file transmission time for all the referenced objects

- › two types of HTTP messages: *request, response*
- › HTTP request message:

- ASCII (human-readable format)

request line
(GET, POST,
HEAD commands)

header
lines

carriage return,
line feed at start
of line indicates
end of header lines

Assignment Project Exam Help


carriage return character

line-feed character

<https://eduassistpro.github.io/>

Host: www-net.cs.\r\nUser-Agent: Firef\r\nAccept: text/html,application/xhtml+xml\r\nAccept-Language: en-us,en;q=0.5\r\nAccept-Encoding: gzip,deflate\r\nAccept-Charset: ISO-8859-1,utf-8;q=0.7\r\nKeep-Alive: 115\r\nConnection: keep-alive\r\n\r\n

HTTP request message: general format





GET method

Assignment Project Exam Help

<https://eduassistpro.github.io/>

POST method: Add WeChat edu_assist_pro

- › web page often includes form input
- › input is uploaded to server in entity body

HTTP/1.0:

- › GET
- › POST
- › HEAD
 - asks server to leave requested object out of response

HTTP/1.1:

- › GET, POST, HEAD
- › PUT

Assignment Project Exam Help

<https://eduassistpro.github.io/>

le in entity body
ified in URL

Add WeChat edu_assist_pro

- › DELETE

- deletes file specified in the URL field

status line

(protocol

status code

status phrase)

07 17:00:02

header
lines

data, e.g.,
requested
HTML file

```
HTTP/1.1 200 OK\r\n
Date: Sun, 26 Sep 2010 20:09:20 GMT\r\n
Server: Apache/2.0.52 (CentOS) \r\n
Last
G
ETag
Accept-Ranges: byt
Content-Length: 26
Keep-Alive: timeout
Connection: Keep-Alive\r\n
Content-Type: text/html; charset=ISO-8859-1\r\n
\r\n
\r\n
```

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

00\r\n

data data data data data ...

- › status code appears in 1st line in server-to-client response message.
- › some sample codes:

200 OK Assignment Project Exam Help

- request succeed

<https://eduassistpro.github.io/>

301 Moved P

- requested object moved, new loca
(Location:)

[Add WeChat edu_assist_pro](#)

later in this msg

400 Bad Request



- request msg not understood by server

404 Not Found

- requested document not found on this server

505 HTTP Version Not Supported

Cookies: keeping “state” (cont’d)



many Web sites use cookies

four components:

- 1) cookie header ~~Assignment Project Exam Help~~ message
- 2) cookie header ~~https://eduassistpro.github.io/~~ message
- 3) cookie file kept ~~Add WeChat~~ by user's browser
- 4) back-end database at ~~Web sit~~ ~~Add WeChat~~ edu_assist_pro

what cookies can be used for:

› authorization

› shopping carts

› recommendations

› user session state

Assignment Project Exam Help

<https://eduassistpro.github.io/>


Add WeChat edu_assist_pro

how to keep “state”:

- protocol endpoints: maintain state at sender/receiver over multiple transactions
- cookies: http messages carry state

goal: satisfy client request without involving origin server

- › user sets browser: Web
- accesses via cache
- › browser sends all H requests to cache
- › if object in cache:
 - then cache returns object
 - else cache requests object from origin server, then returns object to client



› Q: Does the cache act as a client or a server?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

› R: cache acts as both client and server

- server for original requesting client
- client to origin serv

why Web caching?

› reduce response time for client request

› typically cache is installed by ISP (university, company, residential ISP)

<https://eduassistpro.github.io/>

traffic on an access link

Add WeChat edu_assist_pro

assumptions:

- ❖ avg object size: 100K bits
- ❖ avg request rate from browsers to origin servers: 15/sec (1.5 Mbps service)
- ❖ RTT from institutional router to any origin server: 2 sec
- ❖ access link rate: 1.54


Assignment Project Exam Help

<https://eduassistpro.github.io/>

consequences:

- ❖ LAN utilization: 0.15%
- ❖ LANU = avg req rate * size / link bandwidth
- ❖ access link utilization = **99% problem!**
- ❖ ALU = avg req rate * size / link bandwidth
- ❖ total delay = 2 sec + minutes + usecs

Add WeChat edu_assist_pro



Q: what happens with fatter access link?

Caching example: fatter access link

assumptions:

- ❖ avg object size: 100K bits
- ❖ avg request rate from browsers to origin servers: 15/sec
- ❖ RTT from institutional router to any origin server: 2 sec
- ❖ access link rate: 1.54


Assignment Project Exam Help

<https://eduassistpro.github.io/>

consequences:

- ❖ LAN utilization: 0.15%
- ❖ access link utilization = ~~99%~~ ^{0.99%}
- ❖ total delay = 2 sec + minutes + usecs

msecs



Cost: increased access link speed (not cheap!)

Caching example: install local cache

assumptions:

- ❖ avg object size: 100K bits
- ❖ avg request rate from browsers to origin servers: 15/sec
- ❖ RTT from institutional router to any origin server: 2 sec
- ❖ access link rate: 1.54


Assignment Project Exam Help

<https://eduassistpro.github.io/>

consequences:

- ❖ LAN utilization: 0.15%
- ❖ access link utilization = 0%
- ❖ total delay = usecs

Add WeChat edu_assist_pro



Cost: web cache (cheap!)

Caching example: install local cache

Calculating access link utilization, delay with cache:


- › suppose cache hit rate is 0.4
 - 40% requests satisfied at cache,
 - 60% requests satisfied at origin
- › access link utilization <https://eduassistpro.github.io/>
 - 60% of requests use access link
- › average total delay

$$= 0.6 * (\text{delay from origin servers}) + 0.4 * (\text{delay when satisfied at cache})$$

Link utilization is around 60%, queueing delay is small enough

$$= 0.6 (\sim 2.x \text{ second}) + 0.4 (\sim \text{usecs})$$

less than with 154 Mbps link (and cheaper too!)



- › **Goal:** don't send object if client **client** has up-to-date cached version

- no object transmission delay
- lower link utilization

- › **client:** specify date of copy in HTTP request

If-modified-since: <https://eduassistpro.github.io/>

- › **server:** response contains no object if cached copy is up-to-date:

HTTP/1.0 304 Not Modified

