

DOCUMENTATION

[Table of Contents](#)
[Class Inheritance Tree](#)

NAVIGATION

[Description](#)
[Packages](#)
[Types](#)

Package: *Generic_Message_Structures (generic)*
• [Goto spec source](#)

DESCRIPTION

generic
with package Routers_Configuration is
Framework: Uwe R. Zimmer, Australia, 2015

PACKAGES

Routers_Configuration (new [Generic_Routers_Configuration](#))
package Routers_Configuration is new [Generic_Routers_Configuration](#) (<>);
Message_Strings (new [Generic_Bounded_Length](#))
package Message_St

TYPES

subtype The_Core_Message is [Bounded_String](#);
• [Goto \[rce_\]\(#\)](#)
Add WeChat [edu_assist_pro](#)

References:

[generic_message_structures.ads:18:12](#) (declaration)
[generic_message_structures.ads:22:21](#) (reference)
[generic_message_structures.ads:27:21](#) (reference)

Messages_Client

- [Goto declaration in source](#)

type Messages_Client is record
Destination : [Router_Range](#);
The_Message : [The_Core_Message](#);
end record;

References:

[generic_message_structures.ads:20:9](#) (declaration)
[generic_router.ads:31:44](#) (reference)

Messages_Mailbox

- [Goto declaration in source](#)

type Messages_Mailbox is record
Sender : [Router_Range](#) := [Router_Range](#)'Invalid_Value;
The_Message : [The_Core_Message](#) := [Message_Strings.To_Bounded_String](#) ("");
Hop_Counter : [Natural](#) := 0;
end record;

References:

[generic_message_structures.ads:25:9](#) (declaration)
[generic_router.ads:32:44](#) (reference)
[test_routers.adb:241:37](#) (reference)

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro