

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat  edu_assist_pro

Dr. Liam O'Connor
University of Edinburgh LFCS
UNSW, Term 3 2020

λ-Calculus

The term language we defined for Higher Order Abstract Syntax is almost a full featured programming language.
Just enrich the syntax slightly:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

| $\lambda x. t$ (λ -

Add WeChat edu_assist_pro

There is just one rule to evaluate terms, called

$$(\lambda x. t) u \mapsto_{\beta} t[x := u]$$

Just as in Haskell, $(\lambda x. t)$ denotes a **function** that, given an argument for x , will return t .

Syntax Concerns

Function application is left-associative:

Assignment Project Exam Help

$$f\ a\ b\ c \quad = \quad ((f\ a)\ b)\ c$$

λ -abstraction ex

<https://eduassistpro.github.io/>

$$\lambda a. f\ a\ b \quad = \quad \lambda a. (f\ a\ b)$$

All functions are unary like Haskell. Multiple argument functions are written as nested λ -abstractions:

Add WeChat edu_assist_pro

$$\lambda x. \lambda y. x + y$$

β-reduction

β-reduction is a *congruence*:

Assignment Project Exam Help

$$(\lambda x. t) u \mapsto_{\beta} t[x := u]$$

<https://eduassistpro.github.io/>

This means we can pick any reducible subexpression (called a *redex*) and perform β-reduction.

Add WeChat edu_assist_pro

β-reduction

β-reduction is a *congruence*:

Assignment Project Exam Help

$$(\lambda x. t) u \mapsto_{\beta} t[x := u]$$

<https://eduassistpro.github.io/>

This means we can pick any reducible subexpression (called a *redex*) and perform β-reduction.

Example:

Add WeChat edu_assist_pro

$$(\lambda x. \lambda y. f (y \ x)) \ 5 \ (\lambda x. x)$$

β-reduction

β-reduction is a *congruence*:

Assignment Project Exam Help

$$(\lambda x. t) u \mapsto_{\beta} t[x := u]$$

<https://eduassistpro.github.io/>

This means we can pick any reducible subexpression (called a *redex*) and perform β-reduction.

Example:

Add WeChat edu_assist_pro

$$(\lambda x. \lambda y. f (y x)) 5 (\lambda x. x) \mapsto_{\beta} (\lambda y. f (y 5)) (\lambda x. x)$$

β-reduction

β-reduction is a *congruence*:

Assignment Project Exam Help

$$(\lambda x. t) u \mapsto_{\beta} t[x := u]$$

<https://eduassistpro.github.io/>

This means we can pick any reducible subexpression (called a *redex*) and perform a β-reduction.

Example:

Add WeChat edu_assist_pro

$$\begin{aligned} (\lambda x. \lambda y. f (y x)) 5 (\lambda x. x) &\mapsto_{\beta} (\lambda y. f (y 5)) (\lambda x. x) \\ &\mapsto_{\beta} f ((\lambda x. x) 5) \end{aligned}$$

β-reduction

β-reduction is a *congruence*:

Assignment Project Exam Help

$$(\lambda x. t) u \mapsto_{\beta} t[x := u]$$

<https://eduassistpro.github.io/>

This means we can pick any reducible subexpression (called a *redex*) and perform a β-reduction.

Example:

$$\begin{aligned} (\lambda x. \lambda y. f (y x)) 5 (\lambda x. x) &\mapsto_{\beta} (\lambda y. f (y 5)) (\lambda x. x) \\ &\mapsto_{\beta} f ((\lambda x. x) 5) \\ &\mapsto_{\beta} f 5 \end{aligned}$$

Confluence

Supposing we arrive via one reduction path to an expression that cannot be reduced further (called a *normal form*), then any other reduction path will result in the same normal form.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Confluence

Supposing we arrive via one reduction path to an expression that cannot be reduced further (called a *normal form*), then any other reduction path will result in the same normal form.

<https://eduassistpro.github.io/>

Add WeChat $(\lambda y. f y) 5$ edu_assist_pro

$f 5$

Confluence

Supposing we arrive via one reduction path to an expression that cannot be reduced further (called a *normal form*), then any other reduction path will result in the same normal form.

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

$(\lambda y. f y) 5$

$f 5$

Equivalence

Confluence means we can define another notion of *equivalence*, which equates more than α -equivalence. Two terms are $\alpha\beta$ -equivalent, written $s \equiv_{\alpha\beta} t$ if they β -reduce to α -equivalent no

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Equivalence

Confluence means we can define another notion of *equivalence*, which equates more than α -equivalence. Two terms are $\alpha\beta$ -*equivalent*, written $s \equiv_{\alpha\beta} t$ if they β -reduce to α -equivalent no

η

There is also another notion of equivalence alone, called η -reduction:

Add WeChat $\lambda x. \lambda y. x \rightarrow y$ edu_assist_pro

Adding this reduction to the system preserves confluence and uniqueness of normal forms, so we have a notion of $\alpha\beta\eta$ -*equivalence* also.

Normal Forms

Assignment Project Exam Help

Does every term in

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Normal Forms

Assignment Project Exam Help

Does every term in

<https://eduassistpro.github.io/>

Try to β -reduce this! (the answer is that it doesn't have a normal form)

Add WeChat edu_assist_pro

Why learn this stuff?

Assignment Project Exam Help

- λ -calculus is a *Turing-complete* programming language.

- λ -calculus is a non-functional programming language.

- λ -calculus is one of the two main foundations used for mathematics in interactive theorem provers.

- λ -calculus is the smallest example of a usable programming language for teaching about programming languages.

<https://eduassistpro.github.io/>

Add WeChat [edu_assist_pro](#)

Making λ -Calculus Usable

Assignment Project Exam Help

In order to demonstrate that λ calculus is actually a usable programming language, we will demonstrate terms, along with their operations.

<https://eduassistpro.github.io/>

General Idea

We transform a data type into the type of its *eli* e a function that can serve the same purpose as the data type at its use s

Add WeChat edu_assist_pro

Booleans

How do we **use** booleans?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Booleans

How do we use booleans? To choose between two results!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Booleans

How do we use booleans? To choose between two results!

So, a boolean will be a function that, given two arguments, returns the first one if it is true and the second one if it is false:

<https://eduassistpro.github.io/>

How do we write conjunction? to board

Add WeChat edu_assist_pro

Booleans

How do we use booleans? To choose between two results!

So, a boolean will be a function that, given two arguments, returns the first one if it is true and the second one if it is false:

<https://eduassistpro.github.io/>

How do we write conjunction? to board

$\text{AND} \equiv \lambda p. \lambda$
Add WeChat edu_assist_pro

Booleans

How do we **use** booleans? **To choose between two results!**

So, a boolean will be a function that, given two arguments, returns the first one if it is true and the second one if it is false:

<https://eduassistpro.github.io/>

How do we write conjunction? to board

Add WeChat $\text{AND} \equiv \lambda p. \lambda$ **edu_assist_pro**

Example (Test it out!)

Try β -normalising AND TRUE FALSE .

Booleans

How do we **use** booleans? **To choose between two results!**

So, a boolean will be a function that, given two arguments, returns the first one if it is true and the second one if it is false:

<https://eduassistpro.github.io/>

How do we write conjunction? to board

Add WeChat $\text{AND} \equiv \lambda p. \lambda$ **edu_assist_pro**

Example (Test it out!)

Try β -normalising AND TRUE FALSE .

What about **OR**?

Natural Numbers

How do we **use** natural numbers?

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Natural Numbers

How do we **use** natural numbers? To do something n times!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Natural Numbers

How do we use natural numbers? To do something n times!

Assignment Project Exam Help

So, a natural number will be a function that takes a function f and a value x , and applies the function f to x that number of times:

<https://eduassistpro.github.io/>

• • •

How do we write SUE? Add WeChat edu_assist_pro

Natural Numbers

How do we **use** natural numbers? **To do something n times!**

So, a natural number will be a function that takes a function f and a value x , and applies the function f to x that number of times:

<https://eduassistpro.github.io/>

How do we write SUC ? ...

$$SUC \equiv \lambda n. \lambda f. \lambda x$$

Add WeChat edu_assist_pro

Natural Numbers

How do we **use** natural numbers? **To do something n times!**

So, a natural number will be a function that takes a function f and a value x , and applies the function f to x that number of times:

<https://eduassistpro.github.io/>

How do we write **SUC**?

$$\text{SUC} \equiv \lambda n. \lambda f. \lambda x.$$

How do we write **ADD**?

...
Add WeChat edu_assist_pro

Natural Numbers

How do we **use** natural numbers? **To do something n times!**

So, a natural number will be a function that takes a function f and a value x , and applies the function f to x that number of times:

<https://eduassistpro.github.io/>

How do we write **SUC**?

$$\text{SUC} \equiv \lambda n. \lambda f. \lambda x.$$

How do we write **ADD**?

$$\text{ADD} \equiv \lambda m. \lambda n. \lambda f. \lambda x. m f (n f x)$$

Natural Numbers

How do we **use** natural numbers? **To do something n times!**

So, a natural number will be a function that takes a function f and a value x , and applies the function f to x that number of times:

<https://eduassistpro.github.io/>

How do we write **SUC**?

$$\text{SUC} \equiv \lambda n. \lambda f. \lambda x.$$

How do we write **ADD**?

$$\text{ADD} \equiv \lambda m. \lambda n. \lambda f. \lambda x. m f (n f x)$$

Natural Number Practice

Assignment Project Exam Help

Example

Try β -normalis

Example

<https://eduassistpro.github.io/>

Try writing a different λ -term for defining SUC.

Example

Add WeChat edu_assist_pro

Try writing a λ -term for defining MULTIPLY.