

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat **edu_assist_pro**

Christine Rizkallah
CSE, UNSW
Term 3 2020

Where we're at

- **Syntax Foundations** ✓

Concrete/Abstract Syntax, Ambiguity, HOAS, Binding, Variables, Substitution

- **Semantic**

Static Sem

Abstract M

Assignment 0)

- **Features**

- Algebraic Data Types ✓

- Polymorphism

- Polymorphic Type Inference (Assignment 2)

- Overloading

- Subtyping

- Modules

- Concurrency

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

A Swap Function

Assignment Project Exam Help

Consider the hum

<https://eduassistpro.github.io/>

In our MinHS with algebraic data types from last lecture, we can'

Add WeChat edu_assist_pro

Monomorphic

In MinHS, we're stuck copy-pasting our function over and over for every different type we want to use it with:

Assignment Project Exam Help

```
recfun swap1 :: ((Int × Bool) → (Bool × Int))
```

<https://eduassistpro.github.io/>

```
p = (snd p, fst p)
```

Add WeChat edu_assist_pro

```
recfun swap3 :: ((Bool × Bool
```

```
p = (snd p, fst p)
```

```
...
```

This is an acceptable state of affairs for some domain-specific languages, but not for general purpose programming.

Solutions

Assignment Project Exam Help

We want some way to specify that we **don't care** what the types of the tuple elements are.

<https://eduassistpro.github.io/>

This is called *parametric polymorphism* (or just programming circles). In Java and some other languages, this *parametric* and polymorphism refers to something else. Don't be confused.

Add WeChat [edu_assist_pro](https://eduassistpro.github.io/)

How it works

There are two main components to parametric polymorphism:

- 1 *Type abstraction* is the ability to define functions regardless of specific types (like the swap example before). In MinHS, we will write using **type** expressions like so:
(the literature uses Λ)

<https://eduassistpro.github.io/>

recfun swap :: (a b) (b a)

- 2 *Type application* is the ability to *instantiate* types. In MinHS, we use @ signs.

swap@Int@Bool (3, True)

Add WeChat edu_assist_pro

cfic

Analogies

The reason they're called type abstraction and application is that they behave analogously to λ -calculus.

We have a β -reduction principle, but for types:

<https://eduassistpro.github.io/>

Example (Identity Function)

```
type a. recfun f :: (a
  ↳ (recfun f :: (Int → Int
  ↳ 3
```

This means that **type** expressions can be thought of as **functions** from types to values.

Type Variables

What is the type of this?

Assignment Project Exam Help

(type a. recfun f : (a → a) x = x)

<https://eduassistpro.github.io/>

Types can mention *type variables* now¹.

Add WeChat edu_assist_pro

If $id : \forall a. a \rightarrow a$, what is the type of $id@Int$?

$$(a \rightarrow a)[a := Int] = (Int \rightarrow Int)$$

¹Technically, they already could with recursive types.

Typing Rules Sketch

Assignment Project Exam Help

We would like rules that look something like this:

<https://eduassistpro.github.io/>

$$\frac{\Gamma \vdash e : \forall a. \tau}{\Gamma \vdash e @ \rho : \tau[a : \rho]}$$

Add WeChat [edu_assist_pro](#)

But these rules don't account for what **type variables** are available

Type Wellformedness

With variables in the picture, we need to check our types to make sure that they only refer to well-scoped variables

Assignment Project Exam Help

<https://eduassistpro.github.io/>

$\Delta \vdash \tau_1 \rightarrow \tau_2 \text{ ok}$

Add WeChat (etc.) edu_assist_pro

$\Delta, a \text{ bound} \vdash \tau \text{ ok}$

$\Delta \vdash \forall a. \tau \text{ ok}$

Typing Rules, Properly

Assignment Project Exam Help

We add a **second context** of type variables that are bound.

<https://eduassistpro.github.io/>

$$\Delta; \Gamma \vdash e : \forall a. \tau$$

Add WeChat $\Delta; \Gamma \vdash e @ \rho : \tau[\rho]$ edu_assist_pro

(the other typing rules just pass Δ through)

Dynamic Semantics

Assignment Project Exam Help

First we evaluate the LHS of a type application as much as possible:

$\frac{}{\text{https://eduassistpro.github.io/}}$

Then we apply our β -reduction principle:

$\frac{}{(\text{type } a. e)@t \xrightarrow{\beta} e_M}$
Add WeChat edu_assist_pro

Curry-Howard

Previously, we noted the correspondence between types and logic:

Assignment Project Exam Help

<https://eduassistpro.github.io/>

→ ⇒
Add WeChat 1 edu_assist_pro

0 ⊥

∀ ∃

Curry-Howard

The type quantifier \forall corresponds to a universal quantifier \forall , but it is *not* the same as the \forall from first-order logic. What's the difference?

First-order logic quantifiers range over a set of *individuals* or values, for example the natural numbers

These quantifier

second-order logic, not first-order:

$$\begin{aligned} &\forall A. \forall B. A \times B \\ &\forall A. \forall B. A \times B \end{aligned}$$

The first-order quantifier has a type-theoretic analogue too (type indices), but this is not nearly as common as polymorphism.

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Generality

If we need a function of type $\text{Int} \rightarrow \text{Int}$, a polymorphic function of type $\forall a. a \rightarrow a$ will do just fine: we can just instantiate the type variable to Int . But the reverse is not true. This gives rise to an ordering.

Generality

A type τ is *more general* than a type ρ if ρ can be instantiated to give the type ρ .

Example (Functions)

$$\text{Int} \rightarrow \text{Int} \sqsubseteq \forall z. z \rightarrow z \sqsubseteq \forall x y. x \rightarrow y \sqsubseteq \forall a. a$$

Implementation Strategies

Assignment Project Exam Help

Our simple dyna

While we can easily

this is compiled to m

type in question.

There are two main approaches to solve this problem.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Template Instantiation

Key Idea

Automatically generate a monomorphic copy of each polymorphic function based on the types applied to it.

For example, if we d

<https://eduassistpro.github.io/>

$p =$

Then a type application like `swap@Int@Bool` w
compiler with the monomorphic version:

$$\begin{aligned} \text{swap}_{\text{IB}} &= \text{recfun } \text{swap} :: (\text{Int} \times \text{Bool}) \rightarrow (\text{Bool} \times \text{Int}) \\ p &= (\text{snd } p, \text{fst } p) \end{aligned}$$

A new copy is made for each unique type application.

Evaluating Template Instatiation

This approach has a number of advantages:

- 1 Little to no run-time cost
- 2 Simple men
- 3 Allows for cu
- 4 Easy to impl

However the downsides are just as numerous:

- 1 Large binary size if many instantiations are used
- 2 This can lead to long compilation times
- 3 Restricts the type system to **statically** instantiated type variables.

Languages that use Template Instantiation: Rust, C++, Cogent, some ML dialects

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Polymorphic Recursion

Consider the following Haskell data type:

Assignment Project Exam Help

`data Dims a = Step a (Dims [a]) | Epsilon`

This describes a list

<https://eduassistpro.github.io/>

We can write a sum function like this:

Add WeChat edu_assist_pro

`sumDims :: forall a. (a -> Int) -> Dims a -> Int`
`sumDims f Epsilon = 0`
`sumDims f (Step a t) = (f a) + sumDims (sum f) t`

How many different instantiations of the type variable *a* are there? We'd have to run the program to find out.

HM Types

Assignment Project Exam Help

Automatically generating a copy for each instantiation is great but can't handle all polymorphic programs.

In practice a static programs can be

- 1 Only allow \forall functions or type constructors).
- 2 Recursive functions ~~cannot~~ call themselves with differ

This restriction is sometimes called *Hindley-Milner* the subset for which *type inference* is both complete and tractable.

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

Boxing

Assignment Project Exam Help

An alternative to our copy-paste-heavy template instantiation approach is to make **all types** represent a

function in the generic

Typically this is done by storing a **pointer** to a data structure.

Exactly 32 (or 64) bits of stack space.

The extra indirection has a run-time penalty, and it can make garbage collection necessary, but it results in smaller binaries and unrestricted polymorphism.

Languages that use boxing: Haskell, Java, C#, OCaml

Constraining Implementations

Assignment Project Exam Help

How many possible implementations are there of a function of the following type?

<https://eduassistpro.github.io/>

How about this type

$\forall a. a \rightarrow a$
Add WeChat [edu_assist_pro](#)

Polymorphic type signatures constrain implementation

Parametricity

Definition

The principle of parametricity states that the result of polymorphic functions cannot depend on **values** of an abstracted type.

More formally, suppose f is a polymorphic function with n parameters. If we run any arbitrary function g on the result of f , then g must return the same result as f applied to the same parameters. If we run any arbitrary function g on the result of f , then g must return the same result as f applied to the same parameters.

Example

We know that **every** element of the output occurs in the input. The parametricity theorem we get is, for all f :

$$foo \circ (map\ f) = (map\ f) \circ foo$$

More Examples

Assignment Project Exam Help

$head :: \forall a. [a] \rightarrow a$

What's the param

<https://eduassistpro.github.io/>

Example (Ans

For any f :

Add WeChat edu_assist_pro

$f (head \ell) = head$

More Examples

Assignment Project Exam Help

$(++) :: a. [a] \rightarrow [a] \rightarrow [a]$

What's the param

<https://eduassistpro.github.io/>

Example (Answer)

Add WeChat `edu_assist_pro`

$map\ f\ (a ++ b) = map\ f\ a ++ map\ f\ b$

More Examples

Assignment Project Exam Help

concat :: *a*. $[[a]] \rightarrow [a]$

What's the param

<https://eduassistpro.github.io/>

Example (Answer)

Add WeChat [edu_assist_pro](#)

map f (concat s) = concat

Higher Order Functions

Assignment Project Exam Help

What's the param

<https://eduassistpro.github.io/>

Example (Ans

filter p (map f l) = map f

Add WeChat edu_assist_pro

Parametricity Theorems

Assignment Project Exam Help

Follow a similar str

parametricity f

the famous paper,

Upshot: We can ask lambdabot on the Haskell IRC c

relational

r in

<https://eduassistpro.github.io/>

Add WeChat edu_assist_pro

²<https://people.mpi-sws.org/~dreyer/tor/papers/wadler.pdf>