

# Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

Christine Rizkallah  
CSE, UNSW  
Term 3 2020

## Shared Data

Consider the **Readers and Writers** problem:

### Problem

We have a **large data structure** (i.e. a structure that cannot be updated in one atomic step) that is shared between many readers and some writers. Some of the data structure is mutable.

<https://eduassistpro.github.io/>

Desiderata:

- We want **atomicity**, in that each update happens in one step. Updates-in-progress or partial updates are not observable.
- We want **consistency**, in that any reader that starts after an update finishes will see that update.
- We want to minimise **waiting**.

Add WeChat edu\_assist\_pro

## A Crappy Solution

# Assignment Project Exam Help

Treat both reads and updates as critical sections — use any old critical section solution (locks, et

<https://eduassistpro.github.io/>

### Observation

Updates are *atomic* and reads are *consistent* — b tly,  
which leads to unnecessary *contention*.

Add WeChat edu\_assist\_pro

## A Better Solution

# Assignment Project Exam Help

A more elaborate locking mechanism (*condition variables*) could be used to allow multiple readers to read atomically.

<https://eduassistpro.github.io/>

### Observation

We have atomicity and consistency, and now multiple readers can

Still, we don't allow updates to execute concurrently with reads. Updates must wait until no readers are observing the data.

Add WeChat [edu\\_assist\\_pro](https://eduassistpro.github.io/)

## Reading and Writing

### Complicated Assignment Project Exam Help

Now suppose we don't want readers to wait (much) while an update is performed.  
Instead, we'd rather

**Trick:** Rather than *their own local* copy of the data structure, and then merely updates the (shared) data structure to point to their copy.

**Atomicity** The only shared write is now just to one pointer.

**Consistency** Reads that start before the pointer update get the older version, but reads that start after get the latest.


<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

## Persistent Data Structures

Copying is  $\mathcal{O}(n)$  in the worst case, but we can do better for many tree-like types of data structure.

# Assignment Project Exam Help

Example (Binary Search Tree)



## Purely Functional Data Structures

# Assignment Project Exam Help

Persistent data structures that exclusively make use of copying over mutation are called *purely functional* data structures. They are so called because operations on them are best expressed as returning a new structure, rather than mutating the old one.

<https://eduassistpro.github.io/>

*insert*  $v$  (Branch  $\times l$   $r$ ) = if

Add WeChat *edu\_assist\_pro*

els

Branch  $\times l$  (*insert*  $v$   $r$ )

## Computing with Functions

# Assignment Project Exam Help

We model real processes in Haskell using the `IO` type. We'll treat `IO` as an abstract type for now, and `gi`

$\text{IO } \tau =$  <https://eduassistpro.github.io/>  
result of type  $\tau$

Note the semantics of *evaluation* and *execution*

Add WeChat edu\_assist\_pro



## Building up IO

Recall **monads**:

# Assignment Project Exam Help

```
return :: ∀a. a → IO a
(≫=) :: ∀a b. IO a → (a → IO b) → IO b
getChar :: IO Char
```

Example (Echo)

```
echo :: IO ()
echo = getChar ≫= (λx. put
```

Or, with **do** notation:

```
echo :: IO ()
echo = do x ← getChar
          putChar x
          echo
```

<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

## Adding Concurrency

We can have multiple threads easily enough

<https://eduassistpro.github.io/>

Example (Duel)

```
let loop c = do putC
in do for IO loop a'
```

Add WeChat edu\_assist\_pro

But what sort of *synchronisation primitives* are available?

## MVars

The **MVar** is the simplest synchronisation primitive in Haskell. It can be thought of as a shared box which holds at most one value.

Processes must take an **empty** box to update.

### MVar Functions

$\text{newMVar} :: \forall a. a \rightarrow \text{IO (MVar } a)$	Create a new MVar
$\text{takeMVar} :: \forall a. \text{MVar } a \rightarrow \text{IO } a$	Read/retire
$\text{putMVar} :: \forall a. \text{MVar } a \rightarrow a \rightarrow \text{IO } ()$	Update/increase

Taking from an empty MVar or putting into a full one results in blocking.  
An MVar can be thought of as channel containing at most one value.

## Readers and Writers

We can treat MVars as shared variables with some definitions:

Assignment Project Exam Help

```
writeMVar m v = do takeMVar m; putMVar m v  
readMVar m = do v ← takeMVar m; putMVar m v; return v
```

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

```
let reader = readMVar db >>= ...  
let writer = do  
  takeMVar wl  
  d ← readMVar db  
  let d' = update d  
  evaluate d'  
  writeMVar db d'  
  putMVar wl ()
```

## Fairness

# Assignment Project Exam Help

Each MVar has an a  
fairness property

*No thread can  
that MVar indefinitely.*

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## The Problem with Locks

# Assignment Project Exam Help

### Problem

Write a procedure  
simple, both acco

The procedure must operate correctly in a concurrent program, in which many threads  
may call transfer simultaneously. No thread should be able to o  
the money has left one account, but not arrived in the other (or vice v

<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

## The Problem with Locks

# Assignment Project Exam Help

Assume some infrastructure for accounts.

*t*

*t*

*w*

*withdraw a m = takeMVar a >>= (*

*deposit* : Account → Int → IO ())

*deposit a m = withdraw a (−m)*

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Attempt #1

## Assignment Project Exam Help

$$\text{transfer } f \ t \ m = \text{do } \text{withdraw } f \ m; \text{deposit } t \ m$$

## Problem

The intermediate state is not externally observable.

In a bank, we might want the invariant that at all points during the transaction, the amount of money in the system remains constant. We should have a missing<sup>a</sup>.

---

<sup>a</sup>We're not CBA

<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro



## Attempt #2

## Assignment Project Exam Help

```
transfer f t m = do  
  fb ← takeMVar f
```

<https://eduassistpro.github.io/>

## Problem

We can have *deadlock* here, when two people transfer 1 and both transfers proceed in lock-step.

Also, not being able to compose our existing *withdrawal* and *deposit* operations is unfortuitous from a software design perspective.

Add WeChat edu\_assist\_pro

## Solution

We should enforce a *global* ordering of locks.

# Assignment Project Exam Help

```
type Account = (MVar Balance, AccountNo)
```

```
transfer (f, fa) (t, ta) m = do
```

<https://eduassistpro.github.io/>

```
    tb ← takeMVar t
```

```
    pure (fb, tb)
```

```
  else do
```

```
    tb ← takeMVar t
```

```
    fb ← takeMVar f
```

```
    pure (fb, tb)
```

```
    putMVar t (tb + m)
```

```
    putMVar f (fb - m)
```

# Add WeChat edu\_assist\_pro

## It Gets Complicated

# Assignment Project Exam Help

### Problem

Now suppose that  
withdrawn from if I

<https://eduassistpro.github.io/>

Should you take the lock for the backup account?

**To make life even harder:** What if we want to  
available?

Add WeChat [edu\\_assist\\_pro](#)

## Conclusion

*Lock-based methods* have their place, but from a software engineering perspective they're a nightmare.

- Remember
- Remember
- Remember
- Remember not to take the locks in the wrong order.
- Remember to deal with locks when an error occurs.
- Remember to signal condition variables and release loc

Most importantly, *modular programming* becomes impossible.

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

## The Solution

Represent an account as a simple shared variable containing the balance.

# Assignment Project Exam Help

*transfer f t m = atomically \$ do*

<https://eduassistpro.github.io/>

Where *atomic*

**Atomicity** The effects of the action  $P$  become

**Isolation** The effects of action  $P$  is not affected

# Add WeChat edu\_assist\_pro

### Problem

How can we implement *atomically*?

## The Global Lock

# Assignment Project Exam Help

We can adopt the so

### Problem

Atomicity is guar

Also, performance is predictably garbage.

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Ensuring Isolation

Rather than use regular shared variables, use special *transactional variables*.

**Assignment Project Exam Help**

$createTVar \quad :: \quad a \rightarrow STM \ (TVar \ a)$

<https://eduassistpro.github.io/>

The type constructor `STM` is also an instance of the `Monad` type class, thus supports the same basic operations as `IO`.

**Add WeChat edu\_assist\_pro**

$pure \quad :: \quad a \rightarrow STM \ (TVar \ a)$   
 $(\gg=) \quad :: \quad STM \ a \rightarrow (a \rightarrow STM \ b) \rightarrow STM \ b$

## Implementing Accounts

# Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`

**Observe:** *withdraw* (resp. *deposit*) can **only** be called **linearly** ⇒ **We have isolation.**

But, we'd still like to run more than one transaction at once — one global lock isn't good enough.



## Optimistic Execution

Each transaction (atomically block) is executed *optimistically*. This means they do not need to check that they are allowed to execute the transaction first (unlike, say, locks, which prefer a *pessimistic* model).

### Implementation

Each transaction

- The values written to any TVars with *write*
- The values read from any TVars with *read* ies first.

First the log is *validated*, and, if validation succeeds, ch *ted.*

Validation and commit are *one atomic step*.

What can we do if validation fails? *We re-run the transaction!*

## Re-running transactions

# Assignment Project Exam Help

<https://eduassistpro.github.io/>

To avoid serious international side-effects, the transaction  
can't change the world until *commit* time

Add WeChat **edu\_assist\_pro** *able*. We

A real implementation is smart enough not to retry with exactly t

## Blocking and *retry*

### Problem

We want to *block* if insufficient funds are available.

We can use the help of

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

```
withdraw a m = do
```

```
  balance ← readTVar
```

```
  if m > 0 && m > b
```

```
    retry
```

```
  else
```

```
    writeTVar a (balance - m)
```

## Choice and *orElse*

### Problem

# Assignment Project Exam Help

We want to transfer from a backup account if the first account has insufficient funds, and *block* if neit

We can use the helpf

<https://eduassistpro.github.io/>

*orElse* :: STM *a* → ST

## Add WeChat edu\_assist\_pro

*wdBackup* :: Account → Account →

*wdBackup* *a*<sub>1</sub> *a*<sub>2</sub> *m* = *orElse* (*withdraw*' *a*<sub>1</sub> *m*) (*withdraw*' *a*<sub>2</sub> *m*)

## Evaluating STM

# Assignment Project Exam Help

STM is *modular*. We can compose transactions out of smaller transactions. We can hide concurrency invariants.

Lock-free data structures have low contention and under those circumstances scale better than lock-based ones.

Most importantly, the resulting code is often simpler and more profitable!

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Progress

# Assignment Project Exam Help

*One transaction can force another to abort only when it commits.*

*At any time,*

*t.*

<https://eduassistpro.github.io/>

Traditional dea

transactions constantly cancel each other.

*Starvation* is possible (*when*), however uncommon in pra  
don't have *eventual* entry.

Add WeChat edu\_assist\_pro

## Performance

# Assignment Project Exam Help

A concurrent cha

MVar version.

The STM version p

If of the heap

space → Pro

<https://eduassistpro.github.io/>

The implementation is a bit simpler as well. Let's do it if we have time! Jus

Add WeChat edu\_assist\_pro

---

<sup>1</sup>Mostly, the MVar implementation performed poorly due to lots of overhead to make it exception-safe.

## Database Guarantees

# Assignment Project Exam Help

**Atomicity** ✓ Each transaction should be 'all or nothing'.

**Consistency**

**Isolation** <sup>p</sup> <https://eduassistpro.github.io/>  
transactions.

**Durability** The transaction's effect on the state survive

STM gives you 75% of a database system. The Haskell package *te* builds on STM to give you all four.

Add WeChat [edu\\_assist\\_pro](#)



## Hardware Transactional Memory

The latest round of Intel processors support *Hardware Transactional Memory* instructions.

**XBEGIN** Begin a hardware transaction

**XEND**

**XTEST**

**XABORT**

The “log” we described earlier is stored in *L1 cache* and to the amount of cache we have. If a speculative read overflows the cache, sometimes generate a *spurious conflicts* and cause t

For this reason, progress can only be ensured through the *combination* of STM and HTM. Work is currently underway to implement this for Haskell, and prototypes show promising performance improvements.

Assignment Project Exam Help  
<https://eduassistpro.github.io/>  
Add WeChat edu\_assist\_pro

## That's it

We have now covered all the content in COMP3161/COMP9164. Thanks for sticking with the course

- **Syntax Foundations**

Concrete/

$\lambda$ -calculus

tution,

- **Semantic**

Static Semantics, Dynamic Semantics (Small-Step/Big-Step), Abstract Machines, Environments, Stacks, Safety, Liveness, Type Safety

- **Features**

- Algebraic Data Types, Recursive Types
- Exceptions
- Polymorphism, Type Inference, Unification
- Overloading, Subtyping, Abstract Data Types
- Concurrency, Critical Sections, STM

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## MyExperience

# Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

<https://myexperience.unsw.edu.au>

## Further Learning

- UNSW courses:

- COMP3141 — Software System Design and Implementation
- COMP6721 — (In-)formal Methods
- COMP3131 — Compilers
- COMP
- COMP
- COMP
- COMP4161 — Advanced Topics in Verification
- COMP3153 — Algorithmic Verification

- Online Learning

- Oregon Programming Languages Summer School  
(<https://www.cs.uoregon.edu/research/summerschool/archives.html>)  
Videos are available from here! Also some on YouTube.
- Bartosz Milewski's Lectures on Category Theory are on YouTube.

- Books — see Liam's Book List!

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## What's next?

# Assignment Project Exam Help

The exam is on

- I have posted
- The final exa
- It runs for 2 hours and 10 minutes.

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro

## Evaluation Semantics

The semantics of Haskell's evaluation are interesting but not particularly relevant for us. We will assume that it happens quietly without a fuss:

<https://eduassistpro.github.io/>

Let our ambient congruence relation  $\equiv$  be  $\equiv_{\alpha\beta\eta}$  tra  
equations, justified by the *monad laws*:

$$\begin{aligned} \text{return } N \gg= M &\equiv M \ N \\ (X \gg= Y) \gg= Z &\equiv X \gg= (\lambda x. Y \ x \gg= Z) \\ X &\equiv X \gg= \text{return} \end{aligned}$$

Add WeChat edu\_assist\_pro

## Processes

This means that a Haskell expression of type  $\text{IO } \tau$  for will boil down to either *return*  $x$  where  $x$  is a value of type  $\tau$ , or a  $\gg= M$  where  $a$  is some primitive IO *action* (*forkIO*  $p$ , *readMVar*  $v$ , etc.) and  $M$  is some function producing another  $\text{IO } \tau$ . This is the *head normal form*.

### Definition

Define a language  
 $\text{IO } ()$ .

ons of type

We want to define the semantics of the *execution*  
*operational semantics*:

$$(\mapsto) \subseteq P \times P$$

## Semantics for forkIO

To model *forkIO*, we need to model the parallel execution of multiple processes in our process language. We shall add a *parallel composition* operator to the language of processes:

<https://eduassistpro.github.io/>

| ...

And the following ambient congruence equations

$$\begin{aligned} P \parallel Q &\equiv Q \parallel P \\ P \parallel (Q \parallel R) &\equiv (P \parallel Q) \parallel R \end{aligned}$$

Add WeChat [edu\\_assist\\_pro](#)



## Semantics for forkIO

# Assignment Project Exam Help

If we have multiple processes active, pick one of them non-deterministically to move:

<https://eduassistpro.github.io/>

The *forkIO* operation introduces a new process:

Add WeChat  $(\text{forkIO } P \gg \equiv M) \parallel F$  edu\_assist\_pro

## Semantics for MVars

MVars are modelled as a special type of *process* identified by a *unique name*. Values of `MVar` type merely contain the name of the process, so that `putMVar` and friends know where to look

<https://eduassistpro.github.io/>

Add WeChat [edu\\_assist\\_pro](#)

$$\langle \rangle_n \parallel (\text{putMVar } n \ v \gg M) \mapsto \langle \rangle_n \parallel M$$

$$\langle v \rangle_n \parallel (\text{takeMVar } n \gg M) \mapsto \langle \rangle_n \parallel (\text{return } v \gg M)$$

## Semantics for newMVar

We might think that `newMVar` should have semantics like this:

(  
resh)

But this approach

- The name *n* is now globally-scoped, without an `exp`
- It doesn't accurately model the *lifetime* of the garbage-collected object once all processes that can access it finish
- It makes MVars *global* objects, so our semantics aren't very *abstract*. We would like local communication to be local in our model.

## Restriction Operator

We introduce a *restriction operator*  $\nu$  to our language of processes:

# Assignment Project Exam Help

$$P, Q ::= \dots \gg M$$

<https://eduassistpro.github.io/>

Writing  $(\nu n) P$  says that the MVar name  $n$  is <sup>o</sup> Mentioning  $n$  outside  $P$  is not well-formed. We need the following  $\text{gadt}$  li.

$$\begin{aligned} (\nu n) (\nu m) P &\equiv (\nu m) (\nu n) P \\ (\nu n) (P \parallel Q) &\equiv P \parallel (\nu n) Q \quad (\text{if } n \notin P) \end{aligned}$$

## Better Semantics for newMVar

The rule for *newMVar* is much the same as before, but now we explicitly restrict the MVar to *M*.

$$\frac{}{(new \quad \text{---} \quad (n \text{ fresh}))}$$

We can always exe

$$\frac{P \mapsto P'}{(M \ n) \ P \mapsto (P')}$$

### Question

What happens when you put an MVar inside another MVar?

## Garbage Collection

# Assignment Project Exam Help

If an MVar is no longer used, we just replace it with the do-nothing process:

<https://eduassistpro.github.io/>

Extra processes that have outlived their usefulness disappear:

Add WeChat `return () || P` edu\_assist\_pro

## Process Algebra

# Assignment Project Exam Help

Our language  $P$  is called a *process algebra*, a common means of describing semantics for concurrent pr

Process algebras  
with Rob van Glab

<https://eduassistpro.github.io/>

**If there's time!**

We can talk about more concurrency topics.

Add WeChat edu\_assist\_pro

## Bibliography



Simon Marlow

Parallel and Concurrent Programming in Haskell

O'Reilly, 2013

<http://chi>



Simon Peyton

Concurrent H

POPL '96

Association for Computer Machinery

<http://microsoft.com/ecs/research/wp-content/uploads/2016/01/c>



Simon Marlow (Editor)

Haskell 2010 Language Report

<https://www.haskell.org/onlinereport/haskell2010/>

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro



## Bibliography



Simon Peyton Jones

Beautiful Concurrency

In "Beautiful Code", ed. Greg Wilson, O'Reilly, 2001

<http://www.microsoft.com/en-us/research/wp-content/uploads/2016/02/beautiful.pdf>



Tim Harris, Si

Composable

PPoP '05

Association for Computer Machinery

[www.microsoft.com/en-us/research/wp-content/uploads/2005/01/2005-pp](http://www.microsoft.com/en-us/research/wp-content/uploads/2005/01/2005-pp)



David Himmelstrup

Acid-State Library

<https://github.com/acid-state/acid-state>



Ryan Yates and Michael L. Scott

A Hybrid TM for Haskell

TRANSACT '14

Association for Computer Machinery

Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat edu\_assist\_pro