C501: Computer Architecture Assessed Coursework

Due date: 15^{th} November 2017 (Hard-copy to SAO by 16:00)

1. Boolean Algebra and Digital Circuits

(a) Simplify the following Boolean expressions to its simplest form. The symbols ●, +, and ' represent "AND", "OR" and "NOT" operations respectively. Please show the sequence of steps and state the reduction rules used.

(i)
$$E = A \cdot B + B \cdot (A' + A \cdot B)$$
 (5 marks)

Answer

 $E = A \cdot B + B \cdot (A' + A \cdot B)$
 $E = B \cdot (A + A' + A \cdot B)$ (Distributed Rule)

ASSIGNMENT Project Exam Hemitication Rule)

 $E = B$

(ii) $E = ($ (10 marks)

Answhittps://eduassistpro.github.io/

 $E = A' \cdot B' \cdot C' \cdot D' \cdot F' + A' \cdot B'$ (De Morgan's Rule)

 $E = (A' \cdot B') \cdot (C' \cdot D' \cdot F' + 1)$ (Distributed Rule)

 $E = (A \cdot B') \cdot (C' \cdot D' \cdot F' + 1)$ (Distributed Rule)

 $E = (A \cdot B') \cdot (C' \cdot D' \cdot F' + 1)$ (Distributed Rule)

 $E = (A \cdot B') \cdot (C' \cdot D' \cdot F' + 1)$ (Distributed Rule)


 $E = (A \cdot B') \cdot (C' \cdot D' \cdot F' + 1)$ (Distributed Rule)

 $E = (A \cdot B') \cdot (C' \cdot D' \cdot F' + 1)$ (Distributed Rule)

(b) Use Boolean Algebra to simplify the following expression and then draw the logic circuit for the simplified expression. $E = A \bullet (B + A \bullet B) + A \bullet C$ (10 marks)


Answer

$$\begin{split} E &= A \bullet (B + A \bullet B) + A \bullet C \\ E &= A \bullet B + A \bullet C \\ E &= A \bullet (B + C) \end{split} \tag{Simplification Rule}$$



(c) NOR gates as well as NAND gates are considered as universal gates. Build a circuit for the following Boolean expression $E = A \bullet B$ using only NOR gates. Prove that your circuit works, either by using truth tables or Boolean Algebra reduction rules. (15 marks)

Answer



Looking at the circuit, we get:

$$E = ((A+A)' + (B+B)')'$$

$$E = ((A+A)')' \bullet ((B+B)')'$$

$$E = (A+A) \bullet (B+B)$$
(Negation Rule)
$$E = A \bullet B$$
(Idempotent Rule)

This shows that the circuit above gives us $E = A \bullet B$ using only NOR gates.

2. Binary Arithmetic

Show your working clearly.

(a) Assume that you use 5-bits to represent a number. Using 2's complement representation for numbers, show the calculations of:

A Signment Project Exam Help (5 marks)

While using 2's complement, 9 - 11 can be calculated as 9 + (-11). Converting to binary repre

https://eduassistpro.github.io/

Binary value of 11 = 01011

1s complement of 11=10100 2s complement of 11=10100 2s complement of 11=10100 Putting this together:

01001 + 10101 - 11110

We get a two's complement number. Converting back into positive, we get 00010 = 2.

(ii) -12 - 10. (10 marks)

While using 2's complement, -12 - 10 can be calculated as -12 + (-10). Converting to binary representations for -12 and (-10), we get:

Binary value of 12 = 011001s complement of 12 = 100112s complement of 12 = 10011 + 1 = 10100Binary value of 10 = 010101s complement of 10 = 101012s complement of 10 = 10101 + 1 = 10110 Putting this together:

10100 +

10110

101010

Discarding the overflow, we have 01010, but this is a positive number. In this case two numbers whose signs were different were subtracted, but the result has the opposite sign and the sign of the subtrahend, which is an Overflow and hence a wrong value.

(b) Evaluate $\frac{189}{27}$ using Binary Arithmetic.

(15 marks)

Answer

Binary value of 189 = 10111101

Binary value of 27 = 11011

Using long-division method (any other method is also acceptable)

0111

Assignment Project Exam Help

https://eduassistpro.github.io/
Add-WeChat edu_assist_pro

Answer = 111

3. Floating Point Numbers

Show your working clearly.

(a) Convert the decimal number, -31.1 into IEEE Single Precision format and its corresponding hexadecimal value. (15 marks)

Answer

We start off by ignoring the sign.

Breaking up the number into before and after decimal, we get

Binary of 31 = 11111

Binary of 0.1 is = 0.000110011001100110011001 (recurring)

Binary of 31.1 is = 11111.000110011001100110011001 (recurring)

Normalising, we get: 1.11110001100110011001101 (rounding up) * 2^4

Significand is thus: 1111000110011001101

Exponent field is (4 + 127 = 131): 10000011

We can now add the sign field, which would be 1 here.

Stored as: 1100 0001 1111 1000 1100 1100 1101

Hexadecimal: C1F8CCCD

(b) Using the IEEE Single Precision format, convert the following hexadecimal number, 40F109D5 into binary and decimal. (15 marks)

Answer

40F109D5 is stored in binary as: 0100 0000 1111 0001 0000 1001 1101 0101

Sign bit is: 0 (number is positive)

Exponent field is: 10000001 (129 - 127 = 2) Significand is thus: 11100010000100111010101

Normalised number is thus: 1.11100010000100111010101 * 2^2

Number is: 111.100010000100111010101

Converting to Decimal, we get:

Converting to Beefinal, we get: $(2^{2} + 2^{1} + 2^{0}).(2^{-1} + 2^{-5} + 2^{-10} + 2^{-13} 2^{-14} + 2^{-15} + 2^{-17} + 2^{-19} + 2^{-21})$ = 7.53245 (Rounded values are accepted)

https://eduassistpro.github.io/ Add WeChat edu_assist_pro