

# Assignment 4

Due: 20 March at 11:59pm

Implement a LeBlanc-Cook symbol table by completing the given class. You should create unit tests for the given methods.

Create a Visitor class called TypeCheckVisitor by completing the given class. Your visitor should traverse the AST generated by your parser from Assignment 3 and perform type checking according to the rules described below. Your Visitor class will both decorate the tree and check conditions along the way. If a condition is violated, throw a TypeCheckException.

Global rules: no variable may be declared more than once in the same scope.

The name of the program is not a variable name—it is used to name the class implemented by the program but does not preclude the same name being declared as a variable.

## Assignment Project Exam Help

SymbolTable symbab = new SymbolTable()

<https://eduassistpro.github.io/>

```
Program ::= L
ParamDec ::=
Block ::= symtab.enterScope() List<Dec> Li leaveScope()
Dec ::= type ident symtab.insert(ident.getText(), type)
Statement ::= SleepStatement | WhileStatement
              | AssignmentStatement
SleepStatement ::= Expression condition: Expression.type==INTEGER
AssignmentStatement ::= IdentLValue Expression
                      condition: IdentLValue.type== Expression.type
Chain ::= ChainElem | BinaryChain
ChainElem ::= IdentChain | FilterOpChain | FrameOpChain | ImageOpChain
IdentChain ::= ident
              condition: ident has been declared and is visible in the current scope
              IdentChain.type <- ident.type
              ident.type <- symtab.lookup(ident.getText()).getType()
FilterOpChain ::= filterOp Tuple
              condition: Tuple.length == 0
              FilterOpChain.type <- IMAGE
FrameOpChain ::= frameOp Tuple
              if (FrameOP.isKind(KW_SHOW, KW_HIDE) {
                condition: Tuple.length == 0
```

```

    FrameOpChain.type <- NONE
  }
  else if (FrameOp.isKind(KW_XLOC, KW_YLOC){
    condition: Tuple.length == 0
    FrameOpChain.type <- INTEGER
  }
  else if(FrameOp.isKind(KW_MOVE){
    condition: Tuple.length == 2
    FrameOpChain.type <- NONE
  }
  else there is a bug in your parser

```

ImageOpChain ::= imageOp Tuple

```

  if (imageOp.isKind(OP_WIDTH, OP_HEIGHT){
    condition: Tuple.length == 0
    ImageOpChain.type <- INTEGER
  }
  else if (imageOp.isKind(KW_SHOW, KW_HIDE, KW_MOVE){
    condition: Tuple.length==1
    ImageOpChain.type <- FRAME
  }
  else there is a bug in your parser

```

BinaryChain

**Assignment Project Exam Help**  
<https://eduassistpro.github.io/>

Legal combinations shown:

**Add WeChat edu\_assist\_pro**

| BinaryChain    | Chain        | op             |   |
|----------------|--------------|----------------|---|
| type <-IMAGE   | type =URL    | arrow          | type = IMAGE  |
| type <-IMAGE   | type = FILE  | arrow          | type = IMAGE  |
| type <-INTEGER | type = FRAME | arrow          | instanceof FrameOp &<br>firstToken ∈ { KW_XLOC,<br>KW_YLOC}                   |
| type <-FRAME   | type = FRAME | arrow          | instanceof FrameOp &<br>firstToken ∈ { KW_SHOW,<br>KW_HIDE, KW_MOVE}          |
| type <-INTEGER | type = IMAGE | arrow          | instanceof ImageOpChain) &&<br>firstToken ∈ { OP_WIDTH,<br>OP_HEIGHT}         |
| type <-FRAME   | type = IMAGE | arrow          | type = FRAME  |
| type <-NONE    | type = IMAGE | arrow          | type = FILE   |
| type <-IMAGE   | type = IMAGE | arrow   barrow | instanceof FilterOpChain &<br>firstToken ∈ {OP_GRAY,<br>OP_BLUR, OP_CONVOLVE} |
| type <-IMAGE   | type = IMAGE | arrow          | instanceof ImageOpChain &   |

|               |              |       |                             |
|---------------|--------------|-------|-----------------------------|
|               |              |       | firstToken $\in$ {KW_SCALE} |
| type <- IMAGE | type = IMAGE | arrow | instanceof IdentChain       |

WhileStatement ::= Expression Block

condition: Expression.type = Boolean

IfStatement ::= Expression Block

condition: Expression.type = Boolean

Expression ::= IdentExpression | IntLitExpression | BooleanLitExpression |

ConstantExpression | BinaryExpression

IdentExpression ::= ident

condition: ident has been declared and is visible in the current scope

IdentExpression.type <- ident.type

IdentExpression.dec <- Dec of ident

IdentLValue ::= ident

condition: ident has been declared and is visible in the current scope

IdentLValue.dec <- Dec of ident

IntLitExpression ::= intLit

IntLitE

BooleanLitEx

Boole

ConstantExpression ::= screenWidth | screen

ConstantExpression.type <- INTEGER

BinaryExpression ::= Expression op Expressi

Legal combinations shown:

| BinaryExpression.type | Expression0.type | op              | Expression1.type                                     |
|-----------------------|------------------|-----------------|--|
| INTEGER               | INTEGER          | PLUS, MINUS     | INTEGER  |
| IMAGE                 | IMAGE            | PLUS, MINUS     | IMAGE  |
| INTEGER               | INTEGER          | TIMES, DIV      | INTEGER  |
| IMAGE                 | INTEGER          | TIMES           | IMAGE  |
| IMAGE                 | IMAGE            | TIMES           | INTEGER  |
| BOOLEAN               | INTEGER          | LT, GT, LE, GE  | INTEGER  |
| BOOLEAN               | BOOLEAN          | LT, GT, LE, GE  | BOOLEAN  |
| BOOLEAN               |                  | EQUAL, NOTEQUAL | condition:<br>Expression0.type =<br>Expression1.type |

Tuple ::= List<Expression>

condition: for all expression in List<Expression>: Expression.type = INTEGER

op ::= relOp | weakOp | strongOp  
type ::= integer | image | frame | file | boolean | url

You will need to add an attribute along with get and set methods to some of the AST classes to record the type. In particular, add a TypeName field to Expression, Dec, and Chain. TypeName is defined in class cop5556sp17.AST and provided for you. Note that it is inherited by all of the subclasses of the given classes. If your Parser and Scanner have been implemented correctly, you shouldn't need to modify them.

A couple of junit tests have been provided in TypeCheckVisitorTest.java. You need to add more. As before you can work incrementally by calling the parser with a different method than parse.

**Turn in a jar file containing your source code TypeCheckVisitor.java, SymbolTable.java, Parser.java, Scanner.java, all of the AST nodes, Type.java, and your TypeCheckVisitorTest.java.**

## Assignment Project Exam Help

Your TypeCheckVisitorTest.java will not be graded, but may be looked at in case of academic honesty issues. We your grade will be determined solely by the following format:  
*firstname\_lastname*

<https://eduassistpro.github.io/>

## Add WeChat edu\_assist\_pro

Additional requirements:

- Your code must remain package cop5556sp17(case sensitive): do not create additional packages.
- The provided class Type is in package cop5556sp17.AST. As before, all of the classes in this package should be in a folder called AST inside the cop5556sp17 folder
- Names (of classes, method, variables, etc.) in the provided AST classes must not be changed.
- Unless otherwise specified, your code should not import any classes other than those from the standard Java distribution or those that are part of the project.

Submission Checklist

See the checklist from Assignment 1.

Comments and suggestions:

- Work incrementally, starting with small constructs and moving to bigger ones, and

adding tests each time. As in previous assignments, you can call the routines corresponding to fragments of the grammar in Junit tests.

- You can use the `firstToken` field in the case of errors to provide

## Assignment Project Exam Help

<https://eduassistpro.github.io/>

Add WeChat `edu_assist_pro`