

1 logic

1.1 Introduction to logic

This is a draft version of logic algebra package for Maxima. It is being developed by Alexey Beshenov (al@beshenov.ru). All source code is available under the terms of GNU GPL 2.1.

List of recognized operators:

Operator	Type	Binding power	Description	Properties
not	Prefix	70	Logical NOT (negation)	
and	N-ary	65	Logical AND (conjunction)	Commutative
nand	N-ary	62	Sheffer stroke (alternative denial, NAND)	Commutative
nor	N-ary	61	Webb-operation or Peirce arrow (Quine's dagger, NOR)	Commutative
or	N-ary	60	Logical OR (disjunction)	Commutative
implies	Infix	59	Implication	
eq	N-ary	58	Equivalence	Commutative
xor	N-ary	58	Sum modulo 2 (exclusive or)	Commutative

1.2 T_EX output

logic.mac assigns the following T_EX output:

not	<code>\neg</code>
and	<code>\wedge</code>
nand	<code>\mid</code>
nor	<code>\downarrow</code>
or	<code>\vee</code>
implies	<code>\rightarrow</code>
eq	<code>\sim</code>
xor	<code>\oplus</code>

Examples:

```
(%i1) load ("logic.mac")$
(%i2) tex (a implies b)$
$$$ \rightarrow b$$$
(%i3) tex ((a nor b) nand c)$
$$$ \left( a \downarrow b \right) \mid c$$$
```

```
(%i4) tex (zhegalkin_form (a or b or c))$
$$a \wedge b \wedge c \oplus a \wedge b \oplus a \wedge c \oplus b
\wedge c \oplus a \oplus b \oplus c$$
(%i5) tex (boolean_form (a implies b implies c));
$$ \neg \left( \neg a \vee b \right) \vee c$$
(%i6) tex (a eq b eq c);
$$a \sim b \sim c$$
```

$$a \rightarrow b$$

$$(a \downarrow b) \mid c$$

$$a \wedge b \wedge c \oplus a \wedge b \oplus a \wedge c \oplus b \wedge c \oplus a \oplus b \oplus c$$

$$\neg(\neg a \vee b) \vee c$$

$$a \sim b \sim c$$

1.3 Definitions for logic

logic_simp (expr)

[Function]

Returns a simplified version of logical expression *expr*.

Examples:

```
(%i1) load ("logic.mac")$
(%i2) logic_simp (a or (b or false or (a or b)));
(%o2)
a or b
(%i3) logic_simp (b eq a eq false eq true);
(%o3)
eq a eq b false
(%i4) logic_simp ((a xor true) xor b xor true);
(%o4)
a xor b
```

The function applies only basic simplification rules without introducing new functions.

N.B. It should be merged somehow with the basic Maxima simplifier.

characteristic_vector (expr, var_1, ..., var_n)

[Function]

Returns a list of size 2^n with all possible values of *expr*.

For example, **characteristic_vector (f(x,y,z), x, y, z)** is equivalent to list

```
[
  f (false, false, false),
  f (false, false, true),
  f (false, true, false),
  f (false, true, true),
  f ( true, false, false),
  f ( true, false, true),
  f ( true, true, false),
  f ( true, true, true)
]
```

If `var_1, ..., var_n` is omitted, it is assumed that

```
[var_1, ..., var_n] = sort(listofvars(expr))
```

Examples:

```
(%i1) load ("logic.mac")$
(%i2) characteristic_vector (true);
(%o2) [true]
(%i3) characteristic_vector (a xor b);
(%o3) [false, true, true, false]
(%i4) characteristic_vector (a implies b);
(%o4) [true, true, false, true]
(%i5) characteristic_vector (a implies b, a, b);
(%o5) [true, true, false, true]
(%i6) characteristic_vector (a implies b, b, a);
(%o6) [true, false, true, true]
```

`zhegalkin_form (expr)` [Function]

Returns the representation of `expr` in Zhegalkin basis {xor, and, true}.

Examples:

```
(%i1) load ("logic.mac")$
(%i2) zhegalkin_form (a or b or c);
(%o2) (a and b and c) xor (a and b) xor (a and c)
      xor (b and c) xor a xor b xor c
(%i3) zhegalkin_form ((a implies b) or c);
(%o3) (a and b and c) xor (a and b) xor (a and c) xor a
      xor true
```

`logic_equiv (expr_1, expr_2)` [Function]

Returns true if `expr_1` is equivalent to `expr_2` and false otherwise.

Examples:

```
(%i1) load ("logic.mac")$
(%i2) e : ((a or b) xor c) and d$
(%i3) zhegalkin_form (e);
(%o3) (a and b and d) xor (a and d) xor (b and d)
      xor (c and d)
(%i4) logic_equiv (%i2, %o3);
(%o4) true
(%i5) is (characteristic_vector(%i2) = characteristic_vector(%o3));
(%o5) true
(%i6) logic_equiv (x and y eq x, x implies y);
(%o6) true
```

`dual_function (expr)` [Function]

`dual_function (f (x_1, ..., x_n)) := not f (not x_1, ..., not x_n).`

Example:

```
(%i1) load ("logic.mac")$
```

```

(%i2) dual_function (x or y);
(%o2)                not ((not x) or (not y))
(%i3) demorgan (%);
(%o3)                x and y

```

self_dual (expr) [Function]
 Returns true if *expr* is equivalent to dual_function (expr) and false otherwise.

Examples:

```

(%i1) load ("logic.mac")$
(%i2) self_dual (a);
(%o2)                true
(%i3) self_dual (not a);
(%o3)                true
(%i4) self_dual (a eq b);
(%o4)                false

```

closed_under_f (expr) [Function]
 closed_under_f (f (x₁, ..., x_n) returns true if f (false, ..., false) = false and false otherwise.

Examples:

```

(%i1) load ("logic.mac")$
(%i2) closed_under_f (x and y);
(%o2)                true
(%i3) closed_under_f (x or y);
(%o3)                true

```

closed_under_t (expr) [Function]
 closed_under_t (f (x₁, ..., x_n) returns true if f (true, ..., true) = true and false otherwise.

Examples:

```

(%i1) load ("logic.mac")$
(%i2) closed_under_t (x and y);
(%o2)                true
(%i3) closed_under_t (x or y);
(%o3)                true

```

monotonic (expr) [Function]

Returns true if characteristic vector of *expr* is monotonic, i.e.

```

charvec : characteristic_vector(expr)
charvec[i] <= charvec[i+1],   i = 1, ..., n-1

```

where $a \leq b := (a=b \text{ or } (a=\text{false} \text{ and } b=\text{true}))$.

Examples:

```

(%i1) load ("logic.mac")$
(%i2) monotonic (a or b);
(%o2)                true

```

```

(%i3) monotonic (a and b);
(%o3)                                     true
(%i4) monotonic (a implies b);
(%o4)                                     false
(%i5) monotonic (a xor b);
(%o5)                                     false
(%i6) characteristic_vector (a or b);
(%o6)                                     [false, true, true, true]
(%i7) characteristic_vector (a and b);
(%o7)                                     [false, false, false, true]
(%i8) characteristic_vector (a implies b);
(%o8)                                     [true, true, false, true]
(%i9) characteristic_vector (a xor b);
(%o9)                                     [false, true, true, false]

```

linear (expr) [Function]

Returns **true** if `zhgalkin_form(expr)` is linear and **false** otherwise.

Examples:

```

(%i1) load ("logic.mac")$
(%i2) linear (a or b);
(%o2)                                     false
(%i3) linear (a eq b);
(%o3)                                     true
(%i4) zhgalkin_form (a or b);
(%o4)                                     (a and b) xor a xor b
(%i5) zhgalkin_form (a eq b);
(%o5)                                     a xor b xor true

```

Linear functions are also known as counting or alternating functions.

functionally_complete (expr_1, ..., expr_n) [Function]

Returns **true** if `expr_1, ..., expr_n` is a functionally complete system and **false** otherwise. The constants are essential (see the example below).

Examples:

```

(%i1) load ("logic.mac")$
(%i2) functionally_complete (x and y, x xor y);
(%o2)                                     false
(%i3) functionally_complete (x and y, x xor y, true);
(%o3)                                     true
(%i4) functionally_complete (x and y, x or y, not x);
(%o4)                                     true

```

logic_basis (expr_1, ..., expr_n) [Function]

Returns **true** if `expr_1, ..., expr_n` is a functionally complete system without redundant elements and **false** otherwise.

Examples:

```

(%i1) load ("logic.mac")$

```

```

(%i2) logic_basis (x and y, x or y);
(%o2)                false
(%i3) logic_basis (x and y, x or y, not x);
(%o3)                false
(%i4) logic_basis (x and y, not x);
(%o4)                true
(%i5) logic_basis (x or y, not x);
(%o5)                true
(%i8) logic_basis (x and y, x xor y, true);
(%o8)                true

```

All possible bases:

```

(%i1) load ("logic.mac")$
(%i2) logic_functions : { not x, x nand y, x nor y,
                        x implies y, x and y, x or y,
                        x eq y, x xor y, true, false }$
(%i3) subset (powerset(logic_functions),
              lambda ([s], apply ('logic_basis, listify(s))));
(%o3) {{false, x eq y, x and y}, {false, x eq y, x or y},
      {false, x implies y}, {true, x xor y, x and y},
      {true, x xor y, x or y}, {not x, x implies y},
      {not x, x and y}, {not x, x or y},
      {x eq y, x xor y, x and y}, {x eq y, x xor y, x or y},
      {x implies y, x xor y}, {x nand y}, {x nor y}}

```

logic_diff (f, x) [Function]

Returns the logic derivative df/dx of f wrt x .

```

logic_diff (f (x_1, ..., x_k, ..., x_n), x_k) :=
  f (x_1, ..., true, ..., x_n) xor
  f (x_1, ..., false, ..., x_n)

```

Examples:

```

(%i1) load ("logic.mac")$
(%i2) logic_diff (a or b or c, a);
(%o2)                (b and c) xor b xor c xor true
(%i3) logic_diff (a and b and c, a);
(%o3)                b and c
(%i4) logic_diff (a or (not a), a);
(%o4)                false

```

boolean_form (expr) [Function]

Returns the representation of $expr$ in Boolean basis {and, or, not}.

Examples:

```

(%i1) load ("logic.mac")$
(%i2) boolean_form (a implies b implies c);
(%o2)                (not ((not a) or b)) or c
(%i3) demorgan (%);
(%o3)                ((not b) and a) or c

```

```
(%i4) logic_equiv (boolean_form (a implies b implies c),
                      zhegalkin_form (a implies b implies c));
(%o4) true
```

demorgan (expr) [Function]
 Applies De Morgan's rules to *expr*:

```
not (x_1 and ... and x_n) => (not x_1 or ... or not x_n)
not (x_1 or ... or x_n) => (not x_1 and ... and not x_n)
```

Example:

```
(%i1) load ("logic.mac")$
(%i2) demorgan (boolean_form (a nor b nor c));
(%o2) (not a) and (not b) and (not c)
```

pdnf (expr) [Function]
 Returns the perfect disjunctive normal form of *expr*.

Example:

```
(%i1) load ("logic.mac")$
(%i2) pdnf (x implies y);
(%o2) (x and y) or ((not x) and y) or ((not x) and (not y))
```

pcnf (expr) [Function]
 Returns the perfect conjunctive normal form of *expr*.

Example:

```
(%i1) load ("logic.mac")$
(%i2) pcnf (x implies y);
(%o2) (not x) or y
```

Appendix A Function and variable index

B

boolean_form..... 6

C

characteristic_vector 2
 closed_under_f 4
 closed_under_t 4

D

demorgan 7
 dual_function..... 3

F

functionally_complete 5

L

linear..... 5
 logic_basis..... 5
 logic_diff..... 6
 logic_equiv..... 3
 logic_simp..... 2

M

monotonic 4

P

pcnf 7
 pdnf 7

S

self_dual 4

Z

zhegalkin_form 3