



Performance

Metrics			=
First Contentful Paint	0.5 s	Time to Interactive	0.5 s
Speed Index	0.6 s	Total Blocking Time	0 ms
Largest Contentful Paint	0.6 s	Cumulative Layout Shift	0

Values are estimated and may vary. The performance score is calculated directly from these metrics. See calculator.

View Trace

Opportunities — These suggestions can help your page load faster. They don't <u>directly affect</u> the Performance score.

Opportunity Estimated Savings

Preconnect to required origins

0.16 s ^

Consider adding 'preconnect' or 'dns-prefetch' resource hints to establish early connections to important third-party origins. <u>Learn more</u>.

URL Potential Savings

https://api-ratp.pierre-grimaud.fr 160 ms

https://jq-cdn3.s3.amazonaws.com

Diagnostics — More information about the performance of your application. These numbers don't <u>directly affect</u> the Performance score.

Avoid chaining critical requests — 1 chain found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more.

Maximum critical path latency: 460 ms

Initial Navigation

https://longing-numerous-bill.glitch.me

/styles/inline.css (longing-numerous-bill.glitch.me) - 180 ms, 12.14 KB

75tyles/mine.sss (longing-numerous-bin.giten.me) - 100 ii	113, 12.14 105	
Keep request counts low and transfer sizes small — 10 requests •	151 KB	/
To set budgets for the quantity and size of page resources, add a bu	udget.json file. <u>Learn more</u> .	
Resource Type	Requests	Transfer Size
Total	10	150.8 KB
Script	4	131.8 KB
Stylesheet	1	12.1 KB
Document	2	5.1 KB
Other	1	0.9 KB
Image	2	0.9 KB
Media	0	0 KB
Font	0	0 KB
Third-party	5	127.3 KB
This is the element that was identified as the Largest Contentful Pai	nt. <u>Learn More</u>	
div.dialog-title		
Avoid large layout shifts — No elements found		
These DOM elements contribute most to the CLS of the page.		
esed audits (25)		/
Eliminate render-blocking resources — Potential savings of 0 ms		
Resources are blocking the first paint of your page. Consider deliver JS/styles. <u>Learn more</u> .	ring critical JS/CSS inline and	deferring all non-critical
		Show 3rd party resources (0)
URL		Transfer Potentia Size Saving

URL	Transfer Size	Potentia Savings
/styles/inline.css (longing-numerous-bill.glitch.me)	12.1 KB	80 ms
Properly size images		^
Serve images that are appropriately-sized to save cellular data and improve load time. <u>Learn</u>	n more.	
Defer offscreen images		^
Consider lazy-loading offscreen and hidden images after all critical resources have finished linteractive. <u>Learn more</u> .	oading to lower time	to
Minify CSS — Potential savings of 3 KB		^
Minifying CSS files can reduce network payload sizes. <u>Learn more</u> .		
	Show 3rd-party re	esources (0)
URL	Transfer Size	Potentia Savings
/styles/inline.css (longing-numerous-bill.glitch.me)	12.1 KB	2.9 KB
Minify JavaScript — Potential savings of 3 KB		^
Minifying JavaScript files can reduce payload sizes and script parse time. Learn more.		
	Show 3rd party re	esources (0)
URL	Transfer	Potentia
	Size	Savings
/scripts/app.js (longing-numerous-bill.glitch.me)	6.5 KB	3.4 KB
Remove unused CSS		^
Remove dead rules from stylesheets and defer the loading of CSS not used for above-the-forunnecessary bytes consumed by network activity. <u>Learn more</u> .	ld content to reduce	
Remove unused JavaScript — Potential savings of 87 KB		^
Remove unused JavaScript to reduce bytes consumed by network activity. <u>Learn more</u> .		
	Show 3rd-party re	esources (0)
URL	Transfer Size	Potentia Savings
chrome-extension://elgalmkoelokbchhkhacckoklkejnhcd/build/ng-validate.js	124.1 KB	86.8 KB
Efficiently encode images		/
Optimized images load faster and consume less cellular data. <u>Learn more</u> .		
Serve images in next-gen formats		
Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression than faster downloads and less data consumption. <u>Learn more</u> .	PNG or JPEG, which	n means

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. <u>Learn</u> more.

	Show 3rd-party re	sources (0)
URL	Transfer Size	Potential Savings
/styles/inline.css (longing-numerous-bill.glitch.me)	23.9 KB	21.2 KB
/scripts/app.js (longing-numerous-bill.glitch.me)	12.6 KB	10.7 KB
https://longing-numerous-bill.glitch.me	7.7 KB	6.3 KB
Initial server response time was short — Root document took 160 ms		^
Keep the server response time for the main document short because all other requests de	epend on it. <u>Learn more</u> .	
Avoid multiple page redirects		^
Redirects introduce additional delays before the page can be loaded. <u>Learn more</u> .		
Preload key requests		^
Consider using ` k rel=preload>` to prioritize fetching resources that are currently requemore.	ested later in page load.	<u>Learn</u>
Use video formats for animated content		^
Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM PNG/WebP for static images instead of GIF to save network bytes. <u>Learn more</u>	videos for animations ar	nd
Avoids enormous network payloads — Total size was 151 KB		^
Large network payloads cost users real money and are highly correlated with long load tin	nes. <u>Learn more</u> .	
	Show 3rd-party re	sources (2)
URL	7	Fransfer Size
chrome-extension://elgalmkoelokbchhkhacckoklkejnhcd/build/ng-validate.js		124.1 KB
/styles/inline.css (longing-numerous-bill.glitch.me)		12.1 KB
/scripts/app.js (longing-numerous-bill.glitch.me)		6.5 KB
https://longing-numerous-bill.glitch.me		4 KB
<pre>chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/data/js/extn-utils.html</pre>		1 KB
<pre>chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/data/js/extn-utils.js</pre>		1 KB
bastille/A (api-ratp.pierre-grimaud.fr)		0.9 KB
/images/ic_refresh_white_24px.svg (longing-numerous-bill.glitch.me)		0.5 KB
/images/ic_add_white_24px.svg (longing-numerous-bill.glitch.me)		0.4 KB
/js/jquery-3.2.3.js (jq-cdn3.s3.amazonaws.com)		0.3 KB
Uses efficient cache policy on static assets — 0 resources found		^
A long cache lifetime can speed up repeat visits to your page. <u>Learn more</u> .		

Avoids an excessive DOM size — 55 elements

A large DOM will increase memory usage, cause longer style calculations, and produce costly layout reflows. Learn more.

Statistic	Element	Value
Total DOM Elements		55
Maximum DOM Depth	<pre><option value="metros/1/nation/A"></option></pre>	6
Maximum Child Elements	<pre><select id="selectTimetableToAdd"></select></pre>	12

User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. <u>Learn more</u>.

JavaScript execution time — 0.0 s

Category

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>.

Show 3rd party resources (0)

Time Spent

URL	Total CPU Time	Script Evaluation	Script Parse
https://longing-numerous-bill.glitch.me	61 ms	12 ms	6 ms
Minimizes main-thread work — 0.1 s			^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>

Script Evaluation	45 ms
Other	37 ms
Script Parsing & Compilation	17 ms
Parse HTML & CSS	12 ms

Rendering 10 ms

Style & Layout 8 ms

All text remains visible during webfont loads

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. Learn more.

Minimize third-party usage — Third-party code blocked the main thread for 0 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. <u>Learn more</u>.

Third-Party Transfer Size Main-Thread Blocking Time

Amazon Web Services 0 KB 0 ms

Uses HTTP/2 for its own resources

HTTP/2 offers many benefits over HTTP/1.1, including binary headers, multiplexing, and server push. Learn more.

Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as 'passive' to improve your page's scroll performance. Learn more.

Avoids document.write()

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. <u>Learn more</u>.



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Contrast — These are opportunities to improve the legibility of your content.

Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. Learn more.

Failing Elements

h1.header title

Internationalization and localization — These are opportunities to improve the interpretation of your content by users in different locales.

<html> element does not have a [lang] attribute

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. <u>Learn more</u>.

Failing Elements

html

Names and labels — These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

Form elements do not have associated labels

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more.

Failing Elements

select#selectTimetableToAdd

[aria-*] attributes match their roles

[aria-hidden="true"] is not present on the document <body>

more.

Additional items to manually check (10) — These items address areas which an automated testing tool cannot cover. Learn ^ more in our guide on conducting an accessibility review. The page has a logical tab order Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. Learn more. Interactive controls are keyboard focusable Custom interactive controls are keyboard focusable and display a focus indicator. Learn more. Interactive elements indicate their purpose and state Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more. The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order DOM order matches the visual order, improving navigation for assistive technology. Learn more. Offscreen content is hidden from assistive technology Offscreen content is hidden with display: none or aria-hidden=true. Learn more. HTML5 landmark elements are used to improve navigation Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more. Passed audits (9)

Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. Learn

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. Learn more. [aria-*] attributes have valid values Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more. [aria-*] attributes are valid and not misspelled Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more. Buttons have an accessible name When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. [id] attributes on active, focusable elements are unique All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more. Heading elements appear in a sequentially-descending order Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more. [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5. Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more. Not applicable (29) [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more. [aria-hidden="true"] elements do not contain focusable descendents Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn more. ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. [role]s have all required [aria-*] attributes Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more. Elements with an ARIA [role] that require children to contain a specific [role] have all required children. Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more.

[role]s are contained by their required parent element Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more. [role] values are valid ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more. ARIA toggle fields have accessible names When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. The page contains a heading, skip link, or landmark region Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more. <dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements. When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn more. Definition list items are wrapped in <dl> elements Definition list items ('<dt>' and '<dd>') must be wrapped in a parent '<dl>' element to ensure that screen readers can properly announce them. Learn more. ARIA IDs are unique The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn more. No form fields have multiple labels Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn more. <frame> or <iframe> elements have a title Screen reader users rely on frame titles to describe the contents of frames. Learn more. <html> element has a valid value for its [lang] attribute Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more. Image elements have [alt] attributes Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more. <input type="image"> elements have [alt] text When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. Learn more. Presentational elements avoid using , <caption> or the [summary] attribute. A table being used for layout purposes should not include data elements, such as the th or caption elements or the summary attribute, because this can create a confusing experience for screen reader users. Learn more. Links have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. <u>Learn more</u>.

Lists contain only elements and script supporting elements (<script> and <template>).

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. <u>Learn more</u>.

List items () are contained within or parent elements

Screen readers require list items (``) to be contained within a parent `` or `` to be announced properly. <u>Learn more</u>.

The document does not use <meta http-equiv="refresh">

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u>.

<object> elements have [alt] text

Screen readers cannot translate non-text content. Adding all text to `<object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.

No element has a [tabindex] value greater than 0

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u>.

Cells in a element that use the [headers] attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. <u>Learn more</u>.

elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more</u>.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u>.

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.

 $\verb|\colored | elements contain a < track>| element with [kind="description"]|$

Audio descriptions provide relevant information for videos that dialogue cannot, such as facial expressions and scenes. <u>Learn more</u>.



Rest Practices

General

A	Browser errors were logged to the console	
	Errors logged to the console indicate unresolve concerns. <u>Learn more</u>	d problems. They can come from network request failures and other browser
		Show 3rd-party resources (2
	URL	Description
	/js/jquery-3.2.3.js (jq-cdn3.s3.amazonaws.com)	Failed to load resource: the server responded with a status of 404 (Not Found)
	/js/jquery-3.2.3.js (jq-cdn3.s3.amazonaws.com)	Failed to load resource: the server responded with a status of 404 (Not Found)
'as	ssed audits (13)	
	Uses HTTPS	
	where some resources are loaded over HTTP of	ones that don't handle sensitive data. This includes avoiding mixed content, despite the initial request being servedover HTTPS. HTTPS prevents ning in on the communications between your app and your users, and is a atform APIs. Learn more.
	Links to cross-origin destinations are safe	
	Add `rel="noopener"` or `rel="noreferrer"` to an Learn more.	y external links to improve performance and prevent security vulnerabilities.
	Avoids requesting the geolocation permission of	on page load
	Users are mistrustful of or confused by sites that action instead. <u>Learn more</u> .	at request their location without context. Consider tying the request to a user
	Avoids requesting the notification permission or	n page load
	Users are mistrustful of or confused by sites that user gestures instead. <u>Learn more</u> .	at request to send notifications without context. Consider tying the request to
	Avoids front-end JavaScript libraries with know	n security vulnerabilities
	Some third-party scripts may contain known se <u>Learn more</u> .	curity vulnerabilities that are easily identified and exploited by attackers.
	Allows users to paste into password fields	
	Preventing password pasting undermines good	security policy. <u>Learn more</u> .
	Displays images with correct aspect ratio	
	Image display dimensions should match natura	l aspect ratio. <u>Learn more</u> .
	Displays images with appropriate size	
	Image natural dimensions should be proportion more.	al to the display size and the pixel ratio to maximize image clarity. <u>Learn</u>

Page has the HTML doctype	
, , , , , , , , , , , , , , , , , , ,	
Specifying a doctype prevents the browser from switching to quirks-mode. L	earn more.
Properly defines charset	
A character encoding declaration is required. It can be done with a <meta/> t	tag in the first 1024 bytes of the HTML or in the
Content-Type HTTP response header. <u>Learn more</u> .	
Avoids Application Cache	
Application Cache is deprecated. <u>Learn more</u> .	
Detected JavaScript libraries	
All front-end JavaScript libraries detected on the page. <u>Learn more</u> .	
Avoids deprecated APIs	
Deprecated APIs will eventually be removed from the browser. Learn more.	



SFO

These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. <u>Learn more</u>.

Content Best Practices — Format your HTML in a way that enables crawlers to better understand your app's content.

A	Document does not have a meta description	,
	Meta descriptions may be included in search results to concisely summarize page content. <u>Learn more</u> .	
A	Document does not have a valid rel=canonical Points to a different domain (https://weather-pwa-sample.firebaseapp.com/final/)	
	Canonical links suggest which URL to show in search results. Learn more.	
	litional items to manually check (1) — Run these additional validators on your site to check additional SEO best ctices.	
	litional items to manually check (1) — Run these additional validators on your site to check additional SEO best	
	litional items to manually check (1) — Run these additional validators on your site to check additional SEO best ctices.	

Has a <meta name="viewport"> tag with width or initial-scale

Add a `<meta name="viewport">` tag to optimize your app for mobile screens. Learn more.

Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. Page has successful HTTP status code Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more. Links have descriptive text Descriptive link text helps search engines understand your content. Learn more. Page isn't blocked from indexing Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn more. Document has a valid hreflang hreflang links tell search engines what version of a page they should list in search results for a given language or region. Learn more. Document avoids plugins Search engines can't index plugin content, and many devices restrict plugins or don't support them. Learn more. Not applicable (4) robots.txt is valid If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. Learn more. Image elements have [alt] attributes Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more. Document uses legible font sizes Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. Learn more. Tap targets are sized appropriately Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. Learn more.



These checks validate the aspects of a Progressive Web App. Learn more.

Fast and reliable

Page load is fast enough on mobile networks

A fast page load over a cellular network ensures a good mobile user experience. Learn more.

Current page does not respond with a 200 when offline

If you're building a Progressive Web App, consider using a service worker so that your app can work offline. Learn more.

start_ur1 does not respond with a 200 when offline No usable web app manifest found on page.

A service worker enables your web app to be reliable in unpredictable network conditions. Learn more.

Installable

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u>, where some resources are loaded over HTTP despite the initial request being servedover HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. <u>Learn more</u>.

▲ Does not register a service worker that controls page and start_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

▲ Web app manifest does not meet the installability requirements Failures: No manifest was fetched.

Browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

PWA Optimized

▲ Does not redirect HTTP traffic to HTTPS

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u>.

▲ Is not configured for a custom splash screen Failures: No manifest was fetched.

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn more</u>.

Does not set a theme color for the address bar.

Failures: No manifest was fetched, No `<meta name="theme-color">` tag found.

The browser address bar can be themed to match your site. Learn more.

Content is sized correctly for the viewport

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. Learn more.

Has a <meta name="viewport"> tag with width or initial-scale

Add a `<meta name="viewport">` tag to optimize your app for mobile screens. Learn more.

Contains some content when JavaScript is not available

Your app should display some content when JavaScript is disabled, even if it's just a warning to the user that JavaScript is required to use the app. <u>Learn more</u>.

▲ Does not provide a valid apple-touch-icon

For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u>.

Manifest doesn't have a maskable icon No manifest was fetched

A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. Learn more.

Additional items to manually check (3) — These checks are required by the baseline <u>PWA Checklist</u> but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Site works cross-browser

To reach the most number of users, sites should work across every major browser. Learn more.

Page transitions don't feel like they block on the network

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. <u>Learn more</u>.

Each page has a URL

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. <u>Learn more</u>.

Runtime Settings

URL https://longing-numerous-bill.glitch.me/

Fetch Time Aug 23, 2020, 1:58 PM GMT-5

Device Emulated Desktop

Network throttling 40 ms TCP RTT, 10,240 Kbps throughput (Simulated)

CPU throttling 1x slowdown (Simulated)

Channel devtools

User agent (host) Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/84.0.4147.135 Safari/537.36

User agent (network) Mozilla/5.0 (Macintosh; Intel Mac OS X 10 13 6) AppleWebKit/537.36 (KHTML,

like Gecko) Chrome/80.0.3963.0 Safari/537.36 Chrome-Lighthouse

CPU/Memory Power

2104

Generated by **Lighthouse** 6.0.0 | File an issue