



**«Московский государственный технический университет
имени Н.Э. Баумана»**

(МГТУ им. Н.Э. Баумана)

ФАКУЛЬТЕТ Информатика и системы управления

КАФЕДРА Компьютерные системы и сети(ИУ6)

О т ч е т

по зачетной работе

Дисциплина: Языки интернет-программирования

Тема зачетной работы: Tube BMSTU — сервис для публикации
объявления о тубусах

Студент гр. ИУ6-32Б _____ Д.В.Лабзунова
(Подпись, дата) (И.О. Фамилия)

Преподаватель _____
(Подпись, дата) (И.О. Фамилия)

Задача

Сайт позволяет разместить объявление о ненужном тубусе, что достаточно актуально, так как предметы, такие как начертательная геометрия или инженерная графика, у многих делятся всего пару семестров. И возможность после их окончания отдать их нуждающемуся, например, первокурснику была бы полезной.

На сайте пользователь = объявление, пользователи не могут существовать без него. Поэтому регистрация = добавление объявления. Для тех юзеров, кто хочет найти себе тубус, есть доступ к главной странице с объявлением и без авторизации. Там по нажатию на кнопку «Показать больше» отображаются контакты для связи с автором понравившегося объявления.

Код реализации

application_controller.rb:

```
# frozen_string_literal: true

# Application controller
class ApplicationController < ActionController::Base
  include ApplicationHelper
  before_action :set_locale

  def current_user
    @_current_user ||= session[:current_user_id] &&
      .find_by_id(session[:current_user_id])
  end

  private

  def authenticate
    redirect_to signin_path unless current_user
  end

  def set_locale
    @current_user.locale = params[:locale] || I18n.default_locale
  end

  def default_url_options(options = {})
    { locale: @current_user.locale }.merge options
  end
end
```

main_controller.rb:

```
# frozen_string_literal: true

# Controller for logic
class MainController < ApplicationController
  before_action :set_user, only: %i[index profile edit profile_edit]
  before_action :require_login, only: %i[profile edit profile_edit]

  def index
    @users = User.all
  end

  def profile; end

  def set_user
    @user = User.find_by_id(session[:current_user_id])
  end
end
```

```
def profile_edit; end
```

```
def edit
  if !request.get?
    if @user.update(user_params)
      redirect_to main_profile_path
    else
      render :edit
    end
  else redirect_to main_profile_edit_path
  end
end
```

```
private
```

```
def user_params
  params.permit(:username, :headline, :tube_description, :link, :email, :password, :password_confirmation)
end
```

```
def require_login
  redirect_to session_new_url unless signed_in?
end
end
```

session_controller.rb:

```
# frozen_string_literal: true
```

```
# Controller for sessions
```

```
class SessionController < ApplicationController
  before_action :already_logged, only: %i[login create new]
  def new; end
```

```
def login; end
```

```
def create
  user = User.find_by username: params[:session][:username]
```

```
  if user&.authenticate(params[:session][:password])
    p 'Login'
    sign_in user
    redirect_to root_url
  else
    p 'redirect'
    redirect_to session_new_url
  end
end
```

```
def logout
  sign_out
  redirect_to session_new_url
end
```

```
def already_logged
  redirect_to main_index_url if signed_in?
end
end
```

users_controller.rb:

```
# frozen_string_literal: true
```

```
# Controller for users
```

```
class UsersController < ApplicationController
```

```
  before_action :set_user, only: %i[show edit update destroy]
```

```
  before_action :already_logged, only: %i[new create]
```

```
  def show; end
```

```
  def new
```

```
    @user = User.new
```

```
  end
```

```
  def edit; end
```

```
  def create
```

```
    @user = User.new(user_params)
```

```
    respond_to do |format|
```

```
      if @user.save
```

```
        format.html { redirect_to main_index_path, notice: 'User was successfully created.' }
```

```
      else
```

```
        format.html { render :new }
```

```
        format.json { render json: @user.errors, status: :unprocessable_entity }
```

```
      end
```

```
    end
```

```
  end
```

```
  def update; end
```

```
  def destroy; end
```

```
  private
```

```
  def set_user
```

```
    @user = User.find(params[:id])
```

```
  end
```

```
  def user_params
```

```
    params.require(:user).permit(:username, :headline, :tube_description, :link, :email, :password, :password_confirmation)
```

```
  end
```

```
  def already_logged
```

```
    redirect_to main_index_url if signed_in?
```

```
  end
```

```
end
```

session_helper.rb:

```
# frozen_string_literal: true
```

```
# helper for auth
```

```
module SessionHelper
```

```
  def sign_in(user)
```

```
    session[:current_user_id] = user.id
```

```
    self.current_user = user
```

```
  end
```

```
  def signed_in?
```

```
    !current_user.nil?
```

```
  end
```

```
def sign_out
  session[:current_user_id] = nil
  self.current_user = nil
end
```

```
def current_user=(user)
  @current_user = user
end
end
```

user.rb модель:

```
class User < ActiveRecord::Base
  has_secure_password
  validates :username, presence: true, length: { maximum: 30 }, uniqueness: true
  validates :email, presence: true, uniqueness: true
  validates :password_digest, confirmation: true, length: { minimum: 4 }
  validates :headline, length: { maximum: 30 }
  validates :tube_description, length: { maximum: 500 }
  validates :link, length: { maximum: 70 }
end
```

schema.rb:

```
define(version: 2020_12_14_140432) do

  create_table "users", force: :cascade do |t|
    t.text "username"
    t.text "password_digest"
    t.text "email"
    t.text "headline"
    t.text "tube_description"
    t.text "link"
    t.datetime "created_at", precision: 6, null: false
    t.datetime "updated_at", precision: 6, null: false
  end

end
```

en.yml:

```
en:
  labels:
    main: 'tube BMSTU'
    slogan: 'Give your tube a new life'
    login: 'Login'
    signup: 'Add an advertisement'
    profile: 'Your advertisement'
    profile_edit: 'Change your advertisement'
    link: 'Link to contact: '
    email: 'Email: '

  fields:
    username: 'Username'
    password: 'Password'
    password_confirmation: 'Password confirmation'
    email: 'Email'
    link: 'Link to contact'
    headline: 'headline'
    description: 'description'

  buttons:
    login: 'Login'
    signup: 'Signup'
```

```
logout: 'Logout'
edit: 'Edit'
save: 'Save'
show: 'Show more'
```

links:

```
back: 'Back'
to_registrate: 'New here?'
to_login: 'I have an account'
```

ru.yml:

ru:

labels:

```
main: 'тубус.МГТУ'
slogan: 'Подари своему тубусу вторую жизнь'
login: 'Авторизация'
signup: 'Регистрация объявления'
profile: 'Профиль'
profile_edit: 'Изменить свое объявление'
link: 'Ссылка для связи: '
email: 'Электронная почта: '
```

fields:

```
username: 'Имя пользователя'
password: 'Пароль'
password_confirmation: 'Подтверждение пароля'
email: 'Электронная почта'
link: 'Ссылка для связи'
headline: 'Заголовок'
description: 'Описание'
```

buttons:

```
login: 'Войти'
signup: 'Зарегистрироваться'
logout: 'Выйти'
edit: 'Редактировать'
save: 'Сохранить'
show: 'Показать больше'
```

links:

```
back: 'Назад'
to_registrate: 'Впервые тут?'
to_login: 'У меня уже есть аккаунт'
```

routes.rb:

```
    .application.routes.draw do
scope "(:locale)", locale: /#{I18n.available_locales.join("|")}/ do
  get 'users/new'
  get 'session/new'
  get 'session/login'
  post 'session/create'
  root 'main#index'
  get 'main/index'
  get 'main/profile'
  post 'main/edit'
  get 'main/profile_edit'
  get '/signin', to: 'session#new'
  get '/signup', to: 'users#new'
  get '/logout', to: 'session#logout'
  resources :users
end
end
```

application.rb:

```
require_relative 'boot'
```

```
require 'rails/all'
```

```
.require(*%> .groups)
```

```
module Project
```

```
  class Application < Rails::Application
```

```
    config.load_defaults 6.0
```

```
    config.i18n.available_locales = [:ru, :en]
```

```
    config.i18n.default_locale = :en
```

```
  end
```

```
end
```

application.html.erb:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>Project</title>
```

```
    <%= csrf_meta_tags %>
```

```
    <%= csp_meta_tag %>
```

```
    <%= stylesheet_link_tag 'application', media: 'all', 'data-turbolinks-track': 'reload' %>
```

```
    <%= javascript_pack_tag 'application', 'data-turbolinks-track': 'reload' %>
```

```
    <%= javascript_pack_tag 'contacts', 'data-turbolinks-track': 'reload' %>
```

```
    <%= stylesheet_link_tag 'https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css' %>
```

```
    <%= stylesheet_link_tag 'https://fonts.googleapis.com/css2?family=Montserrat:wght@300&display=swap' %>
```

```
  <script>
```

```
    function show(username)
```

```
    {
```

```
      document.getElementById(username.id).style.visibility = "visible";
```

```
    }
```

```
  </script>
```

```
  <style>
```

```
    body{
```

```
      font-family: 'Montserrat', sans-serif;
```

```
    }
```

```
    .navbar-default {
```

```
      color: #bbdefb;
```

```
      background-color: #bbdefb;
```

```
      border-color: #bbdefb;
```

```
    }
```

```
    .navbar-brand{
```

```
      font-size: 32px;
```

```
      color: #212121;
```

```
    }
```

```
    .inline{
```

```
      display: inline-block;
```

```
      vertical-align: middle;
```

```
    }
```

```
    .block{
```

```
      display: block;
```

```
    }
```

```
    .card{
```

```

        background-color: #e3e3e3;
    }

    .profile_page{
        margin-left: auto;
        margin-right: auto;
        width: 24em
    }
</style>
</head>

<body>
<%= yield %>
</body>
</html>

```

_navbar.html.erb: (main)

```

<nav class="navbar navbar-default navbar-expand-lg">
  <div class="container-fluid">
    <a class="navbar-brand" href=" ../main/index"><%= t("lables.main") %>
      
    </a>
    <div class="collapse navbar-collapse" id="navbarText">
      <span class="form-inline mt-2 mt-md-0 ml-auto mr-auto" style="color: #212121; font-size:20px">
        <%= t("lables.slogan") %>
      </span>
      <% if @user %>
        <div class='ml-auto'>
          
          <div class = 'inline'>
            <div class="navbar-right-links">
              <div class="inline">
                <!--
                  <a class="nav-link block profile_box" style="color: #212121; font-size:24px"
href=" ../main/profile">My tube</a>-->
                <a class="nav-link block profile_box" style="color: #212121; font-size:24px" href=" ../main/profile"><%=
user.username %></a>
              </div>
              <a class="nav-link inline profile_box" href=" ../logout"><%= t("buttons.logout") %></a>
            </div>
          </div>
        </div>
      <% else %>
        <div class='ml-auto'>
          <a href=" ../signin"><button type="button" class="btn btn-outline-secondary" ><%= t("buttons.login")
%></button></a>
          <a href=" ../signup"> <button type="button" class="btn btn-outline-secondary"><%= t("buttons.signup")
%></button></a>
        </div>
      <% end %>
    </div>

    <div style="margin-left: 32px">
      <li class="block">
        <%= link_to "Pyc", { locale: :ru }, class: "nav-link" %>
      </li>
      <li class="block">
        <%= link_to "Eng", { locale: :en }, class: "nav-link" %>
      </li>
    </div>
  </div>
</div>
</nav>

```


index.html.erb: (main)

```
<%= render 'navbar', user: @user %>

<% @users.each do |ad| %>
  <% if !@current || @current.id != ad.id %>
    <div class="card" style="margin-top: 20px; margin-left: 32px; margin-right: 64px">
      <div class="card-body row">
        <div class="col-3">
          
          <div class="likes block" style="margin-top: 10px">
            
            <h6 class="inline"><%= ad.username %></h6>
          </div>
        </div>

        <div class="col-5">
          <a class="card-title text-dark" href="#" style="font-size: 32px"><%= ad.headline %></a>
          <p class="card-text" style="font-size: 24px"><%= ad.tube_description %></p>
        </div>

        <div class="col-4">
          <input class="add" type="submit" value="<%= t("buttons.show") %>" onclick='show(<%=ad.username%>)' />
          <div id="<%=ad.username%>" style="visibility: hidden; float: right;">
            <table>
              <tbody>
                <tr>
                  <td><%= t("lables.link") %></td>
                  <td><%= ad.link %></td>
                </tr>
                <tr>
                  <td><%= t("lables.email") %></td>
                  <td><%= ad.email %></td>
                </tr>
              </tbody>
            </table>
          </div>
        </div>
      </div>
    </div>
  <% end %>
<%end %>
```

profile.html.erb: (main)

```
<%= render 'navbar', user: @user %>
<div class="profile_page">
  <h2 class="title inline" colspan="2" style="margin-top: 20px;"><%= t("lables.profile") %></h2>
  <table>
    <tbody>
      <tr>
        <td><strong><%= t("fields.username") %></strong></td>
        <td><%= @user.username %> </td>
      </tr>
      <tr>
        <td><strong><%= t("fields.email") %></strong></td>
        <td><%= @user.email %> </td>
      </tr>
      <tr>
        <td><strong><%= t("fields.link") %></strong></td>
        <td><%= @user.link %> </td>
      </tr>
      <tr>
        <td><strong><%= t("fields.headline") %></strong></td>
```

```

      <td> <%= @user.headline %> </td>
    </tr>
    <tr>
      <td><strong><%= t("fields.description") %></strong></td>
      <td> <%= @user.tube_description %> </td>
    </tr>
  </tbody>
</table>

<hr>
<div style="margin-top: 16px;">
  <a href= "../main/profile_edit" class="block" style="margin-bottom: 16px"> <button type="button" class="btn btn-
outline-secondary"><%= t("buttons.edit") %></button></a>
  <%= link_to t("links.back"), root_url %>
</div>
</div>

```

profile_edit.html.erb: (main)

```

<%= render 'navbar', user: @user %>

<%= form_with url: main_edit_url, method: :post, local:true do |form| %>
  <div class="profile_page">
    <h2 class="title inline" colspan="2" style='margin-top: 20px;'><%= t("lables.profile_edit") %></h2>
    <table>
      <tbody>
        <tr>
          <td><%= t("fields.username") %></td>
          <td>
            <%= form.text_field :username %>
          </td>
        </tr>
        <tr>
          <td><%= t("fields.email") %></td>
          <td>
            <%= form.text_field :email %>
          </td>
        </tr>
        <tr>
          <td><%= t("fields.link") %></td>
          <td>
            <%= form.text_field :link %>
          </td>
        </tr>
        <tr>
          <td><%= t("fields.headline") %></td>
          <td>
            <%= form.text_field :headline %>
          </td>
        </tr>
        <tr>
          <td><%= t("fields.description") %></td>
          <td>
            <%= form.text_area :tube_description, :cols => "21 ", :rows => "5" %>
          </td>
        </tr>
        <tr>
          <td><%= t("fields.password") %></td>
          <td>
            <%= form.password_field :password %>
          </td>
        </tr>
        <tr>
          <td><%= t("fields.password_confirmation") %></td>
          <td>

```

```

        <%= form.password_field :password_confirmation %>
      </td>
    </tr>
  </tr>
  <td colspan="2">
    <%= form.submit t("buttons.save") %>
  </td>
</tr>
</tbody>
</table>
<div style="margin-top: 16px;">
  <%= link_to t("links.back"), main_profile_url %>
</div>
</div>

```

```
<% end %>
```

new.html.erb: (session)

```

<nav class="navbar navbar-default navbar-expand-lg">
  <div class="container-fluid">
    <a class="navbar-brand" href="../main/index"><%= t("lables.main") %>
      
    </a>
    <div class="collapse navbar-collapse" id="navbarText">
      <span class="form-inline mt-2 mt-md-0 ml-auto mr-auto" style="color: #212121; font-size:20px">
        <%= t("lables.slogan") %>
      </span>
    </div>
    <div style="margin-left: 32px">
      <li class="block">
        <%= link_to "Pyc", { locale: :ru }, class: "nav-link" %>
      </li>
      <li class="block">
        <%= link_to "Eng", { locale: :en }, class: "nav-link" %>
      </li>
    </div>
  </div>
</nav>

```

```

<%= form_for(:session, url: session_create_url, method: :post, local:true) do |f| %>
<main role="main" class="flex-shrink-0" >
  <div class="container">
    <div class="row">
      <div class="col-9" style='position: absolute; left: 80px;'>
        <h2 class='title inline' colspan='2' style='margin-top: 20px;'><%= t("lables.login") %></h2>
        <table>
          <tbody>
            <tr>
              <td><%= t("fields.username") %></td>
              <td>
                <%= f.text_field :username, required: true, label: 'username' %>
              </td>
            </tr>
            <tr>
              <td><%= t("fields.password") %></td>
              <td>
                <%= f.password_field :password, required: true, label: 'password' %>
              </td>
            </tr>
            <tr>
              <td colspan="2">
                <%= f.submit t("buttons.login") %>
              </td>
            </tr>
          </tbody>
        </table>
      </div>
    </div>
  </div>

```

```

        </tbody>
      </table>
      <div style="margin-top: 16px;">
        <%= link_to t("links.to_registrate"), new_user_path %>
      </div>

    </div>
    <div class="col-3 tags" style='position: absolute; right: 0;'>
<!--      hello-->
    </div>
  </div>
</div>
</main>
<% end %>

```

_form.html.erb: (users)

```

<%= form_with(model: user, local: true) do |form| %>
  <% if user.errors.any? %>
    <div id="error_explanation">
      <h2><%= pluralize(user.errors.count, "error") %> prohibited this user from being saved:</h2>

      <ul>
        <% user.errors.full_messages.each do |message| %>
          <li><%= message %></li>
        <% end %>
      </ul>
    </div>
  <% end %>

  <div class="container">
    <div class="row">
      <div class="col-9" style='position: absolute; left: 80px;'>
        <h2 class="title inline" colspan="2" style='margin-top: 20px;'><%= t("tables.signup") %></h2>
        <table>
          <tbody>
            <tr>
              <td><%= t("fields.username") %></td>
              <td>
                <%= form.text_field :username %>
              </td>
            </tr>
            <tr>
              <td><%= t("fields.email") %></td>
              <td>
                <%= form.text_field :email %>
              </td>
            </tr>
            <tr>
              <td><%= t("fields.link") %></td>
              <td>
                <%= form.text_field :link %>
              </td>
            </tr>
            <tr>
              <td><%= t("fields.headline") %></td>
              <td>
                <%= form.text_field :headline %>
              </td>
            </tr>
            <tr>
              <td><%= t("fields.description") %></td>

```

```

        <td>
          <%= form.text_area :tube_description, :cols => "21 ", :rows => "5" %>
        </td>
      </tr>
      <tr>
        <td><%= t("fields.password") %></td>
        <td>
          <%= form.password_field :password %>
        </td>
      </tr>
      <tr>
        <td><%= t("fields.password_confirmation") %></td>
        <td>
          <%= form.password_field :password_confirmation %>
        </td>
      </tr>
      <tr>
        <td colspan="2">
          <%= form.submit t("buttons.signup") %>
        </td>
      </tr>
    </tbody>
  </table>
  <div style="margin-top: 16px;">
    <%= link_to t("links.to_login"), session_new_url %>
  </div>
</div>
<div class="col-3 tags" style='position: absolute; right: 0;'>
  <!--      hello-->
</div>
</div>
</div>
</div>

<% end %>

```

new.html.erb: (users)

```

<nav class="navbar navbar-default navbar-expand-lg">
  <div class="container-fluid">
    <a class="navbar-brand" href=" ../main/index"><%= t("lables.main") %>
      
    </a>
    <div class="collapse navbar-collapse" id="navbarText">
      <span class="form-inline mt-2 mt-md-0 ml-auto mr-auto" style="color: #212121; font-size:20px">
        <%= t("lables.slogan") %>
      </span>
    </div>

    <div style="margin-left: 32px">
      <li class="block">
        <%= link_to "Pyc", { locale: :ru }, class: "nav-link" %>
      </li>
      <li class="block">
        <%= link_to "Eng", { locale: :en }, class: "nav-link" %>
      </li>
    </div>
  </div>
</nav>

<%= render 'form', user: @user %>

```

styles.css:

```

.inline{
  display: inline-block;

```

```

    vertical-align: middle;
}

.block{
    display: block;
}

.navbar-right-links{
    margin-top: -16px;
}

main{
    margin-top: 100px;
    font-family: 'Montserrat', sans-serif;
}

.navbar-default {
    color: #FBE9E7;
    background-color: #FBE9E7;
    border-color: #4FC3F7;
}

.navbar-default .navbar-brand:hover,
.navbar-default .navbar-brand:focus {
    color: #880E4F;
}

.navbar-brand{
    font-size: 32px;
    color: #212121;
}

.navbar-user{
    text-align: center;
    height: 100;
}

.profile_box{
    color: #212121;
    text-align: center;
}

.border_bar_header{
    color: #4E342E
}

.tags{
    text-align: center;
}

.card-tags{
    float: right;
}

ul.pagination {
    display: inline-block;
    padding: 0;
    margin: 0;
}

ul.pagination li {display: inline;}

ul.pagination li a {
    color: black;

```

```

float: left;
padding: 8px 16px;
text-decoration: none;
}

table {
  border-spacing: 8px 20px;
}

.title{
  font-size: 48px;
}

.input_text{
  font-size: 24px;
  margin-right: 20px;
  margin-top: 20px;
}

.text_edit{
  width: 400px;
}

.add-question-button{
  height: 80px;
  width: 144px;
  color: #212121;
  font-size: 24px;
  background-color: #FBE9E7;
  margin-top: 32px;
}

.add-answer-button{
  height: 40px;
  width: 80px;
  color: #212121;
  font-size: 16px;
  background-color: #FBE9E7;
  margin-top: 32px;
  margin-bottom: 32px;
}

table{
  border-collapse: separate;
  border-spacing: 8px 16px;
}

```

Код тестов

main_controller_test.rb:

```

require 'test_helper'

class MainControllerTest < ActionDispatch::IntegrationTest
  test "should get index" do # можно получить главную страницу без регистрации
    get main_index_url
    assert_response :success
  end

  test "should redirect from profile without auth" do # нельзя зайти в профиль без регистрации
    get main_profile_url
    assert_redirected_to session_new_url
  end
end

```

```

test 'should redirect from profile edit without auth' do # нельзя редактировать профиль без регистрации
  get main_profile_edit_url
  assert_redirected_to session_new_url
end
end

```

session_controller_test.rb:

```
require 'test_helper'
```

```

class SessionControllerTest < ActionDispatch::IntegrationTest
  test "should get new" do # получение страницы авторизации
    get session_new_url
    assert_response :success
  end
end

```

```

test "can't go to profile without auth" do # нельзя зайти в профиль без регистрации
  get main_profile_url
  assert_redirected_to session_new_url
end
end

```

users_controller_test:

```
require 'test_helper'
```

```

class UsersControllerTest < ActionDispatch::IntegrationTest
  test "should get new" do # получение страницы регистрации
    get users_new_url
    assert_response :success
  end
end

```

```

test "can't go to profile without auth" do # нельзя зайти в профиль без регистрации
  get main_profile_url
  assert_redirected_to session_new_url
end
end

```

```
end
```

main.test.rb:

```
require 'test_helper'
```

```

class MainTest < ActionDispatch::IntegrationTest
  setup do # регистрируем объявление для тестов
    post users_path, params: { user: { email: 'test@mail.ru', password: '1111', username:'test', headline:'Tubus' } }
  end
end

```

```
# с неверными данными нельзя войти
```

```

test 'user with incorrect credentials will be redirected to login page' do
  post session_create_url, params: { session: { username:'hello', password: '1111' } }
  assert_redirected_to session_new_url
end

```

```
# если данные авторизации правильные — редирект на главную
```

```

test 'user with correct credentials will be redirected to main page' do
  post session_create_url, params: { session: { username:'test', password: '1111' } }
  assert_redirected_to "/"
end

```

```
# редирект на авторизация при попытке зайти в профиль без авторизации
```

```

test "should redirect from profile without auth" do
  get main_profile_url
  assert_redirected_to session_new_url
end
end

```



```

# если авторизован — можно зайти в профиль
test 'should do to profile if authorized' do
  post session_create_url, params: { session: { username:'test', password: '1111' } }
  get main_profile_url, params: { session: { username:'test', password: '1111' } }
  assert_response :success
end

# если авторизован — можно зайти в редактирование профиля
test 'should do to profile edit if authorized' do
  post session_create_url, params: { session: { username:'test', password: '1111' } }
  get main_profile_url, params: { session: { username:'test', password: '1111' } }
  assert_response :success
end

# можно редактировать страницу
test 'should do to edit' do
  post session_create_url, params: { session: { username:'test', password: '1111' } }
  get main_profile_edit_url
  assert_response :success
  post main_edit_url, params: { user: { email: 'new_test@mail.ru', password: '1111', username:'new_test',
headline:'new_tubus' } }
  assert_response :redirect
  assert_redirected_to main_profile_url
end

# можно выйти
test 'can logout' do
  post session_create_url, params: { session: { username:'test', password: '1111' } }
  get main_profile_edit_url
  post main_edit_url, params: { user: { email: 'new_test@mail.ru', password: '1111', username:'new_test',
headline:'new_tubus' } }
  get '/logout'
  assert_redirected_to session_new_url
end
end

```

user_test.rb:

```

require 'test_helper'

class UserTest < ActiveSupport::TestCase
  # сохраняется в бд
  test 'should save to db' do
    user = User.new(email: 'test@mail.ru', password: '1111', username: 'test')
    assert user.save
    user.delete
  end

  # нельзя зарегистрироваться с такой же почтой
  test 'check adding not unique email' do
    first = User.create email: 'test@mail.ru', password: '1111', username: 'test1'
    first.save
    second = User.create email: 'test@mail.ru', password: '1111', username: 'test2'
    second.validate
    assert_equal second.errors[:email], ['has already been taken']
  end

  # нельзя зарегистрироваться с таким же логином
  test 'check adding not unique username' do
    first = User.create email: 'test1@mail.ru', password: '1111', username: 'test'
    first.save
    second = User.create email: 'test2@mail.ru', password: '1111', username: 'test'
    second.validate
    assert_equal second.errors[:username], ['has already been taken']
  end
end

```

```


# нельзя зарегистрироваться с пустым логином
test 'username cant be empty' do
  instance = .new(email: "test1@mail.ru", password: '1111' )
  instance.validate
  assert_equal instance.errors[:username], ["can't be blank"]
end


# нельзя зарегистрироваться с пустой почтой
test 'email cant be empty' do
  instance = .new(username: "test", password: '1111' )
  instance.validate
  assert_equal instance.errors[:email], ["can't be blank"]
end

test 'should get added data from db' do
# получение записанных в бд данных
  user = .new(email: 'evgeniy@mail.ru', password: '1111', username: 'Евгений', headline: 'My tube' )
  assert user.save
  assert_equal 'Евгений', .find_by_email('evgeniy@mail.ru').username
  id = user.id
  assert_equal 'My tube', .find_by_id(id).headline
end
end

```


Результаты выполнения:

tube BMSTU

Give your tube a new life
Login
Signup
Рус
Eng


user


tube
nice

Show more


labzunova


Большой тубус
Очень большой тубус для очень больших чертежей!

Show more


Вася Пупкин

Тубус 1968 года
Достался от деда

Show more



cat

Котячий тубус
Можно точить когти

Show more

Главная страница:


Авторизация:

tube BMSTU

Give your tube a new life
Рус
Eng

Login
Username
Password
Login
New here?

Регистрация:

tube BMSTU



Give your tube a new life

[Рус](#)
[Eng](#)

Add an advertisement

Username

Email

Link to contact

headline

description

Password


Password confirmation

Signup

[I have an account](#)

Работает локализация:

тубус.МГТУ



Подари своему тубусу вторую жизнь

[Рус](#)
[Eng](#)

Регистрация объявления

Имя пользователя

Электронная почта

Ссылка для связи

Заголовок

Описание

Пароль


Подтверждение пароля

Зарегистрироваться


[У меня уже есть аккаунт](#)


Главная страница авторизованного пользователя:

тубус.МГТУ



Подари своему тубусу вторую жизнь


 labzunova [Выйти](#) [Рус](#)
[Eng](#)



user

tube
nice


Показать больше



labzunova

Большой тубус
Очень большой тубус для очень больших чертежей!


Показать больше



Вася Пупкин

Тубус 1968 года
Достался от деда

Показать больше




cat


Котячий тубус
Можно точить когти

Показать больше

Профиль:

tube BMSTU


Give your tube a new life


labzunova
Logout
Рус
Eng


Your advertisement

Username	labzunova
Email	dasha.labzunova@mail.ru
Link to contact	https://yandex.ru/
headline	Большой тубус
description	Очень большой тубус для очень больших чертежей!


Edit

Back

Настройки своего аккаунта-объявления:

tube BMSTU


Give your tube a new life


labzunova
Logout
Рус
Eng

Change your advertisement

Username	labzunova
Email	dasha.labzunova@mail.ru
Link to contact	https://yandex.ru/
headline	Большой тубусс
description	hey!
Password
Password confirmation

Save

Back

Тесты:

```
labzunova@labzunova:~/Рабочий стол/Tube BMSTU/project/test$ rake
(in /home/labzunova/Рабочий стол/Tube BMSTU/project)
Run options: --seed 64219

# Running:

....."Login"
.. "Login"
.. "Login"
.. "redirect"
.. "Login"
.. "Login"
..

Finished in 5.389763s, 3.7107 runs/s, 4.6384 assertions/s.
20 runs, 25 assertions, 0 failures, 0 errors, 0 skips
```

Проверка rubocop:

```
labzunova@labzunova:~/Рабочий стол/Tube BMSTU/project/app/controllers$ rubocop
NOTE: Gem.gunzip is deprecated; use Gem::Util.gunzip instead. It will be removed on or after 2018-12-01.
Gem.gunzip called from /usr/lib/ruby/vendor_ruby/unicode/display_width/index.rb:5.
Inspecting 4 files
....

4 files inspected, no offenses detected
```

