Processing

Eduardo Yuki Yada

2022-06-14

Imports

```
library(tidyverse)
library(readxl)
library(yaml)
```

Loading files

```
df <- read_excel("../data/BD Marcapasso_09jun22.xlsx") %>% select(-record_id)
df_names <- read_excel("../data/Dicionario_dados_BD Marcapasso_09jun22.xlsx")
```

Fixing data dictionary

```
names(df_names) <- make.names(names(df_names), unique=TRUE) %>% tolower

df_names <- df_names %>%
  mutate(variable.name = case_when(variable.name == 'icu_days_t0' ~ 'icu_t0',
                                   variable.name == 'dialysis_days_t0' ~ 'dialysis_t0',
                                   TRUE ~ variable.name),  # mismatch with dataset column na
         field.label = str_replace(field.label, "_", " "), # add spaces
         field.label = str_replace_all(field.label, "[\r\n]" , ""),
         abbrev.field.label = str_replace(field.label, " \\s*\\(([^\\)]+\\))", ""),
         abbrev.field.label = if_else(variable.name %in% c('admission_posop_count',
                                                           'admission_pre_t0_count'),
                                      str_replace(field.label, "de episódios", ""),
                                      abbrev.field.label))

# df_names %>% filter(variable.name %in% date_columns)
#
# mean(is.na(df$date_procedure_1))
# mean(is.na(df$date_admission_t0))
```

```r
#
# (df$date_procedure_1 - df$date_admission_t0) / (60 * 60 * 24)
```

Separating columns by type

```r
categorical_columns <- df_names %>%
  filter(stringr::str_detect(options..definition, '\\|')) %>%
  .$variable.name

date_columns <- df_names %>%
  filter(options..definition == 'data') %>%
  .$variable.name

location_columns <- c('zipcode', 'patient_city')

other_columns <- c('record_id')

numerical_columns <- setdiff(names(df),
                             c(categorical_columns, date_columns,
                               location_columns, other_columns))

outcome_columns <- df_names %>% filter(...6 == 'Desfecho de interesse') %>% .$variable.name

columns_list <- list('categorical_columns' = categorical_columns,
                     'numerical_columns' = numerical_columns,
                     'date_columns' = date_columns,
                     'location_columns' = location_columns,
                     'outcome_columns' = outcome_columns)

con <- file('./auxiliar/columns_list.yaml', "w")
write_yaml(columns_list, con)
close(con)
```

Recalculating outcome columns for modeling

```r
df <- df %>%
  mutate(readmission_1year = readmission_30d + readmission_60d + readmission_180d + readmiss
         readmission_180d = readmission_30d + readmission_60d + readmission_180d,
         readmission_60d = readmission_30d + readmission_60d)
```

Saving processed data

```
saveRDS(df, "../data/processed_data.rds")
saveRDS(df_names, "../data/processed_dictionary.rds")
```