

# Model Selection - death\_30days

Eduardo Yuki Yada

## Global parameters

```
k <- params$k # Number of folds for cross validation
grid_size <- params$grid_size # Number of parameter combination to tune on each model
repeats <- params$repeats
```

Minutes to run: 0

## Imports

```
library(tidyverse)
library(yaml)
library(tidymodels)
library(usemodels)
library(vip)
library(bonsai)
library(lightgbm)
library(caret)
library(pROC)

source("aux_functions.R")
```

Minutes to run: 0

## Loading data

```
load('dataset/processed_data.RData')
load('dataset/processed_dictionary.RData')

columns_list <- yaml.load_file("./auxiliar/columns_list.yaml")

outcome_column <- params$outcome_column
features_list <- params$features_list

df <- mutate(df, across(where(is.character), as.factor))
```

Minutes to run: 0.005

```
dir.create(file.path("./auxiliar/model_selection/hyperparameters/"),
           showWarnings = FALSE,
           recursive = TRUE)

dir.create(file.path("./auxiliar/model_selection/performance/"),
           showWarnings = FALSE,
           recursive = TRUE)
```

Minutes to run: 0

## Eligible features

```
cat_features_list = readRDS(sprintf(
  "./auxiliar/significant_columns/categorical_%s.rds",
  outcome_column
))

num_features_list = readRDS(sprintf(
  "./auxiliar/significant_columns/numerical_%s.rds",
  outcome_column
))

features_list = c(cat_features_list, num_features_list)
```

Minutes to run: 0

```
eligible_columns = df_names %>%
  filter(momento.aquisicao == 'Admissão t0') %>%
  .$variable.name

exception_columns = c('death_intraop', 'death_intraop_1', 'disch_outcomes_t0')

correlated_columns = c('year_procedure_1', # com year_adm_t0
  'age_surgery_1', # com age
  'admission_t0', # com admission_pre_t0_count
  'atb', # com meds_antimicrobianos
  'classe_meds_cardio_qtde', # com classe_meds_qtde
  'suporte_hemod', # com proced_invasivos_qtde,
  'radiografia', # com exames_imagem_qtde
  'ecg' # com metodos_graficos_qtde
)

eligible_features = eligible_columns %>%
  base::intersect(c(columns_list$categories_columns, columns_list$numerical_columns)) %>%
  setdiff(c(exception_columns, correlated_columns))

if (is.null(features_list)) {
  features = eligible_features
} else {
  features = base::intersect(eligible_features, features_list)
}

gluedown::md_order(features, seq = TRUE, pad = TRUE)

## 01. sex
## 02. age
## 03. education_level
## 04. underlying_heart_disease
## 05. heart_disease
## 06. nyha_basal
## 07. hypertension
## 08. prior_mi
## 09. heart_failure
## 10. af
## 11. valvopathy
## 12. diabetes
## 13. renal_failure
## 14. hemodialysis
## 15. cancer
## 16. comorbidities_count
## 17. procedure_type_1
## 18. reop_type_1
```

```

## 19. procedure_type_new
## 20. cied_final_1
## 21. cied_final_group_1
## 22. admission_pre_t0_count
## 23. admission_pre_t0_180d
## 24. year_adm_t0
## 25. icu_t0
## 26. antiarritmico
## 27. antihipertensivo
## 28. betabloqueador
## 29. dva
## 30. diuretico
## 31. vasodilatador
## 32. espironolactona
## 33. antiplaquetario_ev
## 34. insulina
## 35. psicofarmacos
## 36. antifungico
## 37. classe_meds_qtde
## 38. meds_cardiovasc_qtde
## 39. meds_antimicrobianos
## 40. vni
## 41. ventilacao_mecanica
## 42. intervencao_cv
## 43. cateter_venoso_central
## 44. proced_invasivos_qtde
## 45. transfusao
## 46. interconsulta
## 47. equipe_multiprof
## 48. holter
## 49. metodos_graficos_qtde
## 50. laboratorio
## 51. cultura
## 52. analises_clinicas_qtde
## 53. citologia
## 54. histopatologia_qtde
## 55. angio_tc
## 56. angiografia
## 57. cintilografia
## 58. ecocardiograma
## 59. flebografia
## 60. ultrassom
## 61. tomografia
## 62. ressonancia
## 63. exames_imagem_qtde
## 64. bic
## 65. hospital_stay

```

Minutes to run: 0

## Train test split (70%/30%)

```

set.seed(42)

if (outcome_column == 'readmission_30d') {
  df_split <- readRDS("./dataset/split_object.rds")
} else {
  df_split <- initial_split(df, prop = .7, strata = all_of(outcome_column))
}

df_train <- training(df_split) %>% dplyr::select(all_of(c(features, outcome_column)))

```

```
df_test <- testing(df_split) %>% dplyr::select(all_of(c(features, outcome_column)))

df_folds <- vfold_cv(df_train, v = k,
                     strata = all_of(outcome_column))
```

Minutes to run: 0.001

## Boosted Tree (XGBoost)

```
xgboost_recipe <-
  recipe(formula = sprintf("%s ~ .", outcome_column) %>% as.formula, data = df_train) %>%
  step_novel(all_nominal_predictors()) %>%
  step_unknown(all_nominal_predictors()) %>%
  step_other(all_nominal_predictors(), threshold = 0.05, other = ".merged") %>%
  step_dummy(all_nominal_predictors())

xgboost_spec <- boost_tree(
  trees = tune(),
  min_n = tune(),
  tree_depth = tune(),
  learn_rate = tune(),
  loss_reduction = tune(),
  sample_size = tune()
) %>%
  set_engine("xgboost",
             nthread = 8) %>%
  set_mode("classification")

xgboost_grid <- grid_latin_hypercube(
  trees(range = c(50L, 300L)),
  min_n(),
  tree_depth(),
  learn_rate(range = c(0.01, 0.3), trans = NULL),
  loss_reduction(),
  sample_prop(range = c(1/10, 1), trans = NULL),
  size = grid_size
)

xgboost_workflow <-
  workflow() %>%
  add_recipe(xgboost_recipe) %>%
  add_model(xgboost_spec)


xgboost_tune <-
  xgboost_workflow %>%
  tune_grid(resamples = df_folds,
            grid = xgboost_grid)

xgboost_tune %>%
  show_best("roc_auc")
```

```
## # A tibble: 5 x 12
##   trees min_n tree_depth learn_rate loss_reduction sample~1 .metric .esti~2 mean      n std_err .config
##   <int> <int>    <int>    <dbl>         <dbl>    <dbl> <chr>   <chr>   <dbl> <int>   <dbl> <chr>
## 1    90    19      10    0.0432        3.50e- 6    0.856 roc_auc binary  0.731     5    0.0272 Prepro~
## 2    50    15       3    0.174         6.19e- 8    0.741 roc_auc binary  0.721     5    0.0500 Prepro~
## 3   128    25       9    0.250         9.47e-10    0.583 roc_auc binary  0.716     5    0.0395 Prepro~
## 4   186     7       6    0.164         5.68e- 1    0.280 roc_auc binary  0.710     5    0.0483 Prepro~
## 5   264    23      11    0.100         1.61e- 4    0.679 roc_auc binary  0.709     5    0.0473 Prepro~
## # ... with abbreviated variable names 1: sample_size, 2: .estimator
```

```
best_xgboost <- xgboost_tune %>%
  select_best("roc_auc")

autoplot(xgboost_tune, metric = "roc_auc")
```




```
final_xgboost_workflow <-
  xgboost_workflow %>%
  finalize_workflow(best_xgboost)


last_xgboost_fit <-
  final_xgboost_workflow %>%
  last_fit(df_split)

final_xgboost_fit <- extract_workflow(last_xgboost_fit)

xgboost_auc <- validation(final_xgboost_fit, df_test)
```



```
## [1] "Optimal Threshold: 0.02"
## Confusion Matrix and Statistics
##
##      reference
## data    0    1
## 0 3976    7
## 1  730   17
##
##              Accuracy : 0.8442
##              95% CI   : (0.8335, 0.8544)
##      No Information Rate : 0.9949
##      P-Value [Acc > NIR] : 1
##
##              Kappa   : 0.0346
##
##  Mcnemar's Test P-Value : <2e-16
##
##              Sensitivity : 0.84488
##              Specificity : 0.70833
##              Pos Pred Value : 0.99824
##              Neg Pred Value : 0.02276
##              Prevalence : 0.99493
##              Detection Rate : 0.84059
##              Detection Prevalence : 0.84207
##              Balanced Accuracy : 0.77661
##
##              'Positive' Class : 0
##
extract_vip(final_xgboost_fit, pred_wrapper = predict,
            reference_class = "0")
```




```
xgboost_parameters <- xgboost_tune %>%
  show_best("roc_auc", n = 1) %>%
  select(trees, min_n, tree_depth, learn_rate, loss_reduction) %>%
  as.list

saveRDS(
  xgboost_parameters,
  file = sprintf(
    "./auxiliar/model_selection/hyperparameters/xgboost_%s.rds",
    outcome_column
  )
)
```

Minutes to run: 1.469

## Histogram of preds



Minutes to run:

0.005

## Boosted Tree (LightGBM)

```
lightgbm_recipe <-  
  recipe(formula = sprintf("%s ~ .", outcome_column) %>% as.formula, data = df_train) %>%  
  step_novel(all_nominal_predictors()) %>%  
  step_unknown(all_nominal_predictors()) %>%  
  step_other(all_nominal_predictors(), threshold = 0.05, other = ".merged") %>%  
  step_dummy(all_nominal_predictors())  
  
lightgbm_spec <- boost_tree(  
  trees = tune(),  
  min_n = tune(),  
  tree_depth = tune(),  
  learn_rate = tune(),  
  # loss_reduction = tune(),  
  sample_size = 1  
) %>%  
  set_engine("lightgbm",  
    nthread = 8) %>%  
  set_mode("classification")  
  
lightgbm_grid <- grid_latin_hypercube(  
  trees(range = c(50L, 300L)),  
  min_n(),  
  tree_depth(),  
  learn_rate(range = c(0.01, 0.2), trans = NULL),  
  # loss_reduction(),  
  size = grid_size  
)  
  
lightgbm_workflow <-
```



```

workflow() %>%
  add_recipe(lightgbm_recipe) %>%
  add_model(lightgbm_spec)

```

```

lightgbm_tune <-
  lightgbm_workflow %>%
  tune_grid(resamples = df_folds,
            grid = lightgbm_grid)

```

```

lightgbm_tune %>%
  show_best("roc_auc")

```

```
## # A tibble: 5 x 10
```


##	trees	min_n	tree_depth	learn_rate	.metric	.estimator	mean	n	std_err	.config
##	<int>	<int>	<int>	<dbl>	<chr>	<chr>	<dbl>	<int>	<dbl>	<chr>
## 1	216	21	2	0.0337	roc_auc	binary	0.741	5	0.0503	Preprocessor1_Model108
## 2	109	30	4	0.0419	roc_auc	binary	0.725	5	0.0514	Preprocessor1_Model112
## 3	178	36	10	0.178	roc_auc	binary	0.723	5	0.0376	Preprocessor1_Model114
## 4	267	19	5	0.138	roc_auc	binary	0.717	5	0.0346	Preprocessor1_Model107
## 5	123	6	11	0.0139	roc_auc	binary	0.713	5	0.0508	Preprocessor1_Model102

```

best_lightgbm <- lightgbm_tune %>%
  select_best("roc_auc")

```

```
autoplot(lightgbm_tune, metric = "roc_auc")
```



```

final_lightgbm_workflow <-
  lightgbm_workflow %>%
  finalize_workflow(best_lightgbm)

```


```

last_lightgbm_fit <-
  final_lightgbm_workflow %>%
  last_fit(df_split)

```

```
final_lightgbm_fit <- extract_workflow(last_lightgbm_fit)

lightgbm_auc <- validation(final_lightgbm_fit, df_test)
```



```
## [1] "Optimal Threshold: 0.00"
## Confusion Matrix and Statistics
##
##      reference
## data    0    1
## 0 3445    6
## 1 1261   18
##
##              Accuracy : 0.7321
##              95% CI : (0.7193, 0.7447)
##      No Information Rate : 0.9949
##      P-Value [Acc > NIR] : 1
##
##              Kappa : 0.0178
##
##  McNemar's Test P-Value : <2e-16
##
##              Sensitivity : 0.73204
##              Specificity : 0.75000
##      Pos Pred Value : 0.99826
##      Neg Pred Value : 0.01407
##      Prevalence : 0.99493
##      Detection Rate : 0.72833
##      Detection Prevalence : 0.72960
##      Balanced Accuracy : 0.74102
##
##      'Positive' Class : 0
##
```


```
# pfun_lightgbm <- function(object, newdata) predict(object, data = newdata)
# extract_vip(final_lightgbm_fit, pred_wrapper = pfun_lightgbm,
#             reference_class = "1")

lightgbm_parameters <- lightgbm_tune %>%
  show_best("roc_auc", n = 1) %>%
  select(trees, min_n, tree_depth, learn_rate) %>%
  as.list

saveRDS(
  lightgbm_parameters,
  file = sprintf(
    "./auxiliar/model_selection/hyperparameters/lightgbm_%s.rds",
    outcome_column
  )
)
```

Minutes to run: 2.057

## Histogram of preds



Minutes to run:

0.007

## GLM

```
glmnet_recipe <-
  recipe(formula = sprintf("%s ~ .", outcome_column) %>% as.formula, data = df_train) %>%
  step_novel(all_nominal_predictors()) %>%
  step_unknown(all_nominal_predictors()) %>%
  step_other(all_nominal_predictors(), threshold = 0.05, other = ".merged") %>%
  step_dummy(all_nominal_predictors()) %>%
  step_zv(all_predictors()) %>%
  step_normalize(all_numeric_predictors())

glmnet_spec <-
```

```


logistic_reg(penalty = 0) %>%
set_mode("classification") %>%
set_engine("glmnet")

glmnet_workflow <-
  workflow() %>%
  add_recipe(glmnet_recipe) %>%
  add_model(glmnet_spec)

glm_fit <- glmnet_workflow %>%
  fit(df_train)

glmnet_auc <- validation(glm_fit, df_test)

```



```


## [1] "Optimal Threshold: 0.01"
## Confusion Matrix and Statistics
##
##      reference
## data    0    1
## 0 3764    6
## 1  942   18
##
##              Accuracy : 0.7996
##              95% CI : (0.7879, 0.8109)
##    No Information Rate : 0.9949
##    P-Value [Acc > NIR] : 1
##
##              Kappa : 0.027
##
##  McNemar's Test P-Value : <2e-16
##
##              Sensitivity : 0.79983
##              Specificity : 0.75000

```


```
##      Pos Pred Value : 0.99841
##      Neg Pred Value : 0.01875
##      Prevalence : 0.99493
##      Detection Rate : 0.79577
##      Detection Prevalence : 0.79704
##      Balanced Accuracy : 0.77492
##
##      'Positive' Class : 0
##
```

```
pfun_glmnet <- function(object, newdata) predict(object, newx = newdata)
```

```
extract_vip(glm_fit, pred_wrapper = pfun_glmnet,
             reference_class = "1", method = 'model')
```



```
extract_vip(glm_fit, pred_wrapper = pfun_glmnet,
             reference_class = "1", method = 'permute')
```



Minutes to run:

1.525

## Decision Tree

```
tree_recipe <-
  recipe(formula = sprintf("%s ~ .", outcome_column) %>% as.formula, data = df_train) %>%
  step_novel(all_nominal_predictors()) %>%
  step_unknown(all_nominal_predictors()) %>%
  step_other(all_nominal_predictors(), threshold = 0.05, other = ".merged") %>%
  step_dummy(all_nominal_predictors()) %>%
  step_zv(all_predictors())

tree_spec <-
  decision_tree(cost_complexity = tune(),
                tree_depth = tune(),
                min_n = tune()) %>%
  set_mode("classification") %>%
  set_engine("rpart")


tree_grid <- grid_latin_hypercube(cost_complexity(),
                                   tree_depth(),
                                   min_n(),
                                   size = grid_size)

tree_workflow <-
  workflow() %>%
  add_recipe(tree_recipe) %>%
  add_model(tree_spec)

tree_tune <-
  tree_workflow %>%
  tune_grid(resamples = df_folds,
            grid = tree_grid)
```

```
tree_tune %>%
  collect_metrics()

autoplot(tree_tune, metric = "roc_auc")
```



```
tree_tune %>%
  show_best("roc_auc")


best_tree <- tree_tune %>%
  select_best("roc_auc")

final_tree_workflow <-
  tree_workflow %>%
  finalize_workflow(best_tree)


last_tree_fit <-
  final_tree_workflow %>%
  last_fit(df_split)

final_tree_fit <- extract_workflow(last_tree_fit)

tree_auc <- validation(final_tree_fit, df_test)
```



```
extract_vip(final_tree_fit, pred_wrapper = predict,
            reference_class = "0", use_matrix = FALSE,
            method = 'model')
```



```
# extract_vip(final_tree_fit, pred_wrapper = predict,
#             reference_class = "1", use_matrix = FALSE,
```




```
# method = 'permute')
```

Minutes to run: 0.876

## Random Forest

```
rf_recipe <-  
  recipe(formula = sprintf("%s ~ .", outcome_column) %>% as.formula,  
    data = df_train) %>%  
  step_nominal(all_nominal_predictors()) %>%  
  step_unknown(all_nominal_predictors()) %>%  
  step_other(all_nominal_predictors(), threshold = 0.05, other = ".merged") %>%  
  step_dummy(all_nominal_predictors()) %>%  
  step_zv(all_predictors()) %>%  
  step_impute_mean(all_numeric_predictors())  
  
rf_spec <-  
  rand_forest(mtry = tune(),  
    trees = tune(),  
    min_n = tune()) %>%  
  set_mode("classification") %>%  
  set_engine("randomForest",  
    probability = TRUE,  
    nthread = 8)  
  
rf_grid <- grid_latin_hypercube(mtry(range = c(1L, 50L)),  
  trees(range = c(100L, 300L)),  
  min_n(),  
  size = grid_size)  
  
rf_workflow <-  
  workflow() %>%  
  add_recipe(rf_recipe) %>%  
  add_model(rf_spec)  
  
rf_tune <-  
  rf_workflow %>%  
  tune_grid(resamples = df_folds,  
    grid = rf_grid)  
  
rf_tune %>%  
  collect_metrics()  
  
autoplot(rf_tune, metric = "roc_auc")
```



```
rf_tune %>%
  show_best("roc_auc")


best_rf <- rf_tune %>%
  select_best("roc_auc")

final_rf_workflow <-
  rf_workflow %>%
  finalize_workflow(best_rf)

last_rf_fit <-
  final_rf_workflow %>%
  last_fit(df_split)


final_rf_fit <- extract_workflow(last_rf_fit)

rf_auc <- validation(final_rf_fit, df_test)
```



```
pfun_rf <- function(object, newdata) predict(object, data = newdata)

extract_vip(final_rf_fit, pred_wrapper = predict,
            reference_class = "1", use_matrix = FALSE,
            method = 'model')
```




```
# extract_vip(final_rf_fit, pred_wrapper = predict,
#             reference_class = "1", use_matrix = FALSE,
#             method = 'permute')
```

Minutes to run: 13.084

## Models Comparison

```
df_auc <- tibble::tribble(
  ~Model, ~`AUC`, ~`Lower Limit`, ~`Upper Limit`,
  'XGBoost', as.numeric(xgboost_auc$auc), xgboost_auc$ci[1], xgboost_auc$ci[3],
  'LightGBM', as.numeric(lightgbm_auc$auc), lightgbm_auc$ci[1], lightgbm_auc$ci[3],
  'GLM', as.numeric(glmnet_auc$auc), glmnet_auc$ci[1], glmnet_auc$ci[3],
  'Decision Tree', as.numeric(tree_auc$auc), tree_auc$ci[1], tree_auc$ci[3],
  'Random Forest', as.numeric(rf_auc$auc), rf_auc$ci[1], rf_auc$ci[3]
) %>%
  mutate(Target = outcome_column)

df_auc %>%
  ggplot(aes(x = Model, y = AUC, ymin = `Lower Limit`, ymax = `Upper Limit`)) +
    geom_point() +
    geom_errorbar()
```



```
saveRDS(df_auc, sprintf("./auxiliar/model_selection/performance/%s.RData", outcome_column))
```

Minutes to run: 0.01