

Computer Networks

Streaming Media (§7.4.3)



David Wetherall (djw@uw.edu)

Professor of Computer Science & Engineering

UNIVERSITY *of* WASHINGTON


Topic

- Playback of media over the network
 - Using the best effort Internet
 - Coursera, YouTube, Netflix, etc.
 - Huge usage!




Streamed vs. Interactive Media

- Streamed is less demanding case:
 - ➔ Only a single direction to consider
 - ➔ Low delay not essential; affects startup but not interactivity
 - ➔ Still need to handle bandwidth, jitter




Handling Jitter

- As before, buffer media at receiver until ready for playout time
 - Smooth out variable network delay




Handling Jitter (2)

- Use HIGH and LOW watermarks to control source over/underfill
 - Start pulling media at low level
 - Stop pulling media at high level



Handling Bandwidth

- Send file in one of multiple encodings
 - ➔ Higher quality encodings require more bandwidth
 - ➔ Select best encoding given available bandwidth



By Toytoy, CC-BY-SA-3.0, from Wikimedia Commons

➤ Streaming over TCP or UDP?


- ➤ UDP minimizes message delay for interactive, real-time sessions
- ➤ TCP is typically used for streaming
 - Low delay is not essential; startup
 - Loss recovery simplifies presentation
 - HTTP/TCP passes through firewalls

Components of Streaming Media

- Session consists of several parts:
 - ➡ — Signaling, e.g., with RTSP »
 - ➡ — Media transport, e.g., with HTTP »
 - ➡ — Media playout, with buffer
 - ➡ — Evolving standards, e.g., HTML5
- [Typically to an individual party
 - Use CDNs to reach many viewers


Streaming with RTSP

- Video started using HTTP to get metafile
- Invokes media player
 - Talks RTSP (Real-Time Streaming Protocol) to media server
- Media sent with, e.g., RTP over TCP/UDP



Streaming with HTTP

- Fetch media description data
 - Gives index of clips, rates
- Fetch small segments
 - Put in playout buffer
- Adapt selection of encoding
 - Based on buffer occupancy
- Evolving standards, e.g., DASH
 - Leverages HTTP and HTML5
 - Server is otherwise stateless



END

© 2013 D. Wetherall

Slide material from: TANENBAUM, ANDREW S.; WETHERALL, DAVID J., COMPUTER NETWORKS, 5th Edition, © 2011.
Electronically reproduced by permission of Pearson Education, Inc., Upper Saddle River, New Jersey