Computer Networks

Wireless Security (§8.6.4)

David Wetherall (djw@uw.edu)
Professor of Computer Science & Engineering
UNIVERSITY of WASHINGTON

Topic

- Securing wireless networks
  - Focus on 802.11



Goal and Threat Model

- Unlike wired, wireless messages are broadcast to all nearby receivers
  - Don't need physical network access
  - Heightens security problems



Goal and Threat Model (2)

- Two main threats:
  1. Eavesdropping on conversations
  2. Unauthorized access to network
- We'll consider 802.11 setting
  - Assume external attacker can send/receive wireless messages

802.11 Security

- Security is based on passwords
  - For access control and confidentiality and integrity/authenticity
- 802.11 standard (1999) used WEP
  - For "Wired Equivalent Privacy"
  - Badly flawed, easily broken
- 802.11i standard in 2004
  - WiFi Protected Access or WPA2
  - This is what you should use

802.11 Security

- Security is part of 802.11 protocol
  - Encrypted message between client and AP; removed after AP



Home Network

- AP is set up with network password
- Each client also knows password
- Client proves it knows password »
  - AP grants network access if successful



Home Network (2)

- For access, client authenticates to AP »
  - Both compute a shared session key based on the password
  - If client knows the session key it has proved that is has the password
- For usage, client/AP encrypt messages
  - For confidentiality, integrity/authenticity
  - No access without the session key
  - Also group key for AP to reach all clients

Home Network (3)

- Master key is from password; nonces for freshness
  - K_S lets client talk to AP; K_G lets AP talk to all clients



Enterprise Network

- Network has authentication server
- Each client has own credentials
- AP lets client talk to auth. server
  - Grants network access if successful



END