

Computer Networks

HTTP Caching and Proxies (§7.3.4, §7.5.2)




David Wetherall (djw@uw.edu)

Professor of Computer Science & Engineering

UNIVERSITY *of* WASHINGTON


Topic

- HTTP caching and proxies
 - Enabling content reuse



Web Caching


- Users often revisit web pages
 - Big win from reusing local copy!
 - This is caching



- Key question:
 - When is it OK to reuse local copy?


Web Caching (2)

- Locally determine copy is still valid
 - ➔ Based on expiry information such as “Expires” header from server
 - ➔ Or use a heuristic to guess (cacheable, freshly valid, not modified recently)
 - ➔ Content is then available right away




Web Caching (3)

- Revalidate copy with remote server
 - Based on timestamp of copy such as “Last-Modified” header from server
 - Or based on content of copy such as “Etag” header from server
 - Content is available after 1 RTT



Web Caching (4)

- Putting the pieces together:




Web Proxies

- Place intermediary between pool of clients and external web servers
 - Benefits for clients include greater caching and security checking
 - Organizational access policies too!
- Proxy caching
 - Clients benefit from larger, shared cache
 - Benefits limited by secure / dynamic content, as well as “long tail”

Web Proxies (2)

- Clients contact proxy; proxy contacts server



END

© 2013 D. Wetherall

Slide material from: TANENBAUM, ANDREW S.; WETHERALL, DAVID J., COMPUTER NETWORKS, 5th Edition, © 2011.
Electronically reproduced by permission of Pearson Education, Inc., Upper Saddle River, New Jersey