Markdown to Typst Feature Reference

This document exercises every Markdown feature supported by mdtyp.

Headings

Third Level

Fourth Level

Fifth Level

Sixth Level

Heading with **bold** and *italic* words

Heading with `inline code`

Inline Formatting

This is **bold text** and this is *italic text* and this is ~~strikethrough text~~.

Combining: **bold and *italic* together** and ~~strikethrough with **bold**~~.

*Emphasis with ***bold and*** nested emphasis ***inside*** and the correct ending*.

Here is `inline code` in a sentence.

Links and Images

Here is a link to Google and a link with **bold** text.

Lists

Unordered List

- Item one
- Item two
- Item three

Ordered List (Starting at Three)

3. First item
4. Second item
5. Third item

Nested Unordered

- Top level
  - Second level
    - Third level
  - Back to second
- Back to top

Nested Ordered

1. First
    7. Sub first
    8. Sub second
2. Second
    1. Another sub

Mixed Nesting

1. Ordered top
    - Unordered child
    - Another child
2. Back to ordered
    - Child again
        1. Deep ordered
        2. More deep

List Items with Formatting

- **Bold item**
- *Italic item*
- Item with `code`
- Item with a link

Blockquotes

“This is a simple blockquote.”

“This is a blockquote that spans multiple lines in the source.”

“First paragraph of a blockquote.

Second paragraph of the same blockquote.”

“Blockquote with **bold**, *italic*, and `code`.”

“‘Nested blockquote inside a blockquote.’”

“Blockquote with a list:

- Item one
- Item two

”

Code Blocks

Inline: use `print("hello")` to print.

Fenced with language:

```
def factorial(n):
    if n <= 1:
        return 1
    return n * factorial(n - 1)
```

```
function greet(name) {
    console.log(`Hello, ${name}!`);
}
```

Fenced without language:

```
Just plain text in a code block.
No syntax highlighting.
```

Indented code block:

```
this is an indented
code block with
four spaces
```

Tables

Simple Table

Name	Age	City
Alice	30	London
Bob	25	Paris

Table with Alignment

Left	Center	Right
L1	C1	R1
L2	C2	R2
L3	C3	R3

Table with Formatting

Feature	Syntax	Output
Bold	`**text**`	**text**
Italic	`_text_`	*text*
Code	`` `code` ``	`code`
Link	`[t](url)`	t

Single Column Table

Values
One
Two
Three

Wide Table

Col1	Col2	Col3	Col4	Col5	Col6
a	b	c	d	e	f

Horizontal Rules

Content above the first rule.

Content between rules.

Content after the last rule.

Math

Inline Math

The quadratic formula is $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$.

Euler's identity: $e^{i\pi} + 1 = 0$.

A simple sum: $\sum_{i=1}^{n} i = \frac{n(n+1)}{2}$.

Display Math

$$\int_0^\infty e^{-x^2}\ \mathrm{dx} = \frac{\sqrt{\pi}}{2}$$

$$\boldsymbol{F} = m\boldsymbol{a}$$

Fractions and Roots

$\frac{a}{b}$, $\frac{1}{\sqrt{2}}$, $\sqrt[3]{x}$

Greek Letters

$\alpha, \beta, \gamma, \delta, \varepsilon, \theta, \lambda, \mu, \pi, \sigma, \omega$

$\Gamma, \Delta, \Theta, \Lambda, \Pi, \Sigma, \Omega$

Matrices

$$\begin{bmatrix} a & b \\ c & d \end{bmatrix}$$

$$\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

Aligned Equations

$$\begin{aligned} f(x) &= x^2 + 2x + 1 \\ &= (x+1)^2 \end{aligned}$$

Cases

$$f(x) = \begin{cases} x^2 & \text{if } x \geq 0 \\ -x & \text{otherwise} \end{cases}$$

Operators and Relations

$\leq, \geq, \neq, \approx, \equiv, \sim, \propto$

$\in, \notin, \subset, \subseteq, \cup, \cap$

$\forall, \exists, \nabla, \partial, \infty$

Accents and Decorations

$\hat{x}, \bar{y}, \vec{v}, \dot{x}, \ddot{x}, \tilde{n}$

Big Operators

$$\prod_{i=1}^{n} x_i \qquad \sum_{k=0}^{\infty} a_k \qquad \int_{a}^{b} f(x)\,\mathrm{dx}$$

Subscripts and Superscripts

$x_1, x_{12}, x^2, x^{2n}, x_i^2, a_{i,j}^{k+1}$

Text in Math

$x = 0 \quad \text{when} \quad y > 1$

$\text{two spaces; cost \$5; set \{a, b\}}$

Adjacent Commands

$$\eta\sqrt{\Gamma\left(1+\frac{2}{\beta}\right)-\Gamma\left(1+\frac{1}{\beta}\right)^2}, \quad \alpha\sqrt[3]{x}, \quad \eta x, \quad \eta \neq$$

Blackboard Bold

$\mathbb{R}, \mathbb{N}, \mathbb{Z}, \mathbb{Q}, \mathbb{C}, \mathbb{R}(x)$

HTML Elements

Some inline HTML: bold via HTML and emphasis via HTML.

A block of HTML:

Special Characters

Ampersands & angles < > and quotes "double" 'single'.

Backslash: \ and tilde: ~ and caret: ^

Dollar sign: $100 and hash: #hashtag and at: @mention

Consecutive Formatting

bold1 bold2 *italic1 italic2* `code1 code2`

Paragraph and Soft Breaks

This is the first paragraph. It has multiple sentences. They should flow together.

This is the second paragraph, separated by a blank line.

This line has a soft break that should become a space.

A paragraph with **bold**, *italic*, `code`, and a link all mixed together in one flowing block of text.