

## Lab 03: Installing the APTARE IT Analytics Data Collectors

---

In this lab, you create Data Collectors in the Portal and install the Data Collector software on a Windows and a Linux Server.

### Lab Exercises

This lab includes the following exercises:

- [Exercise A: Adding Data Collectors](#)
- [Exercise B: Installing the Data Collectors](#)

⚠ It is recommended to use Google Chrome to perform the lab exercises. After launching the lab, zoom out the lab browser window to 80% to fit the APTARE Portal interface and view all the tabs within the window.

## Exercise A: Adding Data Collectors

To enable the Data Collector server to pass data to the Portal server, a corresponding Data Collector must be created in the Portal, along with Data Collector policies for each of the vendor-specific enterprise objects. Data Collector policies are specific to the type of data that is being collected; however, multiple types of policies often can be combined within one Data Collector.

In this exercise, you create two new Data Collectors in the Portal.

### Adding your first Data Collector

- ☐ 1. Sign in to the  **console** system using the following credentials:

**Username:**

**Password:**

- ☐ 2. Double-click the **Aptare Portal** shortcut, located on the desktop of the **console.example.com** system, to launch the **APTARE IT Analytics Portal**.
- ☐ 3. When the **APTARE IT Analytics Portal** login page is displayed, login using the below credentials.

**Username**


**Password**

- ☐ 4. In the **APTARE IT Analytics Portal**, navigate to **Admin > Data Collection > Collector Administration**. The list of currently configured Portal Data Collectors is displayed.
- ☐ 5. In the **Collector Administration** page, click **Add Collector**. The **Add Collector** dialog box is displayed.
- ☐ 6. In the **Add Collector** dialog box, enter the following details:

Field	Value
Collector Name	<input type="text" value="collector1"/>
Passcode	<input type="text" value="P@ssw0rd"/>
Domain	<input type="text" value="Aptare"/>

Field	Value
Auto-upgrade aptare.jar	<input checked="" type="checkbox"/> Yes
Auto-upgrade Upgrade Manager	<input checked="" type="checkbox"/> Yes


- ☐ 7. Click **OK** to create the Data Collector and return to the **Collector Administration** page.
- ☐ 8. The following message is displayed. Click **OK** to continue.



## Adding a second Data Collector

- ☐ 9. On the **Collector Administration** page, click **Add Collector** to create a second Data Collector in the Portal.
- ☐ 10. In the **Add Collector** dialog box that is displayed, enter the following details:

Field	Value
Collector Name	<input checked="" type="checkbox"/> collector2
Passcode	<input checked="" type="checkbox"/> P@ssw0rd
Domain	<input checked="" type="checkbox"/> Aptare
Auto-upgrade aptare.jar	<input checked="" type="checkbox"/> Yes
Auto-upgrade Upgrade Manager	<input checked="" type="checkbox"/> Yes


 **collector2** is an alias for the NetBackup master server, **nbmaster1.example.com**.

- ☐ 11. Click **OK** to create the Data Collector and return to the **Collector Administration** page.
- ☐ 12. A message regarding the **key pair** is displayed. Click **OK** to continue.

The newly created Data Collectors, **collector1** and **collector2** are now listed on the **Collector Administration** page.

Name	Domain	Enab...	Policy S...	Collector S...	St...	Last Modified	Collector Version	Upgrade Mana...	Auto Upgra...	Host	Notes
APTARE	Kiwi Insurance Co.	Yes	Offline			Feb 21, 2019 9:21:35 AM			Full Auto		short notes
apteng	APTAREEng	Yes	Offline			Sep 6, 2017 2:30:29 PM	10.0.0.01 (02232016-1126)	10.0.0.01	Full Auto	SrinivasK-PC	
AWS_NBU	HQ	Yes	Offline			Jul 28, 2017 11:56:56 AM	10.1.60.01 (07282017-0011)	10.1.60.01	Full Auto	nbu777corp	
boston	Agency of Commer	Yes	Offline			Feb 1, 2017 10:58:01 AM			Full Auto		
collector1	Aptare	Yes	Offline			Dec 9, 2021 7:12:55 PM			Full Auto		
collector2	Aptare	Yes	Offline			Dec 9, 2021 7:16:36 PM			Full Auto		
CommVault Simpana	FP2	Yes	Offline			Mar 14, 2013 4:18:16 PM			Full Auto	aptare.jar	
Corp	Agency of Commer	Yes	Offline			Jun 18, 2018 4:01:15 PM			Full Auto		
cs	Agency of Commer	Yes	Offline			Apr 26, 2018 1:50:34 PM			Full Auto		


- ☐ 13. Minimize the **APTARE IT Analytics Portal**.
- ☐ 14. From the desktop of the **Console** system, locate and double-click the shortcut for **File Explorer**.
- ☐ 15. Navigate to the **Downloads** folder. There are two **.key** files located in this folder. You need to copy the **collector1.key** and **collector2.key** files to the **collector1** and **nbmaster1** systems respectively. Refer to the following instructions:
  - ☐ a. Right-click the **collector1.key** file and select **Copy**.
  - ☐ b. In the Navigation Bar of the **File Explorer**, type **T \\collector1\c\$** and press **Enter**.



- ☐ c. Right-click anywhere in the empty pane and select **Paste** to copy the **collector1.key** file.
- ☐ d. Close the **File Explorer**.
- ☐ e. From the desktop of the **Console** system, locate and double-click the shortcut for **WinSCP**.
- ☐ f. In the **Login** window, select **New Site**. Provide the following information:
  - ☐ i. In the **Host name** field, enter **T nbmaster1.example.com**
  - ☐ ii. In the **User name** field, enter **T root**.
  - ☐ iii. In the **Password** field, enter **T P@ssw0rd**.
  - ☐ iv. Click **Login**.
- ☐ g. Click **Yes** to cache the host key.

You are now connected to the **nbmaster1** system.

- ☐ h. In the left pane of the **WinSCP**, specify the path as **C:\Users\Administrator\Downloads**.
- ☐ i. In the right pane, select the path as **/root/aptare\_install\_files/**.
- ☐ j. Move the **collector2.key** file to the **aptare\_install\_files**. You may use the drag and drop or copy-paste feature.




- ☐ k. Close the **WinSCP** window.


[Go to Lab Exercises](#)

## Exercise B: Installing the Data Collectors

In this exercise, you install the Data Collector binaries on **collector1** and **collector2** systems.

 **collector2** is an alias for the NetBackup master server, **nbmaster1.example.com**.


### Installing the Data Collector software on a Windows server

- ☐ 1. Sign in to the  **collector1** system using the following credentials.

**Username:**  **EXAMPLE\Administrator**

**Password:**  **P@ssw0rd**

- ☐ 2. Double-click the **Aptare\_DC\_Install\_Files** shortcut, located on the desktop of the **collector1.example.com** system, to launch **File Explorer**.
- ☐ 3. In the **File Explorer** window that is displayed, double-click the **sc\_datacollector\_win\_10600** file to launch the installer.

 After checking the available disk space and downloading the installer, a window to select the **Language** is displayed.




- ☐ 4. Select the language as **English** and click **OK**.
- ☐ 5. In the **Introduction** window, click **Next** to proceed to the **License Agreement** screen.
- ☐ 6. On the **License Agreement** screen, select the **I accept the terms of the License Agreement** checkbox and click **Next** to proceed to the **Choose Install Folder** screen.
- ☐ 7. On the **Choose Install Folder** screen, retain the default values and click **Next** to proceed to the **Pre-Installation Summary** screen.
- ☐ 8. On the **Pre-Installation Summary** screen, review the details that are displayed and click **Install** to start the installation.

**Note:** The installation process might take 1-2 minutes to complete.


After the installation completes, the **Configuration Settings** window is displayed.

- ☐ 9. On the **APTARE IT Analytics Data Collector – Configuration Settings** window, select **Data Collector (includes WMI Proxy)** in the **Data Collection Tasks** drop-down box and click **Next** to proceed to the next screen.
- ☐ 10. Enter the following configuration settings and click **Finish**.

Field	Value
-------	-------

Field	Value
<b>Data Collector Name</b>	 <b>collector1</b>
<b>Password</b>	 <b>P@ssw0rd</b>
<b>Data Receiver URL</b>	 <b>http://aptareagent.example.com</b>
<b>Data Collector Key File:</b>	Click the <b>Browse</b> icon and navigate to <b>This PC\C:</b> . Select the <b>collector1.key</b> file.

- ☐ 11. On the **Get User Input** screen that is displayed, select the **Run later** radio button and click **Done** to proceed to the **Installation Complete** screen.
- ☐ 12. On the **Installation Complete** screen, click **Done** to exit the installer.


 The installer configures the Data Collector to start automatically, however, it does not start it upon completion of the installation. Perform the steps below to start the Data Collector.

- ☐ 13. Access the desktop of the **collector1.example.com** system.
- ☐ 14. Double-click the **Command Prompt** shortcut, located on the desktop of the **collector1.example.com** system, to launch the **Command Prompt**.
- ☐ 15. In the **Command Prompt** window, type the following command and press **Enter** to change directory to **C:\Program Files\Aptare\mbs\bin**.


**Command:**  **cd /d "C:\Program Files\Aptare\mbs\bin"**

- ☐ 16. In the **Command Prompt** window, type the following command and press **Enter** to start the **Aptare Agent** service.

**Command:**  **startservices.bat**

 The Data Collector installer configures the Data Collector process as a Service and hence the Windows services console (**services.msc**) can be used as an alternative to start the **Aptare Agent** service.

## Installing the Data Collector software on a Linux server

- ☐ 17. Access the desktop of the  **console** system.
- ☐ 18. If required, Sign in using the following credentials.

	User name:	Password:
<b>console.example.com</b>	<b>EXAMPLE\Administrator</b>	<b>P@ssw0rd</b>

☐

19. Double-click the **PuTTY** shortcut, located on the desktop of the **console.example.com** system, to launch **PuTTY**.

- ☐ 20. In the **PuTTY Configuration** window that is displayed, double-click the pre-configured entry for **nbmaster1.example.com**. The login prompt is displayed in a new window.
- ☐ 21. Login to the **nbmaster1.example.com** system using the following credentials.

---

 **nbmaster1.example.com**    User ID: T **root**    Password: T **P@ssw0rd**

---


- ☐ 22. In the **Terminal window** that is displayed, type the following command and press **Enter** to change directory to **/aptare\_install\_files**

**Command:** T **cd /aptare\_install\_files**

- ☐ 23. In the **Terminal window**, type the following command and press **Enter** to launch the **APTARE IT Analytics Data Collector** installer.


**Command:** T **./sc\_datacollector\_linux\_10600.bin**

- ☐ 24. At the **CHOOSE LOCALE BY NUMBER:** prompt, enter **1** and press **Enter**.
- ☐ 25. Press **Enter** at the **Introduction** to continue. The **License Agreement** is displayed.
- ☐ 26. Read the license agreement and press **Enter** until the "**DO YOU ACCEPT THE TERMS OF THIS LICENSE AGREEMENT? (Y/N):**" prompt is displayed.
- ☐ 27. At the "**DO YOU ACCEPT THE TERMS OF THIS LICENSE AGREEMENT**" prompt, type **Y** and press **Enter** to continue.
- ☐ 28. At the "**ENTER AN ABSOLUTE PATH, OR PRESS TO ACCEPT THE DEFAULT:**" prompt, press **Enter** to accept the **Default Install Folder** and continue.
- ☐ 29. Review the details that are displayed and press **Enter** to start the installation.

 The installation process might take 1-2 minutes to complete.

After the installation is complete, the installer prompts for configuration settings.


- ☐ 30. At the **Data Collector Name** prompt that is displayed, type T **collector2** and press **Enter** to continue.

 **collector2** is an alias for the NetBackup master server, **nbmaster1.example.com**.

- ☐ 31. At the **Data Collector Password** prompt that is displayed, type T **P@ssw0rd** and press **Enter** to continue.
- ☐ 32. At the **Data Receiver URL** prompt that is displayed, type T **http://aptareagent.example.com** and press **Enter** to continue.
- ☐ 33. At the **Data Collector Key File :** prompt that is displayed, type T **/aptare\_install\_files/collector2.key**
- ☐ 34. At the **Use Proxies** prompt that is displayed, press **Enter** to retain the default value **(N)** and continue.



- ☐ 35. Press **Enter** to start the configuration.
- ☐ 36. After the configuration completes, press **Enter** to exit the installer.

 The installer configures the Data Collector to start automatically, however, it does not start it upon completion of the installation. Perform the steps below to start the Data Collector.

- ☐ 37. In the **Terminal window**, type the following command and press **Enter** to change directory to **/opt/aptare/mbs/bin**.

**Command:**  `cd /opt/aptare/mbs/bin`

- ☐ 38. In the **Terminal window**, type the following command and press **Enter** to start the **Aptare Agent**.

**Command:**  `./aptare_agent start`

- ☐ 39. In the **Terminal window**, type **exit** to close the session and return to the desktop of the **console.example.com** system.

## Checking the Data Collector status in the Portal

- ☐ 40. Access the **APTARE IT Analytics Portal**.
- ☐ 41. If required, login to the **APTARE IT Analytics Portal** using the following credentials:

**Username**  `admin@example.com`

**Password**  `P@ssw0rd`

- ☐ 42. If required, navigate to **Admin > Data Collection > Collector Administration**. The list of currently configured Portal Data Collectors is displayed.
- ☐ 43. Locate the entries for **collector1** and **collector2** and verify the **Collector State**.

The **Collector State** for both these collectors should be **Online** as illustrated in the figure below.

Collector Administration

















Filter by Name ...

Advanced

Refresh

Add Collector

Expand All

Name	Domain	Enab...	Policy S...	Collector St...	St...	Last Modified	Collector Version	Upgrade Mana...	Auto Upgrade	Host	Notes
 APTARE	Kiwi Insurance Co.	Yes		Offline		Feb 21, 2019 9:21:35 AM			Full Auto		short notes
 apteng	APTAREEng	Yes		Offline		Sep 6, 2017 2:30:29 PM	10.0.0.01 (02232016-1126)	10.0.0.01	Full Auto	SrinivasK-PC	
 AWS_NBU	HQ	Yes		Offline		Jul 28, 2017 11:56:56 AM	10.1.60.01 (07282017-0011)	10.1.60.01	Full Auto	nbu77.corp	
 boston	Agency of Commer	Yes		Offline		Feb 1, 2017 10:58:01 AM			Full Auto		
 collector1	Aptare	Yes		Online		Dec 9, 2021 9:26:53 PM	10.6.5.01 (09202021-1346)	10.6.5.01	Full Auto	collector1	
 collector2	Aptare	Yes		Online		Dec 10, 2021 1:56:37 AM	10.6.5.01 (09202021-1346)	10.6.5.01	Full Auto	nbmaster1.exan	
 CommVault Simpna	FP2	Yes		Offline		Mar 14, 2013 4:18:16 PM				aptare.jar	
 Corp	Agency of Commer	Yes		Offline		Jun 18, 2018 4:01:15 PM			Full Auto		

 If the **Collector State** for the above collectors is **Offline**, click the **Refresh** button available on the **Collector Administration** page to refresh the view.

Also, note the **Collector Version** and the **Upgrade Manager** version. These were updated to version **10.6.5.01** automatically because the **Auto-Upgrade** settings were set to **Yes** while creating the **Data Collector**.

If the **Collector Version** and the **Upgrade Manager** version is not displayed on the **Collector Administration** page, check the Collector updates by navigating to **Admin > Data Collection > Collector Updates** page. The figure below displays the **Collector Updates** page.

Name	Domain	E...	Poli...	Collector State	S...	Last Modified	Collector Versi...	Upgrade...	Auto ...	Host	Notes
APTARE	Kiwi Insuran	Yes		Offline		Feb 21, 2019 9:2			Full Auto		short not
apteng	APTAREEng	Yes		Offline		Sep 6, 2017 2:30	10.0.0.01 (0223201	10.0.0.01	Full Auto	Srinivask-	
AWS_NBU	HQ	Yes		Offline		Jul 28, 2017 11:5	10.1.60.01 (072820	10.1.60.01	Full Auto	nbu77.cor .	
boston	Agency of Ci	Yes		Offline		Feb 1, 2017 10:5			Full Auto		
collector1	Aptare	Yes		Online		Dec 14, 2021 2:3	10.6.5.01 (0920202	10.6.5.01	Full Auto	collector1	
collector2	Aptare	Yes		Online		Dec 14, 2021 2:4	10.6.5.01 (0920202	10.6.5.01	Full Auto	nbmaster:	
CommVault Simpana	FP2	Yes		Offline		Mar 14, 2013 4:1			aptare.jar		
Corp	Agency of Ci	Yes		Offline		Jun 18, 2018 4:0			Full Auto		
cs	Agency of Ci	Yes		Offline		Apr 26, 2018 1:5			Full Auto		
d	Agency of Ci	Yes		Offline		Nov 13, 2018 2:4			Full Auto		

- ☐ 44. In the **APTARE IT Analytics Portal**, click **System Administrator > Log Out** to log out from the **APTARE IT Analytics Portal**.
- ☐ 45. Close the **Google Chrome** browser window and log out from the **console.example.com** system.

**End of Lab**