Annotation Type OnMethod

@Retention(value=RUNTIME)

@Target(value=METHOD)

public @interface OnMethod

Optional Element Summary

指定一个"探测点",通过在Java类、方法和特定的位置上指定

This annotation <u>specifies</u> a BTrace probe point <u>by specifying</u> a java class (or classes), a method (or methods in it) and a specific location within it. A BTrace trace action method annotated by this annotation <u>is called when matching the traced program</u> reaches the specified location.

Author: 当匹配的追踪程序抵达"指定的位置"时,"追踪行为方法"会被调用

A. Sundararajan

Required Element Summary		
Required Elements	必配元素	
Modifier and Type	Required Element and Description	
java.lang.String	The probed (or traced) class name.	待探测或追踪的"全路径类名/ 正则匹配/注解类"

<u>optional Ziomoni</u> caninally			
Optional Elements	可选元素		
Modifier and Type	Optional Element and Description		
boolean	follow		
Location	Tocation 在"方法集"中标识精确的"位置"或感兴趣的"探测点" Identifies exact "location" or "point" of interest to probe within the set of methods.		
java.lang.String	method The probed (or traced) method name.	待探测或追踪的"方法名/ 正则匹配/注解方法"	
java.lang.String	type		

方法类型声明

Element Detail

clazz

public abstract java.lang.String clazz

The probed (or traced) class name. This is either <u>fully qualified name of the class</u> or <u>regular</u>

This is <u>method type declaration</u>.

<u>expression within two forward slash characters</u> [like /java\\.awt\\.<u>.+/</u>] or <u>@annotation of the class</u>. i.e., specify a class indirectly as a class annotated by specified annotation.

method

public abstract java.lang.String method

The probed (or traced) method name. This is either the name of the method or regular expression within two forward slash characters [like /read,+/] or @annotation of the method. i.e., specify a method indirectly as a method annotated by specified annotation.

Default:

" "

type

public abstract java.lang.String type

This is method type declaration. This is <u>like</u> Java method declaration but <u>not including</u> method name, parameter names and throws clause. *

Eg. public void myMethod(java.lang.String param) will become void (java.lang.String)

Default:

11 11

location

public abstract Location location

<u>Identifies</u> exact "location" or "point" of interest to probe within the set of methods.

Default:

@com.sun.btrace.annotations.Location

follow

public abstract boolean follow

Default:

false