

Practical examples: use the geolocation API altogether with Google Maps

In this section, we give some examples that shows how to get a static map (a picture), using [the Google Static Map API](#), how to display an interactive map using [the Google Map JavaScript API](#) and even how to get an estimation of the surface address from the longitude and latitude, using [the Google Reverse Geocoding JavaScript API](#).

These three examples have an increasing complexity, but most of the code is reused and adapted without even reading the Google documentation about the different APIs.

EXAMPLE 1 (EASY): HOW TO GET A STATIC IMAGE MAP CENTERED ON YOUR LONGITUDE AND LATITUDE

[Online example available on JS Bin](#), or try it here in your browser:

Click the button to get your position:

Try It

It also illustrates the use of the error callback from the previous section. The Google Map API is used to get an image centered at the longitude and latitude collected with the HTML5 Geolocation API.

Source code extract:

```
<!DOCTYPE html>
<html>
<body>
<p id="demo">Click the button to get your position:</p>
<button onclick="getLocation()">Try It</button>
<div id="mapholder"></div>
<script>
var x=document.getElementById("demo");
```

```

10. function getLocation() {
    if (navigator.geolocation) {
        navigator.geolocation.getCurrentPosition(showPosition,showError);
    } else{
        x.innerHTML="Geolocation is not supported by this browser.";
    }
}

19. function showPosition(position) {
    // Google map API needs the latitude and longitude separated by a comma
    varlatlon=position.coords.latitude+","+position.coords.longitude;
    // Google map API URL that returns an image centered on the longitude and
    latitude
    varimg_url="http://maps.googleapis.com/maps/api/staticmap?center="
        +latlon+"&zoom=14&size=400x300&sensor=false";
    document.getElementById("mapholder").innerHTML="<img src='"+img_url+"'
/>";
}

    function showError(error) {
        ...
    }
</script>
</body>
35. </html>

```


The magic occurs at line 23, where we use [the Google Static Map API](#).

EXAMPLE 2 (A BIT MORE COMPLICATED...) THAT SHOWS HOW TO DISPLAY AN INTERACTIVE GOOGLE MAP CENTERED ON THE CURRENT POSITION

This example is just given as is, as there are so many possibilities for rendering a map with [the Google Map API](#). However, we think having such a basic example might be useful.

[Online example at JS Bin](#)

Got position :
Latitude : 43.63989420000001
Longitude: 7.0606103
Altitude : null



Source code of the example:

```
<!doctype html>
<html>
<head>
</head>
<body>
<!-- for position display -->
<div id="myposition"></div>

<!-- for gmap display -->
10. <div id="map" style="width:640px;height:480px"></div>

<!-- get gmap API -->
<script src="http://maps.google.com/maps/api/js?sensor=false"></script>
```

```

<script>
// Default position
var centerpos = newgoogle.maps.LatLng(48.579400,7.7519);

// default options for the google map
20. var optionsGmaps = {
    center:centerpos,

    navigationControlOptions: {style:google.maps.NavigationControlStyle.SMALL},
    mapTypeId: google.maps.MapTypeId.ROADMAP,
    zoom: 15
};

// Init map object
var map = newgoogle.maps.Map(document.getElementById("map"),optionsGmaps);

30. if(navigator.geolocation) {

    // callback function, called by getCurrentPosition() in case of success
    function drawPosition(position) {
        var infopos = "Got position : <br>";
        infopos += "Latitude : "+position.coords.latitude+"<br>";
        infopos += "Longitude : "+position.coords.longitude+"<br>";
        infopos += "Altitude : "+position.coords.altitude+"<br>";
        document.getElementById("myposition").innerHTML= infopos;

39.

        // Make new object LatLng for Google Maps
        var latlng = newgoogle.maps.LatLng(position.coords.latitude,
            position.coords.longitude);

        // Add a marker at position
        var marker = new google.maps.Marker({
            position: latlng,
            map: map,
            title:"You are here"
        });

50.

        // center map on longitude and latitude
        map.panTo(latlng);
    }
}

```

```
// callback function, called by getCurrentPosition() in case of error
function errorPosition(error) {
    ...
}
navigator.geolocation.getCurrentPosition(drawPosition,errorPosition);
} else {
    alert("Geolocation API not supported by your browser");
}
</script>
64. </body>
</html>
```

EXAMPLE 3 (ADVANCED) SHOWS HOW TO GET A SURFACE ADDRESS FROM THE LONGITUDE AND LATITUDE

This is another example that gets the surface address from longitude and latitude. It uses [the Google Reverse Geocoding JavaScript API](#). For those of you really interested to know how this API works, please read the Google documentation and tutorials.


Without going into detail, the below example might be useful to copy/paste/adapt for trying to pre-fill a form where one is asked for an address. Geolocation is useful for guessing the country, city, zip code, street, etc. Some examples that use this feature will be given in the next section of the course.

[Online example at JS Bin.](#)

Latitude: 43.639129399999995

Longitude: 7.0606103

Adress: 117 Impasse des Mésanges, 06410 Biot, France



Source code of the example:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <scriptsrc="https://maps.googleapis.com/maps/api/js?
v=3.exp&sensor=false"></script>
    <script>
      // p elements for displaying lat / long and address
      var displayCoords, myAddress;
      // used with the google apis
10.   var geocoder;
      var map;
      var infowindow = new google.maps.InfoWindow();
      var marker;
      // Called when the page is loaded
      function init() {
        displayCoords=document.getElementById("msg");
        myAddress =document.getElementById("address");
20.   geocoder = new google.maps.Geocoder();
```

```
// In order to show something even before a user clicked on the button
```

```
var latlng = new google.maps.LatLng(34.0144,-6.83);
```

```
var mapOptions = {
```

```
  zoom: 8,
```

```
  center: latlng,
```

```
  mapTypeId: 'roadmap'
```

```
}
```

30.

```
map = new google.maps.Map(document.getElementById('map_canvas'),mapOptions);
```

```
} // end of init()
```

```
// Called when the button is clicked
```

```
function getLocation() {
```

```
  if (navigator.geolocation) {
```

```
    navigator.geolocation.getCurrentPosition(showPosition);
```

```
  } else {
```

```
    displayCoords.innerHTML="Geolocation API not supported by your  
browser.";
```

```
  }
```

40.

```
}
```

```
// Called when a position is available
```

```
function showPosition(position) {
```

```
  displayCoords.innerHTML="Latitude: " +position.coords.latitude +  
                           "<br />Longitude: " +position.coords.longitude;
```

```
// Display the map
```

```
showOnGoogleMap(new google.maps.LatLng(position.coords.latitude,  
                                         position.coords.longitude));
```

```
}
```

```
function showOnGoogleMap(latlng) {
```

```
  // Ask google geocoder for a surface address once we get a longitude and
```

```
  // a latitude. In fact the reverse geocoder sends back an array of "guesses"
```

```
  // i.e. not only one address object, but several. Each entry in this array
```

```
  // has several properties like street, city, etc. We use the "formatted_address"
```

```
  // one here, but it might be interesting to get the detailed properties in other
```

```
  // applications like a form with street, city, zip code etc.
```

58.

```
geocoder.geocode({'latlng':latlng},reverseGeocoderSuccess);
```

```
function reverseGeocoderSuccess(results, status) {
```

```
  if (status == google.maps.GeocoderStatus.OK) {
```

```
    if (results[1]) {
```

```
      map.setZoom(11);
```

```
      marker = new google.maps.Marker({
```

```

        position: latlng,
        map: map
    });
68.    infowindow.setContent(results[1].formatted_address);
    infowindow.open(map, marker);
    // Display address as text in the page
    myAddress.innerHTML="Adress: " +results[0].formatted_address;
    } else {
        alert('No surface address found');
    }
    } else {
77.    alert('Geocoder failed due to: ' + status);
    }
    } // end of reverseGeocoderSuccess
} // end of showOnGoogleMap
</script>
</head>
<body onload="init()">
<title>HTML5 + Geolocalisation + Google Maps API Reverse Geocoding</title>
<p id="msg">Click the button to get your coordinates:</p>
87. <p id="address"></p>
    <button onclick="getLocation()">Where am I ?</button>
    <div id="map_canvas" style="width: 500px; height:300px"></div>
</body>
</html>

```