

# Measuring time between frames to achieve a constant speed on screen, even when the frame rate changes

## METHOD 1 - USING THE JAVASCRIPT DATE OBJECT

Now, we just modify the example from the previous lesson by adding a *time-based animation*. Here we use the "standard JavaScript" way for measuring time, using the Date JavaScript object:

```
var time = new Date().getTime();
```

The `getTime()` method returns the number of milliseconds elapsed between midnight of January 1, 1970, and now. This is the number of milliseconds elapsed since the Unix epoch (!).

There is a variant, as we could have called:

```
var time = Date.now();
```

So, if we measure the time at the beginning of each animation loop, and store it, we can then compute the delta of the time elapsed between two consecutive loops.

We then apply some simple maths to compute the number of pixels we need to move the shape to achieve a given speed (in pixels/s).

### First example that uses time based animation: the bouncing square

[Online example at JSBin:](#)



**This example uses time based animation. Try it on a low end smartphone that can't animate at 60 frames per second**

Source code from the example:

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset=utf-8 />
  <title>Move rectangle using time based animation</title>
  <script>
    var canvas, ctx;
    var width, height;
    var x, y, incX; // incX is the distance from the previously
drawn
                                // rectangle to the new one
11.    var speedX; // speedX is the target speed of the rectangle, in
pixels/s
        // for time based animation
        var now, delta;
        var then = new Date().getTime();
        // Called after the DOM is ready (page loaded)
        function init() {
            // Init the different variables
            canvas = document.querySelector("#mycanvas");
21.    ctx = canvas.getContext('2d');
            width = canvas.width;
            height = canvas.height;
            x=10; y = 10;
            // Target speed in pixels/second, try with high values,
1000, 2000...
            speedX = 200;
            // Start animation
            animationLoop();
31.    }
        function animationLoop() {
            // Measure time
            now = new Date().getTime();

            // How long between the current frame and the previous one?
            delta = now - then;
            //console.log(delta);
            // Compute the displacement in x (in pixels) in function of
the time elapsed and
41.    // in function of the wanted speed
            incX = calcDistanceToMove(delta, speedX);
            // an animation involves: 1) clear canvas and 2) draw shapes,
            // 3) move shapes, 4) recall the loop with
requestAnimationFrame

```

```

    // clear canvas
    ctx.clearRect(0, 0, width, height);
    ctx.strokeRect(x, y, 10, 10);
51.
    // move rectangle
    x += incX;
    // check collision on left or right
    if ((x+10 >= width) || (x <= 0)) {
        // cancel move + inverse speed
        x -= incX;
        speedX = -speedX;
    }
61.
    // Store time
    then = now;
    requestAnimationFrame(animationLoop);
}
// We want the rectangle to move at a speed given in
pixels/second
// (there are 60 frames in a second)
72. // If we are really running at 60 frames/s, the delay between
73. // frames should be 1/60
    // = 16.66 ms, so the number of pixels to move = (speed *
    del)/1000.
    // If the delay is twice as
    // long, the formula works: let's move the rectangle for twice as
    long!
    var calcDistanceToMove = function(delta, speed) {
        return (speed * delta) / 1000;
    }
</script>
</head>
84. <body onload="init();">
    <canvas id="mycanvas" width="200" height="50" style="border: 2px solid
    black"></canvas>
</body>
</html>

```

In this example, we just added a few lines of code for measuring the time and computing the time elapsed between two consecutive frames (see *line 38*).

Normally, `requestAnimationFrame(callback)` tries to call the callback function every 16.66 ms (this corresponds to 60 frames/s)... *but this is never exactly the case*. If you do a `console.log(delta)` in the animation loop, you will see that even on a very powerful computer,

the delta is "very close" to 16.6666 ms, but 99% of the time it will be slightly different.

The function `calcDistanceToMove(delta, speed)` takes two parameters: 1) the time elapsed in ms, and 2) the target speed in pixels/s.

Try this example on a smartphone, use this link: <http://jsbin.com/jeribi> to run the JSBin example in stand alone mode. Normally you should see no difference in speed, but it may look a bit jerky on a low end smartphone or on a slow computer. This is the correct behavior.

Or you can try the next example that fakes a complex animation loop that could take a long time to draw a frame...

## A fake example that spends a lot of time in the animation loop, compare with the previous example

Try it on JsBin:

We added a long loop in the middle of the animation loop. This time the animation should be very jerky, however, notice that the apparent speed of the square is the same as in the previous example: the animation adapts itself!

```
function animationLoop() {  
  // Measure time  
  now = new Date().getTime();  
  
  // How long between the current frame and the previous one ?  
  delta = now - then;  
  //console.log(delta);  
  // Compute the displacement in x (in pixels) in function of the  
  time elapsed and  
  // in function of the wanted speed  
10.  incX = calcDistanceToMove(delta, speedX);  
  // an animation is : 1) clear canvas and 2) draw shapes,  
  // 3) move shapes, 4) recall the loop with requestAnimationFrame  
  // clear canvas  
  ctx.clearRect(0, 0, width, height);  
  for(var i = 0; i < 50000000; i++) {  
    // just to slow down the animation  
20.  }  
  ctx.strokeRect(x, y, 10, 10);  
  // move rectangle  
  x += incX;
```

```

    // check collision on left or right
    if((x+10 >= width) || (x <= 0)) {
        // cancel move + inverse speed
30.    x -= incX;
        speedX = -speedX;
    }
    // Store time
    then = now;
    requestAnimationFrame(animationLoop);
}

```

## METHOD 2 - USING THE NEW HTML5 HIGH RESOLUTION TIMER

Since the beginning of HTML5, game developers, musicians, and others have asked for a sub-millisecond timer in order to avoid some glitches that may occur with the regular JavaScript timer. This API is called the "[high resolution time API](#)".

This API is very simple to use - just do:

```
var time = performance.now();
```

... to get a sub-millisecond time. It is similar to `Date.now()` except that the accuracy is much higher and that the result is not exactly the same. The value returned is a floating point number, not an integer value!

From [this article that explains the high resolution time API](#): "*The only method exposed is `now()`, which returns a `DOMHighResTimeStamp` representing the current time in milliseconds. The timestamp is very accurate, with precision to a thousandth of a millisecond. Please note that while `Date.now()` returns the number of milliseconds elapsed since 1 January 1970 00:00:00 UTC, `performance.now()` returns the number of milliseconds, with microseconds in the fractional part, from `performance.timing.navigationStart()`, the start of navigation of the document, to the `performance.now()` call. Another important difference between `Date.now()` and `performance.now()` is that the latter is monotonically increasing, so the difference between two calls will never be negative.*"

To sum up:

- `performance.now()` returns the time since the load of the document (it is called a `DOMHighResTimeStamp`), with a sub ms accuracy, as a floating point value, with very high accuracy.

- `Date.now()` returns the number of ms since the Unix epoch, as an integer value.

Support for this API is good as of November 2015 (check an [up to date version](#)) :

High Resolution Time API 📄 - REC

Global 80.55%  
unprefixed: 80.43%

Method to provide the current time in sub-millisecond resolution and such that it is not subject to system clock skew or adjustments. Called using `performance.now()`

Current aligned Usage relative Show all

IE	Edge	Firefox	Chrome	Safari	Opera	iOS Safari	Opera Mini	Android Browser	Chrome for Android
			31					4.1	
8		38	43					4.3	
9		39	44					4.4	
10		40	45	8		8.4		4.4.4	
11	12	41	46	9	32	9	8	44	46
	13	42	47		33				
		43	48		34				
		44	49						

Here is a version on JSBin of the previous example with the bouncing rectangle, that uses the high resolution timer.

Source code of the example:

```

...
<script>
...
var speedX; // speedX is the target speed of the rectangle in
pixels/s
// for time based animation
var now, delta;
// High resolution timer
var then = performance.now();
10. // Called after the DOM is ready (page loaded)
function init() {
...
}
function animationLoop() {
// Measure time, with high resolution timer

```

```

    now = performance.now();

20.    // How long between the current frame and the previous one?
    delta = now - then;
    //console.log(delta);
    // Compute the displacement in x (in pixels) in function
    // of the time elapsed and
    // in function of the wanted speed
    incX = calcDistanceToMove(delta, speedX);
    //console.log("dist = " + incX);
    // an animation involves: 1) clear canvas and 2) draw shapes,
    // 3) move shapes, 4) recall the loop with
    requestAnimationFrame
31.    // clear canvas
    ctx.clearRect(0, 0, width, height);
    ctx.strokeRect(x, y, 10, 10);
    // move rectangle
    x += incX;
    // check collision on left or right
    if((x+10 >= width) || (x <= 0)) {
41.    // cancel move + inverse speed
        x -= incX;
        speedX = -speedX;
    }
    // Store time
    then = now;
    // call the animation loop again
50.    requestAnimationFrame(animationLoop);
}
...
</script>

```

Only two lines have changed but the accuracy is much higher, if you try to uncomment the `console.log(...)` calls in the main loop. You will see the difference.

### METHOD 3 - USING THE OPTIONAL TIMESTAMP PARAMETER OF THE CALLBACK FUNCTION OF `REQUESTANIMATIONFRAME`

**This is the recommended method!**

There is an optional parameter that is passed to the callback function called

by `requestAnimationFrame`: a timestamp!

The [requestAnimationFrame API specification](#) says that this timestamp corresponds to the time elapsed since the page has been loaded.

It is similar to the value sent by the high resolution timer using `performance.now()`.

Here is a running example of the animated rectangle, that uses this timestamp parameter.

[Online example at JSBin](#):

Source code of the example:

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset=utf-8 />
<title>Time based animation using the parameter of the
requestAnimationFrame callback</title>
<script>
    var canvas, ctx;
    var width, height;
    var x, y, incX; // incX is the distance from the previously drawn
rectangle
                                // to the new one
11.    var speedX; // speedX is the target speed of the rectangle in
pixels/s
    // for time based animation
    var now, delta=0;
    // High resolution timer
    var oldTime = 0;
    // Called after the DOM is ready (page loaded)
    function init() {
        // init the different variables
21.    canvas = document.querySelector("#mycanvas");
        ctx = canvas.getContext('2d');
        width = canvas.width;
        height = canvas.height;
        x=10; y = 10;
        // Target speed in pixels/second, try with high values, 1000,
2000...
        speedX = 200;
```



```

    // Start animation
31.   requestAnimationFrame(animationLoop);
    }
    function animationLoop(currentTime) {
        // How long between the current frame and the previous one?
        delta = currentTime - oldTime;
        // Compute the displacement in x (in pixels) in function of the
time elapsed and
39.   // in function of the wanted speed
        incX = calcDistanceToMove(delta, speedX);
        // clear canvas
        ctx.clearRect(0, 0, width, height);
        ctx.strokeRect(x, y, 10, 10);
46.
        // move rectangle
        x += incX;
        // check collision on left or right
        if(((x+10) > width) || (x < 0)) {
            // inverse speed
            x -= incX;
            speedX = -speedX;
        }
56.
        // Store time
        oldTime = currentTime;
        // asks for next frame
        requestAnimationFrame(animationLoop);
    }
    var calcDistanceToMove = function(delta, speed) {
        return (speed * delta) / 1000;
    }
</script>
</head>
<body onload="init();">
    <canvas id="mycanvas" width="200" height="50" style="border: 2px solid
black"></canvas>
</body>
</html>

```