

```
1: // $Id: listmap.h,v 1.17 2019-10-25 14:56:22-07 - - $
2:
3: #ifndef __LISTMAP_H__
4: #define __LISTMAP_H__
5:
6: #include "xless.h"
7: #include "xpair.h"
8:
9: template <typename key_t, typename mapped_t, class less_t=xless<key_t>>
10: class listmap {
11:     public:
12:         using key_type = key_t;
13:         using mapped_type = mapped_t;
14:         using value_type = xpair<const key_type, mapped_type>;
15:     private:
16:         less_t less;
17:         struct node;
18:         struct link {
19:             node* next{};
20:             node* prev{};
21:             link (node* next_, node* prev_): next(next_), prev(prev_){}
22:         };
23:         struct node: link {
24:             value_type value{};
25:             node (node* next, node* prev, const value_type&);
26:         };
27:         node* anchor() { return static_cast<node*> (&anchor_); }
28:         link anchor_ {anchor(), anchor()};
29:     public:
30:         class iterator;
31:         listmap(){};
32:         listmap (const listmap&);
33:         listmap& operator= (const listmap&);
34:         ~listmap();
35:         iterator insert (const value_type&);
36:         iterator find (const key_type&);
37:         iterator erase (iterator position);
38:         iterator begin() { return anchor()->next; }
39:         iterator end() { return anchor(); }
40:         bool empty() const { return anchor_->next == anchor_; }
41: };
42:
```

```
43:
44: template <typename key_t, typename mapped_t, class less_t>
45: class listmap<key_t,mapped_t,less_t>::iterator {
46:     private:
47:         friend class listmap<key_t,mapped_t,less_t>;
48:         listmap<key_t,mapped_t,less_t>::node* where {nullptr};
49:         iterator (node* where_): where(where_){};
50:     public:
51:         iterator(){}
52:         value_type& operator*();
53:         value_type* operator->();
54:         iterator& operator++(); //++itor
55:         iterator& operator--(); //--itor
56:         void erase();
57:         bool operator== (const iterator&) const;
58:         bool operator!= (const iterator&) const;
59: };
60:
61: #include "listmap.tcc"
62: #endif
63:
```

```
1: // $Id: listmap.tcc,v 1.13 2019-10-22 12:41:48-07 - - $
2:
3: #include "listmap.h"
4: #include "debug.h"
5:
6: //
7: //////////////////////////////////////
8: // Operations on listmap::node.
9: //////////////////////////////////////
10: //
11:
12: //
13: // listmap::node::node (link*, link*, const value_type&)
14: //
15: template <typename key_t, typename mapped_t, class less_t>
16: listmap<key_t,mapped_t,less_t>::node (node* next, node* prev,
17:                                     const value_type& value_):
18:     link (next, prev), value (value_) {
19: }
20:
21: //
22: //////////////////////////////////////
23: // Operations on listmap.
24: //////////////////////////////////////
25: //
26:
27: //
28: // listmap::~~listmap()
29: //
30: template <typename key_t, typename mapped_t, class less_t>
31: listmap<key_t,mapped_t,less_t>::~~listmap() {
32:     DEBUGF ('l', reinterpret_cast<const void*> (this));
33: }
34:
```

```
35:
36: //
37: // iterator listmap::insert (const value_type&)
38: //
39: template <typename key_t, typename mapped_t, class less_t>
40: typename listmap<key_t,mapped_t,less_t>::iterator
41: listmap<key_t,mapped_t,less_t>::insert (const value_type& pair) {
42:     DEBUGF ('l', &pair << "->" << pair);
43:     return iterator();
44: }
45:
46: //
47: // listmap::find(const key_type&)
48: //
49: template <typename key_t, typename mapped_t, class less_t>
50: typename listmap<key_t,mapped_t,less_t>::iterator
51: listmap<key_t,mapped_t,less_t>::find (const key_type& that) {
52:     DEBUGF ('l', that);
53:     return iterator();
54: }
55:
56: //
57: // iterator listmap::erase (iterator position)
58: //
59: template <typename key_t, typename mapped_t, class less_t>
60: typename listmap<key_t,mapped_t,less_t>::iterator
61: listmap<key_t,mapped_t,less_t>::erase (iterator position) {
62:     DEBUGF ('l', &*position);
63:     return iterator();
64: }
65:
```

```
66:
67: //
68: ///////////////////////////////////////////////////////////////////
69: // Operations on listmap::iterator.
70: ///////////////////////////////////////////////////////////////////
71: //
72:
73: //
74: // listmap::value_type& listmap::iterator::operator*()
75: //
76: template <typename key_t, typename mapped_t, class less_t>
77: typename listmap<key_t,mapped_t,less_t>::value_type&
78: listmap<key_t,mapped_t,less_t>::iterator::operator*() {
79:     DEBUGF ('l', where);
80:     return where->value;
81: }
82:
83: //
84: // listmap::value_type* listmap::iterator::operator->()
85: //
86: template <typename key_t, typename mapped_t, class less_t>
87: typename listmap<key_t,mapped_t,less_t>::value_type*
88: listmap<key_t,mapped_t,less_t>::iterator::operator->() {
89:     DEBUGF ('l', where);
90:     return &(where->value);
91: }
92:
93: //
94: // listmap::iterator& listmap::iterator::operator++()
95: //
96: template <typename key_t, typename mapped_t, class less_t>
97: typename listmap<key_t,mapped_t,less_t>::iterator&
98: listmap<key_t,mapped_t,less_t>::iterator::operator++() {
99:     DEBUGF ('l', where);
100:     where = where->next;
101:     return *this;
102: }
103:
104: //
105: // listmap::iterator& listmap::iterator::operator--()
106: //
107: template <typename key_t, typename mapped_t, class less_t>
108: typename listmap<key_t,mapped_t,less_t>::iterator&
109: listmap<key_t,mapped_t,less_t>::iterator::operator--() {
110:     DEBUGF ('l', where);
111:     where = where->prev;
112:     return *this;
113: }
114:
```

```
115:
116: //
117: // bool listmap::iterator::operator== (const iterator&)
118: //
119: template <typename key_t, typename mapped_t, class less_t>
120: inline bool listmap<key_t,mapped_t,less_t>::iterator::operator==
121:         (const iterator& that) const {
122:     return this->where == that.where;
123: }
124:
125: //
126: // bool listmap::iterator::operator!= (const iterator&)
127: //
128: template <typename key_t, typename mapped_t, class less_t>
129: inline bool listmap<key_t,mapped_t,less_t>::iterator::operator!=
130:         (const iterator& that) const {
131:     return this->where != that.where;
132: }
133:
```

```
1: // $Id: xless.h,v 1.3 2014-04-24 18:02:55-07 - - $
2:
3: #ifndef __XLESS_H__
4: #define __XLESS_H__
5:
6: //
7: // We assume that the type type_t has an operator< function.
8: //
9:
10: template <typename Type>
11: struct xless {
12:     bool operator() (const Type& left, const Type& right) const {
13:         return left < right;
14:     }
15: };
16:
17: #endif
18:
```

```
1: // $Id: xpair.h,v 1.5 2019-02-21 17:27:16-08 - - $
2:
3: #ifndef __XPAIR_H__
4: #define __XPAIR_H__
5:
6: #include <iostream>
7:
8: using namespace std;
9:
10: //
11: // Class xpair works like pair(c++).
12: //
13: // The implicitly generated members will work, because they just
14: // send messages to the first and second fields, respectively.
15: // Caution: xpair() does not initialize its fields unless
16: // first_t and second_t do so with their default ctors.
17: //
18:
19: template <typename first_t, typename second_t>
20: struct xpair {
21:     first_t first{};
22:     second_t second{};
23:     xpair() {}
24:     xpair (const first_t& first_, const second_t& second_):
25:         first(first_), second(second_) {}
26: };
27:
28: template <typename first_t, typename second_t>
29: ostream& operator<< (ostream& out,
30:                     const xpair<first_t,second_t>& pair) {
31:     out << "{" << pair.first << "," << pair.second << "}";
32:     return out;
33: }
34:
35: #endif
36:
```



```
1: // $Id: debug.h,v 1.2 2019-10-22 12:41:48-07 - - $
2:
3: #ifndef __DEBUG_H__
4: #define __DEBUG_H__
5:
6: #include <bitset>
7: #include <climits>
8: #include <string>
9: using namespace std;
10:
11: // debug -
12: //     static class for maintaining global debug flags.
13: // setflags -
14: //     Takes a string argument, and sets a flag for each char in the
15: //     string. As a special case, '@', sets all flags.
16: // getflag -
17: //     Used by the DEBUGF macro to check to see if a flag has been set.
18: //     Not to be called by user code.
19:
20: class debugflags {
21:     private:
22:         using flagset = bitset<UCHAR_MAX + 1>;
23:         static flagset flags;
24:     public:
25:         static void setflags (const string& optflags);
26:         static bool getflag (char flag);
27:         static void where (char flag, const char* file, int line,
28:                             const char* pretty_function);
29: };
30:
```

```
31:
32: // DEBUGF -
33: //     Macro which expands into debug code.  First argument is a
34: //     debug flag char, second argument is output code that can
35: //     be sandwiched between <<.  Beware of operator precedence.
36: //     Example:
37: //         DEBUGF ('u', "foo = " << foo);
38: //     will print two words and a newline if flag 'u' is on.
39: //     Traces are preceded by filename, line number, and function.
40:
41: #ifdef NDEBUG
42: #define DEBUGF(FLAG, CODE) ;
43: #define DEBUGS(FLAG, STMT) ;
44: #else
45: #define DEBUGF(FLAG, CODE) { \
46:     if (debugflags::getflag (FLAG)) { \
47:         debugflags::where (FLAG, __FILE__, __LINE__, \
48:             __PRETTY_FUNCTION__); \
49:         cerr << CODE << endl; \
50:     } \
51: }
52: #define DEBUGS(FLAG, STMT) { \
53:     if (debugflags::getflag (FLAG)) { \
54:         debugflags::where (FLAG, __FILE__, __LINE__, \
55:             __PRETTY_FUNCTION__); \
56:         STMT; \
57:     } \
58: }
59: #endif
60:
61: #endif
62:
```

```
1: // $Id: debug.cpp,v 1.3 2019-10-22 12:41:48-07 - - $
2:
3: #include <climits>
4: #include <iostream>
5: using namespace std;
6:
7: #include "debug.h"
8: #include "util.h"
9:
10: debugflags::flagset debugflags::flags {};
11:
12: void debugflags::setflags (const string& initflags) {
13:     for (const unsigned char flag: initflags) {
14:         if (flag == '@') flags.set();
15:         else flags.set (flag, true);
16:     }
17: }
18:
19: // getflag -
20: //     Check to see if a certain flag is on.
21:
22: bool debugflags::getflag (char flag) {
23:     // WARNING: Don't TRACE this function or the stack will blow up.
24:     return flags.test (static_cast<unsigned char> (flag));
25: }
26:
27: void debugflags::where (char flag, const char* file, int line,
28:                        const char* pretty_function) {
29:     cout << sys_info::execname() << ": DEBUG(" << flag << ") "
30:          << file << "[" << line << "]" " << endl
31:          << "    " << pretty_function << endl;
32: }
33:
```

```
1: // $Id: util.h,v 1.6 2018-01-25 14:18:43-08 - - $
2:
3: //
4: // util -
5: //     A utility class to provide various services not conveniently
6: //     associated with other modules.
7: //
8:
9: #ifndef __UTIL_H__
10: #define __UTIL_H__
11:
12: #include <iostream>
13: #include <list>
14: #include <stdexcept>
15: #include <string>
16: using namespace std;
17:
18: //
19: // sys_info -
20: //     Keep track of execname and exit status.  Must be initialized
21: //     as the first thing done inside main.  Main should call:
22: //         sys_info::set_execname (argv[0]);
23: //     before anything else.
24: //
25:
26: class sys_info {
27:     private:
28:         static string execname_;
29:         static int exit_status_;
30:         static void execname (const string& argv0);
31:         friend int main (int argc, char** argv);
32:     public:
33:         static const string& execname ();
34:         static void exit_status (int status);
35:         static int exit_status ();
36: };
37:
38: //
39: // datestring -
40: //     Return the current date, as printed by date(1).
41: //
42:
43: const string datestring ();
44:
45: //
46: // split -
47: //     Split a string into a list<string>..  Any sequence
48: //     of chars in the delimiter string is used as a separator.  To
49: //     Split a pathname, use "/".  To split a shell command, use " ".
50: //
51:
52: list<string> split (const string& line, const string& delimiter);
53:
```

```
54:
55: //
56: // complain -
57: //     Used for starting error messages.  Sets the exit status to
58: //     EXIT_FAILURE, writes the program name to cerr, and then
59: //     returns the cerr ostream.  Example:
60: //         complain() << filename << ": some problem" << endl;
61: //
62:
63: ostream& complain();
64:
65: //
66: // syscall_error -
67: //     Complain about a failed system call.  Argument is the name
68: //     of the object causing trouble.  The extern errno must contain
69: //     the reason for the problem.
70: //
71:
72: void syscall_error (const string&);
73:
74: //
75: // operator<< (list) -
76: //     An overloaded template operator which allows lists to be
77: //     printed out as a single operator, each element separated from
78: //     the next with spaces.  The item_t must have an output operator
79: //     defined for it.
80: //
81:
82: template <typename item_t>
83: ostream& operator<< (ostream& out, const list<item_t>& vec);
84:
85: //
86: // string to_string (thing) -
87: //     Convert anything into a string if it has an ostream<< operator.
88: //
89:
90: template <typename item_t>
91: string to_string (const item_t&);
92:
93: //
94: // thing from_string (const string&) -
95: //     Scan a string for something if it has an istream>> operator.
96: //
97:
98: template <typename item_t>
99: item_t from_string (const string&);
100:
101: //
102: // Put the RCS Id string in the object file.
103: //
104:
105: #include "util.tcc"
106: #endif
107:
```

```
1: // $Id: util.tcc,v 1.3 2014-06-27 17:49:07-07 - - $
2:
3: #include <sstream>
4: #include <typeinfo>
5: using namespace std;
6:
7: template <typename item_t>
8: ostream& operator<< (ostream& out, const list<item_t>& vec) {
9:     bool want_space = false;
10:    for (const auto& item: vec) {
11:        if (want_space) cout << " ";
12:        cout << item;
13:        want_space = true;
14:    }
15:    return out;
16: }
17:
18: template <typename Type>
19: string to_string (const Type& that) {
20:     ostringstream stream;
21:     stream << that;
22:     return stream.str();
23: }
24:
25: template <typename Type>
26: Type from_string (const string& that) {
27:     stringstream stream;
28:     stream << that;
29:     Type result;
30:     if (not (stream >> result and stream.eof())) {
31:         throw domain_error (string (typeid (Type).name())
32:                               + " from_string (" + that + ")");
33:     }
34:     return result;
35: }
36:
```

```
1: // $Id: util.cpp,v 1.14 2018-01-25 14:18:43-08 - - $
2:
3: #include <cerrno>
4: #include <cstdlib>
5: #include <cstring>
6: #include <ctime>
7: #include <stdexcept>
8: #include <string>
9: using namespace std;
10:
11: #include "debug.h"
12: #include "util.h"
13:
14: int sys_info::exit_status_ = EXIT_SUCCESS;
15: string sys_info::execname_; // Must be initialized from main().
16:
17: void sys_info_error (const string& condition) {
18:     throw logic_error ("main() has " + condition
19:         + " called sys_info::execname()");
20: }
21:
22: void sys_info::execname (const string& argv0) {
23:     if (execname_ != "") sys_info_error ("already");
24:     int slashpos = argv0.find_last_of ('/') + 1;
25:     execname_ = argv0.substr (slashpos);
26:     cout << boolalpha;
27:     cerr << boolalpha;
28:     DEBUGF ('u', "execname_ = " << execname_);
29: }
30:
31: const string& sys_info::execname () {
32:     if (execname_ == "") sys_info_error ("not yet");
33:     return execname_;
34: }
35:
36: void sys_info::exit_status (int status) {
37:     if (execname_ == "") sys_info_error ("not yet");
38:     exit_status_ = status;
39: }
40:
41: int sys_info::exit_status () {
42:     if (execname_ == "") sys_info_error ("not yet");
43:     return exit_status_;
44: }
45:
46: const string datestring () {
47:     time_t clock = time (nullptr);
48:     struct tm *tm_ptr = localtime (&clock);
49:     char timebuf[256];
50:     strftime (timebuf, sizeof timebuf,
51:         "%a %b %e %H:%M:%S %Z %Y", tm_ptr);
52:     return timebuf;
53: }
54:
```

```
55:
56: list<string> split (const string& line, const string& delimiters) {
57:     list<string> words;
58:     size_t end = 0;
59:     // Loop over the string, splitting out words, and for each word
60:     // thus found, append it to the output list<string>.
61:     for (;;) {
62:         size_t start = line.find_first_not_of (delimiters, end);
63:         if (start == string::npos) break;
64:         end = line.find_first_of (delimiters, start);
65:         words.push_back (line.substr (start, end - start));
66:     }
67:     DEBUGF ('u', words);
68:     return words;
69: }
70:
71: ostream& complain() {
72:     sys_info::exit_status (EXIT_FAILURE);
73:     cerr << sys_info::execname () << ": ";
74:     return cerr;
75: }
76:
77: void syscall_error (const string& object) {
78:     complain() << object << ": " << strerror (errno) << endl;
79: }
80:
```



```
1: // $Id: main.cpp,v 1.11 2018-01-25 14:19:29-08 - - $
2:
3: #include <cstdlib>
4: #include <exception>
5: #include <iostream>
6: #include <string>
7: #include <unistd.h>
8:
9: using namespace std;
10:
11: #include "listmap.h"
12: #include "xpair.h"
13: #include "util.h"
14:
15: using str_str_map = listmap<string,string>;
16: using str_str_pair = str_str_map::value_type;
17:
18: void scan_options (int argc, char** argv) {
19:     opterr = 0;
20:     for (;;) {
21:         int option = getopt (argc, argv, "@:");
22:         if (option == EOF) break;
23:         switch (option) {
24:             case '@':
25:                 debugflags::setflags (optarg);
26:                 break;
27:             default:
28:                 complain() << "-" << char (optopt) << ": invalid option"
29:                     << endl;
30:                 break;
31:         }
32:     }
33: }
34:
35: int main (int argc, char** argv) {
36:     sys_info::execname (argv[0]);
37:     scan_options (argc, argv);
38:
39:     str_str_map test;
40:     for (char** argp = &argv[optind]; argp != &argv[argc]; ++argp) {
41:         str_str_pair pair (*argp, to_string<int> (argp - argv));
42:         cout << "Before insert: " << pair << endl;
43:         test.insert (pair);
44:     }
45:
46:     for (str_str_map::iterator itor = test.begin();
47:         itor != test.end(); ++itor) {
48:         cout << "During iteration: " << *itor << endl;
49:     }
50:
51:     str_str_map::iterator itor = test.begin();
52:     test.erase (itor);
53:
54:     cout << "EXIT_SUCCESS" << endl;
55:     return EXIT_SUCCESS;
56: }
57:
```

```
1: # $Id: Makefile,v 1.24 2019-10-22 12:41:48-07 - - $
2:
3: MKFILE      = Makefile
4: DEPPFILE    = ${MKFILE}.dep
5: NOINCL      = ci clean spotless
6: NEEDINCL    = ${filter ${NOINCL}, ${MAKECMDGOALS}}
7: GMAKE       = ${MAKE} --no-print-directory
8:
9: GPPWARN      = -Wall -Wextra -Wpedantic -Wshadow -Wold-style-cast
10: GPPOPTS     = ${GPPWARN} -fdiagnostics-color=never
11: COMPILECPP  = g++ -std=gnu++17 -g -O0 ${GPPOPTS}
12: MAKEDEPCPP  = g++ -std=gnu++17 -MM ${GPPOPTS}
13: UTILBIN     = /afs/cats.ucsc.edu/courses/cse111-wm/bin
14:
15: MODULES     = listmap xless xpair debug util main
16: CPPSOURCE   = ${wildcard ${MODULES:=.cpp}}
17: OBJECTS     = ${CPPSOURCE:.cpp=.o}
18: SOURCELIST  = ${foreach MOD, ${MODULES}, ${MOD}.h ${MOD}.tcc ${MOD}.cpp}
19: ALLSOURCE   = ${wildcard ${SOURCELIST}}
20: EXECBIN     = keyvalue
21: OTHERS      = ${MKFILE} ${DEPPFILE}
22: ALLSOURCES  = ${ALLSOURCE} ${OTHERS}
23: LISTING     = Listing.ps
24:
25: all : ${EXECBIN}
26:
27: ${EXECBIN} : ${OBJECTS}
28:             ${COMPILECPP} -o $@ ${OBJECTS}
29:
30: %.o : %.cpp
31:         - ${UTILBIN}/checksource $<
32:         - ${UTILBIN}/cpplint.py.perl $<
33:         ${COMPILECPP} -c $<
34:
35: ci : ${ALLSOURCES}
36:         ${UTILBIN}/cid + ${ALLSOURCES}
37:         - ${UTILBIN}/checksource ${ALLSOURCES}
38:
39: lis : ${ALLSOURCES}
40:         mkpspdf ${LISTING} ${ALLSOURCES}
41:
42: clean :
43:         - rm ${OBJECTS} ${DEPPFILE} core
44:
45: spotless : clean
46:         - rm ${EXECBIN} ${LISTING} ${LISTING:.ps=.pdf}
47:
48: dep : ${ALLCPPSRC}
49:         @ echo "# ${DEPPFILE} created `LC_TIME=C date`" >${DEPPFILE}
50:         ${MAKEDEPCPP} ${CPPSOURCE} >>${DEPPFILE}
51:
52: ${DEPPFILE} :
53:         @ touch ${DEPPFILE}
54:         ${GMAKE} dep
55:
56: again :
57:         ${GMAKE} spotless dep ci all lis
58:
```

10/25/19
14:56:27

\$cse111-wm/Assignments/asg3-listmap-templates/code
Makefile

2/2

```
59: ifeq (${NEEDINCL}, )  
60: include ${DEPFILE}  
61: endif  
62:
```

```
1: # Makefile.dep created Fri Oct 25 14:56:27 PDT 2019
2: debug.o: debug.cpp debug.h util.h util.tcc
3: util.o: util.cpp debug.h util.h util.tcc
4: main.o: main.cpp listmap.h xless.h xpair.h listmap.tcc debug.h util.h \
5:  util.tcc
```