


Agile Software Development Practices

SOF2412 / COMP9412

System Build Automation

Dr. Basem Suleiman

School of Information Technologies



Agenda

- Software Configuration Management

- 1 – System Building

- 2 – Agile System Build


- Software Build Automation Tools

- 1 – Ant

- 2 – Maven


- 3 – Gradle

Software Configuration Management





Revisit – Software Development Process Model

- Rational Unified Process (RUP) iterative and incremental approach to develop OO software systems



Agile Development – Increments

- Software is incrementally developed




<https://blog.capterra.com/agile-vs-waterfall/>

Configuration Management (CM)

- Configuration management (CM) is concerned with the policies, processes and tools for managing changing software systems
- Track of what changes and component versions incorporated into each system version
- Essential for team projects to control changes made by different developers


Configuration Management Activities



Configuration Management Activities

- **System building:** assembling program components, data and libraries, then compiling these to create an executable system
- **Version management:** keeping track of the multiple versions of system components and ensuring that changes made to components by different developers do not interfere with each other
- **Change management:** keeping track of requests for changes to the software from customers and developers, working out the costs and impact of changes, and deciding the changes should be implemented
- **Release management:** preparing software for external release and keeping track of the system versions that have been released for customers

Multi-version System Development




Version Management (VM)


- Keep track of different versions of software components or configuration items and the systems in which these components are used
- Ensuring changes made by different developers to these versions do not interfere with each other
- The process of managing code-lines and baselines

Baselines


Codeline (A)



Codeline (B)




Codeline (C)




Libraries and external components



Baseline - V1



Baseline - V2



Version Management – Codelines and Baselines

- Version Management can be thought of as the process of managing codelines and baselines
- **Codeline:** a sequence of versions of source code with later versions in the sequence derived from earlier versions
 - System's components often have different versions
- **Baseline:** a definition of a specific system
 - Specifies the component versions that are included in the system plus a specification of the libraries used, configuration files, etc.

Baselines

- Baselines may be specified using a configuration language, which allows you to define what components are included in a version of a particular system.
- Baselines are important because you often have to recreate a specific version of a complete system
 - E.g., individual system versions for different customers. If a customer reports bugs in their system one can recreate the version delivered to a specific customer

Semantic Versioning (SemVer)

- Set of rules and requirements that determine how version numbers should be assigned and incremented for software being developed
 - Semantic numbers; numbers with meaning in relation to a certain version
- Why SemVer?
 - Helps managing versioning numbers in a meaningful and standard way
 - Managing dependencies: the bigger your system grows, the more packages/libraries/plugins you integrate into your software
- Given a version number **MAJOR.MINOR.PATCH**, increment the:
 1. **MAJOR** version when you make incompatible API changes,
 2. **MINOR** version when you add functionality in a backwards-compatible manner,
 3. **PATCH** version when you make backwards-compatible bug fixes.

<https://semver.org/>

Semantic Versioning – Example

Stage	Code	Rule	Example
New product	1 st release	Start with 1.0.0	1.0.0
Patch Release	<u>Bug fixes</u> , other <u>minor changes</u>	Increment the <u>3rd</u> digit	1.0. <u>1</u>
Minor Release	<u>New features</u> that do not break existing features	Increment the <u>2nd</u> digit	1. <u>1</u> .0
Major Release	<u>Changes that break backward compatibility</u>	Increment the <u>1st</u> digit	<u>2</u> .0.0

<https://docs.npmjs.com/getting-started/semantic-versioning>

More details on semantic versioning - <https://semver.org/>


SemVer Example – Dependencies

- “**Firetruck**” library requires a semantically versioned package “**Ladder**”
- **Firetruck** uses **Ladder** 3.1.0.
- Assume that Ladder3.1.9 is released, can you safely use it safely to release it in your system? ✓
- Assume that Ladder3.7.7 is released, can you safely use it safely to release it in your system? ✓
- Assume that Ladder4.1.0 is released, can you safely use it safely to release it in your system? ✗

Agile Development in CM

- Agile development, where components and systems are changed several times per day, is impossible without using CM tools
- The definitive versions of components are held in a shared project repository and developers copy these into their own workspace
- They make changes to the code then use system building tools to create a new system on their own computer for testing. Once they are happy with the changes made, they return the modified components to the project repository.

System Building




System Building


- System building is the process of creating a complete, executable system by compiling and linking the system components, external libraries, configuration files, etc.
- System building tools and version management tools must communicate as the build process involves checking out component versions from the repo managed by the version management system.
- The configuration description used to identify a baseline is also used by the system building tool

Software Build Automation Tools

Ant, Maven, Gradle



Tools for Agile Development



Build Tools – Apache Ant

- Java-based software build tool for automating build processes
 - Requires Java platform and best suited for building Java projects
- Does not impose coding conventions
- Does not impose any heavyweight dependency management framework
- XML to describe the code build process and its dependencies
 - Default *build.xml*



Apache ANT – Example

```
1 <?xml version="1.0"?>
2 <project name="Hello" default="compile">
3   <target name="clean" description="remove intermediate files">
4     <delete dir="classes"/>
5   </target>
6   <target name="clobber" depends="clean" description="remove all artifact files">
7     <delete file="hello.jar"/>
8   </target>
9   <target name="compile" description="compile the Java source code to class files">
10    <mkdir dir="classes"/>
11    <javac srcdir="." destdir="classes"/>
12  </target>
13  <target name="jar" depends="compile" description="create a Jar file for the application">
14    <jar destfile="hello.jar">
15      <fileset dir="classes" includes="**/*.class"/>
16      <manifest>
17        <attribute name="Main-Class" value="HelloProgram"/>
18      </manifest>
19    </jar>
20  </target>
21 </project>
```

XML

https://en.wikipedia.org/wiki/Apache_Ant

Apache ANT – Drawbacks

- Too flexible
- Complexity (XML-based build files)
 - Need to specify a lot of things to make simple builds
- No standard structure/layout
 - Developers can create their own structure/layout of the project

Apache Maven



- A build automation tool primarily for java projects
- XML-based description of the software being built
 - Dependencies on other external modules and components, the build order, directories, and required plug-ins
- Central repository (e.g., Maven 2)
- Coding by convention: it uses conventions over configuration for the build procedure
- Supported by Eclipse, IntelliJ, JBuilder, NetBeans IDEs
- Plugin-based architecture
 - Plugin for the .NET framework and native plugins for C/C++ are maintained

Apache Maven – Minimal Example


- Maven projects are configured using Project Object Model (POM) stored in a pom.xml file

XML
POM

```
1 <project>
2   <!-- model version is always 4.0.0 for Maven 2.x POMs -->
3   <modelVersion>4.0.0</modelVersion>
4
5   <!-- project coordinates, i.e. a group of values which
6       uniquely identify this project -->
7
8   <groupId>com.mycompany.app</groupId>
9   <artifactId>my-app</artifactId>
10  <version>1.0</version>
11
12  <!-- library dependencies -->
13
14  <dependencies>
15    <dependency>
16
17      <!-- coordinates of the required library -->
18
19      <groupId>junit</groupId>
20      <artifactId>junit</artifactId>
21      <version>3.8.1</version>
22
23      <!-- this dependency is only used for running and compiling tests -->
24
25      <scope>test</scope>
26
27    </dependency>
28  </dependencies>
29 </project>
```

Apache Maven – Project Structure

- The command *mvn package* will
 - compile all the Java files
 - run any tests
 - package the deliverable code and resources into target (e.g., target/my-app-1.0.jar)



The Maven software tool auto-generated this directory structure for a Java project

https://commons.wikimedia.org/wiki/File:Maven_CoC.svg#/media/File:Maven_CoC.svg

Apache Maven – Central Repository

- Maven uses default Central Repository that maintains required software
→ artefacts (libraries, plug-ins) to manage dependencies
- E.g., project that is dependent on the Hibernate library needs to specify that in the pom.xml project file
 - Maven checks if the referenced dependency is already in the user's local repository
 - It references the dependency from the local repository or
 - Dynamically download the dependency and the dependencies that Hibernate itself needs (transitive dependency) and store them in the user's local repository
- You can configure repositories other than the default (e.g., company-private repository)

Apache Maven – Drawbacks

- Again, XML-based files increase complexity (verbose)
- Rigid; developers are required to understand follow the conventions

Gradle

- **Build automation tool** that builds upon the concepts of Ant and Maven
 - build conventions, and redefine conventions
 - Project described using Groovy-based Domain Specific Language (DSL)
 - Tasks orders determined using a directed acyclic graph (DAC)
 - Multi-project builds
 - Incremental builds; up to date parts of the build tree do not need to be re-executed
 - Dependency handling (transitive dependency management)

Gradle – Groovy

- Gradle build files are Groovy scripts
- Groovy is a dynamic language of the JVM
 - Can be added as a plug-in
 - Allows developers to write general programming tasks in the build files
 - Relief developers from the lacking control flow in Ant or being forced into plug-in development in Maven to declare nonstandard tasks

→ relieve*

Gradle – DSL

- Gradle also presents a DSL tailored to the task of building code
 - Not general-purpose or programming language
 - Gradle DSL contains the language needed to describe how to build Java code and create a WAR file from the output
- Gradle DSL is extensible through plug-ins

Gradle – Extensible DSL

- Extensibility using plug-ins (if it doesn't have the language to describe what you want your build to do)
 - E.g., describe how to run database migration scripts or deploy code to a set of cloud-based QA servers
- Gradle plug-ins allow:
 - Adding new task definitions
 - Change the behavior of existing tasks
 - Add new objects
 - Create keywords to describe tasks that depart from the standard Gradle categories

Gradle Basics



Gradle – Tasks

- **Task:** a single atomic piece of work for a build
 - e.g., compiling classes
- **Project:** a composition of several tasks
 - e.g., Creation of a jar file
- Each task has a name, which can be used to refer to the task within its owning project, and a fully qualified path, which is unique across all tasks in all projects

Gradle – Task Actions

- A task is made up of sequence of **Action objects**

- *Action.execute(T)* to execute a task

- Add actions to a task

- *Task.doFirst()* or *Task.doLast()*

.doFirst, .doLast are actions of Task.

- Task action exceptions

- **StopActionException** to abort execution of the action

- **StopExecutionException** to abort execution of the task and continue to the next task

Gradle – Simplest Build File Example

Build.gradle

```
task helloWorld << {  
    println 'hello, world'  
}
```

Results of Hello World build file

\$ *gradle -q helloWorld*
hello, world

+ask
call

task
name

Build.gradle

```
task hello << {  
    print 'hello, '  
}  
task world(dependsOn: hello) << {  
    println 'world'  
}
```


execute the second task, world

\$ *gradle -q world*
hello, world

Gradle – Simplest Build File for Java Example (1)

```
1 |  
2 package org.gradle.example.simple;  
3  
4 public class HelloWorld {  
5     public static void main(String args[]) {  
6         System.out.println("hello, world");  
7     }  
8 }
```

```
build.gradle x  
1 apply plugin: 'java'
```



Project layout of HelloWorld.java

Simplest possible Gradle file for java

Gradle – Simplest Build File for Java Example (2)

gradle build


Gradle automatically introduces number of tasks for us to run

Note:

- Class files generated and place in a directory
- Test report files (for unit test results)
- JAR built using the project directory

Run HelloWorld Java

```
$ java -cp build/classes/main/  
org.gradle.example.simple.HelloWorld  
hello, world
```



Project Layout of Hello World Java After Build

Gradle – Build Lifecycle

- Phases of executing a build file in gradle:

1 – **Initialization:** projects are to participate in the build

2 – **Configuration:** task objects are assembled into an internal object model called Directed Acyclic Graph (DAG)

3 – **Execution:** build tasks are executed in the order required by their dependency relationship

Gradle – Task Configuration

- **Configuration block:** to setup variables and data structures needed by the task
action when it runs in the build
 - Make tasks rich object model populated with information about the build
 - Runs during gradle's configuration lifecycle when task actions executed
- **Closure:** a block of code specified by curly braces
 - Holding blocks of configuration and build actions

Gradle – Task Configuration Example

build.gradle

```
1 .....  
2 task initializeDatabase Task  
3 initializeDatabase << { println 'connect to database' }  
4 initializeDatabase << { println 'update database schema' }  
5 initializeDatabase { println 'configuring database connection' }
```

Task actions

Configuration block

Closure

Gradle – Tasks are Objects

- Every task is represented internally as an **object**
 - Task's methods and properties
 - Gradle creates an internal object model of the build before executing it
 - Each new task is of *DefaultTask* type - task type can be changed
 - *DefaultTask* contains functionality required for them to interface with Gradle project model

Gradle – Methods of Default Task

Method	Description
dependsOn(task)	Adds a task as a <u>dependency of the calling task</u> . A depended-on task will always run before the task that depends on it
doFirst(closure)	<u>Adds a block of executable code to the beginning of a task's action</u> . During the execution phase, the action block of every relevant task is executed.
doLast(closure)	<u>Appends behavior to the end of an action</u>
onlyIf(closure)	<u>Expresses a predicate which determines whether a task should be executed.</u> The value of the predicate is the value returned by the closure.

Gradle – dependsOn() Example

```
task loadTestData {  
    dependsOn createSchema  
}
```

```
// An alternate way to express the same dependency  
task loadTestData {  
    dependsOn << createSchema  
}
```

```
// Do the same using single quotes (which are usually optional)  
task loadTestData {  
    dependsOn 'createSchema'  
}
```

```
// Explicitly call the method on the task object  
task loadTestData  
loadTestData.dependsOn createSchema
```

```
// A shortcut for declaring dependencies  
task loadTestData(dependsOn: createSchema)
```

Different ways to call the *dependsOn* method

```
// Declare dependencies one at a time  
task loadTestData {  
    dependsOn << compileTestClasses  
    dependsOn << createSchema  
}
```

```
// Pass dependencies as a variable-length list  
task world {  
    dependsOn compileTestClasses, createSchema  
}
```

Gradle – doFirst() Example

```
task setupDatabaseTests << {  
    // This is the task's existing action  
    println 'load test data'  
}
```

```
setupDatabaseTests.doFirst {  
    println 'create schema'  
}
```

OR

```
task setupDatabaseTests << {  
    println 'load test data'  
}
```

```
setupDatabaseTests {  
    doFirst {  
        println 'create schema'  
    }  
}
```

Call the doFirst on the task object (top) and inside task's configuration block (bottom)

```
task setupDatabaseTests << {  
    println 'load test data'  
}  
  
setupDatabaseTests.doFirst {  
    println 'create database schema'  
}  
  
setupDatabaseTests.doFirst {  
    println 'drop database schema'  
}
```

Repeated calls to the doFirst method are additive.

Gradle – onlyIf() Example

```
task createSchema << {  
    println 'create database schema'  
}  
  
task loadTestData(dependsOn: createSchema) << {  
    println 'load test data'  
}  
  
loadTestData.onlyIf {  
    System.properties['load.data'] == 'true'  
}
```

- *onlyIf* method can be used to switch individual tasks on and off using any logic you can express in Groovy code
- E.g., read files, call web services, check security credentials

Using *onlyIf* method to do simple system property tests

Gradle – Default Task's Properties

Method	Description
didWork	A Boolean property indicating whether the task completed successfully
enabled	A Boolean property indicating whether the task will execute.
path	A string property containing the fully qualified path of a task (levels; DEBUG, INFO, LIFECYCLE, WARN, QUIET, ERROR)
logger	A reference to the internal Gradle logger object
logging	The logging property gives us access to the log level
temporaryDir	Returns a File object pointing to a temporary directory belonging to this build file. It is generally available to a task needing a temporary place in to store intermediate results of any work, or to stage files for processing inside the task
description	a small piece of human-readable metadata to document the purpose of a task

Gradle – Dynamic Properties

- Properties (other than built-in ones) can be assigned to a task
- A task object functions can contain other arbitrary property names and values we want to assign to it (do not use built-in property names)

```
task copyFiles {  
    // Find files from wherever, copy them  
    // (then hardcode a list of files for illustration)  
    fileManifest = [ 'data.csv', 'config.json' ]  
}  
  
task createArtifact(dependsOn: copyFiles) << {  
    println "FILES IN MANIFEST: ${copyFiles.fileManifest}"  
}
```

property
value

task
name

Gradle Task Types – Copy

- A copy task copies files from one place into another

```
task copyFiles(type: Copy) {  
  from 'resources'  
  into 'target'  
  include '**/*.xml', '**/*.txt',  
  '**/*.properties'  
}
```

to define
a copy
task!

Note: the *from*, *into*, and *include* methods are inherited from the Copy

Gradle Task Types – Jar

- A Jar task creates a jar file from source files
- The *Java plug-in's jar* creates a task of this type
- It packages the main source set and resources together with a trivial manifest into a jar bearing the project's name in the build/libs directory
- highly customizable

Gradle Task Types – Jar Example

```
apply plugin: 'java'
task customJar(type: Jar){
    manifest {
        attributes firstKey: 'firstValue', secondKey: 'secondValue'
    }
    archiveName = 'hello.jar'
    destinationDir = file("${buildDir}/jars")
    from sourceSets.main.classes
}
```

Gradle Task Types – JavaExec

- A JavaExec task runs a Java class with a main() method
- Tries to take the hassle away and integrate command-line Java
invocations into your build

Gradle Task Types – JavaExec Example

```
apply plugin: 'java'
repositories {
    mavenCentral()
}
dependencies {
    runtime 'commons-codec:commons-codec:1.5'
}
→ task encode(type: JavaExec, dependsOn: classes) {
    main = 'org.gradle.example.commandline.MetaphoneEncoder'
    args = "The rain falls mainly in the plain".split().toList()
    classpath sourceSets.main.classesDir
    classpath configurations.runtime
}
```

Gradle Custom Task Types

- Gradle's built-in tasks might not be sufficient for all scenarios
- Gradle allows defining custom task types in:
 - The **Build File** and must extend the *DefaultTask* class or one of its descendants
 - The **Source Tree**: when the task's logic is significant has its own class hierarchy and might rely on external interface
 - When the custom task logic outgrows the build file, it can be migrated to the **buildSrc** directory at the project root
 - This directory is automatically compiled and added to the build classpath

Gradle Custom Task Types – Build File

- Suppose your build file needs to issue arbitrary queries against a MySQL database

```
task createDatabase(type: MySQLTask*) {  
    sql = 'CREATE DATABASE IF NOT EXISTS example'  
}  
  
task createUser(type: MySQLTask*, dependsOn: createDatabase) {  
    sql = "GRANT ALL PRIVILEGES ON example.*  
        TO exampleuser@localhost IDENTIFIED BY 'passwOrd'"  
}  
  
task createTable(type: MySQLTask*, dependsOn: createUser) {  
    username = 'exampleuser'  
    password = 'passwOrd'  
    database = 'example'  
    sql = 'CREATE TABLE IF NOT EXISTS users  
        (id BIGINT PRIMARY KEY, username VARCHAR(100))'  
}
```

^{*} Actual build tasks inherits MySQLType's properties and actions

```
class MySQLTask* extends DefaultTask {  
    def hostname = 'localhost'  
    def port = 3306  
    def sql  
    def database  
    def username = 'root'  
    def password = 'password'  
  
    @TaskAction  
    def runQuery() {  
        def cmd  
        if(database) {  
            cmd = "mysql -u ${username} -p${password} -h ${hostname}  
                -P ${port} ${database} -e "  
        }  
        else {  
            cmd = "mysql -u ${username} -p${password} -h ${hostname} -P ${port} -e "  
        }  
        project.exec {  
            commandLine = cmd.split().toList() + sql  
        }  
    }  
}
```

Task's properties (Groovy idiom)

Task method will run when the task runs

Gradle Custom Task Types – Source Tree

```
import org.gradle.api.DefaultTask
import org.gradle.api.tasks.TaskAction
```


```
class MySqlTask extends DefaultTask {
    def hostname = 'localhost'
    def port = 3306
    def sql
    def database
    def username = 'root'
    def password = 'password'

    @TaskAction
    def runQuery() {
        def cmd
        if(database) {
            cmd = "mysql -u ${username} -p${password} -h ${hostname}
                -P ${port} ${database} -e "
        }
        else {
            cmd = "mysql -u ${username} -p${password} -h ${hostname} -P ${port} -e "
        }
        project.exec {
            commandLine = cmd.split().toList() + sql
        }
    }
}
```

Similar to the code in the build script (previous example).
However, source tree provides a robust way for elaborating on that simple task behavior, growing an object model, writing tests, and doing everything else we normally do when developing software

Gradle – Plug-ins

Java Plug-in



Gradle – Java Plug-in

- A plug-in is an extension to Gradle which configures projects
- **Java plug-in** adds some tasks to your project which will compile and unit test your Java source code, and bundle into a JAR
 - Convention-based; default values for many aspects of the project are pre-defined
 - In your build.gradle: *apply plugin : 'java'* ←
 - Can customize projects if you do not follow the convention

Gradle – Java Plug-in (Project Structure)

- Gradle expects to find production source code under src/main/java and test source code under src/test/java
- Files under src/main/resources will be included in the JAR as resources
- Files under src/test/resources will be included in the classpath used to run tests
- All output files are created under the build directory, with the JAR file will end up in the build/libs directory

https://docs.gradle.org/current/userguide/java_plugin.html

Gradle – Java Plug-in (Project Build)

- Java plug-in will add a few tasks
- Run *gradle tasks* to list the tasks of a project
by: 1 d
- Gradle will compile and create a JAR file containing main classes and resources – run *gradle build*

```
> gradle build
> Task :compileJava
> Task :processResources
> Task :classes
> Task :jar
> Task :assemble
> Task :compileTestJava
> Task :processTestResources
> Task :testClasses
> Task :test
> Task :check
> Task :build

BUILD SUCCESSFUL in 0s
6 actionable tasks: 6 executed
```

Example of output of gradle build

Gradle – Java Plug-in (Project Build)

- **clean**
 - Deletes the build directory, removing all built files
- **assemble**
 - Compiles and jars your code, but does not run the unit tests
 - Other plugins add more artefacts to this task;
- **check**
 - Compiles and tests your code
 - Other plugins add more checks to this task; e.g., *checkstyle* plugin to run checkstyle against your source code

Gradle Java Plug-in – Dependencies

- Reference external JAR files that the project is dependent on:
 - JAR files in a repository (artefacts/dependencies needed for a project)
 - Different repositories types are supported in Gradle (see [Gradle Repository Types](#))
 - Example (using Central Maven Repository)

```
build.gradle
1 ....
2 repositories {
3     mavenCentral()
4 }
5 dependencies {
6     compile group: 'commons-collections', name: 'commons-collections', version: '3.2.2'
7     testCompile group: 'junit', name: 'junit', version: '4.+'
8 }
```

production classes have a compile-time dependency on commons collections

Test classes have a compile-time dependency on junit

https://docs.gradle.org/current/userguide/java_plugin.html

Gradle – Java Plug-in (Project Customization)

- The Java plug-in adds many properties with default values to a project
- Customize default values to suit project needs
- Use Gradle properties to list properties of a project

```
build.gradle
1 ...|
2 version = '1.0'
3 jar {
4     manifest {
5         attributes 'Implementation-Title': 'Gradle Quickstart',
6                   'Implementation-Version': version
7     }
8 }
```

https://docs.gradle.org/current/userguide/java_plugin.html

Gradle – Java Plug-in (Publish JAR file)

- Artefacts such as JAR files can be published to repositories
- To publish a JAR file
 - **gradle uploadArchives**

```
build.gradle
1  ...
2  uploadArchives {
3      repositories {
4          flatDir {
5              dirs 'repos'
6          }
7      }
8  }
```

Publish a JAR file to a local repository

https://docs.gradle.org/current/userguide/java_plugin.html

Gradle – Complete Build file for Java

build.gradle

```
apply plugin: 'java'
apply plugin: 'eclipse'

version = '1.0'
jar {
    manifest {
        attributes 'Implementation-Title': 'Gradle Quickstart',
                   'Implementation-Version': version
    }
}

repositories {
    mavenCentral()
}

dependencies {
    compile group: 'commons-collections', name: 'commons-collections', version: '3.2.2'
    testCompile group: 'junit', name: 'junit', version: '4.+'
}

test {
    systemProperties 'property': 'value'
}

uploadArchives {
    repositories {
        flatDir {
            dirs 'repos'
        }
    }
}
```

← Eclipse plug-in to create the Eclipse-specific descriptor files, like .project

References

- Ian Sommerville 2016. Software Engineering: Global Edition (3rd edition). Pearson, Englad
- Wikipedia, Apache Ant, https://en.wikipedia.org/wiki/Apache_Ant
- Wikipedia, Apache Maven, https://en.wikipedia.org/wiki/Apache_Maven
- Apache Maven, <https://maven.apache.org/>
- Gradle documentation, <https://docs.gradle.org/current/userguide/>
- Tim Berglund and Matthew McCullough. 2011. Building and Testing with Gradle (1st ed.). O'Reilly Media, Inc.