

4	H	G	F	E	D	C	B	A																											
	DESCRIPTION 3–24V Active Electronic Buzzer MANUFACTURER Generic SPECIFICATION • Operating Voltage: 3V – 24V DC • Rated Voltage: 12V DC (optimal operation) • Current Consumption: ~20 mA • Sound Pressure Level: ~95 dB (at 10 cm) • Frequency: 3100 Hz ±500 Hz • Type: Active buzzer (built-in oscillator circuit) • Mounting Type: Ear mount (40 mm hole spacing) • Diameter: ~29–40 mm (model dependent) • Height: ~15–16 mm • Operating Temperature: -20°C to +85°C • Color: Black FEATURES • Wide operating voltage range (3V–24V DC) • Built-in oscillator (no external signal required) • High sound output (~95 dB) for clear audible alerts • Easy panel or surface mounting with ear holes • Suitable for alarm and warning systems • Low power consumption • Compatible with Arduino, ESP32, PLC and industrial systems • Durable ABS plastic housing • Stable and reliable sound generation TERMINALS • + (VCC) – Positive power input • – (GND) – Ground connection					SAYFA REV DURUMU <table><tr><td>9</td><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td><td>SF</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>+</td><td>REV</td></tr></table> BOLGE REV AÇIKLAMALAR TARİH ONAY				9	8	7	6	5	4	3	2	1	SF									+	REV						
						9	8	7	6	5	4	3	2	1	SF																				
														+	REV																				
																																			
3	H	G	F	E	D	C	B	A																											
	DESCRIPTION 3–24V Active Electronic Buzzer MANUFACTURER Generic SPECIFICATION • Operating Voltage: 3V – 24V DC • Rated Voltage: 12V DC (optimal operation) • Current Consumption: ~20 mA • Sound Pressure Level: ~95 dB (at 10 cm) • Frequency: 3100 Hz ±500 Hz • Type: Active buzzer (built-in oscillator circuit) • Mounting Type: Ear mount (40 mm hole spacing) • Diameter: ~29–40 mm (model dependent) • Height: ~15–16 mm • Operating Temperature: -20°C to +85°C • Color: Black FEATURES • Wide operating voltage range (3V–24V DC) • Built-in oscillator (no external signal required) • High sound output (~95 dB) for clear audible alerts • Easy panel or surface mounting with ear holes • Suitable for alarm and warning systems • Low power consumption • Compatible with Arduino, ESP32, PLC and industrial systems • Durable ABS plastic housing • Stable and reliable sound generation TERMINALS • + (VCC) – Positive power input • – (GND) – Ground connection					SAYFA REV DURUMU <table><tr><td>9</td><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td><td>SF</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>+</td><td>REV</td></tr></table> BOLGE REV AÇIKLAMALAR TARİH ONAY				9	8	7	6	5	4	3	2	1	SF									+	REV						
						9	8	7	6	5	4	3	2	1	SF																				
														+	REV																				
																																			
2	H	G	F	E	D	C	B	A																											
	DESCRIPTION 3–24V Active Electronic Buzzer MANUFACTURER Generic SPECIFICATION • Operating Voltage: 3V – 24V DC • Rated Voltage: 12V DC (optimal operation) • Current Consumption: ~20 mA • Sound Pressure Level: ~95 dB (at 10 cm) • Frequency: 3100 Hz ±500 Hz • Type: Active buzzer (built-in oscillator circuit) • Mounting Type: Ear mount (40 mm hole spacing) • Diameter: ~29–40 mm (model dependent) • Height: ~15–16 mm • Operating Temperature: -20°C to +85°C • Color: Black FEATURES • Wide operating voltage range (3V–24V DC) • Built-in oscillator (no external signal required) • High sound output (~95 dB) for clear audible alerts • Easy panel or surface mounting with ear holes • Suitable for alarm and warning systems • Low power consumption • Compatible with Arduino, ESP32, PLC and industrial systems • Durable ABS plastic housing • Stable and reliable sound generation TERMINALS • + (VCC) – Positive power input • – (GND) – Ground connection					SAYFA REV DURUMU <table><tr><td>9</td><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td><td>SF</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>+</td><td>REV</td></tr></table> BOLGE REV AÇIKLAMALAR TARİH ONAY				9	8	7	6	5	4	3	2	1	SF									+	REV						
						9	8	7	6	5	4	3	2	1	SF																				
														+	REV																				
																																			
1	H	G	F	E	D	C	B	A																											
	DESCRIPTION 3–24V Active Electronic Buzzer MANUFACTURER Generic SPECIFICATION • Operating Voltage: 3V – 24V DC • Rated Voltage: 12V DC (optimal operation) • Current Consumption: ~20 mA • Sound Pressure Level: ~95 dB (at 10 cm) • Frequency: 3100 Hz ±500 Hz • Type: Active buzzer (built-in oscillator circuit) • Mounting Type: Ear mount (40 mm hole spacing) • Diameter: ~29–40 mm (model dependent) • Height: ~15–16 mm • Operating Temperature: -20°C to +85°C • Color: Black FEATURES • Wide operating voltage range (3V–24V DC) • Built-in oscillator (no external signal required) • High sound output (~95 dB) for clear audible alerts • Easy panel or surface mounting with ear holes • Suitable for alarm and warning systems • Low power consumption • Compatible with Arduino, ESP32, PLC and industrial systems • Durable ABS plastic housing • Stable and reliable sound generation TERMINALS • + (VCC) – Positive power input • – (GND) – Ground connection					SAYFA REV DURUMU <table><tr><td>9</td><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td><td>SF</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>+</td><td>REV</td></tr></table> BOLGE REV AÇIKLAMALAR TARİH ONAY				9	8	7	6	5	4	3	2	1	SF									+	REV						
						9	8	7	6	5	4	3	2	1	SF																				
														+	REV																				
																																			
<table><tr><td></td><td></td><td></td><td colspan="4" rowspan="2">TITLE</td></tr><tr><td></td><td></td><td></td></tr><tr><td>PREPARED</td><td></td><td>05.11.2026</td><td colspan="4">3–24V Active Electronic Buzzer</td></tr><tr><td>CHECKED</td><td></td><td></td><td>SIZE A3</td><td colspan="3">DRAWING NO 3–24V_Active_Electronic_Buzzer</td></tr><tr><td>QUALITY APPROVAL</td><td></td><td></td><td>SCALE</td><td>DATE OF RELEASE 05.11.2026</td><td colspan="2">SHEET 1/1</td></tr></table>								TITLE							PREPARED		05.11.2026	3–24V Active Electronic Buzzer				CHECKED			SIZE A3	DRAWING NO 3–24V_Active_Electronic_Buzzer			QUALITY APPROVAL			SCALE	DATE OF RELEASE 05.11.2026	SHEET 1/1	
			TITLE																																
PREPARED		05.11.2026	3–24V Active Electronic Buzzer																																
CHECKED			SIZE A3	DRAWING NO 3–24V_Active_Electronic_Buzzer																															
QUALITY APPROVAL			SCALE	DATE OF RELEASE 05.11.2026	SHEET 1/1																														