SAYFA REV DURUMU										REVIZYONLAR				
9	8	7	6	5	4	3	2	1	SF	BOLGE	REV	AÇIKLAMALAR	TARIH	ONAY
								+	REV		+			

DESCRIPTION

TP4056 Battery Charger Module (Type-C)

MANUFACTURER

NanJing Top Power ASIC Corp. (TPOWER / Top Power)

SPECIFICATION

- **Charging IC:** TP4056
- **Battery Type:** 3.7V Lithium-Ion / Lithium-Polymer (Li-Ion / Li-Po)
- **Input Interface:** USB Type-C
- **Input Voltage**: 4.5V – 5.5V DC
- **Charging Voltage:** 4.2V ±1%
- **Charging Current:** Up to 1A (adjustable via onboard resistor)
- **Charging Method:** Constant Current / Constant Voltage (CC/CV)
- **Protection:** Overcharge, over-discharge, over-current protection
- **Indicators:** Charging (red LED), Fully Charged (blue/green LED)
- **Operating Temperature:** −10°C to +85°C

FEATURES

- USB Type-C input for modern and stable connection
- Built-in TP4056 charging IC for lithium battery management
- Supports 3.7V Li-Ion / Li-Po rechargeable batteries
- Constant Current / Constant Voltage (CC/CV) charging algorithm
- Adjustable charging current up to 1A
- Dual LED indicators for charging status (Charging / Full)
- Integrated protection (overcharge, over-discharge, over-current)
- Compact and easy-to-use single-cell charging solution
- Ideal for DIY electronics and embedded systems



TERMINALS

- **IN+ / IN-** – 5V input (USB Type-C power input internally connected)
- **B+** – Battery positive terminal
- **B-** – Battery negative terminal
- **OUT+** – Load output positive
- **OUT-** – Load output negative
- **USB Type-C Port** – Power input interface

PREPARED		05.11.2026	TITLE TP4056 Battery Charger Module (Type-C)		
CHECKED			SIZE A3	DRAWING NO TP4056_Battery_Charger_Module	
QUALITY APPROVAL			SCALE	DATE OF RELEASE 05.11.2026	SHEET 1/1