



API Documentation

Unified API for interacting with multiple mobile payment networks (e.g., Orange, MTN). Includes endpoints for generating tokens, initiating payments, processing payments, and checking payment statuses.

API Reference

Get TPW Token

Process Payment

Check Payment Status

Environment Variables

base_url: API base URL

network: Payment network (mtn, orange)

secret_key: Secret key obtained on registration

bearer_token: Authentication token

auth_token: Network-specific token

Process Payment

Initiate a payment transaction with the specified mobile money provider.

POST /api/{network}/process-payment

Headers

```
{
  "Content-Type": "application/json",
  "Authorization": "Bearer {bearer_token}",
}
```

Request Body

```
{
  "amount": "1", // Amount to be paid (required)
  "currency": "XAF", // Currency code (required)
  "subscriberMsisdn": "237600000000", // Phone number of the payer
  (required)
  "description": "payment", // Description of the payment (optional)
  "orderId": "", // Unique identifier for the transaction in your
  system (required)
  "verificationToken": "unique-token-123", //
  (=>r("docs.request.verificationToken")) (optional)
  "notifUrl": "https://webhook.site/example", // URL to receive
  payment notifications (required)
}
```

Response

```
// Success Response
{
  "data": {
    "transaction_id": "74d96622-b36c-4993-964d-345decfcbb8d" // Unique
    transaction identifier
  },
  "message": "Payment request successful",
  "status_code": 202
}

// Error Response
{
  "error": "invalid_request",
  "message": "Invalid phone number format",
}
```

```
"status_code": 400
}
```



Authentication Required

This endpoint requires authentication. First obtain a token using the Get TPW Token endpoint, then include it in the Authorization header:

```
{
  "Content-Type": "application/json",
  "Authorization": "Bearer {bearer_token}",
}
```



Duplicate Payment Prevention

The `verificationToken` field helps prevent duplicate payments:

- Optional field that can contain any unique identifier
- Transactions with the same merchant ID, order ID, and verification token will be rejected as duplicates
- Only considers active transactions (excludes FAILED/CANCELED status)
- If omitted, duplicate detection is based only on merchant ID and order ID