



Convergence

Security review

Version 1.0

Reviewed by
nmirchev8
deth

Table of Contents

1	About Egis Security	3
2	Disclaimer	3
3	Risk classification	3
3.1	Impact	3
3.2	Likelihood	3
3.3	Actions required by severity level	3
4	Executive summary	4
5	Findings	5
5.1	Medium risk	5
5.1.1	Malicious user can lock CVX1 cvxcrv rewards in cvxCrvRewards contract .	5
5.1.2	It may be impossible to mint all CVXRush indexes	6
5.2	Low risk	8
5.2.1	getClaimableCyclesAndAmounts will revert when there is rewardAsset with 0 amount	8
5.2.2	Malicious actor can call processCvxRewards without calling getReward previously	9
5.2.3	If CvgRewards#writeStakingRewards is not called for two cycles, user may steal other stakers rewards	9
5.2.4	CvgCVX::setCvxStakingPositionService() - Doesn't reset isSpecialMinter for old cvxStakingPositionService	10
5.2.5	Under specific circumstances withdrawableFees[token] may become larger than balanceOf[token]	10
5.3	Informational	11
5.3.1	StakingServiceBase::claimCvgCvxMultiple() - Function is useless, as it's uncallable	11
5.3.2	Consider emitting events on important state changes	11
5.3.3	If the same gauge is added twice in CvgRewardsV3, it may lead to incrementing its cycle twice per week	12
5.3.4	Usage of block.timestamp in deadline calculations for Uniswap isn't recommended.	12
5.3.5	In CvxRewardDistributorV2#_withdrawRewards if we mint cvgCVX ratio is different from 1:1	13
5.3.6	CvgRewardsV3::setMaxChunkConfigs is redundant and not used anywhere.	13
5.3.7	Setting new CvxRewardPool in CVX1 may lead to small miscalculation . . .	13

1 About Egis Security

Egis Security is a team of experienced smart contract researchers, who strive to provide the best smart contract security services possible to DeFi protocols.

The team has a proven track record on public auditing platforms like Code4rena, Sherlock, and Cantina, earning top placements and rewards exceeding \$170,000. They have identified over 150 high and medium-severity vulnerabilities in both public contests and private audits.

2 Disclaimer

Audits are a time, resource, and expertise bound effort where trained experts evaluate smart contracts using a combination of automated and manual techniques to identify as many vulnerabilities as possible. Audits can show the presence of vulnerabilities **but not their absence**.

3 Risk classification

Severity	Impact: High	Impact: Medium	Impact: Low
Likelihood: High	Critical	High	Medium
Likelihood: Medium	High	Medium	Low
Likelihood: Low	Medium	Low	Low

3.1 Impact

- **High** - leads to a significant loss of assets in the protocol or significantly harms a group of users.
- **Medium** - only a small amount of funds can be lost or a functionality of the protocol is affected.
- **Low** - any kind of unexpected behaviour that's not so critical.

3.2 Likelihood

- **High** - direct attack vector; the cost is relatively low to the amount of funds that can be lost.
- **Medium** - only conditionally incentivized attack vector, but still relatively likely.
- **Low** - too many or too unlikely assumptions; provides little or no incentive.

3.3 Actions required by severity level

- **Critical** - client **must** fix the issue.
- **High** - client **must** fix the issue.
- **Medium** - client **should** fix the issue.
- **Low** - client **could** fix the issue.

4 Executive summary

Overview

Project Name	Convergence
Repository	https://github.com/Convergence-fi/convergence-convex-reaudit
Commit hash	fd825a5d57fba05fdc3a54bd3a40ff58cf5b56a0
Resolution	-
Documentation	-
Methods	Manual review

Scope

contracts/Rewards/CvgRewardsV3.sol
contracts/Staking/Convex/cvgCVX/CvgCVX.sol
contracts/Staking/Convex/cvgCVX/CvgCvxStakingPositionService.sol
contracts/Staking/Convex/cvgCVX/CVX1.sol
contracts/Staking/Convex/CvxRewardDistributorV2.sol
contracts/Staking/Convex/StakingServiceBase.sol

Issues Found

Critical risk	0
High risk	0
Medium risk	2
Low risk	5
Informational	7

5 Findings

5.1 Medium risk

5.1.1 Malicious user can lock CVX1 cvxcrv rewards in cvxCrvRewards contract

Severity: *Medium risk*

Context: CVX1.sol#L168-L172

Description: When user deposit CVX to CVX1 contract, CVX tokens are staked to cvxRewardPool. Corresponding rewards can be withdrawn with CVX1#getReward function, which will transfer accrued CVX_CRV to the cvgControlTower.convexTreasury():

```
function getReward() external {
    cvxRewardPool.getReward(false);

    /// @dev transfer cvxCrv tokens
    CVX_CRV.transfer(cvgControlTower.convexTreasury(), CVX_CRV.balanceOf(address(
        this)));
}
```

The problem is that anyone can call cvxRewardPool.getReward for CVX1 and set _stake = true, which will restake CVX_CRV balance into cvxCrvRewards contract:

```
function getReward(address _account, bool _claimExtras, bool _stake) public
updateReward(_account){
    uint256 reward = earnedReward(_account);
    if (reward > 0) {
        rewards[_account] = 0;
        rewardToken.safeApprove(crvDeposits,0);
        rewardToken.safeApprove(crvDeposits,reward);
        ICrvDeposit(crvDeposits).deposit(reward,false);

        uint256 cvxCrvBalance = cvxCrvToken.balanceOf(address(this));
        if(_stake){
            IERC20(cvxCrvToken).safeApprove(cvxCrvRewards,0);
            IERC20(cvxCrvToken).safeApprove(cvxCrvRewards,cvxCrvBalance);
            IRewards(cvxCrvRewards).stakeFor(_account,cvxCrvBalance);
        }
    }
}
```

Those tokens are locked, because CVX1 don't have function to withdraw from cvxCrvRewards contract.

Recommendation: Consider implementing the same withdrawCvxCrv, which is in CvgCVX contract:

```
function withdrawCvxCrv(uint256 amount, bool claim) external onlyOwner {
    if (amount != 0) {
        CVX_CRV_REWARDS.withdraw(amount, claim);
    } else {
        CVX_CRV_REWARDS.withdrawAll(claim);
    }
}
```

Resolution: Acknowledged

5.1.2 It may be impossible to mint all CVXRush indexes

Severity: *Medium risk*

Context: CvgCVX.sol#L316

Description: When we set `capCVXRushForIndex`, we make the following check to ensure that caps in the array are in increasing order:

```
for (uint256 i; i < cvxRushIndexInfos.length; ) {
    capCVXRushForIndex.push(cvxRushIndexInfos[i]);
    if (i != 0) {
        require(cvxRushIndexInfos[i].cap > cvxRushIndexInfos[i - 1].cap, "
            WRONG_CAP");
        require(cvxRushIndexInfos[i].ratio < cvxRushIndexInfos[i - 1].ratio,
            "WRONG_RATIO");
    }
    unchecked {
        ++i;
    }
}
```

But there is a problem in `_calculateCvgIncentive` function calculation, which may result in inability to use indexes in the end of the array.

Imagine the following scenario:

- We have `capCVXRushForIndex = [{cap = 100}, {cap = 200}, {cap = 300}, {cap = 400}]`
- If we have used first 3 indexes, we will have `cvgCvxAlreadyMintedWithRush = 100 + 200 + 300 = 600`
- Now `cvxRush` designed for the last cycle cannot be used, because in `_calculateCvgIncentive` we fetch `cvgCvxAlreadyMintedWithRush (600)` and compare it against each cap in the array:

```
for (uint256 i; i < _numberOfCvxRushIndex; ) {
    /// @dev Retrieve the cap in cvgCVX
    uint256 currentCap = capCVXRushForIndex[i].cap;

    if (_cvgCvxAlreadyMintedWithRush < currentCap) { // @sus very sus
        uint256 restToMintForIndex = currentCap -
            _cvgCvxAlreadyMintedWithRush;
        if (restToMintForIndex >= cvgCvxAmountUsedForBonus) {
            cvgIncentive += uint128(cvgCvxAmountUsedForBonus *
                capCVXRushForIndex[i].ratio) / 1000;
            _cvgCvxAlreadyMintedWithRush += cvgCvxAmountUsedForBonus;
            delete cvgCvxAmountUsedForBonus;
            break;
        } else {
            cvgCvxAmountUsedForBonus -= restToMintForIndex;
            cvgIncentive += uint128(restToMintForIndex * capCVXRushForIndex[
                i].ratio) / 1000;
            _cvgCvxAlreadyMintedWithRush += restToMintForIndex;
        }
    }
    unchecked {
```

```
        ++i;  
    }  
}
```

- The following results in inability to allocate the amount for the last index, because we we have set `cvxCvxAlreadyMintedWithRush` to value greater than the cap for the last index, because it is set to the sum of all previous indexes caps
- Even though system should allow 400 more tokens to be `mintCVXRushed`, it won't be possible. The transaction will always revert, because `_calculateCvgIncentive` will return `cvxCvxAmountUsedForBonus > 0`

Recommendation: Add additional `filled` field to `CvxRushIndexInfo` and use it to calculate cvg incentive for the correct index.

Resolution: Acknowledged

5.2 Low risk

5.2.1 getClaimableCyclesAndAmounts will revert when there is rewardAsset with 0 amount

Severity: *Low risk*

Context: StakingServiceBase.sol#L841-L849

Description:

StakingServiceBase#getClaimableCyclesAndAmounts is a view function, which returns claimable rewards for an account on each cycle:

```
struct ClaimableCyclesAndAmounts {
    uint256 cycleClaimable;
    uint256 cvgRewards;
    ICommonStruct.TokenAmount[] cvxRewards;
}
```

But there is a problem when we try to reduce `_cvxRewardsClaimable` array length when `rewardAsset.amount == 0`:

```
if (cycleInfo[nextClaimableCvx].isCvxProcessed) {
    _cvxRewardsClaimable = new ICommonStruct.TokenAmount[](
        maxLengthRewards);
    for (uint256 x; x < maxLengthRewards; ) {
        ICommonStruct.TokenAmount memory rewardAsset =
            cvxRewardsByCycle[nextClaimableCvx][x + 1];
        if (rewardAsset.amount != 0) {
            _cvxRewardsClaimable[x] = ICommonStruct.TokenAmount
                ({
                    token: rewardAsset.token,
                    amount: (amountStaked * rewardAsset.amount) /
                        totalStaked
                });
        } else {
            // solhint-disable-next-line no-inline-assembly
            assembly {
                /// @dev this reduce the length of the array to
                /// not return some useless 0 at the end
                // @sus this is wrong! We will have the useless
                // 0 amount at the middle of the array and most
                // probably revert when we try to assign the
                // last reward
                mstore(_cvxRewardsClaimable, sub(mload(
                    _cvxRewardsClaimable), 1))
            }
        }
        unchecked {
            ++x;
        }
    }
}
```

In the assembly block we reduce the array size by 1, but we always increment `++x`. If `maxLengthRewards == 5`. For one of the cycles we don't have rewards for token with `id = 2`, we will change

`_cvxRewardsClaimable` length to be 4. However, on the last `for` iteration we will try to assign value in the array as if we have the original array size `_cvxRewardsClaimable[4]` (5th element). The following results in EVM panic revert, because we try to assign value to index above the new length of the array. The function is `view` and we didn't find existing integration of it in the current scope, so we decided to mark it as `Low`.

Recommendation: If you want to use the same approach, consider implementing another variable, which will be used to count the index. It should be incremented only inside the if branch.

Resolution: Acknowledged

5.2.2 Malicious actor can call `processCvxRewards` without calling `getReward` previously

Severity: *Low risk*

Context: `CvgCVX.sol` & `StakingServiceBase.sol`

Description: Stakers accrue their rewards from `CVX_LOCKER`, which is holding CVX token of all depositors. `CvgCVX` contract is using its balance of reward tokens to calculate the corresponding rewards for the given cycle. The problem is that someone should manually call `CVX_LOCKER#getReward` so the rewards are sent to `CvgCVX` contract. If someone updates a cycle and call `processStakersRewards => processStakersRewards` without getting the rewards from CVX locker, he enforces them to stake for another cycle, or to not receive any rewards for this one.

Recommendation: Consider getting accrued rewards in `cvgCVX#pullRewards` before calculating `rewardsAvailable`:

```
function pullRewards(address processor) external returns (ICommonStruct.TokenAmount
[] memory) {
    require(msg.sender == cvxStakingPositionService, "NOT_CVG_CVX_STAKING");
    CVX_LOCKER.getReward(address(this));
    ...
}
```

Resolution: Acknowledged

5.2.3 If `CvgRewardsV3#writeStakingRewards` is not called for two cycles, user may steal other stakers rewards

Severity: *Low risk*

Context: `CvgRewardsV3.sol` #L149-L154

Description:

If `CvgRewardsV3#writeStakingRewards` is not called for two cycles, user may exploit it by using flashloan to stake, update cycles and rewards, claim, unstake and repay the loan in a single transaction.

Imagine the following scenario:

1. Bob and Alice has both staked \$1000 `cvgCVX` at cycle 1
2. 2 weeks has passed and nobody has called `CvgRewardsV3#writeStakingRewards`
3. Eve sees the opportunity and get a flashloan of \$10M, and in a single tx manages to:

- stake the flashloan as `cvgCVX`
 - calls `CvgRewardsV3#writeStakingRewards` => `processCvxRewards` => `CvgRewardsV3#writeStakingRewards` two times, so staking cycle is incremented from 1 => 3 and we have \$X of cvx rewards distributed for cycle 2
 - unstake all `cvgCVX` and repays the loan
4. Eve has inflated Bob and Alice rewards and she will receive > 99% of the amount accrued for those 2 weeks, because her weight for the distribution is $\sim 10_000_000 / 2_000$

Resolution: Acknowledged

5.2.4 `CvgCVX::setCvxStakingPositionService()` - Doesn't reset `isSpecialMinter` for old `cvxStakingPositionService`

Severity: *Low risk*

Context: `CvgCVX.sol`#L556-L559

Description: The function sets `cvxStakingPositionService` to the new `_cvxStakingPositionService` and sets `_cvxStakingPositionService` as a special minter

```
function setCvxStakingPositionService(address _cvxStakingPositionService) external
    onlyOwner {
        cvxStakingPositionService = _cvxStakingPositionService;
        isSpecialMinter[_cvxStakingPositionService] = true;
    }
```

The issue is that, it doesn't reset `isSpecialMinter` for the old `cvxStakingPositionService`.

In case the old `cvxStakingPositionService` is compromised, he still will be considered a special minter until `toggleIsSpecialMinter` is called.

Marking this as Low, as if `cvxStakingPositionService` is compromised, he can mint `cvgCvx` up to `capCvgCvx` inflating the supply of the tokens and reaching the cap.

Although the gap in time where the compromised address has the special minter role and `toggleIsSpecialMinter` is called is small, it's still possible that the above can happen.

The same is present in `CVX1#setCvgCvx`:

```
function setCvgCvx(ICvgCVX _cvgCVX) external onlyOwner {
    isSpecialMinter[address(_cvgCVX)] = true;
    cvgCVX = _cvgCVX;
}
```

Recommendation: Consider revoking minter role of the old addresses when setting the new ones.

Resolution: Acknowledged

5.2.5 Under specific circumstances `withdrawableFees[token]` may become larger than `balanceOf[token]`

Severity: *Low risk*

Context: CvgCVX.sol#L450

Description: It's possible for `withdrawableFees[token] > balanceOf[token]` under the following circumstances:

- `withdrawableFees[token] = 100` and `balanceOf[token] = 100`.
- Owner removes `token` as a reward token.
- Owner calls `recoverTokens` for `token` and retrieves the entire balance.
- Now we have, `withdrawableFees[token] = 100` and `balanceOf[token] = 0`.
- If `token` is added back as a reward token, there is a chance that the incoming rewards won't be enough to cover the `withdrawableFees`, making the tx revert here:

```
function pullRewards(address processor) external returns (ICommonStruct.TokenAmount
    [] memory) {
    ...
    uint256 withdrawableFeeAmount = withdrawableFees[rewardConfiguration.token];
    uint256 rewardsAvailable = rewardConfiguration.token.balanceOf(address(
        this)) - withdrawableFeeAmount;
    ...
}
```

Resolution: Acknowledged

5.3 Informational

5.3.1 StakingServiceBase::claimCvxCvxMultiple() - Function is useless, as it's uncallable

Severity: Info risk

Context: StakingServiceBase.sol#L271

Description:

Function is useless, as it's only callable by the `CvxRewardDistributor`, but `CvxRewardDistributorV2` doesn't interact with this function, making it redundant

Resolution: Acknowledged

5.3.2 Consider emitting events on important state changes

Severity: Info risk

Context: CvgCVX.sol, StakingServiceBase.sol

Description:

Consider emitting events on important state changes such as:

- In CvgCVX
 - `CvgCVX#setCvxDelegateRegistry`
 - `setCvxStakingPositionService`
 - `setMintFees`
 - `setRewardTokensConfigs`

- toggleIsSpecialMinter
- In StakingServiceBase
 - toggleDepositPaused
 - setBuffer

Resolution: Acknowledged

5.3.3 If the same gauge is added twice in CvgRewardsV3, it may lead to incrementing it's cycle twice per week

Severity: Info risk

Context: CvgRewardsV3.sol#L112-L115

Description:

Consider checking if a gauge with such address exists and revert if it does.

Resolution: Acknowledged

5.3.4 Usage of block.timestamp in deadline calculations for Uniswap isn't recommended.

Severity: Info risk

Context: StakingServiceBase.sol#L668

Description:

Inside `_convertEthToAsset` we use `block.timestamp + 1000` in both UniV2 and UniV3 swaps, using `block.timestamp` as a deadline isn't recommended, as whenever the tx is executed that's what `block.timestamp` will be, thus there is technically no deadline.

Note: Leaving this as info, as slippage protection is enough, but using `block.timestamp` as a deadline is bad practice.

```
if (_poolEthInfo.poolType == IStakingServiceBase.PoolType.UNIV2) {
    address[] memory path = new address[](2);
    path[0] = WETH;
    path[1] = _poolEthInfo.token;
    uint256[] memory amounts = UNISWAPV2_ROUTER.swapExactETHForTokens({value:
        amountIn,
        amountOutMin,
        path,
        address(this),
        //@issue I - hardcoded deadline doesn't do anything
        block.timestamp + 1000
    });
    amountOut = amounts[1];
} else if (_poolEthInfo.poolType == IStakingServiceBase.PoolType.UNIV3) {
    amountOut = UNISWAPV3_ROUTER.exactInputSingle({value: amountIn,
        IUniv3Router.ExactInputSingleParams({
            tokenIn: WETH,
            tokenOut: _poolEthInfo.token,
            fee: uint24(_poolEthInfo.fee),
            recipient: address(this),
```

```
        //@issue I - hardcoded deadline doesn't do anything
        deadline: block.timestamp + 1000,
        amountIn: amountIn,
        amountOutMinimum: amountOutMin,
        sqrtPriceLimitX96: 0
    );
}
```

Resolution: Acknowledged

5.3.5 In `CvxRewardDistributorV2#_withdrawRewards` if we mint `cvgCVX` ratio is different from 1:1

Severity: *Info risk*

Context: `CvgRewardsV3.sol#L112-L115`

Description:

In `CvxRewardDistributorV2#_withdrawRewards` if we mint `cvgCVX` ratio is different from 1:1, because `cvgCVX` is minted with `isLock` param set to **false**, which will result in fee collection from the CVX amount provided.

Resolution: Acknowledged

5.3.6 `CvgRewardsV3::setMaxChunkConfigs` is redundant and not used anywhere.

Severity: *Info risk*

Context: `CvgRewardsV3.sol#L104-L106`

Description:

Consider removing dead code.

Resolution: Acknowledged

5.3.7 Setting new `CvxRewardPool` in `CVX1` may lead to small miscalculation

Severity: *Info risk*

Context: `CvgRewardsV3.sol#L104-L106`

Description:

When `CVX1::setCvxRewardPool` is called, there can be tokens that are still staked in the `cvxRewardPool`, which can lead to a small DoS.

- `cvxRewardPool1` has 100 CVX staked.
- `setCvxRewardPool` is called and now we are using `cvxRewardPool2`.
- `cvxRewardPool2` has 0 CVX staked.
- If a user attempts to `withdraw` and there aren't enough tokens in `CVX1` for him, we'll attempt to withdraw from `cvxRewardPool2`, but it has 0 staked tokens in it, so the tx will revert, blocking the user's withdraw.

Recommendation:

Call `cvxRewardPool.withdrawAll(true)` so that the entire stake and all the rewards are first retrieved, before changing the reward pools.

Resolution: Acknowledged