



Element280

Security review

Version 1.0

Reviewed by
nmirchev8
deth

Table of Contents

1	About Egis Security	3
2	Disclaimer	3
3	Risk classification	3
3.1	Impact	3
3.2	Likelihood	3
3.3	Actions required by severity level	3
4	Executive summary	4
5	Findings	5
5.1	Critical risk	5
5.1.1	Element280::_deployLiquidityPool() - Contract can be DoSed if someone donates to the pair	5
5.2	High risk	6
5.2.1	No slippage protection when providing liquidity in ElementLiquidityManager can result in sandwich attacks	6
5.3	Medium risk	7
5.3.1	No slippage protection ElementBuyBurn could result in sandwich attacks	7
5.3.2	Stepwise jump farming in ElementHolderVault	8
5.4	Low risk	9
5.4.1	ElementBuyBurn::isRebalanceAvailable may return wrong value	9
5.4.2	Same token ids may be used in ElementHolderVault::getRewards	9
5.4.3	Consider emitting events on important state changes	9
5.5	Informational	10
5.5.1	DevDistribute::minAmount cannot be updated and it is set to only 100	10
5.5.2	First check in onlyNftContract is redundant	10
5.5.3	If DevDistribute::changeWallet is called with existing dev wallet, some tokens will be left in the contract after distribution.	10
5.5.4	ElementNFT::calculateAllocation can be called with burned nfts, or duplicate ids	11
5.5.5	Set lpPurchases[TITANX] to 5 in _registerLPPool	11
5.5.6	Rounding down in calculating tokensPerMultiplier results in small amounts of locked tokens	11
5.5.7	Claim rewards design may be used for honey-pot exploits	12
5.5.8	In ElementBuyBurn::buyAndBurn we will use at most 80% of capPerSwapEco when swapping the token	12
5.5.9	require(HOLDER_VAULT != address(0)) is redundant and it is guaranteed if above line has passed	12
5.5.10	Some ecosystem tokens in constants.sol has address(0)	13
5.5.11	Rebalance interval check in isRebalanceAvailable is slightly off	13
5.5.12	Typo in _userPurchases mapping	13
5.5.13	Wrong natspec comment	14

1 About Egis Security

Egis Security is a team of experienced smart contract researchers, who strive to provide the best smart contract security services possible to DeFi protocols.

The team has a proven track record on public auditing platforms like Code4rena, Sherlock, and Cantina, earning top placements and rewards exceeding \$170,000. They have identified over 150 high and medium-severity vulnerabilities in both public contests and private audits.

2 Disclaimer

Audits are a time, resource, and expertise bound effort where trained experts evaluate smart contracts using a combination of automated and manual techniques to identify as many vulnerabilities as possible. Audits can show the presence of vulnerabilities **but not their absence**.

3 Risk classification

Severity	Impact: High	Impact: Medium	Impact: Low
Likelihood: High	Critical	High	Medium
Likelihood: Medium	High	Medium	Low
Likelihood: Low	Medium	Low	Low

3.1 Impact

- **High** - leads to a significant loss of assets in the protocol or significantly harms a group of users.
- **Medium** - only a small amount of funds can be lost or a functionality of the protocol is affected.
- **Low** - any kind of unexpected behaviour that's not so critical.

3.2 Likelihood

- **High** - direct attack vector; the cost is relatively low to the amount of funds that can be lost.
- **Medium** - only conditionally incentivized attack vector, but still relatively likely.
- **Low** - too many or too unlikely assumptions; provides little or no incentive.

3.3 Actions required by severity level

- **Critical** - client **must** fix the issue.
- **High** - client **must** fix the issue.
- **Medium** - client **should** fix the issue.
- **Low** - client **could** fix the issue.

4 Executive summary

Overview

Project Name	Element280
Repository	https://github.com/DudeGuy420/Element280-Contracts
Commit hash	9e248629d57db7099e71f0b69f001b4535821121
Resolution	e496519562057f4157bf1c04350b87f24d447153
Documentation	https://docs.helios-hlx.win/element280
Methods	Manual review

Scope

contracts/lib/constants.sol
contracts/DevDistribute.sol
contracts/Element280.sol
contracts/ElementBuyBurn.sol
contracts/ElementHolderVault.sol
contracts/ElementLiquidityManager.sol
contracts/ElementNFT.sol

Issues Found

Critical risk	1
High risk	1
Medium risk	2
Low risk	3
Informational	13

5 Findings

5.1 Critical risk

5.1.1 Element280::_deployLiquidityPool() - Contract can be DoSed if someone donates to the pair

Severity: *Critical risk*

Context: Element280.sol#L382-L391

Description: When we try to deploy a LP, we call Uni's addLiquidity, which will try to create a pair if it doesn't exist, but anyone can create a pair beforehand, which wouldn't be a problem in most cases except one.

If someone creates a pair between E280 and Flux for example, then transfers a bit of Flux directly to the pair then calls sync on the pair, this will increase the reserves of Flux, but not for E280, so the pair will now have `reservesE280 == 0` and `reservesFlux != 0`.

This is very problematic, as when addLiquidity is called, it calls the internal function _addLiquidity, which has several cases in it. UniswapRouter#_addLiquidity function Because the reserves are the pair are `reserveA == 0(E280)` and `reserveB != 0(Flux)`, we'll go into the else statement. Then we call UniswapV2Library.quote.

The tx will revert on the second **require**, as `reserveA == 0(E280)`.

Because of this attack, `_enableTrading` will be impossible to call, thus it will make the token completely untransferable.

Recommendation: Fetch the corresponding univ2 pool and check if the other token `balance > 0`. If so, calculate e280 token amount that should be send to the pair to make the ratio correct. Send it to the pair and call `sync` on the pool. Then call `addLiquidity`, but be sure to calculate `amountAmin` and `amountBmin` correspondingly.

Resolution: Fixed

5.2 High risk

5.2.1 No slippage protection when providing liquidity in ElementLiquidityManager can result in sandwich attacks

Severity: *High risk*

Context: ElementLiquidityManager.sol#L63-L64

Description: Under certain circumstances actors with large capital can sandwich a call to `ElementLiquidityManager#addLiquidity` to extract value from the manipulated changes in the reserves. NOTE that the following issue also exists in `removeLiquidity`

Recommendation: Consider adding `minAmountA` & `minAmountB` params and pass them to `addLiquidity` function.

Resolution: Acknowledged

5.3 Medium risk

5.3.1 No slippage protection EElementBuyBurn could result in sandwich attacks

Severity: *Medium risk*

Context: ElementBuyBurn.sol#L401

Description: When swaping weth -> titanX in rebalance there is hardcoded `amountMin = 0`, which means that if there is ether to be swapped and exploiter has enough liquidity, he can manipulate the pool, call the func and extract value from the slippage.

On `buyAndBurn` user provides `minTokenAmount` and `minE280Amount`. Those can be set to 0/1 and user can extract value if the swapped amount is large enough, or reserves in the pool are low. This may also brick protocol tokenomics.

Recommendation: Consider using a twap to dynamically calculate the slippage tolerance.

Resolution: Acknowledged

5.3.2 Stepwise jump farming in ElementHolderVault

Severity: *Medium risk*

Context: ElementHolderVault.sol#L85

Description: Mint nft right before cycle update and then redeem it after 48 hours. Do the same for the next cycle update, etc. The user claims rewards accrued for 7 days, when he has held the nft for only 2 days.

Recommendation: Consider forcing user to be able to redeem nft after at least 7 days

Resolution: Acknowledged

5.4 Low risk

5.4.1 ElementBuyBurn::isRebalanceAvailable may return wrong value

Severity: *Low risk*

Context: ElementBuyBurn.sol#L135-L136

Description: When we call `rebalance` we do eth swaps and then we check if the `unaccounted titan` > 0 . But when we fetch `unaccountedTitan` we check if the value is $> \text{minTitanX}$:

```
uint256 titanBalance = IERC20(TITANX).balanceOf(address(this));
unchecked {
    // titanX that we have swapped // titanX that
    // have already been allocated for tokens
    unaccountedTitan = titanBalance + totalTitanXUsed - totalTitanXAllocated
    ;
}
if (unaccountedTitan < minTitanX) return 0;
return unaccountedTitan;
```

So there may be the situation, when `isRebalanceAvailable` will return true, because `address(this).balance` > 0 , but a call to `rebalance` would revert, because of the `minTitanX` check.

Recommendation: Don't revert `rebalance` call, if `unaccounted titan` $= 0$.

Resolution: Fixed

5.4.2 Same token ids may be used in ElementHolderVault::getRewards

Severity: *Low risk*

Context: ElementHolderVault.sol#L129

Description: If the view function `getRewards` is used by an outside integrator, it may manipulate the returned value by providing same `tokenId`, which will lead to manipulated `totalReward` value.

Recommendation: Consider reverting if there are duplicate `tokenIds` in the `tokenIds` array.

Resolution: Fixed

5.4.3 Consider emitting events on important state changes

Severity: *Low risk*

Context: Everywhere

Description: Consider emitting events on important state changes in the following functions:

- In `Element280.sol`:
 - `_enableTrading`
 - `setProtocolAddresses`
 - `setWhitelistTo`
 - `setWhitelistFrom`
- In `ElementHolderVault.sol`:

- `setMinCyclePool`
 - `setTreasury`
- In `ElementBuyBurn.sol`
 - `setTreasury`
 - `setIncentiveFee`
 - `setEthCapPerSwap`
 - `setRebalanceInterval`
 - `setTokenInterval`
 - `setTokenCapPerSwap`
- In `ElementNFT`:
 - `setContractURI`
 - `setBaseURI`

Recommendation: Emit event on important state changes.

Resolution: Partially Fixed

5.5 Informational

5.5.1 `DevDistribute::minAmount` cannot be updated and it is set to only 100

Severity: *Informational*

Context: `DevDistribute.sol`#L12-L13

Description:

`DevDistribute::minAmount` cannot be updated and it is set to only 100. Consider making it constant, or implementing a setter.

Resolution: Acknowledged

5.5.2 First check in `onlyNftContract` is redundant

Severity: *Informational*

Context: `Element280.sol`#L93-L94

Description:

First check is redundant. `msg.sender` cannot be `address(0)` anyways.

Resolution: Fixed

5.5.3 If `DevDistribute::changeWallet` is called with existing dev wallet, some tokens will be left in the contract after distribution.

Severity: *Informational*

Context: `DevDistribute.sol`#L39-L43

Description:

```
function changeWallet(address newWallet) external {
    require(isTeamWallet(msg.sender), "Unauthorized");
    _teamWallets.remove(msg.sender);
    _teamWallets.add(newWallet);
}
```

`_teamWallets` is `EnumerableSet`, which means that if we try to add an element, which is already existent, we skip the operation. As a result we will have `_teamWallets.length = 2`, but `distributeToken` always divide the balance by 3:

```
uint256 share = availableBalance / 3;
for (uint256 j = 0; j < _teamWallets.length(); j++) {
    token.safeTransfer(_teamWallets.at(j), share);
}
```

Consider checking if the `newWallet` is already in the set.

Resolution: Fixed

5.5.4 ElementNFT::calculateAllocation can be called with burned nfts, or duplicate ids

Severity: *Informational*

Context: ElementNFT.sol#L174

Description:

Consider not counting the allocation of nfts, that have already been burned. Also consider checking for duplicate ids, which would otherwise return manipulated data.

Resolution: Fixed.

5.5.5 Set `lpPurchases[TITANX]` to 5 in `_registerLPPool`

Severity: *Informational*

Context: Element280.sol#L367-L368

Description:

Since we now only have 5 purchases for LP tokens, inside `_registerLPPool` which is a function used only for TitanX we still set `lpPurchases[TITANX] = 10`, while now there are only 5 purchases. To be completely accurate, `lpPurchases[TITANX]` should be set to 5, so it mirrors the logic that applies for all other tokens.

Resolution: Fixed.

5.5.6 Rounding down in calculating `tokensPerMultiplier` results in small amounts of locked tokens

Severity: *Informational*

Context: ElementHolderVault.sol#L84-L86

Description:

Here is an example: `multiplierPool = 1100; rewardPool = 12341234 => tokensPerMultiplier = 12341234 / 1100 = 11219.30 => 11219 11219 * 1100 = 12340900 (claimable amount) => 12341234 - 12340900 = 334` is accounted as claimed, but it won't and will continue increasing for the next cycles.

Consider increasing `totalRewardPool` to the value after the rounding. This way we will use tokens, which we haven't accounted for on the next cycle:

```
totalRewardPool += cycles[currentCycle].tokensPerMultiplier * IElementNFT(E280_NFT)
    .multiplierPool();
```

Resolution: Fixed

5.5.7 Claim rewards design may be used for honey-pot exploits

Severity: *Informational*

Context: `ElementHolderVault`

Description:

Imagine a scenario where Bob has listed his E280 Nft in Opensea and it is Tier 6. Let's assume Tier 6 NFT can be redeemed for \$100, but additionally holds \$50 in rewards from `ElementHolderVault`. Bob has listed it for \$125 and instantly a victim submit a purchase order (Instant money - you buy \$150 for \$125). Then Bob front-runs victim's transaction with `ElementHolderVault#claimRewards`, so the buyer receives \$100 worth NFT for \$125. Consider implementing `claimRewardRequest`, which makes you claim with a little cooldown. Or you can just document potential frauds from 3rd parties.

Resolution: Acknowledged

5.5.8 In ElementBuyBurn : buyAndBurn we will use at most 80% of capPerSwapEco when swapping the token

Severity: *Informational*

Context: `ElementBuyBurn.sol#L169-L175`

Description:

`capPerSwapEco` limits the pool swaps and prevents potential sandwich attacks or big slippage. In current implementation we first: - limit the token allocation to `capPerSwapEco` (if allocation is greater) - calculate and send incentive fee - calculate, send and burn `tokenDisperse`, which is 20% from the `capPerSwapEco - incentive fee` - and then swap `(capPerSwapEco - incentiveFee) * 0.8`

Which means that the value that we swap is much smaller than `capPerSwapEco`.

Resolution: Acknowledged

5.5.9 require(HOLDER_VAULT != address(0)) is redundant and it is guaranteed if above line has passed

Severity: *Informational*

Context: Element280.sol#L178-L179

Description:

We set `E280NFT` and `HOLDER_VAULT` in `setProtocolAddresses` function, where we do `address(0)` check for each of the arguments. As a result if `E280NFT != address(0)` guarantees that `HOLDER_VAULT` is also `!= address(0)`

Resolution: Fixed

5.5.10 Some ecosystem tokens in constants.sol has address(0)

Severity: *Informational*

Context: constants.sol#L20-L26

Resolution: Acknowledged

5.5.11 Rebalance interval check in isRebalanceAvailable is slightly off

Severity: *Informational*

Context: ElementBuyBurn.sol#L242

Description:

In `rebalance` we can only call the func if `block.timestamp` is larger than `token.lastTimestamp + token.interval`

```
require(block.timestamp > token.lastTimestamp + token.interval, "Cooldown in progress");
```

In `isRebalanceAvailable` it can return true if `block.timestamp` is larger than or equal to `token.lastTimestamp + token.interval`

```
if (block.timestamp < lastRebalance + rebalanceInterval) return false;
```

Resolution: Fixed

5.5.12 Typo in _userPurchases mapping

Severity: *Informational*

Context: Element280.sol#L81

Description:

Element280's `_userPurchases` mapping is defined as: `mapping(address token => EnumerableSet.UintSet) private _userPurchases`; While in reality token are user addresses, so it should be like so: `mapping(address user => EnumerableSet.UintSet) private _userPurchases`;

Resolution: Fixed

5.5.13 Wrong natspec comment**Severity:** *Informational***Context:** Element280.sol#L78-L79**Description:**

Consider updating the comment about `Element280::lpPurchases` to follow the updated version, which makes 5 purchases, instead of 10.

Resolution: Fixed