

# Bayesian Inference for RL

Sergey Bartunov  
DeepMind, HSE

# Outline

# Outline

- (very brief) Introduction to Reinforcement Learning

# Outline

- (very brief) Introduction to Reinforcement Learning
- Solving MDP via variational inference

# Outline

- (very brief) Introduction to Reinforcement Learning
- Solving MDP via variational inference
- Stable policy gradients


# Outline

- (very brief) Introduction to Reinforcement Learning
- Solving MDP via variational inference
- Stable policy gradients
- Hierarchical RL with Options as auxiliary variables

# Outline

- (very brief) Introduction to Reinforcement Learning
- Solving MDP via variational inference
- Stable policy gradients
- Hierarchical RL with Options as auxiliary variables
- Adversarial inference for model-based RL


# Unsupervised Learning



# Supervised Learning




**Observation**



**Objective**  $\log p(y|x)$

# Reinforcement Learning



[0] Mnih et al, 2016

# Reinforcement Learning

# Reinforcement Learning

- Sequential decision making

# Reinforcement Learning

- Sequential decision making
- No right or wrong decisions
- Only more or less optimal behaviors

# Reinforcement Learning

- Sequential decision making
  - No right or wrong decisions
    - Only more or less optimal behaviors
  - Potentially sparse, noisy and delayed rewards
  - Credit assignment problem


# Reinforcement Learning

- Sequential decision making
- No right or wrong decisions
  - Only more or less optimal behaviors
- Potentially sparse, noisy and delayed rewards
  - Credit assignment problem
- Exploration / exploitation trade-off

# Reinforcement Learning

- Sequential decision making
- No right or wrong decisions
  - Only more or less optimal behaviors
- Potentially sparse, noisy and delayed rewards
  - Credit assignment problem
  - Exploration / exploitation trade-off
  - Partial observability

# Markov Decision Process




# Markov Decision Process


Policy

$$a_t \sim \pi(a_t | s_t)$$

Agent-defined



# Markov Decision Process



# Markov Decision Process

**Policy**

$$a_t \sim \pi(a_t | s_t)$$

Agent-defined

**Rewards**


$$r_t = r(s_t, a_t, s_{t+1}) \leq 0$$

Likely unknown

**State transitions**

$$s_{t+1} \sim p(s_{t+1} | s_t, a_t)$$

Likely unknown



# Markov Decision Process

**Policy**


$$a_t \sim \pi(a_t | s_t)$$

Agent-defined

**Rewards**

$$r_t = r(s_t, a_t, s_{t+1}) \leq 0$$

Likely unknown



**State transitions**

$$s_{t+1} \sim p(s_{t+1} | s_t, a_t)$$

Likely unknown

**Goal**

$$\max_{\pi} \mathbb{E}_{s_{1:T}, a_{1:T}} \sum_{t=1}^T r_t$$

# Variational inference


## Latent-variable model

- Latent variable  $z \sim p(z)$
- Observation  $x \sim p(x|z)$
- Marginal likelihood  $p(x) = \int p(z)p(x|z)dz$

## Variational lower bound


$$\begin{aligned}\log p(x) &= \log \int p(z)p(x|z)dz = \log \int q(z) \frac{p(z)}{q(z)} p(x|z)dz \\ &\geq \mathbb{E}_{q(z)} [\log p(x|z)] - \text{KL}(q(z)||p(z)) \\ &= \log p(x) - \text{KL}(q(z)||p(z|x)) \\ &= \mathcal{L}(q, p)\end{aligned}$$

# MDP as a probabilistic model



# MDP as a probabilistic model


Prior (w.r.t. some policy)



$$p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = p(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t|s_t)p(s_{t+1}|s_t, a_t)] \pi_0(a_T|s_T)$$

# MDP as a probabilistic model

Prior (w.r.t. some policy)



$$p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = p(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t|s_t)p(s_{t+1}|s_t, a_t)] \pi_0(a_T|s_T)$$

Likelihood

$$p(\hat{\mathbf{R}}_{1:T}|\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \prod_{t=1}^T p(\hat{R}_t = 1|s_t, a_t, s_{t+1}) = \prod_{t=1}^T \exp(\alpha \cdot r_t)$$

# MDP as a probabilistic model

Prior (w.r.t. some policy)


$$p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = p(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t|s_t)p(s_{t+1}|s_t, a_t)] \pi_0(a_T|s_T)$$

Likelihood

$$p(\hat{\mathbf{R}}_{1:T}|\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \prod_{t=1}^T p(\hat{R}_t = 1|s_t, a_t, s_{t+1}) = \prod_{t=1}^T \exp(\alpha \cdot r_t)$$


Approximate posterior (w.r.t. some other policy)

$$q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = p(s_1) \prod_{t=1}^{T-1} [\pi(a_t|s_t)p(s_{t+1}|s_t, a_t)] \pi(a_T|s_T)$$



# MDP as a probabilistic model

Prior (w.r.t. some policy)



$$p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = p(s_1) \prod_{t=1}^{T-1} [\underbrace{\pi_0(a_t|s_t)}_{\text{Different}} \underbrace{p(s_{t+1}|s_t, a_t)}_{\text{Same}}] \pi_0(a_T|s_T)$$


Likelihood

$$p(\hat{\mathbf{R}}_{1:T}|\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \prod_{t=1}^T p(\hat{R}_t = 1|s_t, a_t, s_{t+1}) = \prod_{t=1}^T \exp(\alpha \cdot r_t)$$

Approximate posterior (w.r.t. some other policy)

$$q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = p(s_1) \prod_{t=1}^{T-1} [\underbrace{\pi(a_t|s_t)}_{\text{Different}} \underbrace{p(s_{t+1}|s_t, a_t)}_{\text{Same}}] \pi(a_T|s_T)$$


# Solving MDP via approximate inference



# Solving MDP via approximate inference

## Marginal likelihood

$$\log p(\hat{\mathbf{R}}_{1:T}) = \log \mathbb{E}_{p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} p(\hat{\mathbf{R}}_{1:T} | \mathbf{s}_{1:T}, \mathbf{a}_{1:T})$$




# Solving MDP via approximate inference

## Marginal likelihood


$$\log p(\hat{\mathbf{R}}_{1:T}) = \log \mathbb{E}_{p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} p(\hat{\mathbf{R}}_{1:T} | \mathbf{s}_{1:T}, \mathbf{a}_{1:T})$$

## Variational lower bound

$$\begin{aligned}\log p(\hat{\mathbf{R}}_{1:T}) &= \log \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \frac{p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})}{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} p(\hat{\mathbf{R}}_{1:T} | \mathbf{s}_{1:T}, \mathbf{a}_{1:T}) \\ &\geq \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \text{KL}(q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})) \\ &= \mathcal{L}(q_{\pi}, p_{\pi_0})\end{aligned}$$




# Policy gradients as inference



# Policy gradients as inference

## Variational lower bound

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \text{KL}(q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))$$




# Policy gradients as inference

Variational lower bound

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \text{KL}(q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))$$

Recovering policy gradients algorithm




# Policy gradients as inference

## Variational lower bound

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \text{KL}(q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))$$

## Recovering policy gradients algorithm

- Consider  $\pi_0(a_t | s_t) = \text{Uniform}(a_t)$




# Policy gradients as inference

## Variational lower bound

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \text{KL}(q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))$$

## Recovering policy gradients algorithm




- Consider  $\pi_0(a_t|s_t) = \text{Uniform}(a_t)$

$$\begin{aligned} \text{■ } \text{KL}(q_\pi(\mathbf{s}, \mathbf{a}), p_{\pi_0}(\mathbf{s}, \mathbf{a})) &= \mathbb{E}_{q_\pi} \left[ \log \frac{p(s_1) \prod_{t=1}^T \pi(a_t|s_t) p(s_{t+1}|s_t, a_t) \pi(a_T|s_T)}{p(s_1) \prod_{t=1}^T \pi_0(a_t|s_t) p(s_{t+1}|s_t, a_t) \pi_0(a_T|s_T)} \right] \\ &= \mathbb{E}_{q_\pi} \left[ \sum_{t=1}^T \log \pi(a_t|s_t) - \log \pi_0(a_t|s_t) \right] \\ &= \mathbb{E}_{q_\pi} [-\mathcal{H}(\pi(\cdot|s_t))] + \text{const} \end{aligned}$$

# Policy gradients as inference

## Variational lower bound


$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \text{KL}(q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))$$

## Recovering policy gradients algorithm


- Consider  $\pi_0(a_t|s_t) = \text{Uniform}(a_t)$

- $$\begin{aligned} \text{KL}(q_\pi(\mathbf{s}, \mathbf{a}), p_{\pi_0}(\mathbf{s}, \mathbf{a})) &= \mathbb{E}_{q_\pi} \left[ \log \frac{p(s_1) \prod_{t=1}^T \pi(a_t|s_t) p(s_{t+1}|s_t, a_t) \pi(a_T|s_T)}{p(s_1) \prod_{t=1}^T \pi_0(a_t|s_t) p(s_{t+1}|s_t, a_t) \pi_0(a_T|s_T)} \right] \\ &= \mathbb{E}_{q_\pi} \left[ \sum_{t=1}^T \log \pi(a_t|s_t) - \log \pi_0(a_t|s_t) \right] \\ &= \mathbb{E}_{q_\pi} [-\mathcal{H}(\pi(\cdot|s_t))] + \text{const} \end{aligned}$$

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \alpha r_t + \mathcal{H}(\pi(\cdot|s_t)) \right] + \text{const}$$


# Policy gradients as stochastic EM

$$\nabla_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} r_{t+k} \right) \nabla_{\pi} \log \pi(a_t | s_t) + \nabla_{\pi} \mathcal{H}(q(\cdot | s_t)) \right]$$



# Policy gradients as stochastic EM

$$\nabla_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} r_{t+k} \right) \nabla_{\pi} \log \pi(a_t | s_t) + \nabla_{\pi} \mathcal{H}(q(\cdot | s_t)) \right]$$




Stochastic policy gradient

# Policy gradients as stochastic EM

$$\nabla_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} r_{t+k} \right) \nabla_{\pi} \log \pi(a_t | s_t) + \nabla_{\pi} \mathcal{H}(q(\cdot | s_t)) \right]$$


**Stochastic policy gradient**

- Sample a trajectory  $\hat{\mathbf{s}}_{1:T}, \hat{\mathbf{a}}_{1:T} \sim q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})$



# Policy gradients as stochastic EM

$$\nabla_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} r_{t+k} \right) \nabla_{\pi} \log \pi(a_t | s_t) + \nabla_{\pi} \mathcal{H}(q(\cdot | s_t)) \right]$$




## Stochastic policy gradient

- Sample a trajectory  $\hat{\mathbf{s}}_{1:T}, \hat{\mathbf{a}}_{1:T} \sim q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})$
- Estimate gradient w.r.t. policy parameters:

$$\tilde{\nabla}_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} \hat{r}_{t+k} \right) \nabla_{\pi} \log \pi(\hat{a}_t | \hat{s}_t) + \nabla_{\pi} \mathcal{H}(\pi(\cdot | \hat{s}_t))$$

# Policy gradients as stochastic EM

$$\nabla_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} r_{t+k} \right) \nabla_{\pi} \log \pi(a_t | s_t) + \nabla_{\pi} \mathcal{H}(q(\cdot | s_t)) \right]$$



## Stochastic policy gradient


- Sample a trajectory  $\hat{\mathbf{s}}_{1:T}, \hat{\mathbf{a}}_{1:T} \sim q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})$
- Estimate gradient w.r.t. policy parameters:

$$\tilde{\nabla}_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} \hat{r}_{t+k} \right) \nabla_{\pi} \log \pi(\hat{a}_t | \hat{s}_t) + \nabla_{\pi} \mathcal{H}(\pi(\cdot | \hat{s}_t))$$

- Model-free learning algorithm

# Policy gradients as stochastic EM

$$\nabla_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} r_{t+k} \right) \nabla_{\pi} \log \pi(a_t | s_t) + \nabla_{\pi} \mathcal{H}(q(\cdot | s_t)) \right]$$



## Stochastic policy gradient


- Sample a trajectory  $\hat{\mathbf{s}}_{1:T}, \hat{\mathbf{a}}_{1:T} \sim q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})$
- Estimate gradient w.r.t. policy parameters:

$$\tilde{\nabla}_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} \hat{r}_{t+k} \right) \nabla_{\pi} \log \pi(\hat{a}_t | \hat{s}_t) + \nabla_{\pi} \mathcal{H}(\pi(\cdot | \hat{s}_t))$$

- Model-free learning algorithm
- Known as REINFORCE [2] Williams, 1992

# Policy gradients as stochastic EM

$$\nabla_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} r_{t+k} \right) \nabla_{\pi} \log \pi(a_t | s_t) + \nabla_{\pi} \mathcal{H}(q(\cdot | s_t)) \right]$$




## Stochastic policy gradient

- Sample a trajectory  $\hat{\mathbf{s}}_{1:T}, \hat{\mathbf{a}}_{1:T} \sim q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})$
- Estimate gradient w.r.t. policy parameters:

$$\tilde{\nabla}_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_0}) = \sum_{t=1}^T \left( \alpha \sum_{k=0}^{T-t} \hat{r}_{t+k} \right) \nabla_{\pi} \log \pi(\hat{a}_t | \hat{s}_t) + \nabla_{\pi} \mathcal{H}(\pi(\cdot | \hat{s}_t))$$


- Model-free learning algorithm
- Known as REINFORCE [2] Williams, 1992
- Basis for the modern RL algorithms [3] Mnih et al, 2016

# Improving policy optimization





# Improving policy optimization

- Reward optimization can be a **very** hard optimization problem




# Improving policy optimization

- Reward optimization can be a **very hard** optimization problem
- Typical rewards vs time plot:




# Improving policy optimization




# Improving policy optimization

- Policy can change too fast




# Improving policy optimization

- Policy can change too fast
- We want to make small, reliable improvements



# Improving policy optimization


- Policy can change too fast
- We want to make small, reliable improvements
- Our lower bound has already all necessary ingredients



$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \text{KL}(q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))$$

# Improving policy optimization


- Policy can change too fast
- We want to make small, reliable improvements
- Our lower bound has already all necessary ingredients



$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \boxed{\text{KL}(q_\pi(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))}$$

# Improving policy optimization

- Policy can change too fast
- We want to make small, reliable improvements
- Our lower bound has already all necessary ingredients




$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(s_{1:T}, a_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \boxed{\text{KL}(q_\pi(s_{1:T}, a_{1:T}) || p_{\pi_0}(s_{1:T}, a_{1:T}))}$$

- Looking a bit closer:  $\text{KL}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q_\pi(s_{1:T})} \sum_{t=1}^T \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t))$

# Improving policy optimization


- Policy can change too fast
- We want to make small, reliable improvements
- Our lower bound has already all necessary ingredients




$$\mathcal{L}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T})} \left[ \alpha \sum_{t=1}^T r_t \right] - \boxed{\text{KL}(q_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) || p_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}))}$$

- Looking a bit closer:  $\text{KL}(q_{\pi}, p_{\pi_0}) = \mathbb{E}_{q_{\pi}(\mathbf{s}_{1:T})} \sum_{t=1}^T \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t))$
- Use this constraint to prevent too rapid changes in the policy

# Stable iterative algorithm




# Stable iterative algorithm




- Initialize  $\pi_0$

# Stable iterative algorithm




- Initialize  $\pi_0$
- For each  $j = 1, 2, \dots$ :

# Stable iterative algorithm




- Initialize  $\pi_0$
- For each  $j = 1, 2, \dots$ :
- Obtain  $\pi_j \approx \arg \max_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_{j-1}})$

# Stable iterative algorithm




- Initialize  $\pi_0$
- For each  $j = 1, 2, \dots$ :
  - Obtain  $\pi_j \approx \arg \max_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_{j-1}})$
  - Repeat

# Stable iterative algorithm



- Initialize  $\pi_0$
- For each  $j = 1, 2, \dots$ :
  - Obtain  $\pi_j \approx \arg \max_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_{j-1}})$
  - Repeat
- Monotonically improves the (expected) return

# Stable iterative algorithm



- Initialize  $\pi_0$
- For each  $j = 1, 2, \dots$ :
  - Obtain  $\pi_j \approx \arg \max_{\pi} \mathcal{L}(q_{\pi}, p_{\pi_{j-1}})$
  - Repeat
- Monotonically improves the (expected) return
- Closely related to trust-region and proximal policy optimization

[4] Schulman et al, 2015

[8] Schulman et al, 2017

# Hierarchical Reinforcement Learning

# Hierarchical Reinforcement Learning

[https://en.wikipedia.org/wiki/Roller\\_skating](https://en.wikipedia.org/wiki/Roller_skating)



**Task: roller skating**

# Hierarchical Reinforcement Learning

[https://en.wikipedia.org/wiki/Roller\\_skating](https://en.wikipedia.org/wiki/Roller_skating)



**Task: roller skating**




**Low-level actions  
muscles control**

# Hierarchical Reinforcement Learning


[https://en.wikipedia.org/wiki/Roller\\_skating](https://en.wikipedia.org/wiki/Roller_skating)



Task: roller skating




Low-level actions  
muscles control




Macro-actions  
turn, gain speed, slow down

# RL with Options



[5] Sutton et al, 1999

# RL with Options



[5] Sutton et al, 1999


# RL with Options

Option-policy

$$o_t \sim \pi(o_t | s_t, o_{t-1})$$

Policy

$$a_t \sim \pi(a_t | s_t, o_t)$$



# Auxiliary variables in variational inference

## Augmented model and the lower bound

$$\begin{aligned}\log p(x) &= \log \int p(z)p(x|z)\tilde{q}(t|x, z)dzdt \\ &= \log \int \int q(t)q(z|t) \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z)dtdz \\ &\geq \int \int q(t)q(z|t) \log \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z)dtdz \\ &= \mathbb{E}_{q(t,z)} \left[ \log p(x|z) - \log \frac{q(t)}{\tilde{q}(t|x, z)} \right] - \mathbb{E}_{q(t)} \text{KL}(q(z|t)||p(z))\end{aligned}$$

# Auxiliary variables in variational inference

## Augmented model and the lower bound

- Latent variable  $z$ , observations  $x$

$$\begin{aligned}\log p(x) &= \log \int p(z)p(x|z)\tilde{q}(t|x, z)dzdt \\ &= \log \int \int q(t)q(z|t) \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z)dtdz \\ &\geq \int \int q(t)q(z|t) \log \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z)dtdz \\ &= \mathbb{E}_{q(t,z)} \left[ \log p(x|z) - \log \frac{q(t)}{\tilde{q}(t|x, z)} \right] - \mathbb{E}_{q(t)} \text{KL}(q(z|t)||p(z))\end{aligned}$$

# Auxiliary variables in variational inference

## Augmented model and the lower bound

- Latent variable  $z$ , observations  $x$
- Introduce auxiliary variables  $t$


$$\begin{aligned}\log p(x) &= \log \int p(z)p(x|z)\tilde{q}(t|x, z)dzdt \\ &= \log \int \int q(t)q(z|t) \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z)dtdz \\ &\geq \int \int q(t)q(z|t) \log \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z)dtdz \\ &= \mathbb{E}_{q(t,z)} \left[ \log p(x|z) - \log \frac{q(t)}{\tilde{q}(t|x, z)} \right] - \mathbb{E}_{q(t)} \text{KL}(q(z|t)||p(z))\end{aligned}$$

# Auxiliary variables in variational inference


## Augmented model and the lower bound

- Latent variable  $z$ , observations  $x$
  - Introduce auxiliary variables  $t$
  - Define a hierarchical approximation  $q(z) = \int q(t)q(z|t)dt$
- $$\begin{aligned}\log p(x) &= \log \int p(z)p(x|z)\tilde{q}(t|x, z)dzdt \\ &= \log \int \int q(t)q(z|t) \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z) dt dz \\ &\geq \int \int q(t)q(z|t) \log \frac{p(z)\tilde{q}(t|x, z)}{q(t)q(z|t)} p(x|z) dt dz \\ &= \mathbb{E}_{q(t,z)} \left[ \log p(x|z) - \log \frac{q(t)}{\tilde{q}(t|x, z)} \right] - \mathbb{E}_{q(t)} \text{KL}(q(z|t)||p(z))\end{aligned}$$

# Options as auxiliary variables




# Options as auxiliary variables



## Temporally extended execution

- Options enumerate policies:  $\pi(a_t|s_t, o_t) = \pi_{z_t}(a_t|s_t)$


# Options as auxiliary variables



## Temporally extended execution

- Options enumerate policies:  $\pi(a_t|s_t, o_t) = \pi_{z_t}(a_t|s_t)$
- Probability of continuing an option:  $q_{\text{cont}} = q_{\text{cont}}(s_t, o_{t-1})$

# Options as auxiliary variables




## Temporally extended execution

- Options enumerate policies:  $\pi(a_t|s_t, o_t) = \pi_{z_t}(a_t|s_t)$
- Probability of continuing an option:  $q_{\text{cont}} = q_{\text{cont}}(s_t, o_{t-1})$
- Choosing a policy:

$$\pi(o_t|s_t, o_{t-1}) = q_{\text{cont}}\delta(o_t - o_{t-1}) + (1 - q_{\text{cont}})q(o_t|s_t, o_{t-1})$$

# Options as auxiliary variables



## Temporally extended execution


- Options enumerate policies:  $\pi(a_t|s_t, o_t) = \pi_{z_t}(a_t|s_t)$
- Probability of continuing an option:  $q_{\text{cont}} = q_{\text{cont}}(s_t, o_{t-1})$
- Choosing a policy:

$$\pi(o_t|s_t, o_{t-1}) = q_{\text{cont}}\delta(o_t - o_{t-1}) + (1 - q_{\text{cont}})q(o_t|s_t, o_{t-1})$$

## Augmented approximate posterior

$$q(\mathbf{s}, \mathbf{o}, \mathbf{a}) = p(s_1)\pi(o_1|s_1) \prod_{t=1}^{T-1} [\pi(a_t|o_t)p(s_{t+1}|s_t, a_t)\pi(o_{t+1}|o_t, s_{t+1})] \pi(a_T|s_T, o_T)$$


# Options as auxiliary variables



**Augmented prior**

$$p_{\pi_0}(\mathbf{s}, \mathbf{o}, \mathbf{a}) = p(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t | s_t) p(s_{t+1} | s_t, a_t)] \pi_0(a_T | s_T) \tilde{q}(\mathbf{o} | \mathbf{s}, \mathbf{a})$$

# Options as auxiliary variables




**Augmented prior**

$$p_{\pi_0}(\mathbf{s}, \mathbf{o}, \mathbf{a}) = p(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t | s_t) p(s_{t+1} | s_t, a_t)] \pi_0(a_T | s_T) \tilde{q}(\mathbf{o} | \mathbf{s}, \mathbf{a})$$

- Reverse model is introduced

# Options as auxiliary variables




## Augmented prior

$$p_{\pi_0}(\mathbf{s}, \mathbf{o}, \mathbf{a}) = p(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t|s_t)p(s_{t+1}|s_t, a_t)] \pi_0(a_T|s_T) \tilde{q}(\mathbf{o}|\mathbf{s}, \mathbf{a})$$

- Reverse model is introduced
- Assume  $\tilde{q}(\mathbf{o}|\mathbf{s}, \mathbf{a}) = \prod_{t=1}^T \tilde{q}(o_t|\mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})$

# Options as auxiliary variables



## Augmented prior

$$p_{\pi_0}(\mathbf{s}, \mathbf{o}, \mathbf{a}) = p(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t|s_t)p(s_{t+1}|s_t, a_t)] \pi_0(a_T|s_T) \tilde{q}(\mathbf{o}|\mathbf{s}, \mathbf{a})$$


- Reverse model is introduced
- Assume  $\tilde{q}(\mathbf{o}|\mathbf{s}, \mathbf{a}) = \prod_{t=1}^T \tilde{q}(o_t|\mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})$

## Variational lower bound

$$\log p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{o}, \mathbf{a}) = \log \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{a}) \frac{p_{\pi_0}(\mathbf{s}, \mathbf{a}) \tilde{q}(\mathbf{o}|\mathbf{s}, \mathbf{a})}{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \right]$$

$$\geq \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi_{o_t}(\cdot|s_t) || \pi_0(\cdot|s_t)) - \log \frac{\pi(o_t|o_{t-1}, s_t)}{\tilde{q}(o_t|\mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})} \right]$$

# Options as auxiliary variables




**Reverse model**

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q(\mathbf{s}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t)) - \underline{\text{KL}(q(\cdot | \mathbf{s}, \mathbf{a}) || \tilde{q}(\cdot | \mathbf{s}, \mathbf{a}))} \right]$$

$$\log p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{o}, \mathbf{a}) \geq \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi_{o_t}(\cdot | s_t) || \pi_0(\cdot | s_t)) - \log \frac{\pi(o_t | o_{t-1}, s_t)}{\tilde{q}(o_t | \mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})} \right]$$

# Options as auxiliary variables




**Reverse model**

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q(\mathbf{s}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t)) - \underline{\text{KL}(q(\cdot | \mathbf{s}, \mathbf{a}) || \tilde{q}(\cdot | \mathbf{s}, \mathbf{a}))} \right]$$

$$\log p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{o}, \mathbf{a}) \geq \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi_{o_t}(\cdot | s_t) || \pi_0(\cdot | s_t)) - \log \frac{\pi(o_t | o_{t-1}, s_t)}{\tilde{q}(o_t | \mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})} \right]$$

# Options as auxiliary variables




## Reverse model

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q(\mathbf{s}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t)) - \underline{\text{KL}(q(\cdot | \mathbf{s}, \mathbf{a}) || \tilde{q}(\cdot | \mathbf{s}, \mathbf{a}))} \right]$$

- Not used in the original Options framework

$$\log p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{o}, \mathbf{a}) \geq \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi_{o_t}(\cdot | s_t) || \pi_0(\cdot | s_t)) - \log \frac{\pi(o_t | o_{t-1}, s_t)}{\tilde{q}(o_t | \mathbf{o}_{, \mathbf{s}, \mathbf{a}})} \right]$$

# Options as auxiliary variables




## Reverse model

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q(\mathbf{s}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t)) - \text{KL}(q(\cdot | \mathbf{s}, \mathbf{a}) || \tilde{q}(\cdot | \mathbf{s}, \mathbf{a})) \right]$$

- Not used in the original Options framework
- Without reverse model options are easier to ignore

$$\log p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{o}, \mathbf{a}) \geq \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi_{o_t}(\cdot | s_t) || \pi_0(\cdot | s_t)) - \log \frac{\pi(o_t | o_{t-1}, s_t)}{\tilde{q}(o_t | \mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})} \right]$$

# Options as auxiliary variables



## Reverse model

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q(\mathbf{s}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t)) - \text{KL}(q(\cdot | \mathbf{s}, \mathbf{a}) || \tilde{q}(\cdot | \mathbf{s}, \mathbf{a})) \right]$$


- Not used in the original Options framework
- Without reverse model options are easier to ignore

$$\log p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{o}, \mathbf{a}) \geq \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi_{o_t}(\cdot | s_t) || \pi_0(\cdot | s_t)) - \log \frac{\pi(o_t | o_{t-1}, s_t)}{\tilde{q}(o_t | \mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})} \right]$$

- Different forms are possible, e.g. forward:

$$\tilde{q}(\mathbf{o} | \mathbf{s}, \mathbf{a}) = \prod_{t=1}^T \tilde{q}(o_t | \mathbf{o}_{>t}, \mathbf{s}, \mathbf{a})$$

# Options as auxiliary variables



## Reverse model

$$\mathcal{L}(q_\pi, p_{\pi_0}) = \mathbb{E}_{q(\mathbf{s}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi(\cdot | s_t) || \pi_0(\cdot | s_t)) - \text{KL}(q(\cdot | \mathbf{s}, \mathbf{a}) || \tilde{q}(\cdot | \mathbf{s}, \mathbf{a})) \right]$$

- Not used in the original Options framework
- Without reverse model options are easier to ignore

$$\log p(\hat{\mathbf{R}} = 1 | \mathbf{s}, \mathbf{o}, \mathbf{a}) \geq \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{o}, \mathbf{a})} \left[ \sum_{t=1}^T \alpha r_t - \text{KL}(\pi_{o_t}(\cdot | s_t) || \pi_0(\cdot | s_t)) - \log \frac{\pi(o_t | o_{t-1}, s_t)}{\tilde{q}(o_t | \mathbf{o}_{<t}, \mathbf{s}, \mathbf{a})} \right]$$

- Different forms are possible, e.g. forward:

$$\tilde{q}(\mathbf{o} | \mathbf{s}, \mathbf{a}) = \prod_{t=1}^T \tilde{q}(o_t | \mathbf{o}_{>t}, \mathbf{s}, \mathbf{a})$$

- Practically, one can use K-step lookups

$$\tilde{q}(\mathbf{o} | \mathbf{s}, \mathbf{a}) = \prod_{t=1}^T \tilde{q}(o_t | \mathbf{o}_{t:t+K}, \mathbf{s}_{t-K:t+K}, \mathbf{a}_{t-K:t+K})$$

# Model-based RL

# Model-based RL




**Simulator  
(cheap)**

# Model-based RL




Simulator  
(cheap)



Real world  
(expensive)

# Learning model of environment




# Learning model of environment

## Model of environment

$$q(s_{t+1} | s_t, a_t)$$

Can be learned!



# Learning model of environment

**Model of environment**


$$q(s_{t+1} | s_t, a_t)$$

Can be learned!

**State transitions**

$$s_{t+1} \sim p(s_{t+1} | s_t, a_t)$$

Likely unknown



# Learning model of environment

**Model of environment**

$$q(s_{t+1} | s_t, a_t)$$

Can be learned!


$$r_t = r(s_t, a_t, s_{t+1}) \leq 0$$

Assume that reward is part of  
the observation

**State transitions**

$$s_{t+1} \sim p(s_{t+1} | s_t, a_t)$$

Likely unknown



# Learning model of environment

# Learning model of environment

## Prior

$$q_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = q(s_1) \prod_{t=1}^{T-1} [\pi_0(a_t | s_t) q(s_{t+1} | s_t, a_t)] \pi_0(a_T | s_T)$$

# Learning model of environment

## Prior

$$q_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \underbrace{q(s_1)}_{\text{Assumed environment model}} \prod_{t=1}^{T-1} [\pi_0(a_t | s_t) \underbrace{q(s_{t+1} | s_t, a_t)}_{\text{Assumed environment model}}] \pi_0(a_T | s_T)$$

# Learning model of environment

## Prior

$$q_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \underbrace{q(s_1)}_{\text{Assumed environment model}} \prod_{t=1}^{T-1} [\pi_0(a_t | s_t) \underbrace{q(s_{t+1} | s_t, a_t)}_{\text{Assumed environment model}}] \pi_0(a_T | s_T)$$

## Likelihood

$$p(\hat{\mathbf{R}}_{1:T} | \mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \prod_{t=1}^T p(\hat{R}_t = 1 | s_t, a_t, s_{t+1}) = \prod_{t=1}^T \exp(\alpha \cdot r_t)$$

Assume that reward is part of the observation

# Learning model of environment

## Prior

$$q_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \underbrace{q(s_1)}_{\text{Assumed environment model}} \prod_{t=1}^{T-1} [\pi_0(a_t | s_t) \underbrace{q(s_{t+1} | s_t, a_t)}_{\text{Assumed environment model}}] \pi_0(a_T | s_T)$$

## Likelihood

$$p(\hat{\mathbf{R}}_{1:T} | \mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \prod_{t=1}^T p(\hat{R}_t = 1 | s_t, a_t, s_{t+1}) = \prod_{t=1}^T \exp(\alpha \cdot r_t)$$

Assume that reward is part of the observation

## Approximate posterior

$$p_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = p(s_1) \prod_{t=1}^{T-1} [\pi(a_t | s_t) p(s_{t+1} | s_t, a_t)] \pi(a_T | s_T)$$

# Learning model of environment

## Prior

$$q_{\pi_0}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \underbrace{q(s_1)}_{\text{Assumed environment model}} \prod_{t=1}^{T-1} [\pi_0(a_t | s_t) \underbrace{q(s_{t+1} | s_t, a_t)}_{\text{Assumed environment model}}] \pi_0(a_T | s_T)$$

## Likelihood

$$p(\hat{\mathbf{R}}_{1:T} | \mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \prod_{t=1}^T p(\hat{R}_t = 1 | s_t, a_t, s_{t+1}) = \prod_{t=1}^T \exp(\alpha \cdot r_t)$$


Assume that reward is part of the observation

## Approximate posterior

$$p_{\pi}(\mathbf{s}_{1:T}, \mathbf{a}_{1:T}) = \underbrace{p(s_1)}_{\text{Real model}} \prod_{t=1}^{T-1} [\pi(a_t | s_t) \underbrace{p(s_{t+1} | s_t, a_t)}_{\text{Real model}}] \pi(a_T | s_T)$$

# Learning model of environment


## Variational lower bound



$$\begin{aligned}\mathcal{L}(p_\pi, q_{\pi_0}) = & \mathbb{E}_{p_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t - \text{KL}(p(\cdot|s_t, a_t) || q(\cdot|s_t, a_t)) \right] \\ & - \mathbb{E}_{p_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$

# Learning model of environment

## Variational lower bound




$$\begin{aligned}\mathcal{L}(p_\pi, q_{\pi_0}) = & \mathbb{E}_{p_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t - \text{KL}(p(\cdot|s_t, a_t) || q(\cdot|s_t, a_t)) \right] \\ & - \mathbb{E}_{p_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$

- Optimize the lower bound for both policy and model

# Learning model of environment

## Variational lower bound




$$\begin{aligned}\mathcal{L}(p_\pi, q_{\pi_0}) = & \mathbb{E}_{p_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t - \text{KL}(p(\cdot|s_t, a_t) || q(\cdot|s_t, a_t)) \right] \\ & - \mathbb{E}_{p_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$

- Optimize the lower bound for both policy and model
- Share parameters between policy and model

# Learning model of environment

## Variational lower bound




$$\begin{aligned}\mathcal{L}(p_\pi, q_{\pi_0}) = & \mathbb{E}_{p_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t - \text{KL}(p(\cdot|s_t, a_t) || q(\cdot|s_t, a_t)) \right] \\ & - \mathbb{E}_{p_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$

- Optimize the lower bound for both policy and model
- Share parameters between policy and model
- Use simulated rollouts in the policy

# Learning model of environment

## Variational lower bound




$$\begin{aligned}\mathcal{L}(p_\pi, q_{\pi_0}) = & \mathbb{E}_{p_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t - \text{KL}(p(\cdot|s_t, a_t) || q(\cdot|s_t, a_t)) \right] \\ & - \mathbb{E}_{p_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$

- Optimize the lower bound for both policy and model
- Share parameters between policy and model
- Use simulated rollouts in the policy


Advanced usage in [7] Weber et al, 2017

# Learning from model of environment




# Learning from model of environment

- We would like to learn from simulations, i.e.  $q_{\pi}(s, a)$



# Learning from model of environment


- We would like to learn from simulations, i.e.  $q_\pi(s, a)$



$$\begin{aligned}\mathcal{L}(q_\pi, p_{\pi_0}) = & \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t + \log \frac{p(s_{t+1}|s_t, a_t)}{q(s_{t+1}|s_t, a_t)} \right] \\ & - \mathbb{E}_{q_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$

# Learning from model of environment

- We would like to learn from simulations, i.e.  $q_\pi(s, a)$




$$\begin{aligned}\mathcal{L}(q_\pi, p_{\pi_0}) = & \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t + \log \frac{p(s_{t+1}|s_t, a_t)}{q(s_{t+1}|s_t, a_t)} \right] \\ & - \mathbb{E}_{q_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$

- We might know  $q(s_{t+1}|s_t, a_t)$

# Learning from model of environment


- We would like to learn from simulations, i.e.  $q_\pi(s, a)$



$$\begin{aligned}\mathcal{L}(q_\pi, p_{\pi_0}) = & \mathbb{E}_{q_\pi(\mathbf{s}, \mathbf{a})} \left[ \alpha \sum_{t=1}^T r_t + \log \frac{p(s_{t+1}|s_t, a_t)}{q(s_{t+1}|s_t, a_t)} \right] \\ & - \mathbb{E}_{q_\pi(\mathbf{s})} \left[ \sum_{t=1}^T \text{KL}(\pi(\cdot|s_t) || \pi_0(\cdot|s_t)) \right]\end{aligned}$$


- We might know  $q(s_{t+1}|s_t, a_t)$
- But we don't know  $p(s_{t+1}|s_t, a_t)$

# Density ratio trick




# Density ratio trick

- Denote  $p(s_{t+1}|y_{t+1} = 1) = p(s_{t+1}|s_t, a_t)$   
 $p(s_{t+1}|y_{t+1} = 0) = q(s_{t+1}|s_t, a_t)$



# Density ratio trick




- Denote  $p(s_{t+1}|y_{t+1} = 1) = p(s_{t+1}|s_t, a_t)$

$$p(s_{t+1}|y_{t+1} = 0) = q(s_{t+1}|s_t, a_t)$$

- The density ratio can be written as

$$\begin{aligned}\frac{p(s_{t+1}|s_t, a_t)}{q(s_{t+1}|s_t, a_t)} &= \frac{p(s_{t+1}|y_{t+1} = 1)}{p(s_{t+1}|y_{t+1} = 0)} = \frac{p(y_{t+1} = 1|s_{t+1})p(s_{t+1})p(y_{t+1} = 0)}{p(y_{t+1} = 0|s_{t+1})p(s_{t+1})p(y_{t+1} = 1)} \\ &= \frac{p(y_{t+1} = 1|s_{t+1})}{p(y_{t+1} = 0|s_{t+1})} = \frac{p(y_{t+1} = 1|s_{t+1})}{1 - p(y_{t+1} = 1|s_{t+1})}\end{aligned}$$

# Density ratio trick



- Denote  $p(s_{t+1}|y_{t+1} = 1) = p(s_{t+1}|s_t, a_t)$

$$p(s_{t+1}|y_{t+1} = 0) = q(s_{t+1}|s_t, a_t)$$


- The density ratio can be written as

$$\begin{aligned}\frac{p(s_{t+1}|s_t, a_t)}{q(s_{t+1}|s_t, a_t)} &= \frac{p(s_{t+1}|y_{t+1} = 1)}{p(s_{t+1}|y_{t+1} = 0)} = \frac{p(y_{t+1} = 1|s_{t+1})p(s_{t+1})p(y_{t+1} = 0)}{p(y_{t+1} = 0|s_{t+1})p(s_{t+1})p(y_{t+1} = 1)} \\ &= \frac{p(y_{t+1} = 1|s_{t+1})}{p(y_{t+1} = 0|s_{t+1})} = \frac{p(y_{t+1} = 1|s_{t+1})}{1 - p(y_{t+1} = 1|s_{t+1})}\end{aligned}$$

- We can train a classifier to **discriminate** between imagined and real transitions

# Model-based learning

[10] Ho & Efron, 2017




# Model-based learning

Policy

$$a_t \sim \pi(a_t | s_t)$$

Agent-defined

[10] Ho & Efron, 2017



# Model-based learning

## Policy

$$a_t \sim \pi(a_t | s_t)$$


Agent-defined

[10] Ho & Efron, 2017

## State transitions

$$s_{t+1} \sim q(s_{t+1} | s_t, a_t)$$

Known




# Model-based learning

**Policy**

$$a_t \sim \pi(a_t | s_t)$$

Agent-defined



[10] Ho & Efron, 2017

**State transitions**

$$s_{t+1} \sim q(s_{t+1} | s_t, a_t)$$

Known

**Goal**

$$\max_{\pi} \mathbb{E}_{s_{1:T}, a_{1:T}} \sum_{t=1}^T r_t$$

# Model-based learning

[10] Ho & Efron, 2017

## Policy

$$a_t \sim \pi(a_t | s_t)$$

Agent-defined

## State transitions

$$s_{t+1} \sim q(s_{t+1} | s_t, a_t)$$


Known

## Goal

$$\max_{\pi} \mathbb{E}_{s_{1:T}, a_{1:T}} \sum_{t=1}^T r_t$$

## Rewards KL-corrected

$$r_t = r(s_t, a_t, s_{t+1}) - \underline{\text{KL}(q(\cdot | s_t, a_t) || p(\cdot | s_t, a_t))}$$



# Further reading

# Further reading

- Uncertainty over parameters

# Further reading

- Uncertainty over parameters
- Exploration

# Further reading

- Uncertainty over parameters
- Exploration
- Distributional RL

# Further reading

- Uncertainty over parameters
- Exploration
- Distributional RL
- Intrinsic motivation

# Further reading

- Uncertainty over parameters
- Exploration
- Distributional RL
- Intrinsic motivation
- Other picks on Hierarchical RL

# Further reading

- Uncertainty over parameters
- Exploration
- Distributional RL
- Intrinsic motivation
- Other picks on Hierarchical RL
- Other picks on Bayesian RL

# Further reading

- Uncertainty over parameters
- Exploration
- Distributional RL
- Intrinsic motivation
- Other picks on Hierarchical RL
- Other picks on Bayesian RL
- there are quite a few

# Further reading

- Uncertainty over parameters
- Exploration
- Distributional RL
- Intrinsic motivation
- Other picks on Hierarchical RL
- Other picks on Bayesian RL
- there are quite a few

See references!

# Thank you!

Questions?

# References

- [0] Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., ... & Petersen, S. (2015). Human-level control through deep reinforcement learning. *Nature*, 518(7540), 529-533.
- [1] Rawlik, K., Toussaint, M., & Vijayakumar, S. (2012, July). On stochastic optimal control and reinforcement learning by approximate inference. In *Robotics: science and systems*.
- [2] Williams, R. J. (1992). Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4), 229-256.
- [3] Mnih, V., Badia, A. P., Mirza, M., Graves, A., Lillicrap, T., Harley, T., ... & Kavukcuoglu, K. (2016, June). Asynchronous methods for deep reinforcement learning. In *International Conference on Machine Learning* (pp. 1928-1937).
- [4] Schulman, J., Levine, S., Abbeel, P., Jordan, M., & Moritz, P. (2015). Trust region policy optimization. In *Proceedings of the 32nd International Conference on Machine Learning (ICML-15)* (pp. 1889-1897).

# References

- [5] Sutton, R. S., Precup, D., & Singh, S. (1999). Between MDPs and semi-MDPs: A framework for temporal abstraction in reinforcement learning. *Artificial intelligence*, 112(1-2), 181-211.
- [6] Jaderberg, M., Mnih, V., Czarnecki, W. M., Schaul, T., Leibo, J. Z., Silver, D., & Kavukcuoglu, K. (2016). Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv: 1611.05397*.
- [7] Weber, T., Racanière, S., Reichert, D. P., Buesing, L., Guez, A., Rezende, D. J., ... & Pascanu, R. (2017). Imagination-Augmented Agents for Deep Reinforcement Learning. *arXiv preprint arXiv:1707.06203*.
- [8] Schulman, John, et al. "Proximal Policy Optimization Algorithms." *arXiv preprint arXiv: 1707.06347* (2017).
- [9] Huszár, Ferenc. "Variational Inference using Implicit Distributions." *arXiv preprint arXiv: 1702.08235* (2017).

# References

- [10] Ho, Jonathan, and Stefano Ermon. "Generative adversarial imitation learning." *Advances in Neural Information Processing Systems*. 2016.
- [11] Ghavamzadeh, M., Mannor, S., Pineau, J., & Tamar, A. (2015). Bayesian reinforcement learning: A survey. *Foundations and Trends® in Machine Learning*, 8(5-6), 359-483.
- [12] Houthooft, R., Chen, X., Duan, Y., Schulman, J., De Turck, F., & Abbeel, P. (2016). Vime: Variational information maximizing exploration. In *Advances in Neural Information Processing Systems* (pp. 1109-1117).
- [13] Bellemare, M. G., Dabney, W., & Munos, R. (2017). A distributional perspective on reinforcement learning. *arXiv preprint arXiv:1707.06887*.
- [14] Gregor, K., Rezende, D. J., & Wierstra, D. (2016). Variational Intrinsic Control. *arXiv preprint arXiv:1611.07507*.
- [15] Mohamed, S., & Rezende, D. J. (2015). Variational information maximisation for intrinsically motivated reinforcement learning. In *Advances in neural information processing systems* (pp. 2125-2133).