Power Management

LiPo Charger

Battery supervisor

1V8 regulator

SEL1 LOW => charge with 100mA
SEL1 HIGH => charge to 4.2V

Battery can do 500mA charging
however it requires the source to deliver 500mA.
USB hubs for example may only deliver 100mA.
Not sure what will happen in that case if set charger
to 500mA. Stay safe and use 100mA for now.

IMU with step counter, gesture detection etc.

Careful with rotation, if not put as default. SW axix swap is needed.
Right now placed upsidedown, hence this is adjusted in SW.

High accuracy pressure sensor

Magnetometer

Gas, Pressure, Temperature & Humidity

ESD protection

SWD pins will probably touch the skin, hence we need ESD protection.
Those are not for 1.8V, but they will limit significately and
then interna nRF chip ESD protection handles the rest(if I understand correctly).

Test Points

Pull-up/down resistors

Pull down all EN.
Battery is connected directly to some of those ICs
but since EN is pulled low and only set high by ANNA, they
will be off when battery is low (NORA shut off).

Display

Display backlight

9.53t gives I_{DD} 30mA (max)

Vibration motor (ERM Mode)

Microcontroller (NORA-B106/nRF5340)

Light sensor

Dock connector

GPIO

Buttons

External 16MB Flash

I2C addresses

BMI270	0x68
BMP581	0x46
BME688	0x76
LIS2MDLTR	0x1E
APDS-9306-065	0x52

github.com/jakkra/ZSWatch-HW

Sheet: /
File: ZSWatch.kicad_sch

Title: ZSWatch v2

Size: User	Date: 2023-09-25	Rev: 3
KiCad E.D.A. kicad 7.0.2		Id: #/1