

초도품 검사 기록서 (AS 9102)
First Article Inspection Record (AS 9102)

AS 9102 Rev A

Form 1 : Part Number Accountability

Sheet **1** of **1**

1. Part Number 115U7676-7	2. Part Name PANEL ASSY LWE-TE	3. Part Serial Number K0014	4. FAI Report Number QPI2243
5. Part Revision Level See the attached #1	6. Drawing Number See the attached #1	7. Drawing revision level See the attached #1	8. Additional Changes N/A
9. Manufacturing Process Reference 3554722	10. Organization Name KAL-ASD	11. Supplier Code 583971	12. P.O. Number N/A (Sub Assembly)
13. Detail FAI ☐ Assembly FAI ☒		14. Full FAI ☒ Partial FAI ☐	

Reason for Partial FAI / Baseline Part Number including revision Level:

First article on K0014 / Baseline P/N: 115U7676-1 Rev. A, FAI F3C010372

- a) if above part number is a detail part only, go to Field 19
b) if above part number is an assembly, go to the "INDEX" section below.

INDEX of part numbers or sub-assembly numbers required to make the assembly noted above.

15. Part Number	16. Part Name	17. Part Serial Number	18. Note
115U7676-809A	CLOTH KIT - BOND ASSY, LOWER TE	N/A	Cloth Kit
115U7686-11	CORE	N/A	
115U7686-13	CORE	N/A	
115U7686-15	CORE	N/A	
115U7686-17	CORE	N/A	
115U7686-19	CORE	N/A	
115U7686-33	WEDGE_INBD,PANEL ASSY, LWR TE	N/A	
115U7686-35	WEDGE_INBD,PANEL ASSY, LWR TE	N/A	
115U7686-37	WEDGE_OUTBD,PANEL ASSY, LWR TE	N/A	
115U7686-39	WEDGE_OUTBD,PANEL ASSY, LWR TE	N/A	
115U7686-41	WEDGE_OUTBD,PANEL ASSY, LWR TE	N/A	
BACN10JN3CM	NUT PLATE	N/A	
BACR15DR3AC4	RIVET	N/A	per MBD

Signature indicates that all characteristics are accounted for; meet drawing requirements or are properly documented for disposition.

Indicate if the FAI is complete per applicable QMS: ☐ FAI complete

☒ FAI not Complete
ANCR8989

19. Signature **J.D. Sous**


KE 2176

20. Date **15Jun2010**

21. Reviewed By

22. Date

23. Customer Approval

24. Date

Attachment #1 for Form 1 Drawing Revision Status

FAI Part Number: 115U7676-7

FAI Report Number: QPI2243

[illegible]

F-02-351 (1)

Rev. Date : 01 Nov 05



초도품 검사 기록서 (AS 9102)

First Article Inspection Record (AS 9102)

AS 9102 Rev A

Sheet 1 of 1

Form 2 : Product Accountability Raw Material, Specifications and Special Process(s), Functional Testing

1. Part Number 115U7676-7		2. Part Name PANEL ASSY LWE-TE		3. Part Serial Number K0014		4. FAI Report Number QPI2243	
5. Material or Process Name		6. Spec. No.	7. Code	8. Special Process Supplier Code (Name, Address)		9. CAV	10. CoC Number
BMS8-341,TY-2&3,,G R-1.0,,,FM-1,BMS5-1 54,TY2,CL1, GR3,CYTEC1515-3M ,IN,0^36,0,		BMS8-341 TY-3	N/A	QPL, Cytec		Yes	RIR #5011
GLASS FABRIC PREPREG		BMS 8-79 CL-4 GR-B	N/A	219561, Cytec		Yes	D1-4426 RIR #7782
STRUCTURAL ADHESIVES		BMS 5-129 TY-2 C-1A GR-5	N/A	196991, Cytec		Yes	D1-4426 RIR #6869
WHITE TEDLAR		TWH10BS3	N/A	BAC 5317, DuPont		N/A	RIR #05-2929
ADHESIVE		BMS 5-92 TY-1 CL-4	N/A	QPL, 3M		Yes	RIR #1302
ANTI-STATIC COATINGS		BMS 10-21 TY-3	N/A	QPL, PRC Desoto		Yes	RIR #5394
NONCHROMATED PRIMER		BMS 10-103 TY-1	N/A	QPL, PRC Desoto		Yes	RIR #9750
COMPOSITE PARTS		BAC 5317 GR-A, CL-D	N/A	583971, KAL-ASD BUSAN, KOREA		Yes	D1-4426
LOW TEMPERATURE CURED PARTS		BAC 5317-2 GR-A, CL-D	N/A	583971, KAL-ASD BUSAN, KOREA		Yes	D1-4426
ELECTRICAL BONDING		BAC 5117-13	N/A	N/A		N/A	N/A
GROUND STUD INSTALLATION		BAC 5117-3	N/A	N/A		N/A	N/A
BLIND FASTNER INSTALLATION		BAC 5063-3	N/A	N/A		N/A	N/A
PART MARKING		BAC 5307	N/A	N/A		N/A	N/A
SURFACE TEXTURE		BACD 2097	N/A	N/A		N/A	N/A
TEMPORARY PROTECTION		BAC 5034	N/A	N/A		N/A	N/A
ANTI-STATIC COATINGS		BAC 5639	N/A	N/A		N/A	N/A
NONCHROMATED PRIMER APPLICATION		BAC 5325	N/A	N/A		N/A	N/A
CLEANING, DEBURRING, AND FINISHING		BAC 5748	N/A	N/A		N/A	N/A
SOLVENT CLEANING		BAC 5750	N/A	N/A		N/A	N/A
PREPARING EXTERIOR		BAC 5837	N/A	N/A		N/A	N/A
ADHESIVES APPLICATION		BAC 5010	N/A	N/A		N/A	N/A
Laminar X-500 Off-White Surfacer		8-W-5 (Base)	N/A	BAC 5837, Dexter Aerospace		N/A	RIR #6474
NDI		BAC 5980	N/A	583971, KAL-ASD BUSAN, KOREA		Yes	D1-4426
Resin		BMS 8-301	N/A	QPL, HENKEL		Yes	RIR #6652
11. Functional Test Procedure Number		12. Acceptance report number, if applicable					
N/A		N/A					
13. Comments N/A							
14. Prepared By J.D. Sous				15. Date 15Jun2010			

F-02-351 (1)

Rev. Date : 01 Nov 05

1. FAI Part Number (and Engineering Part Number) 115U7676-7 (115U7676-9-A)				2. Part Name PANEL ASSY LWE-TE		3. Part Serial Number K0014	4. FAI Report Number QPI2243
Characteristic Accountability				Inspection / Test Results			
5. Char. No.	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designed Tooling	11. NCR Number	14. Notes
N1	Sheet2 [Page: 4]	Dimension.2	R1.56 +/- .03	R 1.57	N/A		
N2	Sheet2 [Page: 4]	Dimension.3	.153 +/- .010	.155	N/A		
N3	Sheet2 [Page: 5]	Text.2	5 X DIA0.375 +/-0.030 DRAIN HOLE	.374 ~ .377	N/A		
N4	Sheet5 [Page: 11]	Standard Notes	5SN0000007452 THE BOEING COMPANY	KE 2176 15Jun2010			
N5	Sheet5 [Page: 11]	Standard Notes	5SN0000007471 THE 3D GEOMETRY CONTAINED				
N6	Sheet5 [Page: 11]	Standard Notes	5SN0000007644 BOEING PROPRIETARY				
N7	Sheet5 [Page: 11]	Standard Notes	5SN0000007409 DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994				
N8	Sheet5 [Page: 11]	Standard Notes	5SN0000007996 DATA SET PER ASME Y14.41-2003				
N9	Sheet5 [Page: 11]	Standard Notes	5SN0000008431 SEE PL FOR LIST OF MATERIAL, USAGE AND NOTES				
N10	Sheet5 [Page: 11]	Standard Notes	5SN0000007995 THE CATIA DATA SET CONTAINING THE 3D GEOMETRY				
N11	Sheet5 [Page: 11]	Part Notes	5SN0000008414 115U7676-9 IS AN EXACT OPPOSITE OF 115U7676-10	Verified	N/A		
N30	Sheet6 [Page: 12]	Sequence10WPly1	Orientation 0 +/- 5 Deg.	0 Deg.	LP-115U7676-9		Rev. 01
N31	Sheet6 [Page: 12]	Sequence20WPly2	Orientation 45 +/- 5 Deg.	45 Deg.	↓		↓
N32	Sheet6 [Page: 12]	Sequence30WPly3	Orientation 0 +/- 5 Deg.	0.5 Deg.	↓		↓
N33	Sheet6 [Page: 12]	Sequence40WPly4	Orientation 45 +/- 5 Deg.	45.5 Deg.	↓		↓
N34	Sheet6 [Page: 12]	Sequence50WPly5	Orientation 0 +/- 5 Deg.	0.5 Deg.	LP-115U7676-9		Rev. 01

See Characteristic Designator

IP에 Char. No.를 일일이 기입하지 않기 위해 7번 Field의 Unique한 Char. Designator를 대신 Char. No.로 사용함

1. FAI Part Number (and Engineering Part Number) 115U7676-7 (115U7676-9-A)				2. Part Name PANEL ASSY LWE-TE		3. Part Serial Number K0014	4. FAI Report Number QPI2243
Characteristic Accountability				Inspection / Test Results			
5. Character. No	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designed Tooling	11. NCR Number	14. Notes
N35	Sheet6 [Page: 12]	Sequence60WPly6	Orientation 45 +/- 5 Deg.	45 Deg.	LP-115U7676-9		Rev. 01
N36	Sheet6 [Page: 12]	Sequence70WPly7	Orientation 0 +/- 5 Deg.	0 Deg.			
N37	Sheet6 [Page: 12]	Sequence90WPly8	Orientation 45 +/- 5 Deg.	46 Deg.			
N38	Sheet6 [Page: 12]	Sequence100WPly9	Orientation 45 +/- 5 Deg.	44.5 Deg.			
N39	Sheet6 [Page: 12]	Sequence110WPly10	Orientation 0 +/- 5 Deg.	0.5 Deg.			
N40	Sheet6 [Page: 12]	Sequence120WPly11	Orientation 45 +/- 5 Deg.	45 Deg.			
N41	Sheet6 [Page: 12]	Sequence130WPly12	Orientation 0 +/- 5 Deg.	0.5 Deg.			
N42	Sheet6 [Page: 12]	Sequence140WPly13	Orientation 45 +/- 5 Deg.	46 Deg.			
N43	Sheet6 [Page: 12]	Sequence150WPly14	Orientation 0 +/- 5 Deg.	0 Deg.			
N44	Sheet6 [Page: 12]	Sequence160WPly15	Orientation 45 +/- 5 Deg.	45 Deg.			
N45	Sheet6 [Page: 12]	Sequence170WPly16	Orientation 0 +/- 5 Deg.	0.5 Deg.	↓		↓
N46	Sheet6 [Page: 12]	Sequence180WPly17	Orientation 0	Accept Tedlar Film	LP-115U7676-9		Rev. 01
N47	PL	PL	See attached PL sheet, 115U7676-9 Rev. B	See attached PL sheet	N/A		
N48	Sheet 2 [Page 3]	Sequence80	Cores (Core Detail Location) +/- .10	-.09 ~ +.09	LP-115U7676-9		Rev. 01
N49	PSDL	PSDL	See attached PSDL sheet 115U7676	See attached PSDL sheet	N/A	ANCR8989	See FL 5 for Discrepancy
N50	BAC5639	BMS 10-21, TYPE III	Anti-static Coating Thickness 0.4~0.8 MILS	0.44~0.51 MILS	N/A		See PL, for Finish Sequence 2

See Characteristic Designator

See Characteristic Designator

F-02-351(2)

PARTS LIST	BOEING	CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676-9	REV B	SHEET 1 of 4	
LIST TITLE					MODEL	CONTRACT NUMBER		DATE
BOND ASSY - LOWER TRAILING EDGE, WBL 1116.00 - 1243.75								11-20-2009
THE PARTS LIST IN THIS REPORT SUPERSEDES THE DRAWING SHEET PARTS LIST FOR THIS PART								
OWNER WING, HUNG PHAM, (425)717-7683				PIN/ITEM 11-570300				
***** QPI2243, Char. No. 47 Attachment *****								
. . . REVISIONS . . .								
REV	REVISION DESCRIPTION	APPROVED DATE	CHANGE NUMBER	PHASE		CLASS		
B	REVISED PLY LAY-UP. REASON: NEGATIVE MARGIN ON WEIGHT SAVINGS LAY-UP. NBMT SIMILAR TO 115U7176-7 REV "A". PROD INFO: AIRPLANES/PARTS MUST COMPLY. MFG INFO: 4235, PRR86201-4 (SUPPL) NOSAR, IN-SEQ KAL PER CIR# WRC-E-4235-35664 INCORP AT 1433. RAYMOND E. FALKNER, E-BFDA, PLANNING, 425-717-2598, 11/18/09.	11-20-2009	PRR	86201-4		PRODUCTION		

. . . PART SPECIFIC DATA . . .								
NOTE TITLE		NOTE DESCRIPTION						
BREAK SHARP EDGES		✓ BREAK SHARP EDGES AND CORNERS TO A RADIUS OF .01 +/- .005 INCH. VISUALLY INSPECT ONLY.						
CORE LOCATION		✓ CORE LOCATION TOLERANCE PER 5317. Verified Accept KE 2176 15Jun2010						
DATASET FILENAME		115U7676-9 KE 2176 15Jun2010						
DATASET FILENAME		115U7676-9.1						
DATASET FILENAME		115U7676-9.2						
DATASET FILENAME		115U7676-9.3						
DRAWING		✓ 115U7676 SHEET DL See Char. No. 49, attachment KE 2176 15Jun2010						
FINISH - SEQUENCE 1		✓ F-14.696 PREPARE SURFACE IN ACCORDANCE WITH BAC 5837. TOOL SIDE AND EDGES. Verified						
FINISH - SEQUENCE 1		✓ F-25.01 APPLY NO FINISH, EXCEPT THAT TEMPORARY PROTECTION IN ACCORDANCE WITH BAC 5034 MAY Verified KE 2176 15Jun2010						
(CONTINUED ON NEXT PAGE)								
BOEING PROPRIETARY - SEE STANDARD NOTES FOR RESTRICTIONS ON DATA USE OR DISCLOSURE								

PARTS LIST	BOEING	CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676-9	REV B	SHEET 2 of 4
LIST TITLE BOND ASSY - LOWER TRAILING EDGE, WBL 1116.00 - 1243.75					MODEL	CONTRACT NUMBER	
						DATE 11-20-2009	

(CONTINUED FROM PRECEDING PAGE)

NOTE TITLE	NOTE DESCRIPTION		
	BE REQUIRED DURING HANDLING, TRANSPORTATION AND STORAGE. BAGSIDE.		
FINISH - SEQUENCE 2	✓ F-14.685 APPLY ONE COAT OF BMS 10-21, TYPE III ANTI-STATIC COATING IN ACCORDANCE WITH BAC 5639. TOOL SIDE. Verified KE 2176 15Jun2010		
FINISH - SEQUENCE 3	✓ F-14.692 APPLY ONE COAT OF BMS 10-103, TYPE I PRIMER IN ACCORDANCE WITH BAC 5325. TOOL SIDE AND EDGES. Verified KE 2176 15Jun2010		
MATERIAL IDENTIFIER AND TEST REQUIREMENTS CODE	C9200-002-N0		
OPPOSITE PART	115U7676-10 IS OPPOSITE TO 115U7676-9		
PLY ORIENTATION	✓ PLY ORIENTATION CONVENTION. ORIENT FABRIC WARP IN THE DIRECTION SHOWN IN THE COMPOSITE STACKING SEQUENCE. THE 0 AND 90 DEGREE ORIENTATIONS ARE INTERCHANGEABLE. THE +45 AND -45 DIRECTIONS ARE INTERCHANGEABLE. NO SPECIFIC ORIENTATION IS REQUIRED FOR ADHESIVE FILM AND TEDLAR REGARDLESS OF INFORMATION PROVIDED IN COMPOSITE STACKING. Verified KE 2176 15Jun2010		
PROCESS SPECIFICATION	✓ FABRICATE PER BAC 5317-2, GRADE A CLASS D. ALL EDGE BAND REGIONS SHALL BE CONSIDERED FAYING SURFACES. FIRST PART QUALIFICATION REQUIRED. Verified KE 2176 15Jun2010		
PROCESS SPECIFICATION	✓ MARK PARTS PER BAC 5307 CODE M Verified KE 2176 15Jun2010		
PROCESS SPECIFICATION	✓ SEE FLAGNOTE(S) OR PICTURE SHEET(S) FOR PROCESSING REQUIREMENTS PER BAC 5748 Verified KE 2176 15Jun2010		
PROCESS SPECIFICATION	✓ SURFACE ROUGHNESS 125 MICROINCHES RA IN BOND PART EDGES PER BACD 2097. 65 RA max. KE 2176 15Jun2010		
STORAGE REPOSITORY	DATASET IS STORED IN THE DATABASE REPOSITORY ENOVIA 747. KE 2176 15Jun2010		
SURFACE WAVINESS	✓ FAYING AND TOOLSIDE SURFACE WAVINESS NOT TO EXCEED .005 IN/IN. Accept visually KE 2176 15Jun2010		
UNDIMENSIONED FEATURE TOLERANCE	✓ UNDIMENSIONED FEATURE TOLERANCE +/- .03. -.01 ~ +.025 KE 2176 15Jun2010 KE 2176 15Jun2010		
* * * * * . . . COMPONENTS . . .			
QTY REQD	PART OR IDENTIFYING DESCRIPTION	NOTE TITLE	NOTE DESCRIPTION
PARENTHESIS () INDICATES SUBSTITUTE PART			
BOEING PROPRIETARY - SEE STANDARD NOTES FOR RESTRICTIONS ON DATA USE OR DISCLOSURE			

PARTS LIST	BOEING		CORPORATE OFFICES SEATTLE, WA 98124		EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676-9		REV B	SHEET 3 of 4
LIST TITLE							MODEL	CONTRACT NUMBER	DATE 11-20-2009	
BOND ASSY - LOWER TRAILING EDGE, WBL 1116.00 - 1243.75										
NUMBER										
1	115U7686-11	CORE - PANEL LOWER TRAILING EDGE, WBL 1116 TO WBL 1249								
1	115U7686-13	CORE - PANEL LOWER TRAILING EDGE, WBL 1116 TO WBL 1249								
1	115U7686-15	CORE - PANEL LOWER TRAILING EDGE, WBL 1116 TO WBL 1249								
1	115U7686-17	CORE - PANEL LOWER TRAILING EDGE, WBL 1116 TO WBL 1249								
1	115U7686-19	CORE - PANEL LOWER TRAILING EDGE, WBL 1116 TO WBL 1249								
1	N0000557	DUPONT; TWH10BS3 FILM	PROCESS SPECIFICATION	APPLY ONE LAYER OF 1 MIL WHITE TEDLAR TO THE BAGSIDE OF THE PART PER BAC 5317-2.						
1	NT091P977	BMS 8-79	SHEET	PLY ID	FILLER					
				SUBSTITUTION	NT091P977 HAS SUBSTITUTE NN843T429.					
(1)	(NN843T429)	BMS 8-79	SHEET	SUBSTITUTION	NN843T429 IS A SUBSTITUTE FOR NT091P977.					
				PLY ID	FILLER					
1	NT091P977	BMS 8-79	SHEET	PLY ID	FULL, DBLR					
PARENTHESIS () INDICATES SUBSTITUTE PART										
BOEING PROPRIETARY - SEE STANDARD NOTES FOR RESTRICTIONS ON DATA USE OR DISCLOSURE										

PICTURE SHEET DATA LIST	BOEING	CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676 SHEET DL	REV A	SHEET 1 OF 2																														
LIST TITLE BOND ASSY					MODEL	CONTRACT NUMBER																															
						DATE 04-25-2008																															
QPI2243, Char. No. 49 Attachment FLAGNOTES AND GEOMETRY RELATED NOTES IN THIS REPORT SUPERSEDE THE DRAWING SHEET PL FOR THIS DRAWING PIN/ITEM 11-570300 ***** REVISIONS <table><tr><td>REV</td><td>REVISION DESCRIPTION</td><td>APPROVED DATE</td><td>CHANGE NUMBER</td><td>PHASE</td><td>CLASS</td></tr><tr><td>A</td><td>ADDED FL3,4, AND 5</td><td>04-25-2008</td><td>PIN</td><td>11-570300</td><td></td></tr></table> RC501 ***** FLAGNOTES <table><tr><td>FLAG NOTE NUMBER</td><td>TITLE</td><td>DESCRIPTION</td></tr><tr><td>1</td><td>ROSETTE AXIS DEFINITION</td><td>✓ POSITIVE X-AXIS EQUALS 0 DEGREES. POSITIVE Y-AXIS EQUALS 90 DEGREES. Verified KE 2176 15Jun2010</td></tr><tr><td>2</td><td>PROCESS SPECIFICATION</td><td>✓ USE BMS 8-79, CLASS IV, GRADE B, STYLE 7781 OR 220 AS REQUIRED TO ACHIEVE EDGE BAND THICKNESS. FILLER PLIES ARE TO BE BUTTED OR OVERLAPPED ONTO HONEYCOMB CORE RAMP PER BAC 5317 Verified</td></tr><tr><td>3</td><td>PROCESS SPECIFICATION</td><td>✓ BOND WEDGE TO PANEL PER BAC 5010 TYPE 70 Verified KE 2176 15Jun2010</td></tr><tr><td>4</td><td>PROCESS SPECIFICATION</td><td>✓ BOND ADJACENT WEDGES TOGETHER PER BAC 5010 TYPE 70 FILL ANY VOIDS AT JOINT WITH SAME ADHESIVE AS REQUIRED. Verified KE 2176 15Jun2010</td></tr><tr><td>5</td><td>PROCESS SPECIFICATION</td><td>✓ NON-DESIGNATED BOND - INSTALL FASTENER ON BMS10-21, TYPE III (ANTI-STATIC COATING) SURFACE PER BAC 5117-13. CLEAN UNDERSIDE OF FASTENER HEAD PER SOLVENT CLEANING METHOD CM3. MAXIMUM RESISTANCE PER</td></tr></table> (CONTINUED ON NEXT PAGE) BOEING PROPRIETARY - SEE STANDARD NOTES FOR RESTRICTIONS ON DATA USE OR DISCLOSURE S/B: 300,000 ohm IS: 300,800 ohm max. ANCR8989 Verified KE 2176 16Jun2010								REV	REVISION DESCRIPTION	APPROVED DATE	CHANGE NUMBER	PHASE	CLASS	A	ADDED FL3,4, AND 5	04-25-2008	PIN	11-570300		FLAG NOTE NUMBER	TITLE	DESCRIPTION	1	ROSETTE AXIS DEFINITION	✓ POSITIVE X-AXIS EQUALS 0 DEGREES. POSITIVE Y-AXIS EQUALS 90 DEGREES. Verified KE 2176 15Jun2010	2	PROCESS SPECIFICATION	✓ USE BMS 8-79, CLASS IV, GRADE B, STYLE 7781 OR 220 AS REQUIRED TO ACHIEVE EDGE BAND THICKNESS. FILLER PLIES ARE TO BE BUTTED OR OVERLAPPED ONTO HONEYCOMB CORE RAMP PER BAC 5317 Verified	3	PROCESS SPECIFICATION	✓ BOND WEDGE TO PANEL PER BAC 5010 TYPE 70 Verified KE 2176 15Jun2010	4	PROCESS SPECIFICATION	✓ BOND ADJACENT WEDGES TOGETHER PER BAC 5010 TYPE 70 FILL ANY VOIDS AT JOINT WITH SAME ADHESIVE AS REQUIRED. Verified KE 2176 15Jun2010	5	PROCESS SPECIFICATION	✓ NON-DESIGNATED BOND - INSTALL FASTENER ON BMS10-21, TYPE III (ANTI-STATIC COATING) SURFACE PER BAC 5117-13. CLEAN UNDERSIDE OF FASTENER HEAD PER SOLVENT CLEANING METHOD CM3. MAXIMUM RESISTANCE PER
REV	REVISION DESCRIPTION	APPROVED DATE	CHANGE NUMBER	PHASE	CLASS																																
A	ADDED FL3,4, AND 5	04-25-2008	PIN	11-570300																																	
FLAG NOTE NUMBER	TITLE	DESCRIPTION																																			
1	ROSETTE AXIS DEFINITION	✓ POSITIVE X-AXIS EQUALS 0 DEGREES. POSITIVE Y-AXIS EQUALS 90 DEGREES. Verified KE 2176 15Jun2010																																			
2	PROCESS SPECIFICATION	✓ USE BMS 8-79, CLASS IV, GRADE B, STYLE 7781 OR 220 AS REQUIRED TO ACHIEVE EDGE BAND THICKNESS. FILLER PLIES ARE TO BE BUTTED OR OVERLAPPED ONTO HONEYCOMB CORE RAMP PER BAC 5317 Verified																																			
3	PROCESS SPECIFICATION	✓ BOND WEDGE TO PANEL PER BAC 5010 TYPE 70 Verified KE 2176 15Jun2010																																			
4	PROCESS SPECIFICATION	✓ BOND ADJACENT WEDGES TOGETHER PER BAC 5010 TYPE 70 FILL ANY VOIDS AT JOINT WITH SAME ADHESIVE AS REQUIRED. Verified KE 2176 15Jun2010																																			
5	PROCESS SPECIFICATION	✓ NON-DESIGNATED BOND - INSTALL FASTENER ON BMS10-21, TYPE III (ANTI-STATIC COATING) SURFACE PER BAC 5117-13. CLEAN UNDERSIDE OF FASTENER HEAD PER SOLVENT CLEANING METHOD CM3. MAXIMUM RESISTANCE PER																																			

PICTURE SHEET DATA LIST	BOEING	CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676 SHEET DL	REV A	SHEET 2 OF 2																								
LIST TITLE BOND ASSY					MODEL	CONTRACT NUMBER	DATE 04-25-2008																								
(CONTINUED FROM PRECEDING PAGE) <table><tr><td>FLAG NOTE NUMBER</td><td>TITLE</td><td>DESCRIPTION</td></tr><tr><td></td><td></td><td>BAC5117-13.</td></tr><tr><td></td><td></td><td>*****</td></tr><tr><td></td><td></td><td>. . . GEOMETRY RELATED NOTES . . .</td></tr><tr><td></td><td>TITLE</td><td>DESCRIPTION</td></tr><tr><td></td><td></td><td>NO APPLICABLE DATA EXISTS</td></tr><tr><td></td><td></td><td>*****</td></tr><tr><td></td><td></td><td>. . . STANDARD NOTES . . .</td></tr></table> NOTICE - THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO THE BOEING COMPANY AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OR USED FOR ANY PURPOSE EXCEPT WHEN SUCH USER POSSESSES DIRECT, WRITTEN AUTHORIZATION FROM THE BOEING COMPANY. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES DIMENSIONS AND SURFACE TEXTURE DESIGNATIONS APPLY BEFORE PLATING OR SURFACE FINISH COATING UNLESS OTHERWISE NOTED.								FLAG NOTE NUMBER	TITLE	DESCRIPTION			BAC5117-13.			*****			. . . GEOMETRY RELATED NOTES . . .		TITLE	DESCRIPTION			NO APPLICABLE DATA EXISTS			*****			. . . STANDARD NOTES . . .
FLAG NOTE NUMBER	TITLE	DESCRIPTION																													
		BAC5117-13.																													

		. . . GEOMETRY RELATED NOTES . . .																													
	TITLE	DESCRIPTION																													
		NO APPLICABLE DATA EXISTS																													

		. . . STANDARD NOTES . . .																													

1. FAI Part Number (and Engineering Part Number) 115U7676-7 (CA115U7676-7)				2. Part Name PANEL ASSY LWE-TE		3. Part Serial Number K0014	4. FAI Report Number QPI2243
Characteristic Accountability				Inspection / Test Results			
5. Character No	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designed Tooling	11. NCR Number	14. Notes
N1	Sheet 2 [Page: 5]	Text.18	12 X DIA .218/.229 HOLES THRU	.218 ~ .220	N/A		
N2	Sheet 2 [Page: 5]	Geometrical Tolerance.1	TRUP/D.014M	Accept per MOI	HRF 115U7676-3		Rev. C
N3	Sheet 2 [Page: 6]	Text.21	16 X DIA .218/.229 HOLES THRU	.218 ~ .221	N/A		
N4	Sheet 2 [Page: 6]	Geometrical Tolerance.2	TRUP/D.014M A B	Accept per MOI	HRF 115U7676-3		Rev. C
N5	Sheet 5 [Page: 9]	Joint definition 01	.098 - .101 /Qty132	.099 ~ .100	N/A		
N6	Sheet 5 [Page: 9]	Joint definition 02	.098 - .101 /Qty20	.099 ~ .100			
N7	Sheet 5 [Page: 9]	Joint definition 03	0.218 IN - 0.229 IN /Qty76	.221 ~ .223			
N8	Sheet 5 [Page: 9]	Sealant Definition 01	Fay Seal BMS 5-95, 115U7676-5 115U7686-33	Accept			per BAC 5010, FL3
N9	Sheet 5 [Page: 9]	Sealant Definition 02	Fay Seal BMS 5-95, 115U7676-5 115U7686-35	Accept			
N10	Sheet 5 [Page: 9]	Sealant Definition 03	Fay Seal BMS 5-95, 115U7676-5 115U7686-37	Accept			
N11	Sheet 5 [Page: 9]	Sealant Definition 04	Fay Seal BMS 5-95, 115U7676-5 115U7686-39	Accept			
N12	Sheet 5 [Page: 9]	Sealant Definition 05	Fay Seal BMS 5-95, 115U7676-5 115U7686-39	Accept			
N13	Sheet 5 [Page: 9]	Sealant Definition 06	Fay Seal BMS 5-95, 115U7686-33 115U7686-35	Accept			
N14	Sheet 5 [Page: 9]	Sealant Definition 07	Fay Seal BMS 5-95, 115U7686-39 115U7686-37	Accept			
N15	Sheet 5 [Page: 9]	Sealant Definition 08	Fay Seal BMS 5-95, 115U7686-41 115U7686-39	Accept			per BAC 5010, FL3
N16	Sheet 5 [Page: 9]	Joint definition 01	BACR15DR3AC5 / BACR15DR3AC5 Installation	Accept	N/A		

See Characteristic Designator

1. FAI Part Number (and Engineering Part Number) 115U7676-7 (CA115U7676-7)				2. Part Name PANEL ASSY LWE-TE		3. Part Serial Number K0014	4. FAI Report Number QPI2243
Characteristic Accountability				Inspection / Test Results			
5. Character No	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designed Tooling	11. NCR Number	14. Notes
N17	Sheet 5 [Page: 9]	Joint definition 02	BACR15DR3AC5 / BACR15DR3AC5 Installation	Accept	N/A		
N18	Sheet 5 [Page: 9]	Joint definition 03	BACR15DR3AC5 / Installation	N/A			Drill only holes per MBD
N19	PL	PL	See attached PL sheet, 115U7676-7 Rev. A	See attached PL sheet			
N20	BAC 5317-2	Autoclave Cure	BAC 5317-2	Accept			See attached cure chart summary Load No. L10-0029
N21	BAC 5317-2	NDI	BAC 5317-2 Class D, BAC 5980	Accept per PCP	N/A		PCP002-747-8 Rev. 02
요건 내용을 기입하는데 여백이 부족하면 Field 14 Notes 난에 기입							
All the characteristics/requirements within PL, PSDL, TSD, REP, Part Notes, CUSTOMER LETTER, Ply Group, or COP/COA should be verified individually (requirement by requirement), and then recorded respectively. Instead of direct recording in Form #3, document copy and attachment with individual requirement stamp-offs is allowed.							
PL, PSDL, TSD, PSS, REP, Part Notes, CUSTOMER LETTER, Ply Group, or COP/COA의 모든 요건들은 항목별로 개별 확인 후 기록되어야 한다. Form #3에 직접 기록하는 대신, 해당 문서를 복사하여 해당 항목에 개별 인장 날인 후 첨부하는 방법이 허용된다.						Verified By: KE 2176 15Jun2010	
12. Prepared By : J.D. Sous KE 2176				13. Date: 16Jun2010			

PARTS LIST	BOEING	CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676-7	REV A	SHEET 1 of 3	
LIST TITLE					MODEL	CONTRACT NUMBER		DATE
PANEL ASSY LWE-TE WBL 1116-1243.75								04-10-2009
THE PARTS LIST IN THIS REPORT SUPERSEDES THE DRAWING SHEET PARTS LIST FOR THIS PART								
OWNER WING, HUNG PHAM, 425-717-7683				PIN/ITEM 11-570300				
***** QPI2243, Char. No. 19 Attachment *****								
. . . REVISIONS . . .								
REV	REVISION DESCRIPTION	APPROVED DATE	CHANGE NUMBER	PHASE	CLASS			
A	REV NEW. NEW ASSY FOR WEIGHT SAVINGS PRR 86201-4. SIMILAR PART FOR NBMT APPROVAL 115U7676-1. REASON : INCORPORATE COMMITTED CHANGE.	04-10-2009	PRR	86201-4	PRODUCTION			
NA								

. . . PART SPECIFIC DATA . . .								
NOTE TITLE		NOTE DESCRIPTION						
DATASET FILENAME		115U7676-7						
DATASET FILENAME		CA115U7676-7						
DRAWING		✓ 115U7676 SHEET DL See Char. No. 49 of 115U7676-9, attachment						
MATERIAL IDENTIFIER AND TEST REQUIREMENTS CODE		C9200-002-N0						
OPPOSITE PART		115U7676-8 IS OPPOSITE TO 115U7676-7						
PROCESS SPECIFICATION		✓ INSTALL FASTENERS IN COMPOSITE PER BAC 5063. Verified KE 2176 16Jun2010						
PROCESS SPECIFICATION		✓ MARK PARTS PER BAC 5307 CODE M Verified KE 2176 16Jun2010						
PROCESS SPECIFICATION		✓ SURFACE ROUGHNESS 125 MICROINCHES RA IN BOND PART EDGES PER BACD 2097. 65 RA max. KE 2176 16Jun2010						
BOEING PROPRIETARY - SEE STANDARD NOTES FOR RESTRICTIONS ON DATA USE OR DISCLOSURE								

PARTS LIST	BOEING	CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676-7	REV A	SHEET 3 of 3
LIST TITLE PANEL ASSY LWE-TE WBL 1116-1243.75					MODEL	CONTRACT NUMBER	
						DATE 04-10-2009	
***** STANDARD NOTES NOTICE - THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO THE BOEING COMPANY AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OR USED FOR ANY PURPOSE EXCEPT WHEN SUCH USER POSSESSES DIRECT, WRITTEN AUTHORIZATION FROM THE BOEING COMPANY. MATERIALS, PART & PROCESS SUBSTITUTION AND EQUIVALENTS PER 65B88700 (747), 012T2100 (767), 012W6100 (777), 012W6101 (EVERETT LIAISON) AND 65-88700 (ALL OTHERS). FASTENER SYMBOL CODES PER BACD2074. INSTALL PER BAC5004 AND BAC5047 (FLUID TIGHT). SURFACE ROUGHNESS INTERPRETATION PER BACD2097. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. FOR DRAWING SHEETS DATED PRIOR TO 8/27/84: DIMENSIONING AND TOLERANCING PER ANSI Y14.5-1973. FOR DRAWING SHEETS DATED ON OR AFTER 8/27/84: DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982, UNLESS OTHERWISE NOTED ON DRAWING SHEET. UNLESS OTHERWISE SPECIFIED, RIVET & BOLT EDGE MARGINS PLUS OR MINUS .05. .02 max. KE 2176 16Jun2010 UNLESS OTHERWISE SPECIFIED, BEND RADII SHALL BE PLUS OR MINUS .01 INCH ON MATERIAL THICKNESS BELOW .06 INCH AND PLUS OR MINUS .03 ON MATERIAL THICKNESS GREATER THAN .06 INCH. UNLESS OTHERWISE SPECIFIED, SHEET METAL CORNER RADII SHALL BE .16 INCH TO .19 INCH ON INTERNAL RADII AND .00 INCH TO .25 INCH ON EXTERNAL RADII. DIMENSIONS AND SURFACE TEXTURE DESIGNATIONS APPLY BEFORE PLATING OR FINISH COATING UNLESS OTHERWISE NOTED. UNLESS OTHERWISE SPECIFIED, FABRICATION, ASSEMBLY, AND INSTALLATION SHALL CONFORM TO THE FOLLOWING: BAC5009 FOR INSTALLATION OF BOLTS AND NUTS. BAC5300 TO FORM, PUNCH, STRAIGHTEN, BREAK SHARP EDGES AND FIT METAL PARTS. BAC5307 FOR PART MARKING. BAC5602 FOR HEAT TREAT OF ALUMINUM ALLOYS.							