

초도품 검사 기록서 (AS 9102)
First Article Inspection Record (AS 9102)

Sheet 1 of 2

AS 9102 Rev A

Form 1 : Part Number Accountability

1. Part Number 488Z4880-402	2. Part Name FIREWALL INSTALLATION	3. Part Serial Number K0026	4. FAI Report Number QPI3044
5. Part Revision Level <i>See the attached #1</i>	6. Drawing Number <i>See the attached #1</i>	7. Drawing revision level <i>See the attached #1</i>	8. Additional Changes <i>N/A</i>
9. Manufacturing Process Reference <i>3818016</i>	10. Organization Name <i>KAL-ASD</i>	11. Supplier Code 867704	12. P.O. Number <i>N/A</i>
13. Detail FAI ☐ Assembly FAI ☒		14. Full FAI ☐ Partial FAI ☒	

Reason for Partial FAI

P-FAI :482Z8010-2 Rev. New 적용 사항 확인 .

**(Sealant 작업 시, Remove Exposed sealant from fay surface
seal squeeze out 수행).**

482Z8010-1에서 -2로 변경된 MBD에
대한 Partial인데 정보가 부족함

- a) if above part number is a detail part only, go to Field 19
b) if above part number is an assembly, go to the "INDEX" section below.

INDEX of part numbers or sub-assembly numbers required to make the assembly noted above

15. Part Number	16. Part Name	17. Part Serial Number	18. Note
482Z5111-11	FR10-SUPT_CLIP-FWD-LH	<i>K0026</i>	<i>N/A</i>
482Z5111-12	FR10-SUPT_CLIP-FWD-RH		
482Z6120-2	DR-SUPT-LONGN_FWD-EXT-RH		
482Z6120-901	DR-SUPT-LONGN_FWD-EXT-LH		
482Z6210-901	DR-SUPT-LONGN_FWD-FTG-UPR-LH		
482Z6210-902	DR-SUPT-LONGN_FWD-FTG-UPR-RH		
482Z6210-903	DR-SUPT-LONGN_FWD-FTG-LWR-LH		
482Z6210-904	DR-SUPT-LONGN_FWD-FTG-LWR-RH		
482Z6240-901	DR-SUPT-LONGN_FWD-EXT-FTG-LH		
482Z6240-902	DR-SUPT-LONGN_FWD-EXT-FTG-RH		
482Z6240-903	DR-SUPT-LONGN_FWD-EXT-FTG-LH		
482Z6240-904	DR-SUPT-LONGN_FWD-EXT-FTG-LH		
482Z7131-5	CLIP-LONGN-FWD-INBD		

Detail로 실제 호기가 지정되어
있지 않은데, FAI 수행 호기를
그대로 기입함. --> S/B N/A

FAI Complete ☒		FAI Not Complete ☐	
19. Signature <i>[Signature]</i>	20. Date 26 APR 2010	21. Reviewed By <i>[Signature]</i>	22. Date <i>3 May 2010</i>
23. Customer Approval <i>See the next page</i>		24. Date	

페이지가 반복되는 경우 맨 마지막
페이지에만 날인하는 것이 적함

F-02-351 (1)

초도품 검사 기록서 (AS 9102)
First Article Inspection Record (AS 9102)

Sheet 2 of 2

AS 9102 Rev A

Form 1 : Part Number Accountability

1. Part Number 488Z4880-402	2. Part Name FIREWALL INSTALLATION	3. Part Serial Number K0026	4. FAI Report Number QPI3044
INDEX of part numbers or sub-assembly numbers required to make the assembly noted above			
15. Part Number	16. Part Name	17. Part Serial Number	18. Note
482Z7131-6	CLIP-LONGN-FWD-OUTBD	K0026	N/A
488Z4880-401	FIREWALL ASSEMBLY		
488Z5101-3	APU-SUPT-BKUP-FTG-LWR-LH		
488Z5101-4	APU-SUPT-BKUP-FTG-LWR-RH		
488Z5204-1	APU-DR_DR_PAD		
BACS40R008C033F	SHIM,LAMINATED		
BACS40V008F008	SHIM, LAMINATED	↓	↓

FAI Complete ☒	
FAI Not Complete ☐	
19. Signature	20. Date 26 APR 2010
21. Reviewed By	22. Date 3 May 2010
23. Customer Approval	24. Date

F-02-351 (1)

Rev. Date : 27 APR 09

초도품 검사 기록서 (AS 9102)
First Article Inspection Record (AS 9102)

Sheet 1 of 3

AS 9102 Rev A

Form 2 : Product Accountability Raw Material, Specifications and Special Process(s), Functional Testing

1. Part Number 488Z4880-402	2. Part Name FIREWALL INSTALLATION	3. Part Serial Number K0026	4. FAI Report Number QPI3044
--------------------------------	--	--------------------------------	---------------------------------

5. Material or Process Name	6. Specification Number	7. Code	8. Special Process Supplier Name	9. Customer Approval Verification (Yes/No/NA)	10. Certificate of Conformance Number
BACB30MR4A18	N/A	N/A	N/A	N/A	08-3830
BACB30MR4A19					284598141443
BACB30NN3K6					2841915721127
BACB30NX6B4					9919
BACB30NX6B5					08-3865
BACB30NX6B6					2006-4154
BACB30NX6B7					286461751214210
BACB30NX6B8					B3-7
BACB30NX6K3					08-2057
BACB30NX6K4					08-6821
BACB30NX6K5					225701
BACB30NX6K6					08-0441
BACB30NX6K7					08-7000
BACB30NX8K3					200861811115392
BACB30NX8K4					08-3724
BACB30NY6B5					08-579
BACB30NY6B6					08-0576
BACB30NY6B7					080592
BACB30NY6B8					08-3829
BACB30NY6K4					08-3120
BACB30NY6K5					08-2879
BACB30NY6K6					08-0211
BACB30NY6K7					2006068

Partial 내용이 Sealant 관련 사항인데, 필요 없이 많은 정보를 기입함

11. Functional Test Procedure Number N/A	12. Acceptance Report Number, If Applicable N/A
13. Comments N/A	15. Date 26 APR 2010
14. Prepared By 	

F-02-351 (1)

Rev. Date : 27 APR 09

Form 3: Characteristic accountability, Verification and Compatibility Evaluation

1. Part Number 488Z4880-402(482Z8010_2 NEW)				2. Part Name FIREWALL INSTALLATION		3. Part Serial Number K0026	4. FAI Report Number QPI3044
Characteristic Accountability				Inspection / Test Results			
5. Char No	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designated Tooling	11. Non-Conformance Number	14. Notes
N01	SEQUENCE 200	Sealant Definition 02	REMOVE EXPOSE SEALANT	VERIFIED	N/A		PER BAC5000
N02	PL	PL	See attached PL sheet	See attached PL sheet	N/A		

All the characteristics/requirements within PL, PSDL, TSD, REP, Part Notes, CUSTOMER LETTER, Ply Group, or COP/COA should be verified individually (requirement by requirement), and then recorded respectively. Instead of direct recording in Form #3, document copy and attachment with individual requirement stamp-offs is allowed.

PL, PSDL, TSD, PSS, REP, Part Notes, CUSTOMER LETTER, Ply Group, or COP/COA의 모든 요건들은 항목별로 개별 확인 후 기록되어야 한다. Form #3에 직접 기록하는 대신, 해당 문서를 복사하여 해당 항목에 개별 인장 날인 후 첨부하는 방법이 허


12. Prepared By :



13. Date:

26 APR 2010

Verified By:



6 APR 2010

의미 이해 어려움

26 APR 2010
The remaining work 2043.
performing next FAI test
VOID.
BGSUN
KE

Partial 내용이 Sealant Squeeze-out 확인
사항인데, 관련 없는 내용이 기록됨

Extracted by Administrator (bgshin) from 482Z8010-2 on 2010-04-26, 오전 9:04:47

Note title	Note text
482Z8010-2W Mater N0000700 FIREWALL SEALANT KIT PER BMS 5-63 TYPE II	
482Z8010-2W Mater N0005266 POLYSULFIDE SEALANT KIT PER BMS 5-45 CLASS, GRADE AND FORM ARE OPTIONAL	
482Z8010-2W EOCN 9E991	
482Z8010-2W Stand 5SN0000007452 THE BOEING COMPANY, BOEING COMMERCIAL AIRPLANES, SEATTLE, WASHINGTON 98124	
482Z8010-2W Stand 5SN0000007995 THE CATIA DATASET CONTAINING THE 3D GEOMETRY, DIMENSIONS, TOLERANCES, AND ANNOTATION ALONG WITH ITS' RELATED DATA SPECIFY THE COMPLETE PRODUCT DEFINITION.	
482Z8010-2W Stand 5SN0000007644 BOEING PROPRIETARY - THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO THE BOEING COMPANY AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OR USED FOR ANY PURPOSE EXCEPT WHEN SUCH USER POSSESSES DIRECT, WRITTEN AUTHORIZATION FROM THE BOEING COMPANY.	
482Z8010-2W Stand 5SN0000007409 DIMENSIONING AND TOLERANCING PER ASME Y14.5M -1994.	
482Z8010-2W Stand 5SN0000007410 DIMENSIONS AND SURFACE TEXTURE DESIGNATIONS APPLY BEFORE PLATING OR FINISH COATING UNLESS OTHERWISE NOTED.	
482Z8010-2W Stand 5SN0000007407 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.	
482Z8010-2W Stand 5SN0000007996 DATA SET PER ASME Y14.41-2003.	
482Z8010-2W Stand 5SN0000007471 THE 3D GEOMETRY CONTAINED IN THE CATIA DATASET IS MODELED AT FULL SCALE AND AT THE NOMINAL CONDITION.	
482Z8010-2W Stand 5SN0000007939 787 PROGRAM SUBSTITUTIONS AND EQUIVALENTS SHALL BE IN ACCORDANCE WITH 787N9-2116 (MATERIALS, PROCESSES, AND MECHANICAL STANDARD PARTS); 787N3-3172 (ELECTRICAL STANDARDS); 787N3-3173 (FLUID SYSTEMS STANDARDS); AND 787N9-3174 (LIAISON).	
482Z8010-2W Part N F-14.9962 TREAT SCRATCHES AND OTHER SURFACES BARED AFTER APPLICATION OF FIRST COAT OF PRIMER BY MANUAL APPLICATION OF CHEMICAL CONVERSION COATING IN ACCORDANCE WITH BAC 5719, TYPE II, CLASS A. (FOR NON-ALUMINUM SURFACES PROCEED TO STEP 2.) CLEAN AND REACTIVATE PRIMER IN ACCORDANCE WITH BAC 5736 IN AREAS TO BE PAINTED. APPLY ONE COAT OF BMS 10-11, TYPE I, YELLOW PRIMER TO THE FASTENER HEADS, COLLARS, SCRATCHES, AND BARED SURFACES IN ACCORDANCE WITH BAC 5736. OVERSPRAY SHALL BE LIMITED TO	
482Z8010-2W Part N F-14.9964 CLEAN AND REACTIVATE PRIMER IN ACCORDANCE WITH BAC 5736 IN AREAS TO BE PAINTED. APPLY ONE COAT OF BMS 10-103, TYPE I PRIMER TO SCRATCHES AND BARED SURFACES IN ACCORDANCE WITH BAC 5325. OVERSPRAY SHALL BE LIMITED TO REACTIVATE AREAS	
482Z8010-2W Part N PartNote1 ARM DOES NOT HAVE AN OPPOSITE	
482Z8010-2W Part N PartNote2 UNLESS OTHERWISE NOTED WITHIN THE 3D CATIA DATASET, THE LOCATION OF ALL FASTENERS ARE SUBJECT TO A TOLERANCE OF +/- .030	
482Z8010-2W Part N PartNote3 UNLESS OTHERWISE SPECIFIED, MAINTAIN A MINIMUM EDGE DISTANCE OF 2X THE FASTENER DIAMETER ON METAL PARTS AND 2.5X THE FASTENER DIAMETER ON COMPOSITE PARTS	
482Z8010-2W Part N PartNote4 UNLESS OTHERWISE WITHIN THE 3D CATIA DATASET, THE LOCATION OF ALL PARTS ARE SUBJECT TO A PROFILE TOLERANCE OF .060 MMC WITH RESPECT TO DATUM A (PRIMARY), DATUM B (MMC [IF APPLICABLE] SECONDARY), AND DATUM C (MMC [IF APPLICABLE] TERTIARY)	
482Z8010-2W Part N PartNote5 FOR FEATURES WITHOUT DISPLAYED DIMENSIONS AND/OR TOLERANCES IN THE CATIA DATASET: QUERY IS REQUIRED TO OBTAIN MODEL VALUES. LINEAR VALUES ARE ROUNDED TO TWO DECIMAL PLACES, EXCEPT THICKNESS IS ROUNDED TO THREE DECIMAL PLACES. ANGLES ARE IN DEGREES AND ROUNDED TO ONE DECIMAL PLACE	
482Z8010-2W Part N PartNote6 FAY SURFACE SEAL BOTH SIDES OF SHIMS AND FILLERS WITH BMS 5-45 PER BAC 5000	
482Z8010-2W Part N PartNote7 INSTALL FASTENERS WITH BMS 5-63, TY II SEALANT IN ACCORDANCE WITH BAC 5000, METHOD 3. APPLY TO FASTENERS COMMON TO TITANIUM / ALUMINUM JOINTS	

유사한 항목들을 묶어 날인하는 방법은 이해할 수 있으나,
요건이 전혀 다른 사항을 묶어 날인하는 건 형식적인 기록으로 오해 소지 있음

Note title	Note text
482Z8010-2WPart NPartNote8	SEE 483Z3101 MBD TO DEFINE DATUM TARGET FEATURES
482Z8010-2WPart NPartNote9	APPLY FILLET SEAL WITH BMS 5-63, TYPE II OVER FASTENER HEAD PER BAC 5000
482Z8010-2WPart NPartNote10	FIN SEQ F-14.9962 FOR METALLIC STRUCTURES AND FASTENERS
482Z8010-2WPart NPartNote11	FIN SEQ F-14.9964 FOR COMPOSITE STRUCTURES
482Z8010-2WPart NPartNote12	SHIM IF AND AS REQUIRED USING LAMINATED ALUMINUM SHIM STOCK, BACS40R(C)(F PER BAC 5430, TYPE I. PRE-FIT THE ASSEMBLY USING A MAXIMUM CLAMP-UP FORCE OF 10 POUNDS PER LINEAR FOOT APPLIED ALONG THE FASTENER CENTERLINE. MAXIMUM SHIM THICKNESS SHALL NOT EXCEED 0.047 INCHES FOR 3/16 INCH DIAMETER FASTENERS. LAMINATED PORTION OF SHIM SHALL HAVE A MAXIMUM THICKNESS OF 0.030 INCHES. PLUS TWO COAT OF BMS 10-11, TYPE I, PRIMER IN ACCORDANCE WITH BAC 5736 ON ALL SURFACES. IN ADDITION TO PRIMER, BAC 5000 TO BOTH SIDES OF SHIM
482Z8010-2WPart NPartNote FAYING	Partial 내용이 Sealant Squeeze-out 확인 사항인데, 관련 없는 내용이 기록됨 -29, -62 OR -90 PER BAC 5430, TYPE II. PLUS
482Z8010-2WPart N5PR0000001183	INSTALL FASTENERS PER BAC 5004-2
482Z8010-2WPart N5PR0000001618	FILLET SEAL WASHERS, NUTS AND/OR COLLARS WITH BMS 5-63 PER BAC 5000
482Z8010-2WPart N5PR0000002135	BREAK SHARP EDGES PER BAC 5300. INCLUDING FASTENER HOLES
482Z8010-2WPart N5PR0000002299	PROVIDE TEMPORARY PROTECTION PER BAC5034, AS REQUIRED
482Z8010-2WPart N5PR0000002788	FASTENER INSTALLATION AND HOLE REQUIREMENTS IN COMPOSITE PARTS PER BAC 5063
482Z8010-2WPart N5PR0000003544	PERMANENT STRAIGHT SHANK FASTENER INSTALLATION IN COMPOSITE STRUCTURES PER BAC
482Z8010-2WPart N5PR0000003556	BREAK THE EDGES OF FASTENER HOLES PER BAC 5492, CLASS 2
482Z8010-2WPart N5PR0000003896	DRILL HOLES PER BAC 5004-2
482Z8010-2WPart N5PR0000003983	INSTALL FASTENERS USING BMS 5-45 PER BAC 5000, METHOD 3
482Z8010-2WPart N5PR0000004113	REMOVE EXPOSED SEALANT FROM FAY SURFACE SEAL SQUEEZE OUT AROUND ENTIRE FOOTPRINT OF PART PER BAC 5000. URL
482Z8010-2WPart NCHANGE AUTHORIZATION CN-AA2158	
482Z8010-2WPart NPART REPLACEMENT PART 482Z8010-2 REPLACES 482Z8010-1.	
482Z8010-2WAnnot FL 1 5PR0000001115 MARK PARTS PER BAC 5307, CODE M.	
482Z8010-2WAnnot FL 2 FOR INFORMATION OF BUSHING INSTALLATION, SEE 482Z8011-1.	

유사한 항목들을 묶어 날인하는 방법은 이해할 수 있으나,
요건이 전혀 다른 사항을 묶어 날인하는 건 형식적인 기록으로 오해 소지 있음

QPI 3044

