

1. Manufacturing Number (MBD Number and Revision) 115U7676-7 (CA115U7676-7)				2. Part Name PANEL ASSY		3. Part Serial Number K0014	4. FAI Report Number SPR2243
Characteristic Accountability				Inspection / Test Results			
5. Char No	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designated Tooling	11. Non-Conformance Number	14. Notes
N1	Sheet 2 [Page: 5]	Text.18	12 X DIA .218/.229 HOLES THRU	.218 ~ .220	CALIPERS (1458)		KE 27 FEB 2010
N2	Sheet 2 [Page: 5]	Geometrical Tolerance.1	TRUP/D.014M	ACCEPT PER MPI	HRF 115U7676-3		KE 27 FEB 2010 REV/C
N3	Sheet 2 [Page: 6]	Text.21	16 X DIA .218/.229 HOLES THRU	.218 ~ .221	CALIPERS (1458)		KE 27 FEB 2010 REV/C
N4	Sheet 2 [Page: 6]	Geometrical Tolerance.2	TRUP/D.014M A B	ACCEPT PER MPI	HRF 115U7676-3		BAC 5063-3
N5	Sheet 5 [Page: 9]	Joint definition 01	- /Qty132	.098 ~ .101	CALIPERS (1458)		FL5, BAC 5119-13
N6	Sheet 5 [Page: 9]	Joint definition 02	- /Qty20	.098 ~ .101	"		KAL 검사원이 기록하는 경우 각 항목 별 날인은 불필요
N7	Sheet 5 [Page: 9]	Joint definition 03	- /Qty76	.218 ~ .229	"		
N8	Sheet 5 [Page: 9]	Sealant Definition 01	RAY SEAL (BMS 5-95)	ACCEPT	N/A		
N9	Sheet 5 [Page: 9]	Sealant Definition 02					BAC 5010, FL3
N10	Sheet 5 [Page: 9]	Sealant Definition 03					
N11	Sheet 5 [Page: 9]	Sealant Definition 04					
N12	Sheet 5 [Page: 9]	Sealant Definition 05					
N13	Sheet 5 [Page: 9]	Sealant Definition 06					FL4
N14	Sheet 5 [Page: 9]	Sealant Definition 07					FL4
N15	Sheet 5 [Page: 9]	Sealant Definition 08					BAC 5010, FL4
N16	Sheet 5 [Page: 9]	Joint definition 01	BACR15DR3AC5 / BACR15DR3AC5	ACCEPT	CALIPERS (1458) FLUENESS (10136)		BAC 5063-3

일반 측정기기를 사용하는 경우,
측정기기에 대한 정보 기록 불필요

1. Manufacturing Number (MBD Number and Revision) 115U7676-7 (CA115U7676-7)				2. Part Name PANEL ASSY		3. Part Serial Number K0014		4. FAI Report Number QPI2243	
Characteristic Accountability				Inspection / Test Results					
5. Char No	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designated Tooling	11. Non-Conformance Number	14. Notes		
N17	Sheet 5 [Page: 9]	Joint definition 02	BACR15DR3AC5 / BACR15DR3AC5 / BACN10JN3CM	ACCEPT	CALIPERS (1458) FLUSHNESS (10136)		BAC5063-3, ZLS, BAC5119-13		
N18	Sheet 5 [Page: 9]	Joint definition 03	BACR15DR3AC5 /	N/A	N/A	N/A	N/A		
N19	PL	PL	See attached PL sheet	See attached PL sheet	N/A		14JAH2010		
N20	BAC5317-2	AUTOCLAVE SURFACE ROUGHNESS	RESULT OF AUTOCLAVE CURING IS VERIFIED, see attached (PSDL) see attached PSDL sheet	see attached PSDL sheet	N/A		LOAD NO: L10-0029		
N21	PSDL	SURFACE ROUGHNESS	125 MICRONS (VISUALLY INSPECT)	97 R2 (MAX)	R GAGE		14JAH2010		
N22	PL	BREAK SHARP EDGES	.01 +/- .005 INCH	ACCEPT	N/A		27 FEB 2010		
N23	PL	115U7676					27 FEB 2010		
N24	PL	-7 PL	SEE ATTACHED PL SHEET	SEE ATTACHED PL	N/A		N/A		

Flushness를 측정할 경우 값을 기입

기록 불필요, N/A

중복

N/A 사유가 공금 (Hole Drilling 작업) MBD Error라면 QE에게 확인 후 조치 결과 기입 필요 타 공정서에서 수행한다면, 해당 내용 Note로 기입

필요 없이 기록만 복잡해짐 KAL 검사원이 기록한 경우, 공정서에 의해 기록자 확인 가능

1. Manufacturing Number (MBD Number and Revision) 115U7676-7 (115U7676-9)				2. Part Name PANEL ASSY		3. Part Serial Number K0014		4. FAI Report Number QPI 2243	
Characteristic Accountability				Inspection / Test Results					
5. Char No	6. Reference Location	7. Characteristic Designator	8. Requirement	9. Results	10. Designated Tooling	11. Non-Conformance Number	14. Notes		
N1	Sheet 2 [Page: 3]	Dimension.2	R1.56 +/- .03	???					
N2	Sheet 2 [Page: 3]	Dimension.3	.153 +/- .010	R 1.57	R. GAGE				
N3	Sheet 5 [Page: 6]	Part Note	5SN0000008414 Opposite Part	1.55	CALIPERS				
N4	Sheet 6 [Page: 7]	Sequence10WPly1	Orientation 0_90	VERIFIED	N/A				
N5	Sheet 6 [Page: 7]	Sequence70WPly7	Orientation 45_0/90	0°	LP-11547676-9.1KT REV 0°				
N6	Sheet 6 [Page: 7]	Sequence20WPly2	Orientation 45.0000deg	0°					
N7	Sheet 6 [Page: 7]	Sequence30WPly3	Orientation 0.0000deg	45°					
N8	Sheet 6 [Page: 7]	Sequence40WPly4	Orientation 45.0000deg	0.5°					
N9	Sheet 6 [Page: 7]	Sequence50WPly5	Orientation 45.0000deg 0/90	45.5°					
N10	Sheet 6 [Page: 7]	Sequence60WPly6	Orientation +45_-45	0°					
N11	Sheet 6 [Page: 7]	Sequence80WPly8	Orientation +45_-45	45.5°					
N12	Sheet 6 [Page: 7]	Sequence90WPly9	Orientation +45_-45	45°					
N13	Sheet 6 [Page: 7]	Sequence110WPly11	Orientation +45_-45	45°					
N14	Sheet 6 [Page: 7]	Sequence120WPly12	Orientation 45.0000deg 0/90	45°					
N15	Sheet 6 [Page: 7]	Sequence130WPly13	Orientation 45.0000deg	0°					
N16	Sheet 6 [Page: 7]	Sequence140WPly14	Orientation 0.0000deg	45°					

MBD CATPart -9.2 Rev. A를 반영하고 있지 않은 내용으로 인쇄 후 수정한 경우. QE에게 IP 수정하도록 전화 한통화 해 주세요!

PARTS LIST	BOEING		CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676-9	REV B	SHEET 2 of 4
LIST TITLE BOND ASSY - LOWER TRAILING EDGE. WBL 1116.00 - 1243.75						MODEL	CONTRACT NUMBER	
							DATE 11-20-2009	
(CONTINUED FROM PRECEDING PAGE)								
NOTE TITLE			NOTE DESCRIPTION					
			BE REQUIRED DURING HANDLING, TRANSPORTATION AND STORAGE. BAGSIDE.					
FINISH - SEQUENCE 2			F-14.685 APPLY ONE COAT OF BMS 10-21, TYPE III ANTI-STATIC COATING IN ACCORDANCE WITH BAC 5639. TOOL SIDE.					
FINISH - SEQUENCE 3			F-14.692 APPLY ONE COAT OF BMS 10-103, TYPE I PRIMER IN ACCORDANCE WITH BAC 5325. TOOL SIDE AND EDGES.					
MATERIAL IDENTIFIER AND TEST REQUIREMENTS CODE			C9200-002-N0					
OPPOSITE PART			115U7676-10 IS OPPOSITE TO 115U7676-9					
PLY ORIENTATION			PLY ORIENTATION CONVENTION. ORIENT FABRIC WARP IN THE DIRECTION SHOWN IN THE COMPOSITE STACKING SEQUENCE. THE 0 AND 90 DEGREE ORIENTATIONS ARE INTERCHANGEABLE. THE +45 AND -45 DIRECTIONS ARE INTERCHANGEABLE. NO SPECIFIC ORIENTATION IS REQUIRED FOR ADHESIVE FILM AND TEDLAR REGARDLESS OF INFORMATION PROVIDED IN COMPOSITE STACKING.					
PROCESS SPECIFICATION			FABRICATE PER BAC 5317-2, GRADE A CLASS D. ALL EDGE BAND REGIONS SHALL BE CONSIDERED FAYING SURFACES. FIRST PART QUALIFICATION REQUIRED.					
PROCESS SPECIFICATION			MARK PARTS PER BAC 5307 CODE M					
PROCESS SPECIFICATION			SEE FLAGNOTE(S) OR PICTURE SHEET(S) FOR PROCESSING REQUIREMENTS PER BAC 5748					
PROCESS SPECIFICATION			SURFACE ROUGHNESS 125 MICROINCHES RA IN BOND PART EDGES PER BACD 2097.					
STORAGE REPOSITORY			DATASET IS STORED IN THE DATABASE REPOSITORY ENOVIA 747.					
SURFACE WAVINESS			FAYING AND TOOLSIDE SURFACE WAVINESS NOT TO EXCEED .005 IN/IN.					
UNDIMENSIONED FEATURE TOLERANCE			UNDIMENSIONED FEATURE TOLERANCE +/- .03.					

. . . COMPONENTS . . .								
QTY REQD	PART OR IDENTIFYING	DESCRIPTION	NOTE TITLE	NOTE DESCRIPTION				
PARENTHESIS () INDICATES SUBSTITUTE PART								
BOEING PROPRIETARY - SEE STANDARD NOTES FOR RESTRICTIONS ON DATA USE OR DISCLOSURE								

GOOD

ACCEPT
 03 MAR 2010
 KE

ACCEPT
 04 MAR 2010
 KE

KE
 10 MAR 2010

KE
 10 MAR 2010

VERIFIED
 KE
 10 MAR 2010

FILM THK S/B: 0.4 ~ 0.8 MILS, IS: 0.44 ~ 0.51 MILS
 CONDUCTIVE RESISTANCE VALUE S/B: 300,000 Ω MAX
 FILM THK S/B: 0.3 ~ 0.8 MILS, IS: 0.37 ~ 0.51 MILS

IS: 9540 Ω
 OHM METER
 AF00004916

NOT ACCEPTABLE
 검사/확인 결과를 개별 기록해야 함
 수치는 결과를 수치로 기입

PARTS LIST	BOEING	CORPORATE OFFICES SEATTLE, WA 98124	EXPORT CONTROL COM	CAGE 81205	NUMBER 115U7676-7	REV A	SHEET 3 of 3
LIST TITLE					MODEL	CONTRACT NUMBER	
PANEL ASSY LWE-TE WBL 1116-1243.75						DATE 04-10-2009	

STANDARD NOTES

NOTICE - THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO THE BOEING COMPANY AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OR USED FOR ANY PURPOSE EXCEPT WHEN SUCH USER POSSESSES DIRECT, WRITTEN AUTHORIZATION FROM THE BOEING COMPANY.

MATERIALS, PART & PROCESS SUBSTITUTION AND EQUIVALENTS PER 65B88700 (747), 012T2100 (767), 012W6100 (777), 012W6101 (EVERETT LIAISON) AND 65-88700 (ALL OTHERS).

FASTENER SYMBOL CODES PER BACD2074. INSTALL PER BAC5004 AND BAC5047 (FLUID TIGHT).

SURFACE ROUGHNESS INTERPRETATION PER BACD2097.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.

FOR DRAWING SHEETS DATED PRIOR TO 8/27/84: DIMENSIONING AND TOLERANCING PER ANSI Y14.5-1973. FOR DRAWING SHEETS DATED ON OR AFTER 8/27/84: DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982, UNLESS OTHERWISE NOTED ON DRAWING SHEET.

UNLESS OTHERWISE SPECIFIED, RIVET & BOLT EDGE MARGINS PLUS OR MINUS .05.

UNLESS OTHERWISE SPECIFIED, BEND RADII SHALL BE PLUS OR MINUS .01 INCH ON MATERIAL THICKNESS BELOW .06 INCH AND PLUS OR MINUS .03 ON MATERIAL THICKNESS GREATER THAN .06 INCH.

UNLESS OTHERWISE SPECIFIED, SHEET METAL CORNER RADII SHALL BE .16 INCH TO .19 INCH ON INTERNAL RADII AND .00 INCH TO .25 INCH ON EXTERNAL RADII.

DIMENSIONS AND SURFACE TEXTURE DESIGNATIONS APPLY BEFORE PLATING OR FINISH COATING UNLESS OTHERWISE NOTED.

UNLESS OTHERWISE SPECIFIED, FABRICATION, ASSEMBLY, AND INSTALLATION SHALL CONFORM TO THE FOLLOWING:

BAC5009 FOR INSTALLATION OF BOLTS AND NUTS.

BAC5300 TO FORM, PUNCH, STRAIGHTEN, BREAK SHARP EDGES AND FIT METAL PARTS.

BAC5307 FOR PART MARKING.

BAC5602 FOR HEAT TREAT OF ALUMINUM ALLOYS.

Standard Notes는 해당되는
항목만 확인, 날인해야 함

NOT ACCEPTABLE

검사/확인 결과를 개별 기록해야 함
수치는 결과를 수치로 기입