

Quote No OF13000846/2

Date 27.06.2025

SHORT QUOTATION / OFFER



CUT E 350

CUSTOMER INFORMATION

엠앤씨전자 비나

M&C Electronics Vina

강영규 Manager / Purchasing Team

Lot J1, Que Vo Industrial Zone(Expend area),

Phuong Lieu Commune, Que Va District

160000 Vietnam


Quote No OF13000846/2
Product CUT E 350

EXECUTIVE SUMMARY

GF Machining Solutions Co. Ltd
5F, Main building, K-tower,
88, Iljik-ro, Manan-gu, Anyang-si,
Gyeonggi-do, Seoul 13901

Prepared by :

Deion JH Hwang
GF Machining Solutions
Phone:
E-mail: jh.hwang@georgfischer.com



CUT E 350



Item	Description	Quantity
MACHINE		
995.001.087	CUT E 350	1 PC
VARIANTS		
VAR.001	50Hz	1 PC
EDM.046	Wire guides 0.25	1 PC
W23.003	Chiller	1 PC
EDM.125	CUT E 350 Jobshop package	1 PC
OPTIONS		
W23.017	Centralized manual greasing for CUT E	1 PC
PACKING & DOCUMENTATION		
W23.004	Packing	1 PC
Contract type embedded with the machine		
CSP995011	Bronze - Recover fast	1 PC
Other service contracts		
200011529	My rConnect - Remote Access - Trial 1st year	1 PC
200011531	My rConnect - Live Data - Trial 1st year	1 PC

Quote No OF13000846/2

Product CUT E 350

Item	Description	Quantity
------	-------------	----------

THIRD PARTY PRODUCTS

913745500	AVR 20KVA	1 PC
913745600	Chiller 3RT	1 PC
913745907	Dial Indicator+Bracket	1 PC

Quote No OF13000846/2

Product CUT E 350

CONFIGURATION TOTAL

ADDITIONAL EQUIPMENT AND SERVICES

Item	Description	Quantity
Z100002	Air Dryer	1 PC
913746700	inland transportation	1 PC
913746900	installation hour 1day (8 hours)	2 PC
913747000	training hour 1day (8 hours)	3 PC

OFFER PRICE

USD 127.000

Freight charges are quoted on the basis of current estimates. Additional charges may apply in case market prices change significantly until actual transport occurs.

Quotation valid to 27.07.2025

Quote No OF13000846/2
Product CUT E 350

TERMS AND CONDITIONS

Delivery

계약 후 3~4 개월 이내

본 계약에서 납기라 함은 계약 목적물을 "매수인"이 정하는 장소에 "매도인"이 인도하는 시점을 말한다. 단, 원자재 공급, 노사분규, 차량 운송 사고, 정부의 조치 등 "매도인"의 납품 지연 사유와 납품 장소의 완공 지연, 부대 시설 미비, 노사분규, 천재지변에 의한 "매수인"의 인수 지연 사유가 발생할 시 상호 협의하여 인도 시기를 연장할 수 있다.

"매수인"은 지연이 "매도인"의 잘못으로 인해 발생했으며 "매수인"이 그러한 지연으로 인해 손실을 입었다는 사실이 입증될 수 있는 한 지연된 배송에 대해 청산된 손해배상을 청구할 수 있다. 다만 고객에게 대체 자재를 공급할 수 있는 경우, 후자는 지연에 대한 손해배상을 청구할 수 없다. 배송 지연에 대한 손해배상은 매주 지연될 때마다 0.5%를 초과해서는 안 되며, 어떤 경우에도 지연된 공급물품 계약 가격의 5%를 초과할 수 없다. 지연의 첫 2주 동안은 어떠한 손해배상도 지급되지 않는다. 지연은 이 조항에 명시적으로 규정된 권리와 청구권 외에 고객에게 어떠한 권리와 청구권도 부여하지 않는다.

Prices

본선 인도 조건

계약물품의 인도방법은 "매수인"이 지정한 선박에 "매도인"이 약속한 화물을 적재, 본선상에서 화물의 인도를 마칠때까지로 한다.

Payment

계약금: 계약시 30%

중도금: 납품시 60%

잔금: FAC후 10%

"매수인"은 본 계약물의 인수 후 대금 지불 조건대로 대금 지불을 이행하여야 한다. 대금의 지불 수단이 어음인 경우, 그에 상응하는 담보를 "매도인"에게 제공한다. "매수인"의 대금 지불 및 수금에 대한 제반사항은 "매도인"이 수행하며, 은행자금 및 리스 자금으로 지불시에는 반드시 "매도인"에게 지불한다. "매수인"이 본 계약의 대금 지불, 일자 및 지불 조건을 이행하지 못하였을 경우, "매도인"은 "매수인"에게 연리 5%의 연체 이자를 청구할 수 있다.

무역 관세 정책의 불확실성과 관련된 GF Machine Solutions의 판매 조건 변경

"판매자는 정부의 조치(수입/수출 관련 비용, 관세, 기타 제세공과금의 변경을 포함하되 이에 한정되지 아니함)로 인해 견적상 상품 가격에 영향을 미치는 사정이 발생한 경우, 선적 이전에 해당 가격을 조정할 수 있는 권리를 보유한다."

Warranty

설치 후 12개월

본 계약물의 품질보증기간은 "매도인"이 계약 물품을 "매수인"에게 인도한 날로부터 12개월 동안이나 이 기간중 "매수인"이 과실이나 고의에 의한 하자 발생시 상호 협의하여 유상처리한다.

Quote No OF13000846/2

Product CUT E 350

Reservation of title

1항 : "매수인"이 본 계약물에 대하여 대금 지불 조건을 이행하지 않을 경우 "매도인"의 서면 통지로 계약은 해지되며 "매수인"은 즉시 계약 목적물을 "매도인"에게 반환한다.

2항 : "매수인"은 본 계약물의 대금 완제시까지 "매도인"의 승인 없이는 물품을 제3자의 채무 변제를 하기 위한 저당 설정 등 어떠한 형태로의 처분도 할 수 없다.

3항 : "매수인"이 주소를 이전하였거나 "매도인"의 채권 보전 등 계약 이행에 영향을 미치는 사유가 발생하거나 발생할 우려가 있는 경우 "매수인"은 이를 즉시 "매도인"에게 통보하여야 한다.

Limitation of Liability

계약 또는 그 위반과 관련하여 "매수인"의 클레임이 존재 하는 경우, 청구 총액은 각 구매 주문서에 따라 "매수인"이 지불한 가격으로 제한된다. 특히 손해배상, 가격 인하, 계약 해지 또는 철회에 대해 명시적으로 언급되지 않은 클레임은 제외된다. 어떤 경우에도 "매수인"은 공급품의 결함을 시정하는데 드는 비용에 대한 보상 외에 손해배상을 청구할 수 없다. 이는 특히 생산 손실, 사용 손실, 주문 손실, 리콜 비용, 이익 손실 및 기타 직간접적 또는 결과적 손해를 의미하지만 이에 국한되지 않는다. 이러한 책임 제한은 공급업체의 중대한 과실 또는 고의적 위법 행위로 인한 책임이나 공급업체의 행위 또는 부작위로 인한 사망 또는 신체 상해에 대해서는 적용되지 않는다.

Quote No OF13000846/2

Product CUT E 350

Other conditions of sales

1항 : "매수인"은 "매도인"이 직접 또는 "매도인"의 의뢰에 따라 행하는 신용조사에 성실히 응해야 한다.

2항 : 본 계약서에 유첨되는 서류의 기재사항은 본 계약서의 약정사항과 동일한 효력을 가지며 본 계약서와 중복되는 조항은 본 계약서의 조항에 우선한다.

3항 : 본 계약에 명시되지 않은 사항은 일반 상관례에 따른다. 본 계약에 관하여 소송의 필요가 생긴 경우 "매도인"과 "매수인"이 합의하여 관할 법원을 지정할 수 있다. "매수인"과 "매도인"은 본 계약의 당사자로서 신의를 성실하게 이행한다.

4항 : MAS 기계 활성화 시스템 공급자는 계약 합의된 구매 가격의 전액 지불을 고객의 가장 필수적 의무로 간주한다. 따라서 여기에 명시 합의된 지불 조건과 관련하여 전액 지불하지 않거나 그 일부를 지불하지 않는 것은 본 계약의 중대한 위반으로 간주된다. 고객은 장비에 기계 활성화 시스템이 장착되어 있음을 알고 동의한다. 이 시스템을 통해 공급자는 기계 기능의 전부 또는 일부를 일시적 또는 영구적으로 비활성화 할 수 있다. 고객이 지불 불이행 상태에 있는 경우, 계약서에 동의한 대로 시간이 지남에 따라 기계 기능의 전부 또는 일부가 비활성화되어 코드를 입력하지 않는 한 기계가 작동하지 않을 수 있다. 공급자는 고객의 금액 지불로 계약 위반이 해결될 때까지 기계 활성화를 일시 중지할 권리가 있다. 기계 기능의 전체 또는 부분 비활성화는 15 일 전에 기계 화면에 메시지가 표시 되어 코드를 입력하지 않으면 기계가 비활성화 된다는 것을 고객에게 알린다. 이 알림은 기계 기능의 전체 또는 일부가 비활성화되기 전에 적어도 두 번 표시되어 기계가 작동하지 않을 때까지 남은 일수를 고객에게 알린다. 고객이 공급자에게 서면으로 품질 불만을 전달한 경우, 공급자는 합의된 모든 사양을 충족할 때까지 기계가 전체 기능을 유지하도록 보장한다. 공급자는 고객 클레임에 대한 적절한 조사 후 그러한 클레임이 근거가 없다고 합리적으로 결론을 내릴 경우, 기계의 전체 기능 활성화는 연장되지 않으며, 대금 지불 기한은 이후 15 일 또는 최초 만기일 중 더 늦은 날짜로 적용된다. 고객이 관할 법원에 클레임을 제기하지 않는 한 적용된다. 공급자는 이러한 조건에 따라 기계가 자동으로 비활성화될 경우, 비용 손실 또는 손상에 대해 책임지지 않는다. 고객은 시스템을 제거, 비활성화, 수정 또는 변경할 권한이 없다. 이를 위반하면 기계 보증이 무효화된다.

러시아 또는 벨라루스로 재수출 금지 조약

비 EU 국가에 사업장이 등록된 구매자가 EU이사회 규정 제12조 833/2014호 또는 제8조 2024/1865호의 범위에 해당하는 경우 다음 사항이 적용됩니다:

- (1) 구매자는 본 계약과 관련하여 공급된 물품 중 EU이사회 규정 제 833/2014 제12g조 또는 2024/1865 제8g조의 범위에 해당하는 물품을 러시아 연방 또는 벨라루스에 직접 또는 간접적으로 판매, 수출 또는 재수출하거나 러시아 연방 또는 벨로루시에서 사용하기 위해 판매, 수출 또는 재수출 하는것은 불가합니다.
- (2) 구매자는 (1)항의 목적이 리셀러를 포함하여 상업 체인의 하위에 있는 제3자에 의해 좌절되지 않도록 최선의 노력을 기울여야 합니다.
- (3) 구매자는 리셀러를 포함하여 상업 체인의 하위에 있는 제3자가 (1)항의 목적을 좌절시킬 수 있는 행위를 감지하기 위한 적절한 모니터링 메커니즘을 설정하고 유지해야 합니다.
- (4) (1), (2), (3)항의 위반은 본 계약의 필수 요소에 대한 중대한 위반으로 간주되며, 판매자는 다음을 포함하되 이에 국한되지 않는 적절한 구제책을 모색할 권리가 있습니다:
 - (i) 본 계약의 해지.
 - (ii) 본 계약의 총액의 20% 또는 수출된 상품 가격중 높은 금액의 위약금.
- (5) 구매자는 (1), (2), (3)항을 적용하는 데 문제가 있는 경우, (1)항의 목적을 좌절시킬 수 있는 제3자의 관련 활동을 포

Quote No OF13000846/2

Product CUT E 350

함하여 즉시 판매자에게 알려야 합니다. 구매자는 판매자가 (1), (2) , (3)항에 따른 해당 의무 준수 정보를 요청하는 경우 2주 이내에 판매자에게 제공해야 합니다.

Quote No OF13000846/2
Product CUT E 350

MACHINE DETAILS



CUT E 350 highlights

The CUT E 350 puts efficiency at the touch of your finger with a smart, easy-to-use human-machine interface UNIQUA and onboard technologies that streamline your job setup, improve your cutting speed, improve your surface finish, protect your valuable workpieces, and ensure your process robustness.

+ Power your performance

Your business performance is powered by machine performance, and our Intelligent Power Generator (IPG) boosts wide range expert technologies help you achieve the surface quality & precision your discerning customer's demand.

+ Accelerate your productivity.

Time saved is money in your pocket. Onboard speed technology package puts you on the fast track to provide excellent performances at an affordable price.

+ Benefit from our expertise

You benefit from GF Machining Solutions' legacy of more than 100 years of EDM expertise. ICP detects even the slightest abnormal forces and halts X, Y or Z axis movement in time to avoid damages and related costs.

+ Experience innovation

You're just one click away from machining perfect punches, dies, molds and parts, thanks to our intelligent, intuitive UNIQUA interface. Included are powerful tools for fast, safe machining preparation to make your machine

Quote No OF13000846/2

Product CUT E 350

programmer's life easier.

High performance of GFMS IPG Generator

The Swiss made IPG generator has state-of-the art powerful electronics to increase production output by utilizing efficiently controlled EDM processes that include FPGA technology.

With integrated fine surface module surfaces roughness of less than Ra 0.20 µm is achieved. Extremely high removal rates and low hourly running cost are possible with cheap brass wires (speed technology).

The generator has completely range of technologies including all materials needed for workshop.

The strategies for stepped work pieces machining and corner machining ensure accuracy and quality in whole profile of workpiece.

High accuracy T type mechanics

The T type base frame permits the loading of larger and heavy work pieces without affecting accuracy. The compact and rigid machine structure guarantees good positioning accuracy and highly repeatable results.

Direct measurement of positions by linear scales is used on X and Y axes.

The ICP system on XYZ axes prevents any breakage of sensitive parts and costly elements allowing the operator to work with more confidence during job preparation and execution.

The close clamping frame makes mounting workpiece easily.

The high axis travel speeds up to ease and fastened the manual preparation of the work piece & space

Proven Automatic Wire Threading

The concept of wire circuit is composed by very few components and consumable parts.

The automatic threading is rapid and reliable whatever the type of wire used with ThermoCut system.

Quote No OF13000846/2
Product CUT E 350

INCLUDED FEATURES

MACHINE

995.001.087 CUT E 350

Basic machine pack

CUT E 350

Set of wire guide Ø0.2 or Ø0.25 included

Packing included

Mechanics structure

T type of machine base, worktable moves along X axis and column moves along Y axis, UV slide is based on column, Z axis mounted on V slide, whole machine integrated mechanics, cabinet and dielectric unit and supported on a pallet.

XYUVZ axes

XYUVZ are CNC axes with high precision ball screw and guide way, servo motors are used for all axes, XY axes have dual measurement (linear glass scale and encoder), and UVZ with encoder, Integrated Collision Protection is available on XYZ axes, manual lubrication gun for the lubricating all axes.

Wire system

The wire feeding mechanism is located at the front of the machine. It can accept reels of 1.6 to 8 kg according to DIN standard K100, K125, K160.

The tension and the speed of the wire are permanently controlled by the CNC and can be programmed.

An electromagnetic brake ensures a constant wire tension.

The useful wire diameter: Ø0.10mm, Ø0.15mm, Ø0.20mm, Ø0.25mm, Ø0.30mm.

The wire is cut by thermal effect. This provides a tapered tip, which facilitates the threading into small start holes.

The ThermoCut is maintenance free and highly reliable threading system, it is able to thread brass as well as coated wire.

Automatic wire threading (AWT) system is as standard, suitable for wire diameter Ø0.10mm, Ø0.15mm, Ø0.20mm, Ø0.25mm, Ø0.30mm.

The used wire container is on the behind of the machine.

Working zone

The machine has a drop door as standard.

The working tank is designed to receive work piece up to 820*680*250mm and 400kg.

Submerged machining can be accomplished over the full 250 mm of the Z travel.

The internal side of the working tank is made of stainless steel. A safety device prevents opening the door while the tank is filled or prevents filling if the door is open.

A dielectric circulation ensures removal of eroded particles in the work tank.

Worktable

The working table consists of a closed frame in stainless steel. The thickness is 45 mm to ensure high rigidity. It is

Quote No OF13000846/2

Product CUT E 350

equipped with 76 M8 holes distributed all around the frame with a pitch of 50 mm.

Dielectric unit

The dielectric unit is integrated into the machine. The capacity of the system is 760 l of dielectric.

Deionization is regulated by deionizing bottle with resin about 20 liters.

High pressure flushing is supplied by a pump controlled by frequency converter, energy is saved.

The dielectric temperature is controlled by chiller.

The filtration consists of 2 paper filters with a total capacity of 45 m2 of filtration.

Digital IPG Generator

The Intelligent Power Generator is a digital power supply fully programmable.

A dedicated electronic circuit FPGA (Field Programmable Gate Arrays) includes the EDM know-how used to optimize in real time the sparking efficiency.

Anti-electrolysis setting is used during cutting.

The Corner Strategy is used during the machining to improve the geometry.

Console and remote control

19" TFT touch screen with adjustable position.

USB and Ethernet port is available.

The remote control has following functions: axis movement speed setting; filling and draining work tank; manual & automatic wire threading; return to start point and pause point; wire unspooling, Cutting wire, lamp.

Human Machine Interface UNIQUA

UNIQUA is the next generation of HMI for WEDM machine:

- Easy to use no matter what your previous background is.
- Available for sequential or dynamic programming.
- The unique dynamic processing in the market allows customers to win the competition.

The system is operating on windows 10. Five main modules provide an intuitive and fully logical process & execution process: Manager, Preparation, Manual, Execution and Services.

Manager:

Manage folders and files, create a new job and batches, send them to PREP or EXE modes.

Gives the possibility to organize the execution of a succession of jobs. Gives the possibility to organize the execution of a succession of jobs. Gives the status of each job executed and allows creating and storing job reports.

Preparation:

Define a completely new job. Modify an existing job. Verify the job before going to execution. Send a job to EXE mode.

Allows import or creation of geometries to be cut. Offers tables to store variables and points. Allows 3D graphic preview of the job execution.

Manual:

Access directly to the main machine functions. Perform manual measurements. Run manual movements. Perform manual machining.

Quote No OF13000846/2

Product CUT E 350

Allows setting and commanding Dielectric and Wire functions. Offers tables to store variables and points and displays machine variables. Allows selecting and loading of generator setting for manual machining, modifying setting's parameter. Offers numerous measuring cycles to allow part reference pick-up.

Execution:

Configure the execution of a job. Follow-up the execution of a job. Adjust some generator settings parameters.

Allows setting execution and machine parameters. Provides a Cockpit of the job execution.

Increases its productivity by using dynamic programming mode, this mode gives you the ability to easily work with batches (many parts) simultaneously by being able to change the execution strategy at any time with the goal of increasing productivity.

Services:

Manage consumables. Set machine configuration. Carry out calibration operations. Manages wire, deionization resins and filters consumption. Allows user to set preferences and adjust user's profile. Allows setting and calibrating machine functions, taking axis references. Displays the current configuration of the system and allows various update operation. Service Engineers tools. Management of pallets for automation. Allows set and activate e-connection functions.

Workspace:

With this Workspace page, we want to offer our customers all the smart features of the machine and software in the form of apps, as we use daily on our smart phones.

+GF+ Application available:

- User Technology database
- Custom Measure Profile
- Custom Strategy (Execution Strategy)
- EconoSuite
- and much more...

Chiller - Heat Exchanger:

The chiller is used to control the temperature of the dielectric, the cooling capacity is 5kW.

(Chiller not included into the EU configuration)

Machines with the heat exchanger require at least 7KW cooling capacity.

Europe: Machine is configured with Heat Exchanger Kit and Chiller (W23.022) is an option.

Standard configuration

Fine surface finish down to Ra<0.20µm

Automatic wire threading (AWT) and re-threading

Φ0.20 or Φ0.25 mm wire guide and brass wire

Linear glass scale for X and Y axes

Anti-collision for X, Y, Z axes

User's Manual Hard copy

Filter cartridges: G3/4, 450mm x Φ340mm x 2

Deionizing resin bottle (including 20L resin)

Quote No OF13000846/2

Product CUT E 350

Power Expert technology

Taper up to 30°

Keyboard and mouse

Connectivity:

Ready for Industry 4.0 thanks to optional GFMS OPC UA

VARIANTS

VAR.001 50Hz

Alternative current frequency of the generator

EDM.046 Wire guides 0.25

Wire guide diameter set included in the machine.

W23.003 Chiller

Chiller is used to control the dielectric temperature, the cooling capacity is 5KW.

EDM.125 CUT E 350 Jobshop package

Job shop package:

- Manual/Swivel door
- Console on the pedestal
- Technology standard Database (Best RA µm: Steel Ra0,30, Carbide Ra0,2)

OPTIONS

W23.017 Centralized manual greasing for CUT E

Centralized manual greasing for CUT E

PACKING & DOCUMENTATION

W23.004 Packing

The material of the pallet, lateral plates and the roof: solid wood

Contract type embedded with the machine

CSP995011 Bronze - Recover fast

Bronze is the way to get faster assistance through My rConnect.

You are guaranteed 1 hour callback on support requests, 24/5 access to expert technicians, and fast track service intervention scheduling to ensure quick diagnostics, uninterrupted production and efficient troubleshooting.

BRONZE

CSP000024 Yearly base contract

Quote No OF13000846/2

Product CUT E 350

CSP000008 Fast track for support

Fast response time through My rConnect for digital service requests within 60 minutes.

Fast service engineer dispatching for onsite interventions.

CSP000012 24/5 expert support through My rConnect

Remote support through My rConnect can be reached 24 hours a day, 5 days a week (Monday to Friday)

Other service contracts

200011529 My rConnect - Remote Access - Trial 1st year

Remotely access to your machine anytime, anywhere, to monitor its status and optimize your workflow via the My rConnect web platform. Additionally, you can authorize GF Machining Solutions technical support to troubleshoot your machine remotely. This secure service is available through an annual subscription.

200011531 My rConnect - Live Data - Trial 1st year

Stay informed about your machine status anytime, anywhere. Monitor machine status and operation progress, receive notifications for status changes, messages, or alarms, and react quickly without needing to visit your plant. Combined with Remote Access, you can also view your machine's user interface remotely. This feature is available through an annual subscription.

THIRD PARTY PRODUCTS

913745500 AVR 20KVA

913745600 Chiller 3RT

913745907 Dial Indicator+Bracket

ADDITIONAL EQUIPMENT AND SERVICES

Z100002 Air Dryer

913746700 inland transportation

913746900 installation hour 1day (8 hours)

913747000 training hour 1day (8 hours)

Quote No OF13000846/2

Product CUT E 350

SPECIFICATIONS

Machine		
Dimensions of complete equipment (width x depth x height)	1750 x 2470 x 2200 / 68.9 x 97.24 x 86.61	mm / in
Total weight of equipment without dielectric	2525 / 5567	kg / lbs
Work area		
Part dimensions	820 x 680 x 245 / 32.28 x 26.77 x 9.64	mm / in
Max. part weight	400 / 882	kg / lbs
Level of dielectric min.-max.	0-240 / 0-9.45)	mm / in
Air supply		
Pressure	6-7	bar
Min. flow	150 / 39.6	l/min / gal/min
Axes		
X, Y, Z Travel	350 x 250 x 250 / 13.78 x 9.84 x 9.84	mm / in
U, V Travel	±45 / ±1.77	mm / in
Taper angle/height	±30/50 or ±25/96 / ±30/2.20 or ±25/3.78	°/mm / °/in
X, Y, U, V, Z measurement resolution	0.1 / 3.94	µm / µ-inch
Speed of axis movement (X, Y, Z)	0-3000 / 0-118.1	mm/min / in/min
Anti-collision protection for axes	X, Y, Z	
Dielectric		
Type	Deionised water	
Total volume of dielectric	760 /200.77	l / gal
Filtering cartridges	2	
Deionization bottle (not standard)	1 / 0.26	l / gal
Deionization resin (not standard)	20 / 5.3	l / gal

Quote No OF13000846/2

Product CUT E 350

Electrode/Wire		
Standard wire guide	Ø0.20 or Ø0.25 / Ø0.008 or Ø0.010	mm / in
Wire diameter (according to configuration equipment)	Ø0.1-0.3 / Ø0.004-0.012	mm / in
Automatic threading for wires	Ø0.1-0.3 / Ø0.004-0.012	mm / in
Automatic rethreading for wires	Ø0.1-0.3 / Ø0.004-0.012	mm / in
Min. diameter of pre-hole for automatic threading	Ø0.2-0.3 / Ø0.008-0.012	mm / in
Max. height for automatic threading with 0.25mm / 0.010 in wire	220 / 8.66	mm / in
Permissible weights and types of reel	5 (JIS P5), 25 (DIN 160) / 11.02 (JIS P5), 55.11 (DIN 160)	kg / lbs
Best Ra Tungsten Carbide, Steel	0.14, 0.18 / 5.5, 7.09	µm / µ-inch
Max. machine cutting speed	300 / 0.46	mm2/min / in2/min
Cabinet		
Three-phase input voltage	400	V
Network frequency	50 or 60	Hz
Permissible fluctuations	±10%	
Total installed power	10	kVA
Permissible micro-break	4	ms
Power factor	0.8	
Screen/operating system	TFT 19"/Windows	
Keyboard	Yes	
Ethernet port USB	Yes	
Remote controle	Yes	
Ambient conditions		
Temperature for optimum accuracy	20 ±1 / 68 ±33.8	°C / °F
Temperature for operation of the equipment	15-30 / 59-86	°C / °F
Permissible relative humidity	40-80%	
Max. sound emission of the machine	76	Db(A)
Thermal stabilization time	3	h
Level of protection of electrical equipment	43	IP

Quote No OF13000846/2

Product CUT E 350

ENVIRONMENT AND SERVICE REQUIREMENTS

General technical features

Paint finish

Orange NCS S580-Y60R

White NCS S 1000-N

Electrical

3 x 400 Volt (permissible variation +/-10%, 50 or 60 Hz).

For other voltages a transformer is necessary.

Note: Inconsistent or unstable electrical power will adversely affect both machine performance and reliability. If the electrical power source is known to fluctuate in excess of specifications above, a power conditioner is required.

Compressed Air

6 to 9 bar, steady and uninterrupted supply, filtered and dry.

Temperature

Constant temperature: 68°F (20°C) with variations no more than 1°F (0.5°C) in anyone (1) hour period. Direct heat (sun, etc.) should be avoided. Avoid drafts - air velocity in room max. 1.6 ft./sec. (0.5m/sec.) and a maximum fluctuation of 4°F (2°C) in any 24-hour period to achieve the above-mentioned specifications.

Note: AC systems are designed to operate at ambient temperatures below 83°F (28°C). Operation at temperatures above this limit will result in deviations from specified form tolerance.

Vibration

Max. 0.1g (sporadic)

Max. 3 microns (continuous)

Important

Available mains supply (voltage, frequency, phases)

Air velocity in room: max. 0.5 m/s

Relative humidity: not exceeding 80 %.

Air velocity in room: max. 0.5 m/s

My rConnect

Digital services for all your GF machines, anytime, anywhere

My rConnect is your gateway to advanced digital assistance. This innovative web-based platform provides seamless access to a wide range of digital services to boost machine uptime and productivity. Enjoy simple navigation and direct access to GF support, for all connected and unconnected machines, regardless of their age.

Comprehensive and free-to-use asset management tool for all GF machines

 My rConnect



Organize your workshop and facilities, and manage user access



Use chat, video conferencing, whiteboard, and file transfer for rapid interaction and problem-solving



Manage and access the complete history of service cases for improved decision-making



Easily access machine user manuals in one place, and upload additional documentation

My rConnect

Connect your machine for greater responsiveness and operational efficiency

Get first-class support and real-time insight by subscribing to Remote Access and Live Data service offerings, available on-demand for eligible machines.

Do you want to increase your equipment uptime?



Remote Access

- Connect and share files to/from your machine from anywhere to solve issues efficiently
- Get expert troubleshooting from GF with remote access to your machine's HMI

Do you know if your machine is operating now?



Live Data

- Increase your responsiveness to unexpected events with real-time status notifications and instant alerts.
- Track machine connection and job status anywhere, anytime

Exclusive support when you need it most

Combining Remote Access and Live Data with Success Packs enhances responsiveness and optimizes uptime.

For more information, contact your local Sales Representative.

Bronze

Silver

Gold