

OFFER

offer no. : **MA262498**
 our order date : 24.04.2026
 account no. : 909343
 page : 1 / 14

M&C Electronics VINA Co., Ltd.
 Phuong Lieu Commune , Que Vo District
 Mr. Youn Choi Byoung
 Lot1 J1, Que Vo Industrial Zone

our contact : H. Bolsewig
 Phone : +49 5191/603406
 Email : bolsewig.hagen@roeders.de

Bac Ninh Province
 VIETNAM

PROJECT : 3-axes Precision Machine RXP500

pos.	item no.	description	quantity	PU	unit price EUR	total price EUR
10	M.P50000	3-axes Precision Machine RXP500	1		205.300,00	205.300,00
30	M.HB2000	Hand held pendant II	1		1.440,00	1.440,00
40	M.MMS100	Minimum lubrication	1		1.600,00	1.600,00
50	M.WSR100	Work piece cleaning	1		435,00	435,00
70	M.SVC1224100	Spindle MFW1224/42 HSK-E40	1		12.200,00	12.200,00
80	M.SK1000	Spindle compensation	1		10.200,00	10.200,00
90	M.WZW500100	Tool changer 500 linear	1		0,00	0,00
140	M.USV100	UPS 3-axes/RXD	1		1.240,00	1.240,00
150	M.ZA1000	Lift up Z-axis	1		1.240,00	1.240,00
160	MSWP035010	Remote Control via Teamviewer	1		1.730,00	1.730,00
180	MRDS0650	Initiation I	1			3.100,00
190	MRDS060100	Basic training I	1			3.940,00
200	M.VTRANSPORT/725	Transport charges	1			
.1	M.CIF101	CIF charges 400 / 500 / 601DS / 801	1		6.830,00	6.830,00
210	MTXTLCALLG	Additional services:	1		0,00	0,00

Total price EUR 249.255,00

Options

20	MSWRS0200	RMS6/SO - Surface Optimizer	1		1.620,00	1.620,00
60	M.SUF1230100	Spindle MFW1230/42 HSK-E40	1		0,00	0,00
100	M.WZW500220	Tool changer 500 HC	1		9.530,00	9.530,00
110	M.STWZW100	Manual door tool changer	1		0,00	0,00
120	MSWC025090	NC-Simulation RMSEdit/Sim	1		855,00	855,00
130	MSWC035090	Programming Software RMSEdit/Cam	1		855,00	855,00

OFFER

our order date : 24.04.2026
account no. : 909343
page : 2 / 14

170	M.OEN100	Oil mist suction mechanical 456	1	9.100,00	9.100,00
-----	----------	---------------------------------	---	----------	----------

OFFER

our order date : 24.04.2026
account no. : 909343
page : 3 / 14

10 3-axes Precision Machine RXP500

****** High speed milling machine with high stiffness for highest precision and surface quality in three linear axes. The NC control has been developed especially for high dynamics in 3D milling operations. Patented friction-free weight counterbalance in the Z-axis for optimal precision.

Machining range:

X-axis: 500 mm
Y-axis: 455 mm
Z-axis: 240 mm

The maximum height between spindle nose and the machine table is of approx. 450 mm.

Table:

T-slots 14 mm, distance 50 mm
Dimensions: 550 mm x 450 mm
The table must not be distorted by uneven work pieces

Weight of work piece:

400 kg maximum

Drives:

High dynamical linear motors in all axes with integrated cooling

Feed rates:

0 - 42.000 mm/min in all axes

Cabin:

Fully closed, two doors with safety glass, good view into working area, easy work piece loading by crane possible; for the automated loading of the machine an automatic door is available on request. Partial execution of the inner cabin lining with stainless steel. Maximum retention energy the cabin holds according to DIN EN 12417 is 400 J

Sealing:

All machine parts are protected against soiling, with an suitable industry cleaner graphite, cast iron and plastic can be machined. If a dust extraction is not supplied by Röders, machine-side preparations are needed for the machining of these materials, which that are not included with the machine.(Art.-Nr. M.SAS900)

Numerical control:

Roeders HSC control RMS6, latest version. Including

RMSEdit:

Programming editor for creating and modifying of NC programs.

OFFER

our order date : 24.04.2026
account no. : 909343
page : 4 / 14

RACECUT®:

Reduction of machining time by new control technology and 32kHz-drive regulation which allows an increase of jerk and acceleration.

Usage of ISO and Heidenhain®* programs (reduced set of commands, ,iTNC530) possible. For programming the simulation RMSEdit/Sim is recommended.

19" TFT screen; industrial PC with network adapter for the integration of the machine control into an Ethernet network by the customer.

The Röders NC control is based on a modern industrial computer with Microsoft Windows operating system. Especially in case of integrating the NC control into a local network the protection against viruses and cyber attacks is the responsibility of the customer.

* Heidenhain is a registered trademark of Dr. Johannes Heidenhain GmbH

3D-Touching probe automatic:

Data transmission via IR-Interface, several measuring cycles available in the machine control.

With thermostabilized HSK-cone to minimize heat transfer into the 3D probe after insertion into the warm milling spindle to reach higher measurement accuracies.

Renishaw probes and probes with HSK25 interface will be equipped with a standard cone.

Takes one place in the tool changer.

Laser for tool measuring:

Fixed in the tool changer, for automatic tool length correction, diameter and contour measurement, tool break and wear control

Tool cleaning device:

Nozzle for cleaning of milling tools by pressed air before measurement

Removal of chips:

Two collecting bins below the machine bed

Compressed-air pistol:

Connected to machine air supply

Cooling:

Chiller for tempering of spindle, drives and cabinet. Heat

OFFER

our order date : 24.04.2026
account no. : 909343
page : 5 / 14

removal to the ambient air. Dimensions depending on the equipment
Chiller for heat dissipation to an existing water circulation
on request.

Machinable materials:

All machinable materials can be machined. For dusting materials, such as graphite or ceramic, suitable, if necessary explosion-proof extraction and filtering systems are needed. Flammable materials such as plastics, wood, titanium or magnesium may only be treated with additional equipment for fire protection. This must be agreed with Röders before purchasing the machine. For the processing of hazardous substances, a separate hazard analysis is required.

Dimensions with cabinet and control panel:

W 2.710 x L 2.300 x H 2.350 mm

The maximum allowed unevenness of the floor over the installation area is 10 mm.

Dimensions for transport:

(Height without transport rolls, scantlings etc.)

W 2.020 x L 2.300 x H 2.280 mm

W 2.020 x L 2.300 x H 2.195 mm (without top cover)

The disassembling of the top cover is for additional surcharge.

Supplementary equipment might change the dimensions of the machine, also for transport.

Total weight:

Approx. 6.000 kg

Coloring:

Frame, terminal, sliding door: RAL 3003

Cabin, cabinet, cooling unit: RAL 7035

Chip bin: RAL 7024

For special coloring: see separate position

Connections:

Electrical: 400V +/- 5%, 32 A; connected power approx. 22 kVA

Adjusted for TN or TT network

Pneumatic: minimum 6,5 bar, standard consumption approx.

800 l/min during continuous operation

Necessary air quality, according to ISO 8573.1: Class 4

- Solid contaminants:

max. particle size 15 µm, max. particle density 8 mg/m³

- Total oil content: max. oil concentration 5 mg/m³

- Maximum pressure dew point: +3° Celsius

OFFER

our order date : 24.04.2026
account no. : 909343
page : 6 / 14

Surroundings:

Allowable ambient temperature 15°C - 35°C

Allowable relative humidity 20% - 80%, without condensation

The precision of the machine directly depends on the temperature constancy of the ambient temperature. For high accuracy requirements a temperature constancy of +/- 1° C is necessary. Insolation of the machine and its direct surrounding has to be avoided.

30 Hand held pendant II

For setting mode, allows the safe operation of the machine axes at open doors. Including monitor for displaying of machine coordinates and function keys for defined travel movements (e.g. in safety height)

40 Minimum lubrication

Cooler and lubricator with 2 two-component jets, no waste disposal necessary; recommended for the milling of metallic materials which will not be milled with emulsion.

The use of a mist extractor is recommended for minimal mist lubrication.

50 Work piece cleaning

Pressure air jet in the Z-axis for cleaning of the work piece by air; recommended when dusty materials are milled.

At two-spindle machines two nozzles will be mounted.

70 Spindle MFW1224/42 HSK-E40

High frequency milling spindle, vector controlled, FISCHER MFW1224/42, 100-42.000 1/min, 15 kW (S1), HSK-E40 tool interface, maximum tool diameter 16 mm, automatic tool change

For highest concentricity the HSK taper is ground after assembly of the spindle.

Additional price to the standard spindle

80 Spindle compensation

****** Contactless measuring of the dislocation of milling spindle and tool during milling operation, compensation in the machine control.

Not available for the milling spindles RSA60 and RSA80.

For machine types 400/500/600/900 the option Thermo package is recommended.

OFFER

our order date : 24.04.2026
account no. : 909343
page : 7 / 14

90 Tool changer 500 linear

Tool magazine accessible through the working area of the machine

Capacity:

HSK-E40 - RXP500: 21 places, RXP500DS(C): 19 places

140 UPS 3-axes/RXD

In case of a power failure the control PCs will be shut down automatically after a default time of approx. 5-10 minutes. The milling operation will be interrupted immediately.

150 Lift up Z-axis

In case of a power failure the z-axis of the machine will be lifted up in order to avoid damages of the work piece.

Only available in connection with the UPS and at the RXU1201DSH additional with the DEV - Dynamic Energy Supply Unit.

160 Remote Control via Teamviewer

Remote control of the machine by Röders service via Internet communication (Teamviewer).

The connection to the internet has to be arranged by the customer.

During the warranty period of the machine the use of the telemaintenance is free of charge. After that period Röders may invoice the use of this service at cost-price or by the use of a special telephone service number.

180 Initiation I

Travel charges of our technician on working days for car and train as well as accommodation costs are included in the a.m. price. Flight tickets will be charged, flight hours charged after the 5th hour of traveling at the below mentioned prices.

Röders will choose the most suitable means of travel.

OFFER

our order date : 24.04.2026
account no. : 909343
page : 8 / 14

190 Basic training I

The instruction and training takes place at the customer. It takes 3 days and contains the basical operation of the machine.

Additional travel expenses will not be charged if the training is combined with the initiation of the machine.

A training in Soltau can be offered on request.

200 Transport charges

.1 CIF charges 400 / 500 / 601DS / 801

CIF xxx seaport (according to INCOTERMS 2020)

OFFER

our order date : 24.04.2026
account no. : 909343
page : 9 / 14

210 Additional services:

Time of delivery:

RXP and RPT - Series 5 - 7 months
RXU and RHP - Series 8 - 12 months
after clarification of all technical and commercial details.
Shorter delivery time on request.

If an export license of the German BAFA is mandatory, the date of delivery depends also on the date of licensing.

Prices:

All prices in EURO, without VAT.

Payment:

1/3 down payment upon receipt of order confirmation
2/3 after indication of readiness for shipment, before delivery

or

100% against Irrevocable L/C, payable at sight and confirmed by a German bank. Further conditions:

- Place of expiry: in Germany
- Available with any bank by negotiation
- Instructions to negotiating bank: T/T reimbursement allowed

All banking charges at applicants account.

If the customer is in arrears with an agreed downpayment, on-time delivery of the machine is not guaranteed.

The date of commencement of any agreed contractual penalty will be postponed accordingly. In case of serious delays the purchase order will be renegotiated.

Terms of delivery:

As far as not defined in the order confirmation, the attached ORGALIME conditions will be applied.

Validity:

2 months upon date of quotation

Transport, insurance and packing:

FCA Soltau (according to INCOTERMS 2010)
loaded on truck, excluding transport and insurance.

Unless other arrangements are made, Roeders will send the machine "DAP". Transport and insurance will be invoiced separately.

Discharge advise (for Europe only):

For the discharge of the machine by crane, Roeders will provide the necessary lifting device on loan for free.
It is kindly requested to be delivered back to Roeders within

OFFER

our order date : 24.04.2026
account no. : 909343
page : 10 / 14

7 days from the delivery date, with delivery note and without any charges for Roeders.

Installation:

Installation of the machine by the customer, initiation by our technician, costs according to the above mentioned prices. The connection to the electrics and pneumatics must be done out by the customer, connecting cables/tubes are not included in the scope of delivery.

Acceptance:

The geometry of the machine and all machine functions will be checked at Roeders GmbH before delivery. Additional acceptance conditions have to be committed in writing. The machine must be completely tempered before any acceptance test regarding the accuracy can be done. Depending on the temperature conditions during the transport, a waiting period of several days may be required.

Warranty:

We confirm, that the ordered goods are working properly and that they meet the latest state of technology. Warranties for specific qualities of the goods are not given.

The period of warranty is 12 months after the date of delivery. For the linearmotors and the torquemotors the period of warranty is 5 years after the date of delivery.

Note:

In case that defective parts have to be exchanged within the warranty period Roeders GmbH reserves to install factory overhauled spare parts in the machine. This especially concerns to the milling spindle.

For spare parts the warranty is 12 month. This includes the spindle, in case the kind of machining does not cause an unusual wear.

The warranty period starts latest with the machining of work pieces on the machine.

Software-warranty

Our software is created and checked carefully. Our warranty engagement is limited to a bug-fixing within a adequate time. The instruction for evasion of the impact of a software fault deemed to be as a sufficient rectification of defects. Assumption for the debugging is, that the impacts of the faults are repeatable, enough explained and that the fault would be reported immediately from your side.

OFFER

our order date : 24.04.2026
account no. : 909343
page : 11 / 14

Technical availability:

We warrant a technical availability (VDI 3423) of 96% during the warranty period.

Liability:

The liability will be defined at the sales meeting.

Reference list of Roeders:

Company Roeders will include the delivery of the machine(s) in its official reference list. The name of the customer and the machine model(s) will be mentioned. Roeders sends this reference list to companies interested in the products of Roeders. For your information we may send you the reference list any time.

Retention of Title:

1. Title to the goods sold remains with Vendor until Buyer has paid the purchase price of the goods and all other amounts due to Vendor under the sales contract.
2. Notwithstanding the retention of title clause in favour of the Vendor over the goods delivered, all risks relating therewith shall be borne by the Buyer upon delivery to the first carrier unless otherwise agreed in the sales contract.
3. Until complete transfer of ownership Vendor has the right to insure, at Buyer's expense, the goods delivered delivered against theft, breaks, fire, water or any other risk, unless Buyer can clearly demonstrate to Vendor that he has taken out such insurance in the name and on behalf of the Vendor.
4. Buyer may not pledge the goods sold or assign them as security prior to the complete transfer of ownership.
Buyer shall notify Vendor without undue delay of any distraint or sequestration by court authorities of the goods delivered as well as any third party interference with the goods delivered.
5. If Buyer is in default with the payment of the purchase price, Vendor may request the preliminary return of the unpaid goods, if the Vendor has granted him a grace period for payment together with the announcement of the redemption of the goods and this grace period has expired without payment. Buyer is in this case obligated to return the goods at Buyer's expense to the Vendor. The goods have to be delivered to the Buyer again after the default with the payments has ended.
6. In case of any other substantial breach of Buyer's obligations under the sales contract, including, but not limited to a breach of the obligations under Clause 4 above, Vendor may request the preliminary return of the goods delivered after having requested Buyer in writing to stop and remedy such breach within one week after receipt of such notice and has announced the redemption of the goods.
7. The exercising of Vendor's rights to reclaim the goods

OFFER

our order date : 24.04.2026
account no. : 909343
page : 12 / 14

delivered shall not be deemed a cancellation or rescission of the sales contract. The same applies to distraint of the goods delivered by a court on Vendor's request.

Our constructions, software and controls are regularly developed. Therefore, the technical information in this quotation is subject to change without notice.

Please do not hesitate to contact us any time in case you might need further information:

Phone: +49-5191-603-43
Fax: +49-5191-603-38
E-mail: hsc@roeders.de
Internet: www.roeders.de

Options**20 RMS6/SO - Surface Optimizer**

- Functions for tangential intersections of proximate milling programs in the machine control RMS6
- Speed optimization of the milling spindle

The training for this option is not included in the basic training. The advanced training (MRDS60140) is needed.

60 Spindle MFW1230/42 HSK-E40

High frequency milling spindle, FISCHER MFW1230/42, 3.000-42.000 1/min
14 kW (S1), HSK-E40 tool interface, maximum tool diameter 16 mm, automatic tool change

100 Tool changer 500 HC

Tool magazine accessible during primary processing time of the machine (not when working with oil)

Capacity:

HSK-E25 - 46 places

HSK-E32 - 35 places

HSK-E40 - 35 places

The rotary or automatic door has to be ordered separately.

Capacity according to specification.

OFFER

our order date : 24.04.2026
account no. : 909343
page : 13 / 14

110 Manual door tool changer

Door for the tool changer for manual tool change during production time.

120 NC-Simulation RMSEdit/Sim

Extension of the programming editor RMSEdit

- Macros e.g. for quick creation of command file sections or cycles
- Simple modification programs such as rotation, mirroring, moving and scaling
- Programming of Heidenhain ®* programs and Heidenhain cycles (training not included in the basic training)
* Heidenhain is a registered trademark of Dr. Johannes Heidenhain GmbH

Simulation of cutter paths including

- Representation of three-and five-axis toolpaths as a wire model
- Volume-based simulation for 3-axes NC programs
- Simulation with different view options
- Color coding of cutters
- Forward and backward simulation, adjustable speed simulation
- Detailed statistics of the machining
- Simultaneous display of the editor and the simulation window, e.g. for quick navigation in the program

English, German and French version available.

130 Programming Software RMSEdit/Cam

Software for efficient 2 1/2 D design and programming of toolpaths at the machine:

- Design of geometric primitives including DXF interface.
- Support for cutting strategies such as copying and pocket milling cycle
- Options for efficient high-speed cutting (such as the rounding lanes)
- Drilling and threading
- Cycle for engraving

Available only with the simulation software RMSEdit/Sim.

English, French and German version available.

The training for this option is not included in the basic training.
The advanced training (MRDS60140) is needed.

OFFER

our order date : 24.04.2026
account no. : 909343
page : 14 / 14

170 Oil mist suction mechanical 456

Air-cleaning by a multi-stage mechanical filter. When using minimum lubrication or emulsion cooling on the machine the installation of this oil mist is recommended.

With this option the height of the machine increase as follows:

- RXP400(DS/C) increase by 682 mm
- RXP500(DS/C) increase by 258 mm
- RXP501(DS/C) increase by 175 mm

payment : See above

our VAT number: DE813136641

****)** Important notice:

The marked positions contain goods that are subject to export control.
For the export of these goods from the European Community
an export license is necessary.

A possible later order acceptance and delivery of goods will happen
only under the condition that the export license will be granted
by the German export authorities.