

OFFER

offer no. : **MA262727**
 our order date : 07.05.2026
 account no. : 909343
 page : 1 / 19

M&C Electronics VINA Co., Ltd.
 Phuong Lieu Commune , Que Vo District
 Mr. Youn Choi Byoung
 Lot1 J1, Que Vo Industrial Zone

inquiry of : 07.05.2026
 our contact : H. Bolsewig
 Phone : +49 5191/603406
 Email : bolsewig.hagen@roeders.de

Bac Ninh Province
 VIETNAM

PROJECT : **5-axes Precision Machine RPT600DSH**
 M&C Electronics VINA Co., Ltd.

pos.	item no.	description	quantity	PU	unit price EUR	total price EUR
10	M.P52H00	5-Axes Precision machine RPT600DSH	1		344.700,00	344.700,00
20	M.AK5000	Autocalibration 5	1		5.120,00	5.120,00
30	M.ZRAK10	Cleaning for autocalibration	1		2.080,00	2.080,00
60	M.HB2000	Hand held pendant II	1		1.440,00	1.440,00
70	M.MMS100	Minimum lubrication	1		1.600,00	1.600,00
80	M.WSR100	Work piece cleaning	1		435,00	435,00
90	M.TP51SNU100	Table 500DS/60T dia 250 t-slots	1		3.770,00	3.770,00
110	M.SVC1412100	Spindle MFW1412/36 HSK-E50	1		21.550,00	21.550,00
130	M.SK1000	Spindle compensation	1		10.200,00	10.200,00
160	M.WZW500280	Tool changer 60T HC-XE	1		24.050,00	24.050,00
170	M.STWZW100	Manual door tool changer	1		0,00	0,00
200	M.USV200	UPS for control-PC of 5-axes machines	1		0,00	0,00
210	M.ZA1000	Lift up Z-axis	1		1.240,00	1.240,00
220	MSWP035010	Remote Control via Teamviewer	1		1.730,00	1.730,00
250	M.SFN50010	Scraping conveyor 500 emulsion/oil	1		15.200,00	15.200,00
260	M.EK0210	Emulsion cooling 400/500/RPT BF LP	1		20.600,00	20.600,00
270	M.MODELL10	Machine model	1		1.390,00	1.390,00
280	M.VTRANSPORT/860	Transport charges	1			
.1	M.CIF101	CIF charges 400 / 500 / 601DS / 801	1		6.830,00	6.830,00
290	MRDS0660	Initiation II	1			4.260,00
310	MRDS060120	Basic training III	1			6.570,00
330	MTXTLCALLG	Additional services:	1		0,00	0,00

OFFER

our order date : 07.05.2026
 account no. : 909343
 page : 2 / 19

Total price EUR 472.765,00

Options

40	MSWRS0200	RMS6/SO - Surface Optimizer	1	1.620,00	1.620,00
50	MSWRS0250	RMS6/CP - Collision Protection	1	1.850,00	1.850,00
100	M.SVC1224100	Spindle MFW1224/42 HSK-E40	1	12.200,00	12.200,00
120	M.SVC1709100	Spindle MFW1709/30 HSK-F63	1	28.550,00	28.550,00
140	M.WZW60T200	Tool changer 60T HC	1	0,00	0,00
150	M.WZW60T250	Tool changer 60T HC-E	1	13.600,00	13.600,00
180	MSWC025090	NC-Simulation RMSEdit/Sim	1	855,00	855,00
190	MSWC035090	Programming Software RMSEdit/Cam	1	855,00	855,00
230	M.INSPE50	RMSInspect, 3+2 axes	1	11.950,00	11.950,00
240	M.OEN100	Oil mist suction mechanical 400+ / RPT	1	9.100,00	9.100,00
300	MDL0035120	Geometry 450+ 5X (MI)	1	4.480,00	4.480,00
320	MRDS060140	Advanced training	1	4.260,00	4.260,00

OFFER

our order date : 07.05.2026
account no. : 909343
page : 3 / 19

10 5-Axes Precision machine RPT600DSH

****** Precision machine with integrated turn- and swivel axes for highest precision and surface quality. The NC control has been developed especially for high dynamics in 3D milling operations.

Patented friction-free weight counterbalance in the Z-axis for optimal precision. The turn- and swivel axes are compensated by a precise measurement to reach a high 3D accuracy.

Machining range:

In horizontal table position (table in 0° position)

X-axis: 500 mm

Y-axis: 530 mm

Z-axis: 300 mm (height)

The maximum height is according to the machine table.

Machine table:

Turn-swivel-table with thrust bearing for highest stiffness and precision, integrated into the X-axis.

The designs and dimensions of the tables can be found in the separate items. A three-way rotary leadthrough in the rotary axis for controlling an automatic chuck is included in the scope of delivery.

Other chucks and alternative rotary unions, e.g. for vacuum applications, on request.

Pallets and work pieces may not rise above the machine table.

The table must not be distorted by uneven work pieces.

Swivelling range of the A-axis:

+/- 115°

Turning range of the C-axis:

+/- n x 360°

Weight of work piece:

60 kg maximum

Depending on the selected chuck, pallet and clamping of the work piece the maximum weight might be reduced.

For work piece weights which are more than the half of the maximum possible weight or work pieces with higher inertia, which means greater length and / or width, the machine will operate in the "Heavy work piece mode", which reduces the dynamics in the axes.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 4 / 19

Drives of linear axes:

High dynamical linear motors in all axes with integrated cooling

Drives of rotary axes:

High dynamical torque motors in both axes with integrated cooling

Feed rates:

0 - 60.000 mm/min in all linear axes

Cabin:

Fully closed, two doors with safety glass, good view into working area, simple work piece loading by crane possible; for the automated loading of the machine an automatic door is available on request. Partial execution of the inner cabin lining with stainless steel. Maximum retention energy the cabin holds according to DIN EN 1241 is 900 J

Sealing:

All machine parts are protected against soiling; with an suitable industry cleaner graphite, cast iron and plastic can be machined. If a dust extraction is not supplied by Röders, machine-side preparations are needed for the machining of these materials, which that are not included with the machine.(Art.-Nr. M.SAS900)

Numerical control:

Roeders HSC control RMS6, latest version. Including

RMSEdit:

Programming editor for creating and modifying of NC programs.

RACECUT®:

Reduction of machining time by new control technology and 32kHz-drive regulation which allows an increase of jerk and acceleration.

Usage of ISO and Heidenhain®* programs (reduced set of commands, iTNC530) possible. For programming the simulation RMSEdit/Sim is recommended.

21,5" TFT screen; industrial PC with network adapter for the integration of the machine control into an Ethernet network by the customer.

* Heidenhain is a registered trademark of Dr. Johannes Heidenhain GmbH

3D-Touching probe automatic:

OFFER

our order date : 07.05.2026
account no. : 909343
page : 5 / 19

Data transmission via IR-Interface, several measuring cycles available in the machine control.

With thermostabilized HSK-cone to minimize heat transfer into the 3D probe after insertion into the warm milling spindle to reach higher measurement accuracies.
Renishaw probes and probes with HSK25 interface will be equipped with a standard cone.

Takes one place in the tool changer.

Laser for tool measuring:

For automatic tool length correction, diameter and contour measurement, tool break and wear control

Tool cleaning device:

Nozzle for cleaning of milling tools by pressed air before measurement

Removal of chips:

Two feed screws, chip bin located in the machine back

Compressed-air pistol:

Connected to machine air supply

Cooling:

Chiller for tempering of spindle, drives and cabinet. Heat removal to the ambient air. Dimensions depending on the equipment

Chiller for heat dissipation to an existing water circulation on request.

Machinable materials:

All machinable materials can be machined. For dusting materials, such as graphite or ceramic, suitable, if necessary explosion-proof extraction and filtering systems are needed. Flammable materials such as plastics, wood, titanium or magnesium may only be treated with additional equipment for fire protection. This must be agreed with Röders before purchasing the machine. For the processing of hazardous substances, a separate hazard analysis is required.

Dimensions with cabinet:

W 3.000 x L 2.700 x H 2.870 mm

The maximum allowed unevenness of the floor over the installation area is 10 mm.

Dimensions for transport:

(Height without transport rolls, scantlings etc.)

W 2.200 x L 2.700 x H 2.870 mm

OFFER

our order date : 07.05.2026
account no. : 909343
page : 6 / 19

W 2.200 x L 2.700 x H 2.530 mm (without top cover)
W 2.200 x L 2.700 x H 2.380 mm (without top cover / vacuum tubes)

The disassembling of the top cover and maybe the vacuum tubes
is for additional surcharge

Supplementary equipment might change the dimensions of the machine,
also for transport.

Total weight:
Approx. 9.300 kg

Coloring:
RAL7024 Graphite grey: Frame, chip bin
RAL7035 Light grey: Cabin, doors, cabinet,
external units (chiller etc.)
RAL 3003 Ruby red: design stripe
Mobile terminal: Base RAL7024, control panel: RAL3003
For special coloring: see separate position

Connections:
Electrical: 400V +/- 5%, 32A; connected power approx. 22 kVA
Adjusted for TN or TT network
Pneumatic: minimum 6,5 bar, standard consumption approx.
750 l/min during continuous operation

Necessary air quality, according to ISO 8573.1: Class 4
- Solid contaminants:
max. particle size 15 µm, max. particle density 8 mg/m³
- Total oil content: max. oil concentration 5 mg/m³
- Maximum pressure dew point: +3° Celsius

Surroundings:
Allowable ambient temperature 15°C – 35°C
Allowable relative humidity 20% - 80%, without condensation

The precision of the machine directly depends on the temperature
constancy of the ambient temperature. For high accuracy require-
ments a temperature constancy of +/- 1°C is necessary. Insola-
tion of the machine and its direct surrounding has to be avoided.

20 Autocalibration 5

Compensation of the shifting of the turn and swivel axes in the
machine control by touching of additional reference surfaces.

The thermo package (for RXP machines) and a vector controlled
milling spindle is needed.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 7 / 19

30 Cleaning for autocalibration

Cleaning of the probe units of the machine calibration by spray.

60 Hand held pendant II

For setting mode, allows the safe operation of the machine axes at open doors. Including monitor for displaying of machine coordinates and function keys for defined travel movements (e.g. in safety height)

70 Minimum lubrication

Cooler and lubricator with 2 two-component jets, no waste disposal necessary; recommended for the milling of metallic materials which will not be milled with emulsion.

The use of a mist extractor is recommended for minimal mist lubrication.

80 Work piece cleaning

Pressure air jet in the Z-axis for cleaning of the work piece by air; recommended when dusty materials are milled.

At two-spindle machines two nozzles will be mounted.

90 Table 500DS/60T dia 250 t-slots

T-slot table for the C-axis

Distance: 40 mm

Width of t-slots: 10 mm

The distance between spindle nose and table is of

285 mm in the RXP500DS

335 mm in the RXP501DS

285 mm (HSK25), 335 mm (HSK40) in the RPT450DS

410 mm in the RPT600DSH

Three connections for pressure air are available on the face side of the table, for example to supply a chuck on the table. A manual chuck control is not included in the delivery.

Note: Cannot be used in combination with the MFW1709 milling spindle

OFFER

our order date : 07.05.2026
account no. : 909343
page : 8 / 19

110 Spindle MFW1412/36 HSK-E50

High frequency milling spindle, vector-controlled, FISCHER MFW1412/36, 100-36.000 1/min, 15 kW (S1), HSK-E50 tool interface, maximum tool diameter 20 mm, automatic tool change

For highest concentricity the HSK taper is ground after assembly of the spindle.

Additional price to the standard spindle

130 Spindle compensation

****** Contactless measuring of the dislocation of milling spindle and tool during milling operation, compensation in the machine control.

Not available for the milling spindles RSA60 and RSA80.

For machine types 400/500/600/900 the option Thermo package is recommended.

160 Tool changer 60T HC-XE

****** Tool magazine accessible during primary processing time of the machine
Capacity (approximate indication):

HSK-E25 - 160 places

HSK-E32 - 120 places

HSK-E40 - 120 places

HSK-E50 - 96 places

HSK-F63 - 80 places

The manual or automatic lift door has to be ordered separately.

170 Manual door tool changer

Door for the tool changer for manual tool change during production time.

200 UPS for control-PC of 5-axes machines

In case of a power failure the control PCs will be shut down automatically after a default time of approx. 5-10 minutes. The milling operation will be interrupted immediately.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 9 / 19

210 Lift up Z-axis

In case of a power failure the z-axis of the machine will be lifted up in order to avoid damages of the work piece.

Only available in connection with the UPS and at the RXU1201DSH additional with the DEV - Dynamic Energy Supply Unit.

220 Remote Control via Teamviewer

Remote control of the machine by Röders service via Internet communication (Teamviewer).

The connection to the internet has to be arranged by the customer.

During the warranty period of the machine the use of the telemain-tenance is free of charge. After that period Röders may invoice the use of this service at cost-price or by the use of a special telephone service number.

250 Scraping conveyor 500 emulsion/oil

Scraping conveyor below the machine instead of the serial collecting bin, filter box and lift pump included. Suitable for dry operations and milling with emulsion, prepared for the connection to a band filter unit (not included in the delivery).

Chip collection bin located behind the machine.

Also necessary when using the option "Jig grinding".

260 Emulsion cooling 400/500/RPT BF LP

Emulsion unit with band filter for outer coolant supply.

Equipment:

- Pump for outer coolant supply
- Band filter with tank (capacity about 600 liter)
- Heat exchanger for temperature stabilisation of the emulsion
- Spray nozzle for manual cleaning of the working area

For this unit a separate power supply of 400V / 16A is needed. The emulsion itself is not included.

The scraping conveyor has to be ordered separately.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 10 / 19

270 Machine model

Models of axle kinematics, machine base and cabin included, for use in simulation systems. An integration into simulation systems is not included. For reduction of computing time the model is simplified (unnecessary details, screw connections for example, are omitted)

The Models are available in SAT or STEP for the following machine types: RXP, RXU, RXD.

Price per model.

280 Transport charges

.1 CIF charges 400 / 500 / 601DS / 801

CIF xxx seaport (according to INCOTERMS 2020)

290 Initiation II

Travel charges of our technician on working days for car and train as well as accommodation costs are included in the a.m. price. Flight tickets will be charged, flight hours will be charged for each route from the 5th hour of traveling at the below mentioned prices.

Roeders will choose the most suitable means of travel.

310 Basic training III

The instruction and training takes place at the customer.
It takes 4 days and contains the basical operation of the machine.

Travel charges of our technician on working days for car and train as well as accommodation costs are included in the a.m. price. Flight tickets will be charged, flight hours charged after the 5th hour of traveling at the below mentioned prices.

Röders will choose the most suitable means of travel.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 11 / 19

330 Additional services:

Time of delivery:

RXP and RPT - Series 5 - 7 months
RXU and RHP - Series 8 - 12 months
after clarification of all technical and commercial details.
Shorter delivery time on request.

If an export license of the German BAFA is mandatory, the date of delivery depends also on the date of licensing.

Prices:

All prices in EURO, without VAT.

Payment:

1/3 down payment upon receipt of order confirmation
2/3 after indication of readiness for shipment, before delivery

or

100% against Irrevocable L/C, payable at sight and confirmed by a German bank. Further conditions:

- Place of expiry: in Germany
- Available with any bank by negotiation
- Instructions to negotiating bank: T/T reimbursement allowed

All banking charges at applicants account.

If the customer is in arrears with an agreed downpayment, on-time delivery of the machine is not guaranteed.

The date of commencement of any agreed contractual penalty will be postponed accordingly. In case of serious delays the purchase order will be renegotiated.

Terms of delivery:

As far as not defined in the order confirmation, the attached ORGALIME conditions will be applied.

Validity:

2 months upon date of quotation

Transport, insurance and packing:

FCA Soltau (according to INCOTERMS 2010)
loaded on truck, excluding transport and insurance.

Unless other arrangements are made, Roeders will send the machine "DAP". Transport and insurance will be invoiced separately.

Discharge advise (for Europe only):

For the discharge of the machine by crane, Roeders will provide the necessary lifting device on loan for free.
It is kindly requested to be delivered back to Roeders within

OFFER

our order date : 07.05.2026
account no. : 909343
page : 12 / 19

7 days from the delivery date, with delivery note and without any charges for Roeders.

Installation:

Installation of the machine by the customer, initiation by our technician, costs according to the above mentioned prices. The connection to the electrics and pneumatics must be done out by the customer, connecting cables/tubes are not included in the scope of delivery.

Acceptance:

The geometry of the machine and all machine functions will be checked at Roeders GmbH before delivery. Additional acceptance conditions have to be committed in writing. The machine must be completely tempered before any acceptance test regarding the accuracy can be done. Depending on the temperature conditions during the transport, a waiting period of several days may be required.

Warranty:

We confirm, that the ordered goods are working properly and that they meet the latest state of technology. Warranties for specific qualities of the goods are not given.

The period of warranty is 12 months after the date of delivery. For the linearmotors and the torquemotors the period of warranty is 5 years after the date of delivery.

Note:

In case that defective parts have to be exchanged within the warranty period Roeders GmbH reserves to install factory overhauled spare parts in the machine. This especially concerns to the milling spindle.

For spare parts the warranty is 12 month. This includes the spindle, in case the kind of machining does not cause an unusual wear.

The warranty period starts latest with the machining of work pieces on the machine.

Software-warranty

Our software is created and checked carefully. Our warranty engagement is limited to a bug-fixing within a adequate time. The instruction for evasion of the impact of a software fault deemed to be as a sufficient rectification of defects. Assumption for the debugging is, that the impacts of the faults are repeatable, enough explained and that the fault would be reported immediately from your side.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 13 / 19

Technical availability:

We warrant a technical availability (VDI 3423) of 96% during the warranty period.

Liability:

The liability will be defined at the sales meeting.

Reference list of Roeders:

Company Roeders will include the delivery of the machine(s) in its official reference list. The name of the customer and the machine model(s) will be mentioned. Roeders sends this reference list to companies interested in the products of Roeders. For your information we may send you the reference list any time.

Retention of Title:

1. Title to the goods sold remains with Vendor until Buyer has paid the purchase price of the goods and all other amounts due to Vendor under the sales contract.
2. Notwithstanding the retention of title clause in favour of the Vendor over the goods delivered, all risks relating therewith shall be borne by the Buyer upon delivery to the first carrier unless otherwise agreed in the sales contract.
3. Until complete transfer of ownership Vendor has the right to insure, at Buyer's expense, the goods delivered delivered against theft, breaks, fire, water or any other risk, unless Buyer can clearly demonstrate to Vendor that he has taken out such insurance in the name and on behalf of the Vendor.
4. Buyer may not pledge the goods sold or assign them as security prior to the complete transfer of ownership.
Buyer shall notify Vendor without undue delay of any distraint or sequestration by court authorities of the goods delivered as well as any third party interference with the goods delivered.
5. If Buyer is in default with the payment of the purchase price, Vendor may request the preliminary return of the unpaid goods, if the Vendor has granted him a grace period for payment together with the announcement of the redemption of the goods and this grace period has expired without payment. Buyer is in this case obligated to return the goods at Buyer's expense to the Vendor. The goods have to be delivered to the Buyer again after the default with the payments has ended.
6. In case of any other substantial breach of Buyer's obligations under the sales contract, including, but not limited to a breach of the obligations under Clause 4 above, Vendor may request the preliminary return of the goods delivered after having requested Buyer in writing to stop and remedy such breach within one week after receipt of such notice and has announced the redemption of the goods.
7. The exercising of Vendor's rights to reclaim the goods

OFFER

our order date : 07.05.2026
account no. : 909343
page : 14 / 19

delivered shall not be deemed a cancellation or rescission of the sales contract. The same applies to distraint of the goods delivered by a court on Vendor's request.

Our constructions, software and controls are regularly developed. Therefore, the technical information in this quotation is subject to change without notice.

Please do not hesitate to contact us any time in case you might need further information:

Phone: +49-5191-603-43
Fax: +49-5191-603-38
E-mail: hsc@roeders.de
Internet: www.roeders.de

Options**40 RMS6/SO - Surface Optimizer**

- Functions for tangential intersections of proximate milling programs in the machine control RMS6
- Speed optimization of the milling spindle

The training for this option is not included in the basic training. The advanced training (MRDS60140) is needed.

50 RMS6/CP - Collision Protection

Detection of protection against collisions between tool or spindle with machine components, during the program execution.

Available for all machine types except RXS series In addition, the machine model is required for the machine (M.MODELL10).

100 Spindle MFW1224/42 HSK-E40

High frequency milling spindle, vector controlled, FISCHER MFW1224/42, 100-42.000 1/min, 15 kW (S1), HSK-E40 tool interface, maximum tool diameter 16 mm, automatic tool change

For highest concentricity the HSK taper is ground after assembly of the spindle.

Additional price to the standard spindle

OFFER

our order date : 07.05.2026
account no. : 909343
page : 15 / 19

120 Spindle MFW1709/30 HSK-F63

High frequency milling spindle, vector-controlled, FISCHER MFW1709/30, 100-30.000 1/min, 20 kW (S1), HSK-F63 tool interface, automatic tool change. Max. tooldiameter 25 mm, max. shank diameter 25 mm. Bigger tool diameter are may be possible on request.

Additional price to the standard spindle

140 Tool changer 60T HC

Tool magazine accessible during primary processing time of the machine

Capacity:

HSK-E25 - 56 places

HSK-E32 - 42 places

HSK-E40 - 42 places

HSK-E50 - 33 places

HSK-x63 - 28 places (only RPT600)

The loading door has to be ordered separately.

150 Tool changer 60T HC-E

Tool magazine accessible during primary processing time of the machine

Capacity:

HSK-E25 - 116 places

HSK-E32 - 87 places

HSK-E40 - 87 places

HSK-E50 - 70 places

HSK-x63 - 58 places (only RPT600)

The loading door has to be ordered separately.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 16 / 19

180 NC-Simulation RMSEdit/Sim

Extension of the programming editor RMSEdit

- Macros e.g. for quick creation of command file sections or cycles
 - Simple modification programs such as rotation, mirroring, moving and scaling
 - Programming of Heidenhain ®* programs and Heidenhain cycles (training not included in the basic training)
- * Heidenhain is a registered trademark of Dr. Johannes Heidenhain GmbH

Simulation of cutter paths including

- Representation of three-and five-axis toolpaths as a wire model
- Volume-based simulation for 3-axes NC programs
- Simulation with different view options
- Color coding of cutters
- Forward and backward simulation, adjustable speed simulation
- Detailed statistics of the machining
- Simultaneous display of the editor and the simulation window, e.g. for quick navigation in the program

English, German and French version available.

190 Programming Software RMSEdit/Cam

Software for efficient 2 1/2 D design and programming of toolpaths at the machine:

- Design of geometric primitives including DXF interface.
- Support for cutting strategies such as copying and pocket milling cycle
- Options for efficient high-speed cutting (such as the rounding lanes)
- Drilling and threading
- Cycle for engraving

Available only with the simulation software RMSEdit/Sim.

English, French and German version available.

The training for this option is not included in the basic training.
The advanced training (MRDS60140) is needed.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 17 / 19

230 RMSInspect, 3+2 axes

Software for measuring of work pieces directly on the HSC machine.
After entering the iges-file, the checkpoints can simply be indicated with a mouseclick on the 3D-image of the part. The measuring results will be written into a protocol file with Word or Excel format or to a pdf file, the result will also be shown on the screen.

Additional features:

- BestFit functionality, all rotations can be deactivated together
- Simulation of the probing
- Check of the checkpoints
- Extended probing strategies (line with number of checkpoints, curves, cylinders, holes)
- Tolerance classes can be defined
- Automation (creating of protocol, BestFit and check of results by NC-commands)
- 3+2 axes feature

Following interfaces are included in the delivery:
IGES, VDA-FS, RHINO, STL, DXF, Parasolid

Further interfaces (e.g. CATIA, Unigraphics) are available on request.

Only available with an automatic 3D touching probe.

Scope of delivery

- Dongle for RMSInspect
- Open Office licence to display the measuring result

The training for this option is not included in the basic training.
The advanced training (MRDS060140) is needed.

240 Oil mist suction mechanical 400+ / RPT

Air-cleaning by a multi-stage mechanical filter. When using minimum lubrication or emulsion cooling on the machine the installation of this oil mist is recommended.

With this option the height of the machine increase as follows:

- RXP400(DS/C) increase by 682 mm
 - RXP500(DS/C) increase by 258 mm
 - RXP501(DS/C) increase by 175 mm
-

OFFER

our order date : 07.05.2026
account no. : 909343
page : 18 / 19

300 Geometry 450+ 5X (MI)

Measurement and compensation of the 5-axis machine geometry to achieve the highest possible machining accuracy. This work is done in the course of the installation of the machine.

The machine must be completely tempered before the geometry compensation can be done. Depending on the temperature conditions during the transport, a waiting period of several days may be required.

In order to optimize the accuracy, we ask you to specify the Ambient temperature of the installation site of the machine and the temperature of the machine according to the display of the cooling unit. In case of discrepancies above 1°C, it is advisable to adjust the temperatures in advance.

Travel charges of our technician on working days for car and train as well as accommodation costs are included in the a.m. price. Flight tickets will be charged, flight hours inceptive at the 5th hour per journey at the below mentioned prices.

Company Roeders will chose the most suitable means of travel.

320 Advanced training

The instruction and training takes place at the customer.

It takes 2 days and contains maximum 2 of the following options:

- Advanced operation of machine control
- Heidenhain(R) cyle programming
- Programming of cyles
- ECO-Automatic
- Roeders inspect
- Toolmanagement
- Programming system RMSEdit/CAM
- Jobmanager RMSMain
- RMS6/SO, functions for tangential intersections
- Toolfit - Precision Probing Technology
- Toolfit - Restmaterial

Assumption: Basical training.

Travel charges of our technician on working days for car and train as well as accommodation costs are included in the a.m. price. Flight tickets will be charged, flight hours charged after the 5th hour of traveling at the below mentioned prices.

Roeders will choose the most suitable means of travel.

OFFER

our order date : 07.05.2026
account no. : 909343
page : 19 / 19

payment : 10 days net

This offer is valid until 06.07.2026

our VAT number: DE813136641

****)** Important notice:

The marked positions contain goods that are subject to export control.
For the export of these goods from the European Community
an export license is necessary.
A possible later order acceptance and delivery of goods will happen
only under the condition that the export license will be granted
by the German export authorities.