

BARE HARD & SOFT DRAWN COPPER CONDUCTORS



Stranded Soft Drawn Bare
Copper Conductor

Description

Plain bare soft drawn Copper conductors (Circular - Compacted)

Application

Bare stranded soft-drawn (annealed) copper conductor is suitable for uninsulated hook-up, jumpers and grounding conductors in electrical construction, where high conductivity and flexibility are required.

Technical Data

Relevant Standard	IEC 60228 class 2
Conductor	Plain bare soft drawn Copper conductors
Minimum bending Radius	25 x outer diameter
Packing Condition	Our standard length on Wooden Drum / or according to customer request



Product Code	Cross Sectional Area mm ²	Minimum Number of Wires No.	Max. D.C. Conductor Resistance at 20 °C Ω/km	Approx. Overall Diameter mm ²	Approx. Weight Kg/Km
PR-CT10-00-01-U0	10	6	1.8300	3.70	85
PR-CT11-00-01-U0	16	6	1.1500	4.70	135
PR-CT12-00-01-U0	25	6	0.7270	5.80	215
PR-CT13-00-01-U0	35	6	0.5240	6.90	300
PR-CT14-00-01-U0	50	6	0.3870	8.00	410
PR-CT15-00-01-U0	70	12	0.2680	9.75	595
PR-CT16-00-01-U0	95	15	0.1930	11.30	820
PR-CT17-00-01-U0	120	18	0.1530	12.70	1030
PR-CT18-00-01-U0	150	18	0.1240	14.00	1277
PR-CT19-00-01-U0	185	30	0.0991	15.90	1600
PR-CT20-00-01-U0	240	34	0.0754	18.30	2100
PR-CT21-00-01-U0	300	34	0.0601	20.50	2650
PR-CT22-00-01-U0	400	53	0.0470	23.20	3410
PR-CT23-00-01-U0	500	53	0.0366	26.50	4400
PR-CT24-00-01-U0	630	53	0.0283	30.10	5600

The above data is approximate and subject to manufacturing tolerances