

Multicores Copper & Aluminum Conductors

XLPE Insulated, Steel Tape armored and PVC Sheathed

Voltage Grade

3.6 / 6 (7.2) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compactedAluminum conductor, semiconducting layer as conductor screen, XLPE insulated, semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, three cores assembled together with non hygroscopic Polypropylene fillers, banded with suitable tape, armored with steel tape and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and binded with a Copper tape to achieve electrical contact Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Assembly	The insulated Cores are assembled together using nonhygroscopic polyprobylene filler (if needed), then banded with suitable tape
Inner Sheath	Extruded PVC Compound
Armoring	Double Steel Tapes applied helically over the inner sheath.
Outer Sheath	Extruded PVC Compound
Cores Indentification	by inserting Red, Yellow, Blue narrow plastic tapes between the non metallic & the metallic insulation screen, or any other color according to customer request
Outer Sheath Color	Black (default color), or any other color according to customer request



Maximum Operating Temp. 90° C

Minimum bending Radius 12 x outer diameter

Packing Condition Our standard length on Wooden Drum / or according to customer request

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance		Operating Capacitance	Inductance	Current Rating		Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Laid in Ground	Laid in Free Air		
					mm²	Ω/km	Ω/km	µF/km	mH/km
	A - Copper Conductors								
PM-CT14-X5-03-TP	50	0.3870	0.4957	0.3425	0.3287	206	208	40.4	3070
PM-CT15-X5-03-TP	70	0.2680	0.3438	0.3975	0.3110	253	260	44.7	3940
PM-CT16-X5-03-TP	95	0.1930	0.2483	0.4432	0.2980	302	313	48.1	4830
PM-CT17-X5-03-TP	120	0.1530	0.1976	0.4858	0.2843	342	358	50.9	5660
PM-CT18-X5-03-TP	150	0.1240	0.1609	0.5314	0.2782	383	406	55.0	6750
PM-CT19-X5-03-TP	185	0.0991	0.1299	0.5860	0.2702	432	464	59.1	8000
PM-CT20-X5-03-TP	240	0.0754	0.1005	0.6311	0.2620	498	542	65.1	9980
PM-CT21-X5-03-TP	300	0.0601	0.0820	0.6466	0.2583	556	617	71.3	12175
PM-CT22-X5-03-TP	400	0.0470	0.0667	0.6722	0.2541	627	707	79.5	15760
PM-CT23-X5-03-TP	500	0.0366	0.0552	0.7084	0.2495	701	806	88.1	19585
B - Aluminum Conductors									
PM-AT14-X5-03-TP	50	0.6410	0.8249	0.3548	0.3240	161	162	41.3	2270
PM-AT15-X5-03-TP	70	0.4430	0.5705	0.4006	0.3091	196	201	44.9	2715
PM-AT16-X5-03-TP	95	0.3200	0.4126	0.4493	0.2945	235	243	48.1	3145
PM-AT17-X5-03-TP	120	0.2530	0.3267	0.4889	0.2837	267	279	51.1	3540
PM-AT18-X5-03-TP	150	0.2060	0.2665	0.5405	0.2767	299	317	55.6	4120
PM-AT19-X5-03-TP	185	0.1640	0.2129	0.5951	0.2690	339	364	59.7	4705
PM-AT20-X5-03-TP	240	0.1250	0.1634	0.6311	0.2620	392	426	65.1	5605
PM-AT21-X5-03-TP	300	0.1000	0.1318	0.6466	0.2583	441	488	71.3	6625
PM-AT22-X5-03-TP	400	0.0778	0.1042	0.6722	0.2541	503	566	79.5	8650
PM-AT23-X5-03-TP	500	0.0605	0.0833	0.7084	0.2495	572	657	88.1	10400

The above data is approximate and subject to manufacturing tolerances

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request
Galvanized Steel Tapes is available according to customer request
the below data are applicable for cables with rated voltage 3.8 / 6.6 (7.2) KV