

Multicores Copper & Aluminum Conductors

XLPE Insulated, Steel Wires armored and PVC Sheathed

Voltage Grade

3.6 / 6 (7.2) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated, semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, three cores assembled together with non hygrosopic Polypropylene fillers, banded with suitable tape, Armor with Galvanized steel wires, banded with suitable tape and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502 or BS 6622
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and binded with a Copper tape to achieve electrical contact Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Assembly	The insulated Cores are assembled together using nonhygroscopic polyprobylene filler (if needed), then banded with suitable tape
Inner Sheath	Extruded PVC Compound
Armoring	Galvanized Steel Wires over the inner sheath.
Outer Sheath	Extruded PVC Compound
Cores Indentification	by inserting Red, Yellow, Blue narrow plastic tapes between the non metallic & the metallic insulation screen, or any other color according to customer request
Outer Sheath Color	Black (default color), or any other color according to customer request

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request
the below data are applicable for cables with rated voltage 3.8 / 6.6 (7.2) KV



Maximum Operating Temp. 90° C

Minimum bending Radius 12 x outer diameter

Packing Condition Our standard length on Wooden Drum / or according to customer request

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance		Operating Capacitance	Inductance	Current Rating		Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Laid in Ground	Laid in Free Air		
					mm²	Ω/km	Ω/km	µF/km	mH/km
	A - Copper Conductors								
PM-CT14-X5-03-WP	50	0.3870	0.4957	0.3425	0.3287	208	214	44.4	4220
PM-CT15-X5-03-WP	70	0.2680	0.3438	0.3975	0.3110	256	266	48.7	5225
PM-CT16-X5-03-WP	95	0.1930	0.2483	0.4432	0.2980	304	321	52.1	6220
PM-CT17-X5-03-WP	120	0.1530	0.1976	0.4858	0.2843	344	366	54.9	7130
PM-CT18-X5-03-WP	150	0.1240	0.1609	0.5314	0.2782	385	415	58.8	8290
PM-CT19-X5-03-WP	185	0.0991	0.1299	0.5860	0.2702	433	473	63.1	9705
PM-CT20-X5-03-WP	240	0.0754	0.1005	0.6311	0.2620	497	555	70.6	12645
PM-CT21-X5-03-WP	300	0.0601	0.0820	0.6466	0.2583	553	629	76.6	15035
PM-CT22-X5-03-WP	400	0.0470	0.0667	0.6722	0.2541	617	710	83.7	18235
PM-CT23-X5-03-WP	500	0.0366	0.0552	0.7084	0.2495	682	800	92.3	22355
B - Aluminum Conductors									
PM-AT14-X5-03-WP	50	0.6410	0.8249	0.3548	0.3240	162	166	45.3	3445
PM-AT15-X5-03-WP	70	0.4430	0.5705	0.4006	0.3091	198	206	48.9	3995
PM-AT16-X5-03-WP	95	0.3200	0.4126	0.4493	0.2945	236	249	52.1	4535
PM-AT17-X5-03-WP	120	0.2530	0.3267	0.4889	0.2837	269	286	55.1	5005
PM-AT18-X5-03-WP	150	0.2060	0.2665	0.5405	0.2767	300	324	59.4	5685
PM-AT19-X5-03-WP	185	0.1640	0.2129	0.5951	0.2690	339	371	63.7	6435
PM-AT20-X5-03-WP	240	0.1250	0.1634	0.6311	0.2620	392	439	70.6	8270
PM-AT21-X5-03-WP	300	0.1000	0.1318	0.6466	0.2583	441	499	76.6	9485
PM-AT22-X5-03-WP	400	0.0778	0.1042	0.6722	0.2541	498	572	83.7	11120
PM-AT23-X5-03-WP	500	0.0605	0.0833	0.7084	0.2495	563	658	92.3	13175

The above data is approximate and subject to manufacturing tolerances