

Single core Copper & Aluminum Conductors

XLPE Insulated and PVC Sheathed

Voltage Grade

3.6 / 6 (7.2) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and banded with a Copper tape to achieve electrical contact • Overlapped Copper Tape then Copper Wires are also available (in single core only) Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Outer Sheath	Extruded PVC Compound
Outer Sheath Color	Black (default color), or any other color according to customer request
Maximum Operating Temp.	90° C
Minimum bending Radius	12 x outer diameter
Packing Condition	Our standard length on Wooden Drum / or according to customer request

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request
the below data are applicable for cables with rated voltage 3.8 / 6.6 (7.2) KV

MEDIUM VOLTAGE CABLES

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance			Operating Capacitance	Inductance		Current Rating					Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Flat	Trefoil	Laid in Ground			Laid in Free Air			
			Flat	Trefoil				Flat	Trefoil	Duct	Flat Touched	Trefoil		
	mm²	Ω/km	Ω/km	Ω/km	μF/km	mH/km	mH/km	A	A	A	A	A	mm	kg/km
A - Copper Conductors														
PM-CT14-X5-01-UP	50	0.3870	0.4937	0.4938	0.3425	0.4235	0.3773	225	218	183	241	236	20.0	815
PM-CT15-X5-01-UP	70	0.2680	0.3421	0.3422	0.3975	0.4012	0.3550	277	267	225	302	295	21.8	1035
PM-CT16-X5-01-UP	95	0.1930	0.2466	0.2468	0.4432	0.3867	0.3405	330	316	269	366	358	23.5	1295
PM-CT17-X5-01-UP	120	0.1530	0.1958	0.1960	0.4858	0.3739	0.3277	373	361	307	420	412	25.1	1540
PM-CT18-X5-01-UP	150	0.1240	0.1590	0.1593	0.5314	0.3632	0.3170	412	404	343	474	469	26.6	1895
PM-CT19-X5-01-UP	185	0.0991	0.1276	0.1279	0.5860	0.3538	0.3076	463	456	390	545	540	28.6	2265
PM-CT20-X5-01-UP	240	0.0754	0.0977	0.0982	0.6311	0.3423	0.2961	532	528	454	642	636	31.1	2815
PM-CT21-X5-01-UP	300	0.0601	0.0787	0.0793	0.6466	0.3357	0.2894	597	591	511	733	728	33.7	3425
PM-CT22-X5-01-UP	400	0.0470	0.0626	0.0634	0.6722	0.3307	0.2845	663	665	582	835	842	37.2	4380
PM-CT23-X5-01-UP	500	0.0366	0.0502	0.0512	0.7084	0.3240	0.2778	742	749	662	964	969	41.1	5480
PM-CT24-X5-01-UP	630	0.0283	0.0405	0.0418	0.8036	0.3184	0.2722	829	833	747	1104	1097	45.4	6810
PM-CT25-X5-01-UP	800	0.0221	0.0336	0.0353	0.9056	0.3097	0.2634	908	924	855	1246	1237	49.8	8605
B - Aluminum Conductors														
PM-AT14-X5-01-UP	50	0.6410	0.8219	0.8220	0.3548	0.4177	0.3715	174	169	141	185	184	20.4	545
PM-AT15-X5-01-UP	70	0.4430	0.5682	0.5683	0.4006	0.3990	0.3528	213	207	174	232	232	21.9	625
PM-AT16-X5-01-UP	95	0.3200	0.4106	0.4107	0.4493	0.3849	0.3387	255	247	209	281	278	23.7	735
PM-AT17-X5-01-UP	120	0.2530	0.3248	0.3249	0.4889	0.3731	0.3269	290	281	238	324	324	25.2	835
PM-AT18-X5-01-UP	150	0.2060	0.2647	0.2648	0.5405	0.3612	0.3150	321	315	268	366	366	26.9	1020
PM-AT19-X5-01-UP	185	0.1640	0.2110	0.2112	0.5951	0.3522	0.3060	363	358	306	422	426	28.9	1165
PM-AT20-X5-01-UP	240	0.1250	0.1613	0.1616	0.6311	0.3423	0.2961	419	414	355	506	498	31.1	1360
PM-AT21-X5-01-UP	300	0.1000	0.1295	0.1299	0.6466	0.3357	0.2894	463	465	401	581	574	33.7	1580
PM-AT22-X5-01-UP	400	0.0778	0.1014	0.1019	0.6722	0.3307	0.2845	533	530	463	672	670	37.2	2015
PM-AT23-X5-01-UP	500	0.0605	0.0798	0.0805	0.7084	0.3240	0.2778	602	605	534	782	781	41.1	2425
PM-AT24-X5-01-UP	630	0.0469	0.0630	0.0639	0.8059	0.3182	0.2720	686	686	618	911	907	45.5	2940
PM-AT25-X5-01-UP	800	0.0367	0.0508	0.0521	0.9056	0.3097	0.2634	775	775	714	1051	1038	49.8	3535

The above data is approximate and subject to manufacturing tolerances