

Multicores Copper & Aluminum Conductors

XLPE Insulated, Steel Tape armored and PVC Sheathed

Voltage Grade

6 / 10 (12) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated, semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, three cores assembled together with non hygroscopic Polypropylene fillers, banded with suitable tape, armored with steel tape and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and binded with a Copper tape to achieve electrical contact Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Assembly	The insulated Cores are assembled together using nonhygroscopic polyprobylene filler (if needed), then banded with suitable tape
Inner Sheath	Extruded PVC Compound
Armoring	Double Steel Tapes applied helically over the inner sheath.
Outer Sheath	Extruded PVC Compound
Cores Indentification	by inserting Red, Yellow, Blue narrow plastic tapes between the non metallic & the metallic insulation screen, or any other color according to customer request
Outer Sheath Color	Black (default color), or any other color according to customer request



MEDIUM VOLTAGE CABLES

Maximum Operating Temp. 90° C

Minimum bending Radius 12 x outer diameter

Packing Condition Our standard length on Wooden Drum / or according to customer request

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance		Operating Capacitance	Inductance	Current Rating		Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Laid in Ground	Laid in Free Air		
					mm²	Ω/km	Ω/km	µF/km	mH/km
	A - Copper Conductors								
PM-CT14-X6-03-TP	50	0.3870	0.4957	0.2630	0.3507	206	210	42.1	3455
PM-CT15-X6-03-TP	70	0.2680	0.3438	0.3029	0.3287	253	261	48.3	4235
PM-CT16-X6-03-TP	95	0.1930	0.2482	0.3359	0.3143	302	315	51.8	5170
PM-CT17-X6-03-TP	120	0.1530	0.1974	0.3667	0.3015	343	361	55.2	6025
PM-CT18-X6-03-TP	150	0.1240	0.1607	0.3996	0.2941	384	409	59.3	7165
PM-CT19-X6-03-TP	185	0.0991	0.1296	0.4391	0.2849	432	466	63.4	8430
PM-CT20-X6-03-TP	240	0.0754	0.1002	0.4893	0.2740	498	545	68.7	10360
PM-CT21-X6-03-TP	300	0.0601	0.0818	0.5374	0.2652	556	619	73.5	12385
PM-CT22-X6-03-TP	400	0.0470	0.0665	0.5963	0.2591	628	710	81.4	15975
PM-CT23-X6-03-TP	500	0.0366	0.0551	0.6682	0.2517	701	806	89.1	19680
B - Aluminum Conductors									
PM-AT14-X6-03-TP	50	0.6410	0.8250	0.2719	0.3454	161	163	45.5	2655
PM-AT15-X6-03-TP	70	0.4430	0.5706	0.3051	0.3267	196	202	48.6	3010
PM-AT16-X6-03-TP	95	0.3200	0.4125	0.3403	0.3128	235	244	52.2	3490
PM-AT17-X6-03-TP	120	0.2530	0.3266	0.3689	0.3009	268	281	55.4	3910
PM-AT18-X6-03-TP	150	0.2060	0.2663	0.4062	0.2925	299	319	59.9	4535
PM-AT19-X6-03-TP	185	0.1640	0.2127	0.4456	0.2836	339	365	64.0	5150
PM-AT20-X6-03-TP	240	0.1250	0.1632	0.4893	0.2740	392	428	68.7	5990
PM-AT21-X6-03-TP	300	0.1000	0.1317	0.5374	0.2652	441	489	73.5	6835
PM-AT22-X6-03-TP	400	0.0778	0.1041	0.5963	0.2591	503	568	81.4	8865
PM-AT23-X6-03-TP	500	0.0605	0.0832	0.6682	0.2517	572	657	89.1	10500

The above data is approximate and subject to manufacturing tolerances

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request
Galvanized Steel Tapes is available according to customer request
the below data are applicable for cables with rated voltage 6.35/11 (12) KV