

Single core Copper & Aluminum Conductors

XLPE Insulated, Aluminum Tape armored and PVC Sheathed

Voltage Grade

6 / 10 (12) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, armored with aluminum tape and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and banded with a Copper tape to achieve electrical contact • Overlapped Copper Tape then Copper Wires are also available (in single core only) Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Inner Sheath	Extruded PVC Compound
Armoring	Double Aluminum Tapes applied helically over the inner sheath.
Outer Sheath	Extruded PVC Compound
Outer Sheath Color	Black (default color), or any other color according to customer request
Maximum Operating Temp.	90° C
Minimum bending Radius	12 x outer diameter
Packing Condition	Our standard length on Wooden Drum / or according to customer request



MEDIUM VOLTAGE CABLES

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance			Operating Capacitance	Inductance		Current Rating				Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Flat	Trefoil	Laid in Ground		Laid in Free Air			
			Flat	Trefoil				Flat	Trefoil	Flat Touched	Trefoil		
	mm²	Ω/km	Ω/km	Ω/km	μF/km	mH/km	mH/km	A	A	A	A	mm	kg/km
A - Copper Conductors													
PM-CT14-X6-01-DP	50	0.3870	0.4937	0.4937	0.2630	0.4775	0.4313	224	218	241	236	26.2	1140
PM-CT15-X6-01-DP	70	0.2680	0.3420	0.3421	0.3029	0.4572	0.4064	276	267	302	295	28.2	1395
PM-CT16-X6-01-DP	95	0.1930	0.2466	0.2466	0.3359	0.4335	0.3873	328	316	366	358	29.7	1665
PM-CT17-X6-01-DP	120	0.1530	0.1957	0.1958	0.3667	0.4168	0.3706	372	361	420	412	31.1	1920
PM-CT18-X6-01-DP	150	0.1240	0.1589	0.1590	0.3996	0.4039	0.3576	410	402	474	469	32.6	2295
PM-CT19-X6-01-DP	185	0.0991	0.1274	0.1277	0.4391	0.3919	0.3457	461	454	545	540	34.6	2690
PM-CT20-X6-01-DP	240	0.0754	0.0975	0.0978	0.4893	0.3776	0.3314	530	528	642	636	37.1	3280
PM-CT21-X6-01-DP	300	0.0601	0.0784	0.0789	0.5374	0.3664	0.3202	588	588	733	728	39.3	3900
PM-CT22-X6-01-DP	400	0.0470	0.0623	0.0629	0.5963	0.3569	0.3106	655	662	835	842	42.4	4875
PM-CT23-X6-01-DP	500	0.0366	0.0498	0.0507	0.6682	0.3461	0.2999	720	737	964	969	45.9	5990
PM-CT24-X6-01-DP	630	0.0283	0.0400	0.0411	0.7574	0.3393	0.2931	804	825	1073	1086	50.4	7395
PM-CT25-X6-01-DP	800	0.0221	0.0331	0.0344	0.8532	0.3295	0.2833	879	908	1210	1225	55.0	9300
B - Aluminum Conductors													
PM-AT14-X6-01-DP	50	0.6410	0.8219	0.8219	0.2719	0.4708	0.4246	171	170	185	184	26.6	870
PM-AT15-X6-01-DP	70	0.4430	0.5682	0.5682	0.3051	0.4503	0.4041	210	208	232	232	28.3	985
PM-AT16-X6-01-DP	95	0.3200	0.4106	0.4106	0.3403	0.4314	0.3851	251	248	281	278	29.9	1110
PM-AT17-X6-01-DP	120	0.2530	0.3248	0.3248	0.3689	0.4158	0.3696	285	282	324	324	31.2	1215
PM-AT18-X6-01-DP	150	0.2060	0.2646	0.2647	0.4062	0.4015	0.3553	317	315	366	366	32.9	1420
PM-AT19-X6-01-DP	185	0.1640	0.2109	0.2111	0.4456	0.3899	0.3437	357	358	422	426	34.9	1595
PM-AT20-X6-01-DP	240	0.1250	0.1611	0.1614	0.4893	0.3776	0.3314	417	414	506	498	37.1	1825
PM-AT21-X6-01-DP	300	0.1000	0.1293	0.1296	0.5374	0.3664	0.3202	459	463	581	574	39.3	2055
PM-AT22-X6-01-DP	400	0.0778	0.1012	0.1016	0.5963	0.3569	0.3106	517	527	672	670	42.4	2510
PM-AT23-X6-01-DP	500	0.0605	0.0796	0.0801	0.6682	0.3461	0.2999	595	602	782	781	45.9	2940
PM-AT24-X6-01-DP	630	0.0469	0.0627	0.0634	0.7596	0.3391	0.2929	670	679	894	895	50.5	3530
PM-AT25-X6-01-DP	800	0.0367	0.0504	0.0515	0.8532	0.3295	0.2833	749	761	1025	1025	55.0	4200

The above data is approximate and subject to manufacturing tolerances

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request
the below data are applicable for cables with rated voltage 6.35/11 (12) KV